

**A**

- AAA authentication methods 5-3
- aaa new-model command 5-3, 5-7
- accounting in TACACS+ 5-2
- advertisements, VTP 2-4
- allowed list, VLANs 3-6
- allowed VLANs, configuring 3-6
- allowed-VLAN list 2-19
- AppleTalk Remote Access (ARA) 5-4
- ATM trunks and other features 3-20
- authentication in TACACS+ 5-2
- authorization in TACACS+ 5-2

**B**

- blocking unknown packets 3-20

**C**

- Cisco Connection Online (CCO)
  - URLs ix
- Cisco Visual Switch Manager help system 1-2, 1-3
- class of service (CoS) 2-32
- client mode, VTP 2-3
- clusters of switches 2-18
- command switches
  - in VMPS 4-1
- command-line interface (CLI) 1-3
- configuration guidelines
  - for VMPS 4-4
  - for VTP 2-7
- consistency checks in VTP version 2 2-5
- conventions, document x

**CoS**

- overview 2-33
- values range 2-33

**D**

- default configuration
  - VLANs 2-22
  - VMPS 4-5
  - VTP 2-8
- disable trunking on a port 3-7
- document conventions x
- Documentation CD-ROM ix
- domains, for VLAN management 2-2
- DTP 3-4
- Dynamic ISL (DISL) 3-4
- dynamic port VLAN membership
  - configuring 4-6
  - example 4-12
  - overview 4-3
  - reconfirming 4-9, 4-10
  - troubleshooting 4-10
- Dynamic Trunk Protocol (DTP) 3-4

**E**

- egress port scheduling 2-34
  - transmit queues 2-35
- encapsulation 2-33

**F**

- Fast Ethernet trunks 3-2
- FDDI VLAN defaults and ranges 2-23

FDDI-Net defaults and ranges 2-24  
feedback to Cisco Systems, web ix

## G

Gigabit Ethernet trunks 3-2

## H

help, for manager software 1-3  
hosts, limit on dynamic port 4-10

## I

IEEE 802.1p 1-1  
IEEE 802.1Q  
    configuration considerations 3-2  
    overview 3-2  
    trunk port 3-4  
ingress port scheduling 2-34  
Inter-Switch Link, see ISL  
IP subnetworks and VLANs 2-20  
ISL  
    configuring 3-4  
    overview 3-2

## L

limit of hosts on dynamic ports 4-10  
load sharing  
    via STP path cost 3-13  
    via STP port priorities 3-9

## M

management options  
    Cisco View 1-3  
    Cisco Visual Switch Manager Software 1-3  
    CLI 1-3  
    SNMP 1-3  
member switches  
    accessing CLI 2-31, 3-4  
    in VMPS 4-1  
membership mode 2-19  
modes, VTP  
    client 2-3  
    server 2-3  
    transitions 2-3  
    transparent 2-3

## N

NCPs 5-4  
Network Control Protocols (NCPs) 5-4  
network port 3-20  
note, description xi

## P

parallel links 3-8  
passwords, from a TACACS+ server 5-1  
path cost 3-13  
Point to Point Protocol (PPP) 5-4  
port grouping with trunks 3-20  
port monitoring conflicts with trunks 3-20  
port priorities 3-9  
PortFast STP parameter 4-4

## ports

- dynamic access 2-19
  - dynamic VLAN membership
    - configuring 4-6
    - example 4-12
    - overview 4-3
    - reconfirming 4-9, 4-10
  - multi-VLAN 2-19
  - static-access 2-19
  - trunks 2-19, 3-2
  - VLAN assignments 2-31
- PPP 5-4
- pruning, VTP 2-6

## Q

### QoS

- CoS value ranges 2-33
  - egress port scheduling 2-34
    - transmit queues 2-35
  - ingress port scheduling 2-34
  - overview 2-32
  - port priority
    - displaying information about 2-36
    - frame types 2-33
    - setting 2-36
    - support 1-1
- Quality of Service (QoS) 1-1

## R

### redundancy

- via STP path cost 3-13
  - via STP port priorities 3-9
  - via STP UplinkFast 3-18
- remove vlan-list parameter 3-6

## S

- secure ports 3-20
- security in TACACS+ 5-2
- Serial Line Internet Protocol (SLIP) 5-4
- server mode, VTP 2-3
- show interface command 2-36
- Simple Network Protocol
  - see SNMP
- SLIP 5-4
- SNMP 1-3
- software upgrade 1-2
- Spanning-Tree Protocol
  - see STP
- standard edition software, switches supported on 1-2
- statistics
  - VTP 2-16
- STP
  - load sharing overview 3-8
  - load sharing using path costs 3-13
  - load sharing using port priorities 3-9
  - Port Fast parameter 4-4
  - port grouping parameters 3-20
  - switchport command 3-4
  - switchport priority default command 2-36

## T

### TACACS+

- AAA accounting commands 5-5
- AAA authorization commands 5-4
- creating a TACACS+ server 5-5
- initializing 5-3, 5-7
- tacacs-server host command 5-5, 5-6
- tacacs-server retransmit command 5-6, 5-7
- tacacs-server timeout command 5-6

- Token Ring VLANs
  - overview 2-21
  - TrBRF 2-5
  - TrCRF 2-5
- transparent mode, VTP 2-3
- trunks
  - allowed VLANs 3-6
  - and port grouping 3-20
  - and port monitoring 3-20
  - ATM 3-20
  - blocking unknown packets on 3-20
  - configuration conflicts 3-20
  - configured as network port 3-20
  - configuring 3-4
  - disabling 3-7
  - Gigabit 3-2
  - IEEE 802.1Q 3-2
  - interacting with other features 3-20
  - ISL 3-2
  - load sharing using STP path costs 3-13
  - load sharing using STP port priorities 3-9
  - overview 3-2
  - parallel 3-13
  - VLANs, allowed 3-6

## U

- unknown unicast and multicast packets 3-20
- Unrecognized Type-Length-Value (TLV) support 2-5
- URLs for reaching Cisco ix

## V

- Version-Dependent Transparent Mode 2-5
- VLAN Management Policy Server
  - see VMPS
- VLAN Query Protocol (VQP) 4-2

- VLANs
  - 802.1Q considerations 3-2
  - adding 2-26
  - allowed on trunk 3-6
  - and Cisco Visual Switch Manager 1-3
  - and static-access ports 2-27
  - assigning ports to 2-31
  - changing 2-27
  - configuration guidelines 2-22
  - default configuration 2-22
  - deleting 2-29
  - Ethernet 2-26
  - IP subnetworks and 2-20
  - ISL 3-2
  - maximum number of 1-2
  - membership modes 2-19
  - menu items 1-3
  - overview 2-18
  - ports, assigning to 2-31
  - Token Ring 2-21
  - trunks
    - See trunks
    - trunks configured with other features 3-18
  - VTP domain and 2-20
  - VTP modes 2-3

## VMPS

- administering 4-7
- configuration file example 4-11
- database configuration file 4-11
- dynamic port membership
  - configuring 4-6
  - example 4-12
  - overview 4-3
  - reconfirming 4-9, 4-10
- in a cluster of switches 4-1
- monitoring 4-7
- overview 4-1
- reconfirming membership 4-10
- reconfirming membership information 4-9

## VTP

- advertisements 2-4

- client, configuring 2-11
- configuration guidelines 2-7
- consistency checks 2-5
- default configuration 2-8
- disabling 2-12
- domains 2-2
- modes
  - client 2-3
  - server 2-3
  - transparent 2-3
- monitoring 2-16
- overview 2-2
- pruning 2-6
- server, configuring 2-9
- statistics 2-16
- Token Ring support 2-5
- transparent mode, configuring 2-12
- version 1 2-5
- version 2 2-5
  - disabling 2-15
  - enabling 2-13
  - overview 2-5
- VLANs and 2-20

## **W**

World Wide Web, for providing feedback ix