

Cisco Reader Comment Card

General Information

- 1 Years of networking experience: _____ Years of experience with Cisco products: _____
- 2 I have these network types: LAN Backbone WAN
 Other: _____
- 3 I have these Cisco products: Switches Routers
 Other (specify models): _____
- 4 I perform these types of tasks: H/W installation and/or maintenance S/W configuration
 Network management Other: _____
- 5 I use these types of documentation: H/W installation H/W configuration S/W configuration
 Command reference Quick reference Release notes Online help
 Other: _____
- 6 I access this information through: _____% Cisco.com _____% CD-ROM
_____% Printed docs _____% Other: _____
- 7 I prefer this access method: _____
- 8 I use the following three product features the most:

Document Information

Document Title: Catalyst 2950 and Catalyst 2955 Switch System Message Guide

Part Number: 78-15306-01

S/W Release: Cisco IOS Release 12.1(12c)EA1

On a scale of 1-5 (5 being the best), please let us know how we rate in the following areas:

- _____ The document is written at my technical level of understanding. _____ The information is accurate.
- _____ The document is complete. _____ The information I wanted was easy to find.
- _____ The information is well organized. _____ The information I found was useful to my job

Please comment on our lowest scores:

Mailing Information

Company Name _____ Date _____

Contact Name _____ Job Title _____

Mailing Address _____

City _____ State/Province _____ ZIP/Postal Code _____

Country _____ Phone () _____ Extension _____

Fax () _____ E-mail _____

Can we contact you further concerning our documentation? Yes No

You can also send us your comments by e-mail to bug-doc@cisco.com, or by fax to 408-527-8089.

BUSINESS REPLY MAIL


FIRST-CLASS MAIL PERMIT NO. 4631 SAN JOSE CA

POSTAGE WILL BE PAID BY ADDRESSEE

DOCUMENT RESOURCE CONNECTION
CISCO SYSTEMS INC
170 WEST TASMAN DR
SAN JOSE CA 95134-9916



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES





Catalyst 2950 and Catalyst 2955 Switch System Message Guide

Cisco IOS Release 12.1(12c)EA1
February 2003

Corporate Headquarters
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
<http://www.cisco.com>
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

Customer Order Number: DOC-7815306=
Text Part Number: 78-15306-01



THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

CCIP, CCSP, the Cisco Arrow logo, the Cisco *Powered* Network mark, the Cisco Systems Verified logo, Cisco Unity, Follow Me Browsing, FormShare, iQ Breakthrough, iQ FastTrack, the iQ Logo, iQ Net Readiness Scorecard, Networking Academy, ScriptShare, SMARTnet, TransPath, and Voice LAN are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, The Fastest Way to Increase Your Internet Quotient, and iQuick Study are service marks of Cisco Systems, Inc.; and Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, the Cisco IOS logo, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherSwitch, Fast Step, GigaStack, Internet Quotient, IOS, IP/TV, iQ Expertise, LightStream, MGX, MICA, the Networkers logo, Network Registrar, *Packet*, PIX, Post-Routing, Pre-Routing, RateMUX, Registrar, SlideCast, StrataView Plus, Stratm, SwitchProbe, TeleRouter, and VCO are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries.

All other trademarks mentioned in this document or Web site are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0301R)

Catalyst 2950 and Catalyst 2955 Switch System Message Guide

Copyright © 2003, Cisco Systems, Inc.

All rights reserved.



Preface	v
Audience	v
Purpose	v
Organization	v
Conventions	vi
Related Publications	vi
Obtaining Documentation	vii
Cisco.com	vii
Documentation CD-ROM	viii
Ordering Documentation	viii
Documentation Feedback	viii
Obtaining Technical Assistance	ix
Cisco.com	ix
Technical Assistance Center	ix
Cisco TAC Website	ix
Cisco TAC Escalation Center	x
Obtaining Additional Publications and Information	x

CHAPTER 1

System Message Overview	1-1
How to Read System Messages	1-1
Error Message Traceback Reports	1-4

CHAPTER 2

Message and Recovery Procedures	2-1
CMP Messages	2-2
DOT1X Messages	2-3
DTP Messages	2-4
EC Messages	2-5
ENVIRONMENT Messages	2-8
ETHCNTR Messages	2-10
GBIC Messages	2-10
GBIC_SECURITY Messages	2-12
GIGASTACK Messages	2-14
HWMATM_MOD Messages	2-15

LINK_3 Messages 2-15

PLATFORM_CAT2950 Messages 2-16

PLATFORM_CATALYST2950 Messages 2-20

PLATFORM_CATALYST2955 Messages 2-20

PM Messages 2-21

PORT_SECURITY Messages 2-26

SPAN Messages 2-26

SPANTREE Messages 2-27

SPANTREE_FAST Messages 2-32

SPANTREE_VLAN_SWITCH Messages 2-32

STORM_CONTROL Messages 2-33

SW_VLAN Messages 2-33

UDLD Messages 2-38

UFAST_MCAST_SW Messages 2-39

APPENDIX A

Security and QoS Configuration Messages A-1

INDEX



Preface

Audience

This guide is for the networking professional managing the Catalyst 2950 and Catalyst 2955 switches, hereafter referred to as *the switch*. Before using this guide, you should have experience working with the Cisco IOS and the switch software features.

Purpose

This guide describes only the Catalyst 2950-specific and Catalyst 2955-specific system messages that you might encounter. For a complete list of Cisco IOS system error messages, refer to the *Cisco IOS Software System Error Messages, Cisco IOS Release 12.1*.

This guide does not describe how to install your switch or how to configure software features on your switch. It also does not provide detailed information about commands that have been created or changed for use by the switch. For hardware installation information, refer to the hardware installation guide that shipped with your switch. For software information, refer to the software configuration guide and the command reference for this release.

Organization

This guide is organized into these chapters:

- [Chapter 1, “System Message Overview,”](#) describes how to read the system messages, defines the facility code definitions, and lists the message severity levels.
- [Chapter 2, “Message and Recovery Procedures,”](#) describes the messages and recovery procedures.
- [Appendix A, “Security and QoS Configuration Messages”](#) describes the messages for configuring network security with access control lists (ACLs) and for configuring quality of service (QoS).

Conventions

This publication uses these conventions to convey instructions and information:

Command descriptions use these conventions:

- Commands and keywords are in **boldface** text.
- Arguments for which you supply values are in *italic*.
- Square brackets ([]) mean optional elements.
- Braces ({ }) group required choices, and vertical bars (|) separate the alternative elements.
- Braces and vertical bars within square brackets ([{ | }]) mean a required choice within an optional element.

Interactive examples use these conventions:

- Terminal sessions and system displays are in `screen` font.
- Information you enter is in **boldface screen** font.
- Nonprinting characters, such as passwords or tabs, are in angle brackets (< >).

Notes use this convention and symbol:



Note

Means *reader take note*. Notes contain helpful suggestions or references to materials not in this manual.

Related Publications

These documents provide complete information about the switch and are available from this URL:

<http://www.cisco.com/univercd/cc/td/doc/product/lan/cat2950/index.htm>

You can order printed copies of documents with a DOC-xxxxxx= number from the Cisco.com sites and from the telephone numbers listed in the “[Obtaining Documentation](#)” section on page [Boilerplate 1](#).

Release Notes for the Catalyst 2950 and Catalyst 2955 Switch are not orderable but are available on Cisco.com for each release.



Note

Switch requirements and procedures for initial configurations and software upgrades tend to change and therefore appear only in the release notes. Before installing, configuring, or upgrading the switch, refer to the release notes on Cisco.com for the latest information.

For hardware information for the Catalyst 2950 and Catalyst 2955 switches, refer to these documents:

- *Catalyst 2955 Hardware Installation Guide* (order number DOC-7814944=)
- *Catalyst 2950 Desktop Switch Hardware Installation Guide* (order number DOC-7811157=)

For software information for Release 12.1(12c)EA1, refer to these documents:

- *Catalyst 2950 and Catalyst 2955 Switch Software Configuration Guide* (order number DOC-7815303=)
- *Catalyst 2950 and Catalyst 2955 Switch Command Reference* (order number DOC-7815304=)
- *Catalyst 2950 and Catalyst 2955 Desktop Switch System Message Guide* (order number DOC-7815306=)

For software information for earlier software releases for the Catalyst 2950 switch, refer to these documents:

- *Catalyst 2950 Desktop Switch Software Configuration Guide* (order number DOC-7811380=)
- *Catalyst 2950 Desktop Switch Command Reference* (order number DOC-7811381=)
- *Catalyst 2950 Desktop Switch System Message Guide* (order number DOC-7814233=)

For information about the Catalyst 2950 LRE switches, refer to information about Release 12.1(11)YJ in these documents:

- *Catalyst 2950 Desktop Switch Software Configuration Guide* (order number DOC-7814982=)
- *Catalyst 2950 Desktop Switch Command Reference* (order number DOC-7814984=)
- *Catalyst 2950 Desktop Switch System Message Guide* (order number DOC-7814981=)
- *Release Notes for the Catalyst 2950 LRE Switch, Cisco IOS Release 12.1(11)YJ* (not orderable but available on Cisco.com)

For other information about related products, refer to these documents:

- *Catalyst GigaStack Gigabit Interface Converter Hardware Installation Guide* (order number DOC-786460=)
- Cluster Management Suite (CMS) online help (available only from the switch CMS software)
- *CWDM Passive Optical System Installation Note* (not orderable but available on Cisco.com)
- *1000BASE-T Gigabit Interface Converter Installation Notes* (not orderable but available on Cisco.com)

Obtaining Documentation

Cisco provides several ways to obtain documentation, technical assistance, and other technical resources. These sections explain how to obtain technical information from Cisco Systems.

Cisco.com

You can access the most current Cisco documentation on the World Wide Web at this URL:

<http://www.cisco.com/univercd/home/home.htm>

You can access the Cisco website at this URL:

<http://www.cisco.com>

International Cisco web sites can be accessed from this URL:

http://www.cisco.com/public/countries_languages.shtml

Documentation CD-ROM

Cisco documentation and additional literature are available in a Cisco Documentation CD-ROM package, which may have shipped with your product. The Documentation CD-ROM is updated monthly and may be more current than printed documentation. The CD-ROM package is available as a single unit or through an annual subscription.

Registered Cisco.com users can order the Documentation CD-ROM (product number DOC-CONDOCCD=) through the online Subscription Store:

<http://www.cisco.com/go/subscription>

Ordering Documentation

You can find instructions for ordering documentation at this URL:

http://www.cisco.com/univercd/cc/td/doc/es_inpk/pdi.htm

You can order Cisco documentation in these ways:

- Registered Cisco.com users (Cisco direct customers) can order Cisco product documentation from the Networking Products MarketPlace:

<http://www.cisco.com/en/US/partner/ordering/index.shtml>

- Registered Cisco.com users can order the Documentation CD-ROM (Customer Order Number DOC-CONDOCCD=) through the online Subscription Store:

<http://www.cisco.com/go/subscription>

- Nonregistered Cisco.com users can order documentation through a local account representative by calling Cisco Systems Corporate Headquarters (California, U.S.A.) at 408 526-7208 or, elsewhere in North America, by calling 800 553-NETS (6387).

Documentation Feedback

You can submit comments electronically on Cisco.com. On the Cisco Documentation home page, click **Feedback** at the top of the page.

You can e-mail your comments to bug-doc@cisco.com.

You can submit your comments by mail by using the response card behind the front cover of your document or by writing to the following address:

Cisco Systems
Attn: Customer Document Ordering
170 West Tasman Drive
San Jose, CA 95134-9883

We appreciate your comments.

Obtaining Technical Assistance

Cisco provides Cisco.com, which includes the Cisco Technical Assistance Center (TAC) Website, as a starting point for all technical assistance. Customers and partners can obtain online documentation, troubleshooting tips, and sample configurations from the Cisco TAC website. Cisco.com registered users have complete access to the technical support resources on the Cisco TAC website, including TAC tools and utilities.

Cisco.com

Cisco.com offers a suite of interactive, networked services that let you access Cisco information, networking solutions, services, programs, and resources at any time, from anywhere in the world.

Cisco.com provides a broad range of features and services to help you with these tasks:

- Streamline business processes and improve productivity
- Resolve technical issues with online support
- Download and test software packages
- Order Cisco learning materials and merchandise
- Register for online skill assessment, training, and certification programs

To obtain customized information and service, you can self-register on Cisco.com at this URL:

<http://www.cisco.com>

Technical Assistance Center

The Cisco TAC is available to all customers who need technical assistance with a Cisco product, technology, or solution. Two levels of support are available: the Cisco TAC website and the Cisco TAC Escalation Center. The avenue of support that you choose depends on the priority of the problem and the conditions stated in service contracts, when applicable.

We categorize Cisco TAC inquiries according to urgency:

- Priority level 4 (P4)—You need information or assistance concerning Cisco product capabilities, product installation, or basic product configuration.
- Priority level 3 (P3)—Your network performance is degraded. Network functionality is noticeably impaired, but most business operations continue.
- Priority level 2 (P2)—Your production network is severely degraded, affecting significant aspects of business operations. No workaround is available.
- Priority level 1 (P1)—Your production network is down, and a critical impact to business operations will occur if service is not restored quickly. No workaround is available.

Cisco TAC Website

You can use the Cisco TAC website to resolve P3 and P4 issues yourself, saving both cost and time. The site provides around-the-clock access to online tools, knowledge bases, and software. To access the Cisco TAC website, go to this URL:

<http://www.cisco.com/tac>

All customers, partners, and resellers who have a valid Cisco service contract have complete access to the technical support resources on the Cisco TAC website. Some services on the Cisco TAC website require a Cisco.com login ID and password. If you have a valid service contract but do not have a login ID or password, go to this URL to register:

<http://tools.cisco.com/RPF/register/register.do>

If you are a Cisco.com registered user, and you cannot resolve your technical issues by using the Cisco TAC website, you can open a case online at this URL:

<http://www.cisco.com/en/US/support/index.html>

If you have Internet access, we recommend that you open P3 and P4 cases through the Cisco TAC website so that you can describe the situation in your own words and attach any necessary files.

Cisco TAC Escalation Center

The Cisco TAC Escalation Center addresses priority level 1 or priority level 2 issues. These classifications are assigned when severe network degradation significantly impacts business operations. When you contact the TAC Escalation Center with a P1 or P2 problem, a Cisco TAC engineer automatically opens a case.

To obtain a directory of toll-free Cisco TAC telephone numbers for your country, go to this URL:

<http://www.cisco.com/warp/public/687/Directory/DirTAC.shtml>

Before calling, please check with your network operations center to determine the level of Cisco support services to which your company is entitled: for example, SMARTnet, SMARTnet Onsite, or Network Supported Accounts (NSA). When you call the center, please have available your service agreement number and your product serial number.

Obtaining Additional Publications and Information

Information about Cisco products, technologies, and network solutions is available from various online and printed sources.

- The *Cisco Product Catalog* describes the networking products offered by Cisco Systems as well as ordering and customer support services. Access the *Cisco Product Catalog* at this URL:

http://www.cisco.com/en/US/products/products_catalog_links_launch.html

- Cisco Press publishes a wide range of networking publications. Cisco suggests these titles for new and experienced users: *Internetworking Terms and Acronyms Dictionary*, *Internetworking Technology Handbook*, *Internetworking Troubleshooting Guide*, and the *Internetworking Design Guide*. For current Cisco Press titles and other information, go to Cisco Press online at this URL:

<http://www.ciscopress.com>

- *Packet* magazine is the Cisco monthly periodical that provides industry professionals with the latest information about the field of networking. You can access *Packet* magazine at this URL:

http://www.cisco.com/en/US/about/ac123/ac114/about_cisco_packet_magazine.html

- *iQ Magazine* is the Cisco monthly periodical that provides business leaders and decision makers with the latest information about the networking industry. You can access *iQ Magazine* at this URL:

http://business.cisco.com/prod/tree.taf%3fasset_id=44699&public_view=true&kbns=1.html

- *Internet Protocol Journal* is a quarterly journal published by Cisco Systems for engineering professionals involved in the design, development, and operation of public and private internets and intranets. You can access the *Internet Protocol Journal* at this URL:

http://www.cisco.com/en/US/about/ac123/ac147/about_cisco_the_internet_protocol_journal.html

- Training—Cisco offers world-class networking training, with current offerings in network training listed at this URL:

http://www.cisco.com/en/US/learning/le31/learning_recommended_training_list.html



System Message Overview

This guide describes the Catalyst 2950-specific and Catalyst 2955-specific system messages. During operation, the system software sends these messages to the console (and, optionally, to a logging server on another system). Not all system messages indicate problems with your system. Some messages are purely informational, whereas others can help diagnose problems with communications lines, internal hardware, or the system software. This guide also includes error messages that appear when the system fails.

This chapter contains these sections:

- [How to Read System Messages, page 1-1](#)
- [Error Message Traceback Reports, page 1-4](#)



Note

This software release does not support the Catalyst 2950 LRE switches. For information about these switches, refer to the Catalyst 2950 LRE switch release notes.

How to Read System Messages

System messages begin with a percent sign (%) and are structured as follows:

%FACILITY-SEVERITY-MNEMONIC: Message-text

- FACILITY is a code consisting of two or more uppercase letters that show the facility to which the message refers. A facility can be a hardware device, a protocol, or a module of the system software. [Table 1-1](#) lists the system facility codes.

Table 1-1 Facility Codes

Facility Code	Description	Location
CMP	Cluster Membership Protocol	“CMP Messages” section on page 2-2
DOT1X	802.1X authentication	“DOT1X Messages” section on page 2-3
DTP	Dynamic Trunking Protocol	“DTP Messages” section on page 2-4
EC	EtherChannel	“EC Messages” section on page 2-5

Table 1-1 Facility Codes (continued)

Facility Code	Description	Location
ENVIRONMENT	Environment	“ENVIRONMENT Messages” section on page 2-8
ETHCNTR	Ethernet controller	“ETHCNTR Messages” section on page 2-10
GBIC	Gigabit Interface Converter (GBIC) module identification and validation	“GBIC Messages” section on page 2-10
GBIC_SECURITY	GBIC module security	“GBIC_SECURITY Messages” section on page 2-12
GIGASTACK	GigaStack GBIC module	“GIGASTACK Messages” section on page 2-14
HWMATM_MOD	Hardware MAC address table manager	“HWMATM_MOD Messages” section on page 2-15
LINK_3	Fast Ethernet link-specific messages	“LINK_3 Messages” section on page 2-15
PLATFORM_CAT2950	Application-specific integrated circuit (ASIC) for Catalyst 2950 switches.	“PLATFORM_CAT2950 Messages” section on page 2-16
PLATFORM_CATALYST2950	Low-level platform	“PLATFORM_CATALYST2950 Messages” section on page 2-20
PLATFORM_CATALYST2955	Application-specific integrated circuit (ASIC) for Catalyst 2955 switches.	“PLATFORM_CATALYST2955 Messages” section on page 2-20
PM	Port manager	“PM Messages” section on page 2-21
PORT_SECURITY	Port security	“PORT SECURITY Messages” section on page 2-26
SPAN	Switched Port Analyzer (SPAN)	“SPAN Messages” section on page 2-26
SPANTREE	Spanning tree	“SPANTREE Messages” section on page 2-27
SPANTREE_FAST	Spanning-tree fast convergence	“SPANTREE_FAST Messages” section on page 2-32
SPANTREE_VLAN_SW	Spanning-tree VLAN switch	“SPANTREE_VLAN_SWITCH Messages” section on page 2-32
STORM_CONTROL	Storm control	“STORM_CONTROL Messages” section on page 2-33
SW_VLAN	VLAN manager	“SW_VLAN Messages” section on page 2-33

Table 1-1 Facility Codes (continued)

Facility Code	Description	Location
UDLD	UniDirectional Link Detection (UDLD)	“UDLD Messages” section on page 2-38
UFAST_MCAST_SW	UplinkFast multicast software	“UFAST_MCAST_SW Messages” section on page 2-39

- SEVERITY is a single-digit code from 0 to 7 that reflects the severity of the condition. The lower the number, the more serious the situation. [Table 1-2](#) lists the message severity levels.
- MNEMONIC is a code that uniquely identifies the message.

Table 1-2 Message Severity Levels

Severity Level	Description
0 – emergency	System is unusable.
1 – alert	Immediate action required.
2 – critical	Critical condition.
3 – error	Error condition.
4 – warning	Warning condition.
5 – notification	Normal but significant condition.
6 – informational	Informational message only.
7 – debugging	Message that appears during debugging only.

- Message-text is a text string describing the condition. This portion of the message sometimes contains detailed information about the event, including terminal port numbers, network addresses, or addresses that correspond to locations in the system memory address space. Because the information in these variable fields changes from message to message, it is represented here by short strings enclosed in square brackets ([]). A decimal number, for example, is represented as [dec]. [Table 1-3](#) lists the variable fields in messages.

Table 1-3 Representation of Variable Fields in Messages

Representation	Type of Information
[dec]	Decimal integer
[char]	Single character
[chars]	Character string
[enet]	Ethernet address (for example, 0000.FEED.00C0)
[hex]	Hexadecimal integer
[inet]	Internet address

This is a sample system message:

```
%EC-5-UNBUNDLE:Interface Gi0/9 left the port-channel Po2
```

The messages in [Chapter 2, “Message and Recovery Procedures,”](#) are described in alphabetical order by facility code with the most severe (lowest number) errors described first.

Error Message Traceback Reports

Some messages describe internal errors and contain traceback information. This information is very important and should be included when you report a problem to your technical support representative.

This sample message includes traceback information:

```
-Process= "Exec", level= 0, pid= 17  
-Traceback= 1A82 1AB4 6378 A072 1054 1860
```



Message and Recovery Procedures

This chapter describes the switch system messages in alphabetical order by facility. Within each facility, the messages are listed by severity levels 0 to 7: 0 is the highest severity level, and 7 is the lowest severity level. Each message is followed by an explanation and a recommended action.



Note

The messages listed in this chapter do not include the date/time stamp designation that displays only if the software is configured for system log messaging.

This chapter contains these message categories:

- [CMP Messages, page 2-2](#)
- [DOT1X Messages, page 2-3](#)
- [DTP Messages, page 2-4](#)
- [EC Messages, page 2-5](#)
- [ENVIRONMENT Messages, page 2-8](#)
- [ETHCNTR Messages, page 2-10](#)
- [GBIC Messages, page 2-10](#)
- [GBIC_SECURITY Messages, page 2-12](#)
- [GIGASTACK Messages, page 2-14](#)
- [HWMATM_MOD Messages, page 2-15](#)
- [LINK_3 Messages, page 2-15](#)
- [PLATFORM_CAT2950 Messages, page 2-16](#)
- [PLATFORM_CATALYST2950 Messages, page 2-20](#)
- [PLATFORM_CATALYST2955 Messages, page 2-20](#)
- [PM Messages, page 2-21](#)
- [PORT SECURITY Messages, page 2-26](#)
- [SPAN Messages, page 2-26](#)
- [SPANTREE Messages, page 2-27](#)
- [SPANTREE_FAST Messages, page 2-32](#)
- [SPANTREE_VLAN_SWITCH Messages, page 2-32](#)
- [STORM_CONTROL Messages, page 2-33](#)

- [SW_VLAN Messages, page 2-33](#)
- [UDLD Messages, page 2-38](#)
- [UFAST_MCAST_SW Messages, page 2-39](#)

CMP Messages

This section contains the Cluster Membership Protocol (CMP) messages.

Error Message `CMP-5-ADD: The Device is added to the cluster (Cluster Name:[chars], CMDR IP Address [inet]).`

Explanation This message means that the device is added to the cluster. [chars] is the cluster name, and [inet] is the Internet address of the command switch.

Recommended Action No action is required.

Error Message `CMP-5-MEMBER_CONFIG_UPDATE: Received member configuration from member [dec].`

Explanation This message means that the active or standby command switch received a member configuration. [dec] is the member number of the sender.

Recommended Action No action is required.

Error Message `CMP-5-MGMT_VLAN_CHNG: The management vlan has been changed to [dec].`

Explanation This message means that the management VLAN has changed. [dec] is the new management VLAN number.

Recommended Action No action is required.

Error Message `CMP-5-REMOVE: The Device is removed from the cluster (Cluster Name:[chars]).`

Explanation This message means that the device is removed from the cluster. [chars] is the cluster name.

Recommended Action No action is required.

DOT1X Messages

This section contains the 802.1X authorization messages.

Error Message DOT1X_MOD-3-NULLPTR: Unexpected null pointer in [chars] at [dec].

Explanation This message means that an internal software error occurred. [chars] is the software filename, and [dec] is the line number in the file.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message DOT1X-3-ROUTEDPORT: Received vlan id ([dec]) from RADIUS for routed port [chars].

Explanation This message means that during 802.1X authorization, the RADIUS server provided a VLAN ID for a routed port.

Recommended Action Remove the VLAN ID in the RADIUS configuration, or configure the port as an access port.

Error Message DOT1X-3-VLANINVALID: Received invalid vlan ([dec]) from RADIUS for [chars].

Explanation This message means that during 802.1X authentication, the RADIUS server provided a VLAN ID that is not configured on the switch.

Recommended Action Change the VLAN ID in the RADIUS configuration, or configure the VLAN on the switch.

Error Message DOT1X-3-VLANMALFORMED: Received malformed vlan from RADIUS for [chars].

Explanation This message means that during 802.1X authorization, the RADIUS server provided an invalid VLAN ID.

Recommended Action Correct the VLAN ID in the RADIUS configuration.

Error Message DOT1X-3-VOICEVLAN: Received voice vlan ([dec]) from RADIUS for [chars].

Explanation This message means that during 802.1X authorization, the RADIUS server provided a VLAN ID that conflicts with the voice VLAN ID on the port.

Recommended Action Change the VLAN ID in the RADIUS configuration, or change the voice VLAN on the switch port.

DTP Messages

This section contains the Dynamic Trunking Protocol (DTP) messages.

Error Message DTP-4-MEM_UNAVAIL: Memory was not available to perform the trunk negotiation action.

Explanation This message means that the system is unable to negotiate trunks because of a lack of memory.

Recommended Action Reduce other system activity to ease the memory demands.

Error Message DTP-4-TMRERR: An internal timer error occurred when trunking on interface [chars].

Explanation This message means that a timer used by the trunking protocol unexpectedly expired. [chars] is the trunked interface.

Recommended Action This error is internally corrected, and no long-term ramifications exist. However, if more problems with trunking occur, reload the switch by using the **reload** privileged EXEC command.

Error Message DTP-4-UNKN_ERR: An unknown operational error occurred.

Explanation This message means that the system is unable to negotiate trunks because an internal operation generated an unexpected error.

Recommended Action Reload the switch by using the **reload** privileged EXEC command.

Error Message DTP-5-ILGLCFG: Illegal config (on, isl--on, dot1q) on [chars].

Explanation This message means that one end of the trunk is configured as ON, ISL, and the other end is configured as ON, 802.1Q. [chars] is the interface.

Recommended Action This configuration is illegal and will not establish a trunk between two switches. You must change the encapsulation type so that both ends of the trunk match.

Error Message DTP-5-NONTRUNKPORTON: Port [chars] has become non-trunk.

Explanation This message means that the interface changed from trunk to access. [chars] is the interface that changed.

Recommended Action This message is provided for information only.

Error Message DTP-5-TRUNKPORTCHG: Port [chars] has changed from [chars] trunk to [chars] trunk.

Explanation This message means that the encapsulation type of the trunk has changed. The first [chars] is the interface, the second [chars] is the original encapsulation type, and the third [chars] is the new encapsulation type.

Recommended Action This message is provided for information only.

Error Message DTP-5-TRUNKPORTON: Port [chars] has become [chars] trunk.

Explanation This message means that the interface changed from an access to a trunk. The first [chars] is the interface, and the second [chars] is the encapsulation.

Recommended Action This message is provided for information only.

EC Messages

This section contains the EtherChannel, Link Aggregation Control Protocol (LACP), and Port Aggregation Protocol (PAgP) messages.

Error Message EC-4-NOMEM: Not enough memory available for [chars].

Explanation This message means that either the LACP or the PAgP EtherChannel could not obtain the memory it needed to initialize the required data structures. [chars] is the name of the data structure.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message EC-5-BUNDLE: Interface [chars] joined port-channel [chars].

Explanation This message means that the listed interface joined the specified EtherChannel. The first [chars] is the physical interface, and the second [chars] is the EtherChannel interface.

Recommended Action No action is required.

Error Message %EC-5-CANNOT_ALLOCATE_AGGREGATOR: Aggregator limit reached, cannot allocate aggregator for group [dec].

Explanation This message means that the aggregator cannot be allocated in the group.

Recommended Action Change the port attributes of the ports in the group so that they match and join the same aggregator.

Error Message EC-5-CANNOT_BUNDLE_LACP: [chars] is not compatible with aggregators in channel [dec] and cannot attach to them ([chars]).

Explanation This message means that the port has port attributes that are different from the port channel or ports within the port channel.

Recommended Action Change the port attributes so that they match the other ports in the EtherChannel.

Error Message EC-5-CANNOT_BUNDLE1: Port-channel [chars] is admin-down, port [chars] will remain stand-alone.

Explanation This message means that the EtherChannel is administratively shut down. The first [chars] is the EtherChannel interface, and the second [chars] is the physical interface.

Recommended Action Enable the EtherChannel by using the **no shutdown** interface configuration command.

Error Message EC-5-CANNOT_BUNDLE2: [chars] is not compatible with [chars] and will be suspended ([chars]).

Explanation This message means that the interface has different interface attributes than other ports in the EtherChannel. For the interface to join the bundle (EtherChannel), change the interface attributes to match the EtherChannel attributes. The first [chars] is the interface to be bundled, the second [chars] is the physical interface that is already in the bundle, and the third [chars] is the reason for the incompatibility.

Recommended Action Change the interface attributes to match the EtherChannel attributes.

Error Message %EC-5-ERRPROT: Channel protocol mismatch for interface [chars] in group [dec]: the interface cannot be added to the channel group.

Explanation This message means that the interface cannot be added to the channel group by using the specified mode.

Recommended Action Change the channel group or the mode for the interface.

Error Message %EC-5-ERRPROT2: Command rejected: the interface [chars] is already part of a channel with a different type of protocol enabled.

Explanation This message means that the interface cannot be selected for the specified protocol because it is already part of an EtherChannel group with a different protocol enabled.

Recommended Action Remove the interface from the EtherChannel group.

Error Message %EC-5-ERRPROT3: Command rejected: the interface [chars] is already part of a channel.

Explanation This message means that the interface cannot be unselected for the specified protocol because it is already part of an EtherChannel group.

Recommended Action Remove the interface from the EtherChannel group.

Error Message %EC-5-L3DONTBNL3: [chars] suspended: LACP not enabled on the remote port.

Explanation This message means that LACP is enabled on a Layer 3 interface, but the remote port does not have LACP enabled. In this mode, the local port is put in a suspended state.

Recommended Action Enable LACP on the remote port.

Error Message %EC-5-NOLACP: Invalid EC mode. LACP not enabled.

Explanation This message means that LACP is not included in the image on your switch. An EtherChannel cannot be set into any LACP mode.

Recommended Action Upgrade your switch with an image that supports LACP.

Error Message EC-5-NOPAGP: Invalid EC mode. PAGP not enabled.

Explanation This message means that PAGP is not included in the IOS image and that the EtherChannel mode cannot be set to **desirable** or **auto**.

Recommended Action Obtain an image with PAGP included, or set the mode to **on** by using the **channel-group** *channel-group-number* **mode on** interface configuration command.

Error Message %EC-5-STAYDOWN: no-shut not allowed on [chars]. Module [dec] not online.

Explanation This message means that an interface with an EtherChannel configuration cannot be enabled by using the **no shut** interface configuration command. It is already a member of an EtherChannel group, and that EtherChannel group has been administratively shut down. The interface has an EtherChannel configuration, but no information is available yet about its port channel.

Recommended Action No action is required. Wait until the module is online to determine the port-channel setting of the EtherChannel.

Error Message EC-5-UNBUNDLE: Interface [chars] left the port-channel [chars].

Explanation This message means that the listed interface left the specified EtherChannel. The first [chars] is the physical interface, and the second [chars] is the EtherChannel.

Recommended Action No action is required.

Error Message EC-5-UNSUITABLE: [chars] will not join any port-channel, [chars].

Explanation This message means that one of the interfaces cannot join the EtherChannel because it is configured for PortFast, as a VLAN Membership Policy Server (VMPS), for 802.1X, as a voice VLAN, or as a Switched Port Analyzer (SPAN) destination port. All of these are unsuitable configurations for EtherChannels. The first [chars] is the interface name, and the second [chars] describes the details of the unsuitable configuration.

Recommended Action Reconfigure the port; remove the unsuitable configuration.

ENVIRONMENT Messages

This section contains the Environment message.

Error Message ENVIRONMENT-2-FAN_FAULT: FAN FAULT is detected.

Explanation This message means that an internal fan fault is detected.

Recommended Action Either check the switch itself, or use the **show env** privileged EXEC command to determine if a fan on the switch has failed. The switch can operate normally with one failed fan. Replace the switch at your convenience.

Error Message ENVIRONMENT-4-CONFIG_OVERTEMP: ASSERT MINOR Switch Temp above secondary threshold.

Explanation This message means that the temperature inside the switch exceeds the configured threshold; a minor alarm is raised.

Recommended Action No action is required.

Error Message ENVIRONMENT-4-CONFIG_OVERTEMP: CLEAR MINOR Switch Temp above secondary threshold

Explanation This message means that the temperature inside the switch is below the configured threshold; a minor alarm is cleared.

Recommended Action No action is required.

Error Message ENVIRONMENT-3-OVERTEMP: ASERT MAJOR Switch Temp above max primary threshold.

Explanation This message means that the temperature inside the switch exceeds the maximum primary threshold; a major alarm is raised.

Recommended Action No action is required.

Error Message ENVIRONMENT-3-OVERTEMP: CLEAR MAJOR Switch Temp above max primary threshold.

Explanation This message means that the temperature inside the switch is below the maximum primary threshold; a major alarm is cleared.

Recommended Action No action is required.

Error Message ENVIRONMENT-3-UNDERTEMP: ASSERT MAJOR Switch Temp below min primary threshold.

Explanation This message means that the temperature inside the switch is below the minimum primary threshold; a major alarm is raised.

Recommended Action No action is required.

Error Message ENVIRONMENT-3-UNDERTEMP: CLEAR MAJOR Switch Temp below min primary threshold.

Explanation This message means that the temperature inside the switch is above the minimum primary threshold; a major alarm is cleared.

Recommended Action No action is required.

Error Message ENVIRONMENT-3-RPS_FAILED: ASSERT MAJOR Switch Redundant Pwr missing or failed.

Explanation This message means that the redundant power supply is missing or has failed; a major alarm is raised.

Recommended Action No action is required.

Error Message ENVIRONMENT-3-RPS_FAILED: CLEAR MAJOR Switch Redundant Pwr missing or failed.

Explanation This message means that the redundant power supply is no longer missing nor failed; a major alarm is cleared.

Recommended Action No action is required.

ETHCNTR Messages

This section contains the Ethernet controller messages. These messages are a result of a failure of the switch software when trying to program the hardware. Most of these errors lead to incorrect switch behavior, and you should call your Cisco technical support representative.

Error Message ETHCNTR-3-HALF_DUX_COLISION_EXCEED_THRESHOLD: Collision at [chars] exceed threshold. Consider as loop-back.

Explanation This message means that the collision at a half-duplex port exceeded the threshold and that the port is considered to be in the loop-back state. [chars] is the port.

Recommended Action No action is required.

Error Message ETHCNTR-3-LOOP_BACK_DETECTED: , Loop-back detected on [chars]. The port is forced to linkdown.

Explanation This message means that the loop-back condition might be caused by a balun cable being accidentally plugged into the port. [chars] is the port.

Recommended Action Check the cables. If a balun cable is connected and the loopback condition is desired, no action is required. Otherwise, connect the correct cable, and bring the port up by entering the **no shutdown** interface configuration command.

GBIC Messages

This section contains Gigabit Interface Converter (GBIC) module identification and validation messages. When a GBIC module is inserted into the switch, the software reads information from the module that identifies its type, and for some types of GBIC modules, obtains additional information to validate the compatibility of the module.

Error Message GBIC_1000BASE-T-6-GBIC_1000BASE-T_DEFAULT_CONFIG: 1000BASE-T GBIC module is detected in [chars]. Speed and duplex will be autonegotiated.

Explanation This message means that a 1000BASE-T GBIC module is detected in the slot, and its speed and duplex are automatically autonegotiated. [chars] is the slot in which the module is installed.

Recommended Action No action is required.

Error Message GBIC_1000BASE-T-6-GBIC_1000BASE-T_NO_CONFIG_NEGOTIATE: Configuration ignored. 1000BASE-T GBIC modules only support autonegotiation.

Explanation This message means that the disabling of autonegotiation is ignored. The 1000BASE-T GBIC modules support autonegotiation.

Recommended Action No action is required.

Error Message GBIC-4-CHECK_SUM_FAILED: GBIC EEPROM data check sum failed for GBIC interface [chars].

Explanation This message means that the GBIC module was identified as a Cisco GBIC module, but the system was unable to read vendor-data information to verify its accuracy. [chars] is the interface in which the module is installed.

Recommended Action Remove and re-insert the GBIC module. If it continues to fail after re-insertion, it might be defective.

Error Message GBIC-4-NOREAD_VNAME: Unable to read vendor name for GBIC interface [chars].

Explanation This message means that the GBIC module was identified as a Cisco GBIC module, but the system was unable to read the GBIC vendor name. [chars] is the interface in which the module is installed.

Recommended Action Remove and re-insert the GBIC module. If it continues to fail after re-insertion, it might be defective.

Error Message GBIC-4-NOREAD_VSDATA: Unable to read vendor-specific data for GBIC interface [chars].

Explanation This message means that the GBIC module was identified as a Cisco GBIC module, but the system was unable to read the identifying vendor-specific information to verify its authenticity. [chars] is the interface in which the module is installed.

Recommended Action Remove and re-insert the GBIC module. If it continues to fail after re-insertion, it might be defective.

Error Message GBIC-4-NOREAD_VSERNUM: Unable to read serial number for GBIC interface [chars].

Explanation This message means that the GBIC module was identified as a Cisco GBIC module, but the system was unable to read the serial number of the GBIC module. [chars] is the interface in which the module is installed.

Recommended Action Remove and re-insert the GBIC module. If it continues to fail after re-insertion, it might be defective.

Error Message GBIC-4-UNRECOGNIZED_EXTTYPE: GBIC interface [chars] has unrecognized extended type.

Explanation This message means that the GBIC module was identified as a Cisco GBIC module, but the system does not recognize its reported extended type code. [chars] is the interface in which the module is installed.

Recommended Action Check the list of supported GBIC modules for this version of the system software. An upgrade might be required for newer GBIC modules. Even if the module is unrecognized, it might still operate properly, perhaps with limited functionality.

Error Message GBIC-4-XCVR_INTERR: Internal error occurred in setup for GBIC interface [chars].

Explanation This message means that the system could not allocate resources or had some other problem during the setup for the specified GBIC interface. [chars] is the interface in which the GBIC module is installed.

Recommended Action Reload the switch by using the **reload** privileged EXEC command. If the problem persists, call your Cisco technical support representative.

Error Message GBIC-6-SERDES_MODULE_UNKNOWN: Unrecognizable GBIC found in [chars] (module mask [hex]).

Explanation This message means that the GBIC module presented data to the system that did not correctly identify the type of the GBIC module. The switch will handle it as a generic GBIC module. [chars] is the name of the interface in which the unknown module is installed, and [hex] is the module type value returned by the module.

Recommended Action If the GBIC module fails to become operational, carefully remove and re-insert it in the slot. If it continues to fail after re-insertion, it might be defective or incompatible with the switch.

Error Message GBIC-6-SERDES_SERIAL_INV_DATA: Unrecognizable GBIC found in [chars] (serial data [hex]).

Explanation This message means that the GBIC module presented data to the system that did not correctly identify the type of the GBIC module. The switch will handle it as a generic GBIC module. [chars] is the name of the interface where the unrecognizable module is found, and [hex] is the data value returned by the module.

Recommended Action If the GBIC module fails to become operational, carefully remove and re-insert it in the slot. If it continues to fail after re-insertion, it might be defective or incompatible with the switch.

GBIC_SECURITY Messages

This section contains the Cisco GBIC module security messages. The GBIC modules have a serial EEPROM that contains the serial number, security code, and cyclic redundancy check (CRC). When the GBIC module is inserted into the switch, the software reads the EEPROM to recompute the security code and CRC. The software generates an error message if the CRC is invalid or if the recomputed security code does not match the one stored in the EEPROM.

Error Message GBIC_SECURITY-4-DUPLICATE_SN: GBIC interface [chars] has the same serial number as another GBIC interface.

Explanation This message means that the GBIC module was identified as a Cisco GBIC module, but its serial number matches that of another interface on the system. [chars] is the interface in which the module is installed.

Recommended Action Cisco GBIC modules are assigned unique serial numbers. Verify that the module was obtained from Cisco or a supported vendor.

Error Message GBIC_SECURITY-4-GBIC_INTERR: Internal error occurred in setup for GBIC interface [chars].

Explanation This message means that the system could not allocate resources or had some other problem during the setup for the specified GBIC interface. [chars] is the interface in which the GBIC module is installed.

Recommended Action Reload the switch by using the **reload** privileged EXEC command. If the problem persists, call your Cisco technical support representative.

Error Message GBIC_SECURITY-4-ID_MISMATCH: Identification check failed for GBIC interface [chars].

Explanation This message means that the GBIC module was identified as a Cisco GBIC module, but the system was unable to verify its identity. [chars] is the interface in which the module is installed.

Recommended Action Check the list of supported GBIC modules for this version of the system software. An upgrade might be required for newer modules. Otherwise, verify that the module was obtained from Cisco or a supported vendor.

Error Message GBIC_SECURITY-4-UNRECOGNIZED_VENDOR: GBIC interface [chars] manufactured by an unrecognized vendor.

Explanation This message means that the GBIC module was identified as a Cisco GBIC module, but the system was unable to match its manufacturer with one of the known list of Cisco GBIC vendors. [chars] is the interface in which the module is installed.

Recommended Action Check the list of supported GBIC modules for this version of the system software. An upgrade might be required for newer modules.

Error Message GBIC_SECURITY-4-VN_DATA_CRC_ERROR: GBIC interface [chars] has bad crc.

Explanation This message means that the GBIC module was identified as a Cisco GBIC module, but it does not have a valid CRC in the EEPROM data. [chars] is the interface in which the module is installed.

Recommended Action Check the list of supported GBIC modules for this version of the system software. An upgrade might be required for newer modules. Even if unrecognized, the module might still operate properly, perhaps with limited functionality.

GIGASTACK Messages

This section contains the GigaStack GBIC module messages.

Error Message GIGASTACK-1-NO_LOOP_DETECT: The link neighbor of link [dec] of GigaStack GBIC in [chars] did not respond to the loop detection request. If loop topology is deployed, make sure all switches in the stack are running the latest software.

Explanation This message means that no acknowledgement for the loop-detection request is received from one of the links on a GigaStack GBIC module. Either the neighboring switch does not support the GigaStack GBIC loop-breaking algorithm, or the link between the two GigaStack GBIC modules is broken. Under this condition, a GigaStack loop topology is not automatically detected, and the connectivity between switches in the stack can be lost. [dec] is the link number, and [chars] is the slot number.

Recommended Action If a loop topology is used with the GigaStack GBIC module, ensure that the latest software is running on all switches in the stack. Check the GigaStack GBIC modules involved to ensure that they are functioning.

Error Message GIGASTACK-3-INIT_FAILURE: GigaStack GBIC in [chars] initialization failed.

Explanation This message means that the GigaStack GBIC module failed power-on self-test (POST). [chars] is the interface name.

Recommended Action Remove the GigaStack GBIC module, and re-insert it into the GBIC module slot.

Error Message GIGASTACK-6-LOOP_BROKEN: Link loss is detected in the GigaStack loop. Link 2 of the GigaStack GBIC in [chars] is re-enabled.

Explanation This message means that the loop formed by GigaStack GBIC modules is broken because of a link loss. Link 2 of the master loop breaker is re-enabled to replace the broken link. [chars] is the interface name.

Recommended Action No action is required.

Error Message GIGASTACK-6-LOOP_DETECTED: GigaStack GBIC in [chars] is selected as Master Loop Breaker. Link 2 of the GigaStack GBIC is disabled to break the loop.

Explanation This message means that a loop is detected in the stack, and this GigaStack GBIC module is selected as the master loop breaker. Link 2 of this GigaStack GBIC module is disabled to break the loop. [chars] is the interface name.

Recommended Action No action is required.

HWMATM_MOD Messages

This section contains the hardware MAC address table manager (HW MATM) message.

Error Message HWMATM_MOD-3-NULLPTR: Unexpected null pointer in [chars] at [dec].

Explanation This message means that an internal software error occurred. [chars] is the software filename, and [dec] is the line number in the file.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

LINK_3 Messages

This section contains the Fast Ethernet link-specific messages.

Error Message LINK-3-FCS_ERROR: ASSERT MAJOR FastEthernet0/11

Explanation This message means that the frame check sequence (FCS) error rate exceeds the configured FCS error rate threshold; a major alarm is raised.

Recommended Action No action is required.

Error Message LINK-3-FCS_ERROR: CLEAR MAJOR FastEthernet0/11

Explanation This message means that the frame check sequence (FCS) error rate is below the configured FCS error rate threshold; a major alarm is cleared.

Recommended Action No action is required.

Error Message LINK-3-LINK_FAULT: ASSERT MAJOR FastEthernet0/11 Link Fault.

Explanation This message means there is a FastEthernet link fault; a major alarm is raised.

Recommended Action No action is required.

Error Message LINK-3-LINK_FAULT: CLEAR MAJOR FastEthernet0/11 Link Fault.

Explanation This message means that a FastEthernet link fault has been cleared.

Recommended Action No action is required.

PLATFORM_CAT2950 Messages

This section contains the application-specific integrated circuit (ASIC) driver-related messages for Catalyst 2950 switches.

Error Message PLATFORM_CAT2950-3-ASIC_BIST_FAILURE: C2950 BIST failed for memory [chars] count [dec].

Explanation This message means that, during POST, the built-in memory test on the ASIC failed, which might occur because the ASIC has a defect. [chars] is the name of the ASIC memory table, and [dec] is the number of address failures in the built-in memory test.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-ASIC_INIT_FAILURE: ASIC driver initialization has failed.

Explanation This message means that one of the steps in the ASIC initialization sequence failed. This might occur because of a failure in the peripheral component interconnect (PCI) configuration setup, the Inter-IC (I2C) initialization, the built-in self-test on the ASIC, or another initialization sequence. This failure might also occur because of an ASIC defect.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-GBP_FAILURE: Unable to initialize the external packet memory.

Explanation This message means that during the switch driver initialization, there was an error in the external packet memory initialization, which might occur because of a defect in the ASIC or in the external SDRAM.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-GBP_INIT_FAILURE: GBP currently FULL or UNAVAILABLE.

Explanation This message means that, during the switch driver initialization, an error was detected in the external packet memory, which could be caused by a defect in the ASIC or in the external SDRAM.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-MEM_COPY_FAILURE: Invalid copy [dec] for table [chars].

Explanation This message means that there was an attempt to read or write an invalid copy of the switch internal memory. [dec] is the invalid copy number for the table, and [chars] is the name of the ASIC memory table.

Recommended Action If the message recurs, copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-MEM_INDEX_FAILURE: Invalid index [dec] for table [chars].

Explanation This message means that there was an attempt to access an invalid index of the switch internal memory. [dec] is the index number, and [chars] is the name of the ASIC memory table.

Recommended Action If the message recurs, copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-MEM_INIT_FAILURE: The switch memory resources could not be allocated for [chars], initialization failed.

Explanation This message means that, during the switch driver initialization, driver-related memory resources could not be allocated, which might occur because of an ASIC defect. [chars] can be *asic instance*, *switch ports*, *fast-ethernet queues*, or *gigabit queues*.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-MEM_READ_FAILURE: Read memory failed for memory [chars] at index [dec].

Explanation This message means that an attempt to read a valid location in the internal chip memory failed, which might occur because of an ASIC defect. [chars] is the name of the ASIC memory table, and [dec] is the table index.

Recommended Action If the message recurs, copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-MEM_WRITE_FAILURE: Write memory failed for memory [chars] at index [dec].

Explanation This message means that an attempt to write to a location in the internal chip memory failed, which might occur because of an invalid memory location or an ASIC defect. [chars] is the name of the ASIC memory table, and [dec] is the table index.

Recommended Action If the message recurs, copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-MIIM_OP_FAILURE: Unable to read PHY register at addr [hex] for phy id [hex].

Explanation This message means that there was a failure to read from or write to a PHY register on the switch, which might occur because of a defect in the media independent interface (MII)/Gigabit media independent interface (GMII) switch interface. The first [hex] is the register address, and the second [hex] is the PHY ID.

Recommended Action If the message recurs, copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-PCI_FIND_FAILURE: The number of asics expected were [dec], PCI bus scan found [dec].

Explanation This message means that, during the switch driver initialization, the switch found an incorrect number of ASICs on the PCI bus or did not find any ASICs with a correct PCI value. This might occur because of a system PCI bus defect or an incompatible software version running on the switch. The first [dec] is the number of ASICs that the switch should find, and the second [dec] is the actual number of ASICs that the switch found.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-PCI_INIT_FAILURE: The PCI address space initialization failed.

Explanation This message means that, during the switch driver initialization, the PCI address space for the ASIC could not be initialized, which might occur because of a system PCI-bus problem.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-REG_READ_FAILURE: Register read failed for [chars] in [chars]

Explanation This message means that the register read failed for register [chars] in [chars]. An attempt to read a valid location in the internal chip register failed. This could be due to a hardware defect.

Recommended Action Copy the message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-REG_WRITE_FAILURE: Register write failed for register [chars] in [chars]

Explanation This message means that an attempt to write to a location in the internal chip register failed. This might be caused by writing to an invalid register location or by a defect in the hardware.

Recommended Action Copy the message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-PCI_TEST_FAILURE: PCI address space test failed, Wrote [hex], read [hex], re-read [hex].

Explanation This message means that, during POST, the PCI address space for the ASIC was not mapped correctly. This might occur because of a system PCI-bus problem. The first [hex], the second [hex], and the third [hex] are test data.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-SCHAN_OP_FAILURE: S-channel operation timeout for opcode [chars].

Explanation This message means that there was a failure to read or write to an ASIC register or a memory location because of an ASIC internal bus failure. [chars] is the operation code.

Recommended Action If the message recurs, copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-SCHAN_READ_REG_FAILURE: S-channel operation read register failure at addr [hex].

Explanation This message means that there was a failure to read the ASIC registers, which might occur because of an invalid register address or internal bus failure. [hex] is the register address.

Recommended Action If the message recurs, copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CAT2950-3-SYSTEM_INFO_FAILURE: The board information could not be read correctly, initialization failed.

Explanation This message means that, during switch driver initialization, there was a failure to read the system board information, which might occur because of an ASIC problem.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

PLATFORM_CATALYST2950 Messages

This section contains the Catalyst 2950 low-level platform message.

Error Message PLATFORM_CATALYST2950-1-CRASHED: [chars]

Explanation This message means that the system is attempting to display the failure message from the previous failure. [chars] is the failure message.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

PLATFORM_CATALYST2955 Messages

This section contains the application-specific integrated circuit (ASIC) driver-related messages for Catalyst 2955 switches.

Error Message PLATFORM_CATALYST2955-3-PORT_NOT_OPERATING: ASSERT MAJOR FastEthernet0/2 Port Not Operating.

Explanation The port is not operating; the power-on self-test (POST) has failed.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PLATFORM_CATALYST2955-3-PORT_NOT_OPERATING: CLEAR MAJOR FastEthernet0/2 Port Not Operating.

Explanation The CLEAR MAJOR message displays only if the failed port is shut down.

Recommended Action No action is required.

PM Messages

This section contains the port manager messages. The port manager is a state machine that controls all the logical and physical interfaces. All features, such as VLANs, UDLD, and so forth, work with the port manager to provide switch functions.

Error Message PM-2-NOMEM: Not enough memory available for [chars].

Explanation This message means that the port manager subsystem could not obtain the memory it needed to initialize the specified operation. [chars] is the port manager operation.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-2-VLAN_ADD: Failed to add VLAN [dec] - [chars].

Explanation This message means that the software failed to add the VLAN to the VLAN Trunking Protocol (VTP) database. [dec] is the VLAN ID, and [chars] specifies the reason for the failure.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-BAD_APP_ID: An invalid application id [dec] was detected.

Explanation This message means that the port manager detected an invalid request. [dec] is the application ID.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-BAD_APP_REQ: An invalid [chars] request by the '[chars]' application was detected.

Explanation This message means that the port manager detected an invalid request. The first [chars] is the invalid request, and the second [chars] is the application making the request.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-BAD_CARD_COOKIE: An invalid card cookie was detected.

Explanation This message means that the port manager detected an invalid request.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-BAD_CARD_SLOT: An invalid card slot ([dec]) was detected.

Explanation This message means that the port manager detected an invalid request. [dec] is the slot number.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-BAD_COOKIE: [chars] was detected.

Explanation This message means that the port manager detected an invalid request. [chars] is the invalid request.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-BAD_HA_ENTRY_EVENT: Invalid Host access entry event ([dec]) is received.

Explanation This message means that an invalid host access entry event was received; the host access table entry event should be an add, delete, or update event. [dec] is the event that is received.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-BAD_PORT_COOKIE: An invalid port cookie was detected.

Explanation This message means that the port manager detected an invalid request.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-BAD_PORT_NUMBER: An invalid port number ([dec]) was detected.

Explanation This message means that the port manager detected an invalid request. [dec] is the port number.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-BAD_VLAN_COOKIE: An invalid vlan cookie was detected.

Explanation This message means that the port manager detected an invalid request.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-BAD_VLAN_ID: An invalid vlan id ([dec]) was detected.

Explanation This message means that the port manager detected an invalid request. [dec] is the VLAN ID.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-ERR_DISABLE: [chars] error detected on [chars], putting [chars] in err-disable state.

Explanation This message means that the port manager detected a misconfiguration or misbehavior and placed the interface in an error-disabled state. A recovery is attempted after the configured retry time (the default is 5 minutes). The first [chars] is the error, and the second and third [chars] are the affected interfaces.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-ERR_RECOVER: Attempting to recover from [chars] err-disable state on [chars].

Explanation This message means that the port manager is attempting to bring the interface up after taking it down to the error-disabled state. The first [chars] is the error, and the second [chars] is the affected interface.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-INVALID_HOST_ACCESS_ENTRY: Invalid Host access entry type ([dec]) is received.

Explanation This message means that an invalid host access entry type was received; the host access entry should be a configured or dynamic type. [dec] is the entry type that is received.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-LIMITS: Virtual port count for [chars] exceeded the recommended limit of [dec].

Explanation This message means that the virtual port count exceeded the recommended limit of 1200 virtual ports per module and 4500 per switch. [chars] is the module name (for example, switch or the module number), and [dec] is the recommended limit.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-NO_SUBBLOCK: No PM subblock found for [chars].

Explanation This message means that the port manager failed to find the subblock for this interface. [chars] is the interface name.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-TOO_MANY_APP: Application '[chars]' exceeded registration limit.

Explanation This message means that the port manager detected an invalid request. [chars] is the application.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-UNKNOWN_HOST_ACCESS: Invalid Host access value ([dec]) is received.

Explanation This message means that the host access table is being accessed with an invalid host access value. [dec] is the value that is received.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message PM-4-VMPS_CFG: Dynamic access VLAN [dec] same as voice vlan on [chars].

Explanation This message means that the access VLAN ID on the VMPS server is the same as the voice VLAN ID on the interface. [dec] is the access VLAN ID, and [chars] is the physical interface.

Recommended Action Assign the access VLAN on the VMPS server to a different VLAN ID from the voice VLAN ID.

PORT SECURITY Messages

This section contains the port security message.

Error Message `PORT_SECURITY-2-PSECURE_VIOLATION:Security violation occurred caused by MAC [enet] on port [chars].`

Explanation This message means that an unauthorized device attempted to connect on a secure port. MAC [enet] is the MAC address of the unauthorized device, and port [chars] is the secure port.

Recommended Action Identify the device that attempted to connect on the secure port. Notify your network system administrator of this condition.

SPAN Messages

This section contains the Switched Port Analyzer (SPAN) messages.

Error Message `SPAN-3-MEM_UNAVAIL: Memory was not available to perform the SPAN operation.`

Explanation This message means that the system was unable to perform a SPAN operation because of a lack of memory.

Recommended Action Reduce other system activity to ease the memory demands.

Error Message `SPAN-3-UNKN_ERR: An internal error occurred during a SPAN operation.`

Explanation This message means that SPAN detected an error in its internal operation.

Recommended Action The error might be transient. Try the SPAN operation again. If a second attempt also fails, reload the switch by using the **reload** privileged EXEC command to complete the operation.

Error Message `SPAN-3-UNKN_ERR_PORT: An internal error occurred when configuring SPAN on port [chars].`

Explanation This message means that SPAN detected an error in its internal operation. [chars] is the interface.

Recommended Action The error might be transient. Try the SPAN operation again. If the second attempt also fails, reload the switch by using the **reload** privileged EXEC command to complete the operation.

SPANTREE Messages

This section contains the spanning-tree messages.

Error Message SPANTREE-2-BLOCK-PVID-PEER: Blocking on [chars] [chars]. Inconsistent peer vlan.

Explanation This message means that the spanning-tree port associated with the listed spanning-tree instance and interface will be held in the spanning-tree blocking state until the port VLAN ID (PVID) inconsistency is resolved. The listed spanning-tree instance is that of the native VLAN ID of the interface on the peer switch to which the listed interface is connected. The first [chars] is the interface, and the second [chars] is the spanning-tree instance.

Recommended Action Verify that the configuration of the native VLAN ID is consistent on the interfaces on each end of the 802.1Q trunk connection. When it is corrected, spanning tree automatically unblocks the interfaces, as appropriate.

Error Message SPANTREE-2-BLOCK-PVID-LOCAL: Blocking [chars] on [chars] Inconsistent local vlan.

Explanation This message means that the spanning-tree port associated with the listed spanning-tree instance and interface will be held in the spanning-tree blocking state until the PVID inconsistency is resolved. The listed spanning-tree instance is that of the native VLAN ID of the listed interface. The first [chars] is the interface, and the second [chars] is the spanning-tree instance.

Recommended Action Verify that the configuration of the native VLAN ID is consistent on the interfaces on each end of the 802.1Q trunk connection. When corrected, spanning tree automatically unblocks the interfaces, as appropriate.

Error Message SPANTREE-2-LOOPGUARD_BLOCK: Loop guard blocking port [chars] on [chars].

Explanation This message means that the spanning-tree message age timer has expired because no bridge protocol data units (BPDUs) were received from the designated bridge. Because this condition could be caused by a unidirectional-link failure, the interface is put into the blocking state and marked as loop-guard-inconsistent to prevent possible loops from being created. The first [chars] is the name of this port, and the second [chars] is the spanning-tree mode displayed in the **show spanning-tree** privileged EXEC command.

Recommended Action Enter the **show spanning-tree inconsistentports** privileged EXEC command to review the list of interfaces with loop-guard inconsistencies. Determine why devices connected to the listed ports are not sending BPDUs. One reason might be that they are not running the STP. If so, you should disable loop guard on the inconsistent interfaces by using the **spanning-tree guard none** interface configuration command or by starting STP on the remote side of the links.

Error Message SPANTREE-2-LOOPGUARD_CONFIG_CHANGE: Loop guard [chars] on port [chars] on [chars].

Explanation This message means that the spanning-tree loop-guard configuration for the listed interface has been changed. If enabled, the interface is placed into the blocking state. It is marked as loop-guard-inconsistent when the message-age timer expires because no BPDUs were received from the designated bridge. This feature is mainly used to detect unidirectional links. The first [chars] is the loop-guard state (*enable* or *disable*), the second [chars] is the interface name, and the third [chars] is the spanning-tree instance.

Recommended Action Verify that this is the desired configuration for the listed interface. Correct it if this is not the desired configuration; otherwise, no further action is required.

Error Message SPANTREE-2-LOOPGUARD_UNBLOCK: Loop guard unblocking port [chars] on [chars].

Explanation This message means that the listed interface has received a BPDU, and, therefore, if the inconsistency was caused by a unidirectional link failure, the problem no longer exists. The loop-guard-inconsistency is cleared for the interface, which is taken out of the blocking state, if appropriate. The first [chars] is the name of this port, and the second [chars] is the spanning-tree mode displayed in the **show spanning-tree** privileged EXEC command.

Recommended Action No action is required.

Error Message SPANTREE-2-PVSTSIM_FAIL: Superior PVST BPDU received on VLAN [dec] port [chars], claiming root [dec]:[enet]. Invoking root guard to block the port.

Explanation This message means that when a PVST+ switch is connected to a Multiple Spanning Tree Protocol (MSTP) switch, the internal spanning-tree (IST) root (MSTOO) becomes the root for all PVST+ spanning trees. A loop might be created if any of the PVST+ spanning trees have a better root than the IST. To prevent the loop, the port on the MSTP switch that receives the superior message from the PVST+ side is blocked by root guard. The first [dec] is the VLAN number, [chars] is the port name, and [dec]:[enet] is the priority and MAC address.

Recommended Action When STP is converging after a new switch or switch port is added to the topology, this condition might happen transiently, and the port automatically unblocks in these cases. If the port remains blocked, identify the root bridge as reported in the message, and configure a priority for the VLAN spanning tree so that it is not selected as the root. There could be other superior PVST roots (lower bridge ID, lower path cost, and so forth) than the message indicates, and the port does not recover until all such roots are cleared. If you are unsure, disable and re-enable the port.

Error Message SPANTREE-2-RCV-1Q-NON-1QTRUNK: Received 802.1Q BPDU on non 802.1Q trunk [chars] [chars].

Explanation This message means that the listed interface on which a Shared Spanning Tree Protocol (SSTP) BPDU was received was in trunk mode but was not using 802.1Q encapsulation. The first [chars] is the port, and the second [chars] is the VLAN.

Recommended Action Verify that the configuration and operational state of the listed interface and that of the interface to which it is connected are in the same mode (*access* or *trunk*). If the mode is trunk, verify that both interfaces have the same encapsulation. When the encapsulation is consistent, spanning tree automatically unblocks the interface.

Error Message SPANTREE-2-RECV-BAD-TLV: Received SSTP BPDU with bad TLV on [chars] [chars].

Explanation This message means that the listed interface received an SSTP BPDU without the VLAN ID tag. The BPDU is discarded. The first [chars] is the port, and the second [chars] is the VLAN that received the SSTP BPDU.

Recommended Action If the message recurs, copy the message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SPANTREE-2-RECV-PVID-ERR: Received BPDU with inconsistent peer vlan id [dec] on [chars] [chars].

Explanation This message means that the listed interface received an SSTP BPDU that is tagged with a VLAN ID that does not match the VLAN ID on which the BPDU was received. This occurs when the native VLAN is not consistently configured on both ends of an 802.1Q trunk. [dec] is the VLAN ID, the first [chars] is the port, and the second [chars] is the VLAN.

Recommended Action Verify that the configurations of the native VLAN ID is consistent on the interfaces on each end of the 802.1Q trunk connection. When the configurations are consistent, spanning tree automatically unblocks the interfaces.

Error Message SPANTREE-2-ROOTGUARD_BLOCK: Root guard blocking port [chars] on [chars].

Explanation This message means that on the listed interface a BPDU was received that advertises a superior spanning-tree root bridge (lower bridge ID, lower path cost, and so forth) than that in use. The interface is put into blocking state and marked as *root-guard inconsistent* to prevent a suboptimal spanning-tree topology from forming. The first [chars] is the name of this port, and the second [chars] is the spanning-tree mode displayed in **show spanning-tree** privileged EXEC command.

Recommended Action Enter the **show spanning-tree inconsistentports** privileged EXEC command to review the list of interfaces with root-guard inconsistencies. Determine why devices connected to the listed ports are sending BPDUs with a superior root bridge, and take action to prevent more occurrences. When the inaccurate BPDUs have been stopped, the interfaces automatically recover and resume normal operation. Make sure that it is appropriate to have root guard enabled on the interface.

Error Message SPANTREE-2-ROOTGUARD_CONFIG_CHANGE: Root guard [chars] on port [chars] on [chars].

Explanation This message means that the spanning-tree root guard configuration for the listed interface has changed. If enabled, any BPDU received on this interface that advertises a superior spanning-tree root bridge (lower bridge ID, lower path cost, and so forth) to that already in use causes the interface to be put into the blocking state and marked as *root-guard inconsistent*. The first [chars] is the root-guard state (*enable* or *disable*), the second [chars] is the interface, and the third [chars] is the spanning-tree instance.

Recommended Action Verify that this is the desired configuration for the listed interface. Correct it if it is not the desired configuration; otherwise, no action is required.

Error Message SPANTREE-2-ROOTGUARD_UNBLOCK: Root guard unblocking port [chars] on [chars].

Explanation This message means that the listed interface is no longer receiving BPDUs advertising a superior root bridge (lower bridge ID, lower path cost, and so forth). The root-guard inconsistency is cleared for the interface, and the blocking state is removed from the interface. The first [chars] is the name of this port, and the second [chars] is the spanning-tree mode displayed in **show spanning-tree** privileged EXEC command.

Recommended Action No action is required.

Error Message SPANTREE-2-RX-PORTFAST: Received BPDU on PortFast enabled port. Disabling [chars].

Explanation This message means that a BPDU was received on the listed interface, which has the spanning-tree Port Fast feature enabled. Because spanning-tree BPDU guard is also enabled, the interface is administratively shut down. [chars] is the interface that received the BPDU.

Recommended Action Verify the Port Fast configuration on the interface. If the Port Fast behavior is desired, verify that the interface is connected to only a host or router and not to a bridge or a switch. After resolving the conflict, re-enable the interface by entering the **no shutdown** interface configuration command.

Error Message SPANTREE-2-UNBLOCK-CONSIST-PORT: Unblocking [chars] on [chars]. Port consistency restored.

Explanation This message means that the port VLAN ID or port type inconsistencies have been resolved and spanning tree will unblock the listed interface of the listed spanning-tree instance as appropriate. The first [chars] is the interface, and the second [chars] is the spanning-tree instance.

Recommended Action No action is required.

Error Message SPANTREE-3-BAD_PORTNUM_SIZE: Rejected an attempt to set the port number field size to [dec] bits (valid range is [dec] to [dec] bits).

Explanation This message means that an error occurred in the platform-specific code, which caused it to request more or less bits than are possible. The spanning-tree port identifier is a 16-bit field, which is divided evenly between the port priority and port number, with each subfield being 8 bits. This allows the port number field to represent port numbers between 1 and 255. However, on systems with more than 255 ports, the size of port number portion of the port ID must be increased to support the number of ports. This is performed by the STP subsystem at system initialization because the maximum number of ports on a particular platform will not change. This error occurs because of an error in the platform-specific code, which causes it to request more or less bits than are possible. The first [dec] is the number of bits for the port number, and the second and third [dec] describe the valid range.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show version** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show version** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SPANTREE-3-PORT_SELF_LOOPED: [chars] disabled.- received BPDU src mac [enet] same as that of interface.

Explanation This message means that a BPDU was received on the listed interface with a source MAC address that matches the one assigned to the listed interface. This means that a port might be looped back to itself, possibly because of an installed diagnostic cable. The interface will be administratively shut down. [chars] is the interface that received the BPDU, and [enet] is the source MAC address.

Recommended Action Check the interface configuration and any cable plugged into the interface. When the problem is resolved, re-enable the interface by entering the **no shutdown** interface configuration command.

Error Message SPANTREE%SPANTREE-4-PORT_NOT_FORWARDING: ASSERT MINOR FastEthernet0/5 Port Not Forwarding.

Explanation This message means that the port is not forwarding packets; that is, it is not in a forwarding state.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SPANTREE-5-EXTENDED_SYSID: Extended SysId [chars] for type [chars].

Explanation This message means that the extended system ID feature is either enabled or disabled for the given type of spanning tree. If enabled, the spanning-tree instance identifier is stored in the lower portion of the bridge ID priority field and limits the allowed values for the bridge priority from 0 to 61440, in increments of 4096. If disabled, the bridge ID priority field consists only of the configured priority, but some spanning-tree features might not be available on a given platform (for example, support for 4096 VLANs). On some platforms, this feature might be mandatory. The first [chars] is the extended system ID state (*enable* or *disable*), and the second [chars] is the spanning-tree instance.

Recommended Action No action is required.

Error Message SPANTREE-7-BLOCK-PORT-TYPE: Blocking [chars] on [chars]. Inconsistent port type.

Explanation This message means that the listed interface is being held in the spanning-tree blocking state until the port-type inconsistency is resolved. The first [chars] is the interface, and the second [chars] is the spanning-tree instance.

Recommended Action Verify that the configuration and operational states of the listed interface and those of the interface to which it is connected are in the same mode (*access* or *trunk*). If the mode is trunk, verify that both interfaces have the same encapsulation. When these parameters are consistent, spanning tree automatically unblocks the interface.

Error Message SPANTREE-7-RECV-1Q-NON-TRUNK: Received 802.1Q BPDU on non trunk [chars] [chars].

Explanation This message means that an SSTP BPDU was received on the listed interface, which is not an operational trunking interface. The first [chars] is the port name, and the second [chars] is the VLAN name.

Recommended Action Verify that the configuration and operational state of the listed interface and that of the interface to which it is connected are in the same mode (*access* or *trunk*). If the mode is trunk, verify that both interfaces have the same encapsulation. When these parameters are consistent, spanning tree automatically unblocks the interface.

SPANTREE_FAST Messages

This section contains the spanning-tree fast-convergence message.

Error Message SPANTREE_FAST-7-PORT_FWD_UPLINK: [chars] [chars] moved to Forwarding (UplinkFast).

Explanation This message means that the listed interface has been selected as the new path to the root switch for the listed spanning-tree instance. The first [chars] is the spanning-tree instance, and the second [chars] is the interface.

Recommended Action No action is required.

SPANTREE_VLAN_SWITCH Messages

The section contains the per-VLAN spanning-tree-specific message.

Error Message SPANTREE_VLAN_SW-2-MAX_INSTANCE: Platform limit of [dec] STP instances exceeded. No instance created for [chars] (port [chars]).

Explanation This message means that the number of currently active VLAN spanning-tree instances has reached a platform-specific limit. No additional VLAN instances will be created until the number of existing instances drops below the platform limit. [dec] is the spanning-tree instance limit, and the first [chars] is the smallest VLAN number of those VLANs that are unable to have STP instances created.

Recommended Action Reduce the number of currently active spanning-tree instances by either disabling some of the currently active spanning-tree instances or deleting the VLANs associated with them. You must manually enable the spanning trees that could not be created because of limited instances.

STORM_CONTROL Messages

This section contains the storm control message.

Error Message STORM_CONTROL-2-SHUTDOWN: Storm control shut down [chars].

Explanation This messages means that excessive traffic has been detected on a port that has been configured to be shut down if a storm event is detected. [chars] is the physical interface.

Recommended Action When the source of the packet storm has been fixed, re-enable the port by using the **no shutdown** interface configuration command.

SW_VLAN Messages

This section contains the VLAN manager messages. The VLAN manager receives information from the VTP and enables the proper VLAN membership on all interfaces through the port manager.

Error Message SW_VLAN-3-VLAN_PM_NOTIFICATION_FAILURE: VLAN Manager synchronization failure with Port Manager over [chars].

Explanation This message means that the VLAN manager dropped a notification from the port manager because of a lack of ready pool space. [chars] is the type of port manager notification.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-3-VTP_PROTOCOL_ERROR: VTP protocol code internal error:[chars].

Explanation This message means that the VTP code encountered an unexpected error while processing a configuration request, a packet, or a timer expiration. [chars] is the internal error.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-4-BAD_PM_VLAN_COOKIE_RETURNED: VLAN manager unexpectedly received a bad PM VLAN cookie from the Port Manager, VLAN indicated:[dec].

Explanation This message means that the VLAN manager received an upcall and a VLAN cookie from the port manager, which translated to a bad VLAN number. [dec] is the VLAN ID.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-4-BAD_STARTUP_VLAN_CONFIG_FILE: Failed to configure VLAN from startup-config. Fallback to use VLAN configuration file from non-volatile memory.

Explanation This message means that the VLAN software did not use the VLAN configuration from the startup-configuration file. It will use the binary VLAN configuration file in nonvolatile memory.

Recommended Action No action is required.

Error Message SW_VLAN-4-BAD_VLAN_CONFIGURATION_FILE: VLAN configuration file contained incorrect verification word:[hex].

Explanation This message means that the VLAN configuration file read by the VLAN manager did not begin with the correct value. The VLAN configuration file is invalid, and it has been rejected. [hex] is the incorrect verification value.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-4-BAD_VLAN_CONFIGURATION_FILE_VERSION: VLAN configuration file contained unknown file version:[dec].

Explanation This message means that the VLAN configuration file read by the VLAN manager contained an unrecognized file version number, which might mean an attempt to regress to an older version of the VLAN manager software. [dec] is the file version number.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-4-BAD_VLAN_TIMER_ACTIVE_VALUE: Encountered incorrect VLAN timer active value:[chars].

Explanation This message means that, because of a software error, a VLAN timer was detected as active when it should have been inactive or is inactive when it should have been active. [chars] is the VLAN timer active value.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-4-EXT_VLAN_CREATE_FAIL: Failed to create VLANs [chars]: [chars].

Explanation The message means that the software failed to create VLANs. The first [chars] is the Layer 2 VLAN list, and the second [chars] describes the reason for the failure.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-4-EXT_VLAN_INTERNAL_ERROR: Extended VLAN manager received an internal error [dec] from [chars]: [chars].

Explanation This message means that an unexpected error code was received by the VLAN manager from the extended-range VLAN configuration software. [dec] is the error code. The first [chars] is the function, and the second [chars] describes the error code.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-4-EXT_VLAN_INVALID_DATABASE_DATA: Extended VLAN manager received bad data of type [chars]: value [dec] from function [chars].

Explanation This message means that invalid data was received by the extended-range VLAN manager from an extended-range VLAN configuration database routine. The first [chars] is the data type, [dec] is the number received, and the second [chars] is the function name.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-4-IFS_FAILURE: VLAN manager encountered file operation error: call = [chars] / file = [chars] / code = [dec] ([chars]) / bytes transferred = [dec].

Explanation This message means that the VLAN manager received an unexpected error return from an IOS file system (IFS) call while reading the VLAN database. The first [chars] is the name of the function call, and the second [chars] is the file name. [dec] is the error code, the third [chars] is the textual interpretation of the error code, and the second [dec] is the number of bytes transferred.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-4-NO_PM_COOKIE_RETURNED: VLAN manager unexpectedly received a null [chars] type cookie from the Port Manager, data reference:[chars].

Explanation This message means that the VLAN manager queried the port manager for a reference cookie but received a NULL pointer instead. The first [chars] is the type of port manager cookie, and the second [chars] is the interface or VLAN that is the source of the problem.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-4-STARTUP_EXT_VLAN_CONFIG_FILE_FAILED: Failed to configure extended range VLAN from startup-config. Error [chars].

Explanation This message means that the VLAN software failed to use an extended-range VLAN configuration from the startup configuration file. All extended-range VLAN configurations are lost after the system boots up. [chars] is a description of the error code.

Recommended Action No action is required.

Error Message SW_VLAN-4-VTP_INTERNAL_ERROR: VLAN manager received an internal error [dec] from vtp function [chars]:[chars].

Explanation This message means that the VLAN manager received an unexpected error code from the VTP configuration software. [dec] is the error code, the first [chars] is the VTP function, and the second [chars] is the error-code description.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-4-VTP_INVALID_DATABASE_DATA: VLAN manager received bad data of type [chars]:value [dec] from vtp database function [chars].

Explanation This message means that the VLAN manager received invalid data from a VTP configuration database routine. The first [chars] is the data type; [dec] is the inappropriate value that was received, and the second [chars] is the VTP database function.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-4-VTP_INVALID_EVENT_DATA: VLAN manager received bad data of type [chars]:value [dec] while being called to handle a [chars] event.

Explanation This message means that the VLAN manager received invalid data from the VTP configuration software. The first [chars] is the data type, and [dec] is the value of that data, and the second [chars] is the VTP event.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-4-VTP_USER_NOTIFICATION: VTP protocol user notification: [chars].

Explanation This message means that the VTP code encountered an unusual diagnostic situation. [chars] is a description of the situation.

Recommended Action Copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message SW_VLAN-6-OLD_CONFIG_FILE_READ: Old version [dec] VLAN configuration file detected and read OK. Version [dec] files will be written in the future.

Explanation This message means that the VLAN software detected an old version of the VLAN configuration file format. It interpreted the file without a problem, but it will create files using the new format in the future. The first [dec] is the old version number, and the second [dec] is the new version number.

Recommended Action No action is required.

Error Message SW_VLAN-6-VTP_MODE_CHANGE: VLAN manager changing device mode from [chars] to [chars].

Explanation This message means that an automatic VTP mode device change occurred upon receipt of a VLAN configuration database message containing more than a set number of VLANs. The first [chars] is the previous mode, and the second [chars] is the current mode.

Recommended Action No action is required.

UDLD Messages

This section contains UniDirectional Link Detection (UDLD) messages.

Error Message UDLD-3-UDLD_IDB_ERROR: UDLD error handling [chars] interface:[chars].

Explanation This message means that a software error occurred in UDLD processing associated with a specific interface. The first [chars] is the event, and the second [chars] is the interface.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message UDLD-3-UDLD_INTERNAL_ERROR: UDLD internal error:[chars].

Explanation This message means that a software check failed during UDLD processing. [chars] is a description of the internal error.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message UDLD-3-UDLD_INTERNAL_IF_ERROR: UDLD internal error, interface [chars]:[chars].

Explanation This message means that a software check failed during UDLD processing. The first [chars] is the interface, and the second [chars] is a description of the error.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message UDLD-4-UDLD_PORT_DISABLED: UDLD disabled interface [chars], [chars] detected.

Explanation This message means that the UDLD Protocol disabled an interface because it detected connections between neighbors that were functioning only in one direction, which might potentially cause spanning-tree loops or interfere with connectivity. The cause is likely to be hardware related, either due to a bad port, a bad cable, or a misconfigured cable. The first [chars] is the interface, and the second [chars] is the error detected.

Recommended Action Try to correct the configuration or locate the bad cable. If you are not successful, copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message UDLD-6-UDLD_PORT_RESET: UDLD reset interface [chars].

Explanation This message means that the UDLD Protocol detected a unidirectional connection between neighbors. You reset the port that was disabled by UDLD by using the **udld reset** privileged EXEC command or through a hardware action such as a link-state change. [chars] in the interface.

Recommended Action Copy the error message exactly as it appears on the console or in the system log. Enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

UFAST_MCAST_SW Messages

This section contains the UplinkFast multicast software (UFAST_MCAST_SW) messages. The switch sends these messages when UplinkFast is enabled, a new root port takes over, and fast relearn multicast packets are not sent.

Error Message UFAST_MCAST_SW-3-PROC_START_ERROR: No process available for transmitting UplinkFast packets.

Explanation This message means that no process is available for sending UplinkFast packets.

Recommended Action Reload the switch by using the **reload** privileged EXEC command. If this problem continues after you reload the switch, enter the **show tech-support** privileged EXEC command to gather data that might provide information about the error. If you cannot determine the nature of the error from the error message or from the **show tech-support** command display, call your Cisco technical support representative, and provide the representative with the gathered information.

Error Message UFAST_MCAST_SW-4-MEM_NOT_AVAILABLE: No memory is available for transmitting UplinkFast packets on Vlan [dec].

Explanation This message means that no memory is available for sending UplinkFast packets on VLAN [dec]. [dec] is the VLAN number.

Recommended Action Reduce other system activity to reduce memory demands.



Security and QoS Configuration Messages

This appendix describes the error messages for configuring network security with access control lists (ACLs) and for configuring quality of service (QoS). In [Table A-1](#), Access Control Parameters (ACPs) are referred to as masks. For more information about ACPs, refer to the software configuration guide for this release.

These error messages occur only if you have installed the enhanced software image (EI) on your switch.

Table A-1 Common ACL Error Messages

Error Message	Explanation and Suggested Solution
<code>%Error:Class-map [class-map name] has a different mask than the Policymap [policy-map name]</code>	<p>This error message means that the policy map has a different mask than the class map.</p> <p>Use the same mask in both the class map and the policy map.</p>
<code>%Error:Class-maps have a mix of System Defined and User Defined masks within the Policymap [policy-map name]</code>	<p>This error message means that a combination of system-defined and user-defined masks has been used in the multiple class maps that are part of a policy map.</p> <p>Class maps that are in a policy map cannot have ACLs that use both system-defined masks and user-defined masks.</p>
<code>%Error:System Defined ACEs of TCP/UDP and IP cannot exist together in a policy-map. Check policy-map :[policy-map name]</code>	<p>This error message means that a combination of Layer 3 system-defined access control entries (ACEs) and Layer 4 system-defined ACEs is in the same policy map.</p> <p>A policy map cannot have both Layer 3 system-defined ACEs and Layer 4 system-defined ACEs.</p> <p>Note You cannot have masks such as permit tcp any any, permit udp any any, and permit ip any any within the same policy map.</p>
<code>%Error:Service-Policy is not supported on VLAN interface</code>	<p>This error message means that you have tried to attach a policy map to a VLAN interface.</p> <p>A policy map can be attached only to a physical interface.</p>
<code>%Error:Invalid policy-map</code>	<p>This error message means that the policy map is invalid.</p> <p>This message is normally preceded by a more explicit error message that gives details about the reasons for the invalidity of the policy map.</p>
<code>%Error:Match Numbered Attach Filter :ONLY one ACL allowed in a class-map</code>	<p>This error message means that there was an attempt to add another numbered ACL in the class map.</p> <p>Only one ACL is allowed in a class map.</p>

Table A-1 Common ACL Error Messages (continued)

Error Message	Explanation and Suggested Solution
%Error:Deny ACE not supported in access-group within a class-map. Check class-map : [class-map name]	This error message means that a deny ACE has been entered in an access group within a class map. A deny ACE is not supported in an access group within a class map.
%Error:System Defined and User Defined ACEs cannot exist together in access-group within a class-map. Check class-map : [class-map name]	This error message means that a combination of system-defined and user-defined masks has been used in an access group within a class map. The access group in a class map cannot have ACLs that use both system-defined masks and user-defined masks.
%Error:System Defined ACEs of TCP/UDP and IP cannot exist together in access-group within a class-map. Check class-map :[class-map name]	This error message means that a combination of Layer 3 system-defined access control entries (ACEs) and Layer 4 system-defined ACEs has been configured in the same access group. The access group in a class map cannot have both Layer 3 and Layer 4 system-defined ACEs .
%Error:Match Named Attach Filter :ONLY one ACL allowed in a class-map	This error message means that an attempt was made to add another ACL in the class map. Only one ACL is allowed in a class map.
%Error:The ACL has a different mask than the Policy-map [policy-map name]	This error message means that an attempt was made to create an ACL with a different mask within a policy map. All ACLs within the same class maps of a policy map must have the same mask.
%Error:Service policy cannot be configured	This error message means that the policy map cannot be configured. The exact causes are provided in separate error messages that precede this error message. The switches support the policy-map global configuration command with certain restrictions. For more information, refer to the command reference for this release.
%Error:Service policy cannot be supported - Policers required exceed Maximum Allowed on this interface	This error message means that the policy map cannot be supported because the required number of policers on this interface are more than permitted. A Fast Ethernet port supports 6 policers, and a Gigabit Ethernet port supports 60 policers.
%Error:Service policy cannot be supported - Rules required exceed available resources in ASIC.	This error message means that the policy map cannot be supported because the required number of resources to support this policy map is not available in the hardware. Reduce the number of resources on this policy map.
%Error:Removing service-policy <i>policy-map name</i> from interface <i>interface_number</i>	This error message means that a policy map was invalid and was removed from an interface. If a policy map is attached to an interface and you modify the policy map so that it becomes invalid, the system removes the policy map from the interface.

Table A-1 Common ACL Error Messages (continued)

Error Message	Explanation and Suggested Solution
<code>%Error:ASIC memory read write issues</code>	<p>This error message means that the switch hardware is having problems.</p> <p>If the message recurs, copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.</p>
<code>%Error:ASIC Resources unavailable</code>	<p>This error message means that the hardware does not have sufficient resources to support the user policies.</p>
<code>%Error:Invalid mask</code>	<p>This error message means that the user-defined mask is not entered correctly in the hardware.</p> <p>Remove the mask, and re-enter it.</p>
<code>%Error:Invalid rule</code>	<p>This error message means that the hardware had a problem programming the resource.</p> <p>Re-enter the command that you had entered before receiving the error message.</p> <p>If the message recurs, copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.</p>
<code>%Error:Invalid ingress port</code>	<p>This error message means that an invalid ingress port was detected by the hardware.</p> <p>Re-enter the command that you had entered before receiving the error message.</p> <p>If the message recurs, copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.</p>
<code>%Error:Another security mask on this interface</code>	<p>This error message means that there is another security mask present on the interface.</p> <p>Only one security mask is allowed on any interface.</p> <p>Remove all the security access groups on this interface, and attach the security access group that is required.</p>
<code>%Error:Another qos mask on this interface</code>	<p>This error message means that there is more than one quality of service (QoS) mask on the interface.</p> <p>Only one QoS mask is allowed on any interface.</p> <p>Remove all the QoS policy maps on this interface, and attach the policy map that is required.</p>
<code>%Error:No sec mask on this interface</code>	<p>This error message means that no security mask has been applied on this interface.</p>
<code>%Error:No qos mask on this interface</code>	<p>This error message means that no QoS mask has been applied on this interface.</p>

Table A-1 Common ACL Error Messages (continued)

Error Message	Explanation and Suggested Solution
<code>%Error:No sec rules on this interface</code>	This error message means that there are no security resources on this interface.
<code>%Error:No qos rules on this interface</code>	This error message means that there are no QoS resources on this interface.
<code>%Error:No free masks available</code>	This error message means that there are no free masks available for the user. You must use one of the user-defined masks that is already configured. As an alternative, you can free up one of the masks by removing all the policies that use that mask.
<code>%Error:Invalid sequence - IP protocol ACE not allowed after TCP/UDP protocol ACE</code>	This error message means that a Layer 4 (TCP or UDP protocol) ACE preceded a Layer 3 (IP protocol) ACE.
<code>%Error: Service-Policy is not supported on EtherChannel interface</code>	This error message means that an access group is applied on an EtherChannel interface. Access groups can be applied only to Layer 2 physical interfaces or management VLANs.
<code>%Error:A MAC Access Group exists on this interface</code>	This error message means that a MAC access group was previously configured on this interface. Delete the MAC access group by using the no mac access-group interface configuration command, and re-enter the ip access-group interface configuration command.
<code>%Error:An IP Access Group exists on this interface</code>	This error message means that an IP access group was previously configured on this interface. Delete the IP access group by using the no ip access-group interface configuration command, and re-enter the mac access-group interface configuration command.
<code>%Error:Out of Rule Resources</code>	This error message means that the hardware has run out of resources. Re-enter the command with fewer ACEs.
<code>%Error:No free rules on this interface</code>	This error message means that the hardware has run out of resources. Re-enter the command with fewer ACEs.
<code>%Error:ASIC error</code>	This error message means that the hardware has returned an error and that the command cannot be completed.
<code>%Error:ASIC out of resources</code>	This error message means that the hardware does not have sufficient resources to support the user policies.
<code>%Error:Mask/rule entry failure, errcode=XX</code>	This error message means that the hardware displays an unknown error with the specified error code.
<code>%Error:FAILURE to reinsert old ACL</code>	This error message means a hardware failure has occurred. Delete the access group, and re-enter the command.
<code>%Error:Max limit reached for number of ACEs in ACL :<acl_name></code>	This error message means that the maximum number of ACEs in an ACL has been reached. The ACE cannot be added to the ACL.

Table A-1 Common ACL Error Messages (continued)

Error Message	Explanation and Suggested Solution
<code>%Error:access-list too large to support on this interface. Check class-map :[class-map name] and access-list :[acl name]</code>	<p>This error message means that the access list cannot be applied on this interface because the interface does not have sufficient resources to meet the requirement of this access list.</p> <p>Re-enter the command with fewer ACEs.</p>
<code>%Error:FAILURE to reinsert old ACL, errcode=XX</code>	<p>This error message means that a hardware failure has occurred.</p> <p>Delete the access group, and re-enter the command that you had entered before receiving the error message.</p> <p>If the message recurs, copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.</p>
<code>%Error:Egress port invalid</code>	<p>This error message means that an invalid egress port was detected by the hardware.</p> <p>Re-enter the command that you had entered before receiving the error message.</p> <p>If the message recurs, copy the error message exactly as it appears on the console or in the system log, call your Cisco technical support representative, and provide the representative with the gathered information.</p>
<code>%Error:The field sets of all the ACEs in an ACL on Ethernet interface should match. Please refer to the Software Configuration Guide to understand one mask restriction for ACLs on Ethernet interface</code>	<p>This error message means that one or more of the ACEs in an ACL must have the same mask.</p> <p>Change the ACEs to have the same mask as the other ACEs in the ACL.</p>
<code>%Error:Access-list with '[keyword]' keyword is not supported on Ethernet Interface. The ACL '[acl name]' is either used as a Security ACL or QoS ACL. Please refer to the Software Configuration Guide for all the supported keywords</code>	<p>This error message means that the new ACE added to the ACL contains one or more keywords that are not supported on the Ethernet interface.</p> <p>Remove any nonsupported keywords from ACL.</p>
<code>%Error:Access-list with '[keyword]' keyword is not supported on Ethernet Interface. Please refer to the Software Configuration Guide for all the supported keywords</code>	<p>This error message means that the ACL to be applied to a Layer 2 interface or class-map contains one or more keywords that are not supported.</p> <p>Remove any nonsupported keywords from ACL.</p>
<code>%Error:Policer Configuration Incorrect for this interface. Check the policer rate in policy-map :[policy-map name], class-map :[class-map name]. Please choose either [lower rate] or [upper rate] (bits per second) as the policer rate</code>	<p>This error message means that the granularity of the policer rate in the policy-map is 1 Mbps.</p> <p>Change the policer rate to either of the suggested values.</p>
<code>%Error:The name '[aclname]' has been used for ACL of another type</code>	<p>This error message means that the name on the MAC extended ACL might have been used in another named ACL that is not a MAC extended ACL.</p>





Numerics

802.1X authentication messages

See DOT1X messages

A

abbreviations

char, variable field [1-3](#)

chars, variable field [1-3](#)

dec, variable field [1-3](#)

enet, variable field [1-3](#)

hex, variable field [1-3](#)

inet, variable field [1-3](#)

access control list messages

See ACL messages

ACL messages [A-1](#)

application-specific integrated circuit driver-related messages

See ASIC driver-related messages

ASIC driver-related messages [2-16, 2-20](#)

audience [v](#)

C

Catalyst 2950 ASIC messages [2-16](#)

Catalyst 2955 ASIC messages [2-20](#)

Cisco Technical Assistance Center [ix](#)

Cluster Membership Protocol messages

See CMP messages

CMP messages [2-2](#)

codes [1-1](#)

conventions

command [vi](#)

for examples [vi](#)

publication [vi](#)

text [vi](#)

D

date/time stamp designations [2-1](#)

documentation

feedback [viii](#)

obtaining

CD-ROM [vii](#)

world wide web [vii](#)

ordering [viii](#)

related [vi](#)

document conventions [vi](#)

DOT1X messages [2-3](#)

DTP messages [2-4](#)

Dynamic Trunking Protocol messages

See DTP messages

E

EC messages [2-5](#)

environment messages [2-8](#)

ETHCNTR messages [2-10](#)

EtherChannel messages

See EC messages

Ethernet controller messages

See ETHCNTR messages

examples, conventions for [vi](#)

F

- facility codes [1-1](#)
 - description [1-1](#)
 - table [1-1](#)
- fastEthernet messages [2-15](#)
- feedback to Cisco Systems, web [viii](#)

G

- GBIC messages
 - GigaStack GBIC module [2-14](#)
 - identification and validation [2-10](#)
 - security [2-12](#)
- guide
 - audience [v](#)
 - organization of [v](#)
 - purpose of [v](#)

H

- hardware MAC address table manager messages [2-15](#)

L

- LACP messages [2-5](#)
- Link Aggregation Protocol Control messages
 - See LACP messages
- link-specific messages [2-15](#)

M

- MAC address table manager messages [2-15](#)
- message codes [1-1](#)
- messages
 - ACL [A-1](#)
 - ASIC driver-related [2-16, 2-20](#)
 - CMP [2-2](#)
 - DOT1X [2-3](#)

- DTP [2-4](#)
- environment [2-8](#)
- EtherChannel [2-5](#)
- Ethernet controller [2-10](#)
- fastEthernet [2-15](#)
- GBIC
 - GigaStack [2-14](#)
 - identification and validation [2-10](#)
 - security [2-12](#)
- hardware MAC address table manager [2-15](#)
- LACP [2-5](#)
- link [2-15](#)
- MAC address table manager [2-15](#)
- PAgP [2-5](#)
- per-VLAN spanning-tree [2-32](#)
- PLATFORM_CATALYST2950 [2-20](#)
- port manager [2-21](#)
- port security [2-26](#)
- QoS [A-1](#)
- security [A-1](#)
- SPAN [2-26](#)
- spanning tree [2-27](#)
- spanning-tree fast convergence [2-32](#)
- storm control [2-33](#)
- UDLD [2-38](#)
- UFAST [2-39](#)
- VLAN manager [2-33](#)
- VTP [2-33](#)
- message severity levels
 - description [1-3](#)
 - table [1-3](#)

N

- notes
 - date/time stamp designation [2-1](#)
 - described [vi](#)

P

- PAgP messages [2-5](#)
- per-VLAN spanning-tree messages
 - See SPANTREE_VLAN_SWITCH messages
- PLATFORM_CATALYST2950 messages [2-20](#)
- PM messages [2-21](#)
- Port Aggregation Protocol messages
 - See PAgP messages
- port manager messages
 - See PM messages
- port security messages [2-26](#)
- publications, related [vi](#)

Q

- QoS messages [A-1](#)
- quality of service messages
 - See QoS messages

S

- security messages [A-1](#)
- severity levels
 - description [1-3](#)
 - table [1-3](#)
- SPAN messages [2-26](#)
- spanning-tree fast-convergence messages
 - See SPANTREE_FAST messages
- spanning-tree messages
 - See SPANTREE messages
- spanning-tree per-VLAN messages
 - See SPANTREE_VLAN_SWITCH messages
- SPANTREE_FAST messages [2-32](#)
- SPANTREE_VLAN_SWITCH messages [2-32](#)
- SPANTREE messages [2-27](#)
- storm control messages [2-33](#)

SW_VLAN messages [2-33](#)

Switched Port Analyzer messages
 See SPAN messages

T

- tables
 - message severity levels [1-3](#)
 - variable fields [1-3](#)
- TAC [ix](#)
- TAC, toll-free telephone numbers [x](#)
- technical assistance
 - Cisco.com [viii](#)
 - TAC [ix](#)
 - TAC website [ix](#)
 - toll-free telephone numbers [x](#)
- traceback reports [1-4](#)

U

- UDLD messages [2-38](#)
- UFAST messages [2-39](#)
- UniDirectional Link Detection messages
 - See UDLD messages
- URLs, Cisco [vii](#)

V

- variable fields
 - definition [1-3](#)
 - table [1-3](#)
- VLAN manager messages
 - See SW_VLAN messages
- VLAN Trunking Protocol messages
 - See SW_VLAN messages
- VTP messages
 - See SW_VLAN messages

