



I N D E X

A

abbreviating commands [2-4](#)

AC (command switch) [5-9](#)

access-denied response, VMPS [12-24](#)

accessing

clusters, switch [5-12](#)

command switches [5-10](#)

member switches [5-12](#)

switch clusters [5-12](#)

access ports

in switch clusters [5-8](#)

access ports, defined [10-2](#)

accounting

with 802.1x [9-29](#)

with IEEE 802.1x [9-8](#)

with RADIUS [8-28](#)

with TACACS+ [8-11, 8-17](#)

ACEs

and QoS [28-7](#)

ACLs

applying

to QoS [28-7](#)

classifying traffic for QoS [28-41](#)

examples of [28-41](#)

extended IP, configuring for QoS classification [28-42](#)

IP

fragments and QoS guidelines [28-32](#)

MAC extended [28-43](#)

number per QoS class map [28-32](#)

QoS [28-7, 28-41](#)

standard IP, configuring for QoS classification [28-41](#)

support for [1-8](#)

active traffic monitoring, IP SLAs [27-1](#)

address aliasing [18-2](#)

addresses

displaying the MAC address table [6-26](#)

dynamic

accelerated aging [15-8](#)

changing the aging time [6-21](#)

default aging [15-8](#)

defined [6-19](#)

learning [6-20](#)

removing [6-22](#)

MAC, discovering [6-26](#)

multicast, STP address management [15-8](#)

static

adding and removing [6-24](#)

defined [6-19](#)

address resolution [6-26](#)

Address Resolution Protocol

See ARP

advertisements

CDP [20-1](#)

LLDP [21-2](#)

VTP [12-16, 13-3](#)

aggregatable global unicast addresses [29-3](#)

aggregated ports

See EtherChannel

aggregate policers [28-49](#)

aggregate policing [1-9](#)

aging, accelerating [15-8](#)

- aging time
 - accelerated
 - for MSTP [16-23](#)
 - for STP [15-8, 15-21](#)
 - MAC address table [6-21](#)
 - maximum
 - for MSTP [16-23, 16-24](#)
 - for STP [15-21, 15-22](#)
 - alarms, RMON [24-3](#)
 - allowed-VLAN list [12-18](#)
 - ARP
 - defined [1-4, 6-26](#)
 - table
 - address resolution [6-26](#)
 - managing [6-26](#)
 - attributes, RADIUS
 - vendor-proprietary [8-31](#)
 - vendor-specific [8-29](#)
 - audience [xxix](#)
 - authentication
 - local mode with AAA [8-32](#)
 - NTP associations [6-4](#)
 - RADIUS
 - key [8-21](#)
 - login [8-23](#)
 - TACACS+
 - defined [8-11](#)
 - key [8-13](#)
 - login [8-14](#)

See also port-based authentication
 - authentication failed VLAN
 - See restricted VLAN
 - authoritative time source, described [6-2](#)
 - authorization
 - with RADIUS [8-27](#)
 - with TACACS+ [8-11, 8-16](#)
 - authorized ports with IEEE 802.1x [9-7](#)
 - autoconfiguration [3-3](#)
 - automatic discovery
 - considerations
 - beyond a noncandidate device [5-7](#)
 - brand new switches [5-8](#)
 - connectivity [5-4](#)
 - different VLANs [5-6](#)
 - management VLANs [5-7](#)
 - non-CDP-capable devices [5-6](#)
 - noncluster-capable devices [5-6](#)
 - in switch clusters [5-4](#)
 - See also CDP
 - automatic QoS
 - See QoS
 - automatic recovery, clusters [5-9](#)
 - See also HSRP
 - auto-MDIX
 - configuring [10-15](#)
 - described [10-15](#)
 - autonegotiation
 - duplex mode [1-2](#)
 - interface configuration guidelines [10-12](#)
 - mismatches [32-11](#)
 - autosensing, port speed [1-2](#)
 - auxiliary VLAN
 - See voice VLAN
 - availability, features [1-6](#)
-
- B**
 - BackboneFast
 - described [17-5](#)
 - disabling [17-14](#)
 - enabling [17-13](#)
 - support for [1-6](#)
 - banners
 - configuring
 - login [6-19](#)
 - message-of-the-day login [6-18](#)

banners (continued)

- default configuration 6-17

- when displayed 6-17

- blocking packets 19-7

booting

- boot loader, function of 3-2

- boot process 3-1

- manually 3-13

- specific image 3-14

boot loader

- accessing 3-14

- described 3-2

- environment variables 3-14

- prompt 3-14

- trap-door mechanism 3-2

BPDU

- error-disabled state 17-2

- filtering 17-3

- RSTP format 16-12

BPDU filtering

- described 17-3

- disabling 17-12

- enabling 17-12

- support for 1-6

BPDU guard

- described 17-2

- disabling 17-12

- enabling 17-11

- support for 1-6

bridge protocol data unit

- See BPDU

- broadcast storm-control command 19-4

- broadcast storms 19-1

C

- cables, monitoring for unidirectional links 22-1

candidate switch

- automatic discovery 5-4

- defined 5-3

- requirements 5-3

- See also command switch, cluster standby group, and member switch

CA trustpoint

- configuring 8-40

- defined 8-38

- caution, described xxx

CDP

- and trusted boundary 28-37

- automatic discovery in switch clusters 5-4

- configuring 20-2

- default configuration 20-2

- defined with LLDP 21-1

- described 20-1

- disabling for routing device 20-3 to 20-4

- enabling and disabling

- on an interface 20-4

- on a switch 20-3

- monitoring 20-4

- overview 20-1

- support for 1-4

- transmission timer and holdtime, setting 20-2

- updates 20-2

CGMP

- as IGMP snooping learning method 18-8

- joining multicast group 18-3

- CipherSuites 8-39

- Cisco 7960 IP Phone 14-1

- Cisco Discovery Protocol

- See CDP

- Cisco IOS File System

- See IFS

- Cisco IOS IP Service Level Agreements (SLAs) responder [1-3](#)
- Cisco IOS IP SLAs [27-1](#)
- Cisco Network Assistant
 - See Network Assistant
- CiscoWorks 2000 [1-4, 26-4](#)
- CIST regional root
 - See MSTP
- CIST root
 - See MSTP
- civic location [21-3](#)
- class maps for QoS
 - configuring [28-44](#)
 - described [28-7](#)
 - displaying [28-69](#)
- class of service
 - See CoS
- clearing interfaces [10-19](#)
- CLI
 - abbreviating commands [2-4](#)
 - command modes [2-1](#)
 - configuration logging [2-5](#)
 - described [1-4](#)
 - editing features
 - enabling and disabling [2-7](#)
 - keystroke editing [2-7](#)
 - wrapped lines [2-9](#)
 - error messages [2-5](#)
 - filtering command output [2-10](#)
 - getting help [2-3](#)
 - history
 - changing the buffer size [2-6](#)
 - described [2-6](#)
 - disabling [2-7](#)
 - recalling commands [2-6](#)
 - managing clusters [5-14](#)
 - no and default forms of commands [2-4](#)
- client mode, VTP [13-3](#)
- clock
 - See system clock
- cluster requirements [xxxix](#)
- clusters, switch
 - accessing [5-12](#)
 - automatic discovery [5-4](#)
 - automatic recovery [5-9](#)
 - benefits [1-1](#)
 - compatibility [5-4](#)
 - described [5-1](#)
 - LRE profile considerations [5-14](#)
 - managing
 - through CLI [5-14](#)
 - through SNMP [5-15](#)
 - planning [5-4](#)
 - planning considerations
 - automatic discovery [5-4](#)
 - automatic recovery [5-9](#)
 - CLI [5-14](#)
 - host names [5-12](#)
 - IP addresses [5-12](#)
 - LRE profiles [5-14](#)
 - passwords [5-13](#)
 - RADIUS [5-14](#)
 - SNMP [5-13, 5-15](#)
 - TACACS+ [5-14](#)
- See also candidate switch, command switch, cluster standby group, member switch, and standby command switch
- cluster standby group
 - automatic recovery [5-11](#)
 - considerations [5-10](#)
 - defined [5-2](#)
 - requirements [5-3](#)
 - virtual IP address [5-10](#)
- See also HSRP

- CNS 1-4
 - Configuration Engine
 - configID, deviceID, hostname 4-3
 - configuration service 4-2
 - described 4-1
 - event service 4-3
 - embedded agents
 - described 4-5
 - enabling automated configuration 4-6
 - enabling configuration agent 4-9
 - enabling event agent 4-8
 - management functions 1-4
- Coarse Wave Division Multiplexer
 - See CWDM SFPs
- command-line interface
 - See CLI
- command modes 2-1
- commands
 - abbreviating 2-4
 - no and default 2-4
- commands, setting privilege levels 8-8
- command switch
 - accessing 5-10
 - active (AC) 5-9
 - configuration conflicts 32-11
 - defined 5-2
 - passive (PC) 5-9
 - password privilege levels 5-15
 - priority 5-9
 - recovery
 - from command-switch failure 5-9, 32-7
 - from lost member connectivity 32-11
 - redundant 5-9
 - replacing
 - with another switch 32-10
 - with cluster member 32-8
 - requirements 5-3
 - command switch (continued)**
 - standby (SC) 5-9
 - See also candidate switch, cluster standby group, member switch, and standby command switch
- community strings
 - configuring 5-13, 26-8
 - for cluster switches 26-4
 - in clusters 5-13
 - overview 26-4
 - SNMP 5-13
- compatibility, feature 19-11
- config.text 3-12
- configurable leave timer, IGMP 18-5
- configuration, initial
 - defaults 1-10
 - Express Setup 1-2
 - See also getting started guide and hardware installation guide
- configuration changes, logging 25-10
- configuration conflicts, recovering from lost member connectivity 32-11
- configuration examples, network 1-12
- configuration files
 - archiving B-20
 - clearing the startup configuration B-19
 - creating using a text editor B-10
 - default name 3-12
 - deleting a stored configuration B-19
 - described B-8
 - downloading
 - automatically 3-12
 - preparing B-10, B-13, B-16
 - reasons for B-8
 - using FTP B-13
 - using RCP B-17
 - using TFTP B-11
 - guidelines for creating and using B-9
 - guidelines for replacing and rolling back B-21
 - invalid combinations when copying B-5
 - limiting TFTP server access 26-16

configuration files (continued)

- obtaining with DHCP 3-7
- password recovery disable considerations 8-5
- replacing a running configuration B-19, B-20
- rolling back a running configuration B-19, B-20
- specifying the filename 3-12
- system contact and location information 26-15
- types and location B-10
- uploading
 - preparing B-10, B-13, B-16
 - reasons for B-9
 - using FTP B-14
 - using RCP B-18
 - using TFTP B-12
- configuration logger 25-10
- configuration logging 2-5
- configuration replacement B-19
- configuration rollback B-19, B-20
- configuration settings, saving 3-10
- configure terminal command 10-5
- config-vlan mode 2-2, 12-6
- conflicts, configuration 32-11
- connections, secure remote 8-33
- connectivity problems 32-12, 32-14, 32-15
- consistency checks in VTP Version 2 13-4
- console port, connecting to 2-10
- control protocol, IP SLAs 27-3
- conventions
 - command xxx
 - for examples xxx
 - publication xxx
 - text xxx
- corrupted software, recovery steps with Xmodem 32-2
- CoS
 - in Layer 2 frames 28-2
 - override priority 14-6
 - trust priority 14-6
- CoS input queue threshold map for QoS 28-15
- CoS output queue threshold map for QoS 28-18

- CoS-to-DSCP map for QoS 28-52
- counters, clearing interface 10-19
- crashinfo file 32-21
- critical authentication, IEEE 802.1x 9-33
- cryptographic software image
 - SSH 8-33
 - SSL 8-37
- CWDM SFPs 1-17

D

- daylight saving time 6-13
- debugging
 - enabling all system diagnostics 32-19
 - enabling for a specific feature 32-18
 - redirecting error message output 32-19
 - using commands 32-18
- default commands 2-4
- default configuration
 - 802.1x 9-19
 - auto-QoS 28-20
 - banners 6-17
 - booting 3-12
 - CDP 20-2
 - DNS 6-16
 - EtherChannel 31-9
 - Ethernet interfaces 10-9
 - IGMP filtering 18-24
 - IGMP snooping 18-6, 30-5, 30-6
 - IGMP throttling 18-24
 - initial switch information 3-3
 - IP SLAs 27-5
 - IPv6 29-8
 - Layer 2 interfaces 10-9
 - LLDP 21-3
 - MAC address table 6-21
 - MSTP 16-14
 - MVR 18-19
 - NTP 6-4

default configuration (continued)

- optional spanning-tree configuration [17-9](#)
- password and privilege level [8-2](#)
- RADIUS [8-20](#)
- RMON [24-3](#)
- RSPAN [23-9](#)
- SDM template [7-2](#)
- SNMP [26-7](#)
- SPAN [23-9](#)
- SSL [8-40](#)
- standard QoS [28-30](#)
- STP [15-11](#)
- system message logging [25-3](#)
- system name and prompt [6-15](#)
- TACACS+ [8-13](#)
- UDLD [22-4](#)
- VLAN, Layer 2 Ethernet interfaces [12-16](#)
- VLANs [12-7](#)
- VMPS [12-25](#)
- voice VLAN [14-3](#)
- VTP [13-6](#)
- default gateway [3-10](#)
- deleting VLANs [12-9](#)
- denial-of-service attack [19-1](#)
- description command [10-16](#)
- designing your network, examples [1-12](#)
- destination-IP address-based forwarding, EtherChannel [31-7](#)
- destination-MAC address forwarding, EtherChannel [31-6](#)
- detecting indirect link failures, STP [17-5](#)
- device [B-23](#)
- device discovery protocol [20-1, 21-1](#)
- device manager
 - benefits [1-1](#)
 - described [1-2, 1-3](#)
 - in-band management [1-5](#)
 - requirements [xxx](#)
 - upgrading a switch [B-23](#)

DHCP-based autoconfiguration

- client request message exchange [3-4](#)
- configuring
 - client side [3-3](#)
 - DNS [3-6](#)
 - relay device [3-6](#)
 - server side [3-5](#)
 - TFTP server [3-6](#)
- example [3-8](#)
- lease options
 - for IP address information [3-5](#)
 - for receiving the configuration file [3-5](#)
- overview [3-3](#)
- relationship to BOOTP [3-3](#)
- relay support [1-4](#)
- support for [1-4](#)
- Differentiated Services architecture, QoS [28-2](#)
- Differentiated Services Code Point [28-2](#)
- directed unicast requests [1-4](#)
- directories
 - changing [B-4](#)
 - creating and removing [B-4](#)
 - displaying the working [B-4](#)
- discovery, clusters
 - See automatic discovery
- DNS
 - and DHCP-based autoconfiguration [3-6](#)
 - default configuration [6-16](#)
 - displaying the configuration [6-17](#)
 - in IPv6 [29-4](#)
 - overview [6-15](#)
 - setting up [6-16](#)
 - support for [1-4](#)
- documentation, related [xxx](#)
- document conventions [xxx](#)
- domain names
 - DNS [6-15](#)
 - VTP [13-8](#)

Domain Name System

See DNS

downloading

configuration files

preparing [B-10, B-13, B-16](#)reasons for [B-8](#)using FTP [B-13](#)using RCP [B-17](#)using TFTP [B-11](#)

image files

deleting old image [B-28](#)preparing [B-26, B-29, B-33](#)reasons for [B-23](#)using CMS [1-2](#)using FTP [B-30](#)using HTTP [1-2, B-23](#)using RCP [B-35](#)using TFTP [B-27](#)using the device manager or Network Assistant [B-23](#)DSCP [1-9, 28-2](#)DSCP input queue threshold map for QoS [28-15](#)DSCP output queue threshold map for QoS [28-18](#)DSCP-to-CoS map for QoS [28-55](#)DSCP-to-DSCP-mutation map for QoS [28-56](#)DSCP transparency [28-38](#)DTP [1-7, 12-14](#)Dual IPv4-and-IPv6 SDM Templates [29-7](#)dual IPv4 and IPv6 templates [29-1, 29-6](#)

dual protocol stacks

IPv4 and IPv6 [29-6](#)SDM templates supporting [29-6](#)

dual-purpose uplinks

defined [10-4](#)LEDs [10-4](#)link selection [10-4](#)setting the type [10-10](#)

dynamic access ports

characteristics [12-3](#)configuring [12-26](#)defined [10-3](#)

dynamic addresses

See addresses

dynamic auto trunking mode [12-15](#)dynamic desirable trunking mode [12-15](#)

Dynamic Host Configuration Protocol

See DHCP-based autoconfiguration

dynamic port VLAN membership

described [12-24](#)reconfirming [12-27](#)troubleshooting [12-29](#)types of connections [12-26](#)

Dynamic Trunking Protocol

See DTP

E

editing features

enabling and disabling [2-7](#)keystrokes used [2-7](#)wrapped lines [2-9](#)ELIN location [21-3](#)enable password [8-3](#)enable secret password [8-3](#)encryption, CipherSuite [8-39](#)encryption for passwords [8-3](#)environment variables, function of [3-15](#)error-disabled state, BPDU [17-2](#)error messages during command entry [2-5](#)

EtherChannel

automatic creation of [31-4, 31-5](#)

channel groups

binding physical and logical interfaces [31-3](#)numbering of [31-3](#)configuration guidelines [31-9](#)configuring Layer 2 interfaces [31-10](#)

EtherChannel (continued)

- default configuration 31-9
- described 31-2
- displaying status 31-16
- forwarding methods 31-6, 31-12
- IEEE 802.3ad, described 31-5
- interaction
 - with STP 31-9
 - with VLANs 31-10

LACP

- described 31-5
- displaying status 31-16
- hot-standby ports 31-14
- interaction with other features 31-6
- modes 31-5
- port priority 31-15
- system priority 31-15

- load balancing 31-6, 31-12

PAgP

- aggregate-port learners 31-13
- compatibility with Catalyst 1900 31-13
- described 31-4
- displaying status 31-16
- interaction with other features 31-5
- learn method and priority configuration 31-13
- modes 31-4
- support for 1-3

port-channel interfaces

- described 31-3
- numbering of 31-3

- port groups 10-3

- support for 1-3

EtherChannel guard

- described 17-7
- disabling 17-14
- enabling 17-14

Ethernet VLANs

- adding 12-8
- defaults and ranges 12-7
- modifying 12-8

EUI 29-3

- events, RMON 24-3

examples

- conventions for xxx
- network configuration 1-12

- expedite queue for QoS 28-68

Express Setup 1-2

- See also getting started guide

- extended crashinfo file 32-21

extended-range VLANs

- configuration guidelines 12-12
- configuring 12-11
- creating 12-12
- defined 12-1

extended system ID

- MSTP 16-17
- STP 15-4, 15-14

extended universal identifier

- See EUI

- Extensible Authentication Protocol over LAN 9-1

F

- fa0 interface 1-5

- features, incompatible 19-11

- fiber-optic, detecting unidirectional links 22-1

files

- basic crashinfo
 - description 32-21
 - location 32-21
- copying B-5
- crashinfo, description 32-21
- deleting B-5
- displaying the contents of B-8

files (continued)

- extended crashinfo
 - description [32-22](#)
 - location [32-22](#)
- tar
 - creating [B-6](#)
 - displaying the contents of [B-7](#)
 - extracting [B-7](#)
 - image file format [B-24](#)

file system

- displaying available file systems [B-2](#)
- displaying file information [B-3](#)
- local file system names [B-1](#)
- network file system names [B-5](#)
- setting the default [B-3](#)

filtering

- show and more command output [2-10](#)

filtering show and more command output [2-10](#)**flash device, number of [B-1](#)****flooded traffic, blocking [19-7](#)****flow-based packet classification [1-9](#)****flowcharts**

- QoS classification [28-6](#)
- QoS egress queueing and scheduling [28-16](#)
- QoS ingress queueing and scheduling [28-14](#)
- QoS policing and marking [28-10](#)

flowcontrol

- configuring [10-14](#)
- described [10-14](#)

forward-delay time

- MSTP [16-23](#)
- STP [15-21](#)

FTP

- accessing MIB files [A-3](#)
- configuration files
 - downloading [B-13](#)
 - overview [B-12](#)
 - preparing the server [B-13](#)
 - uploading [B-14](#)

FTP (continued)

- image files
 - deleting old image [B-32](#)
 - downloading [B-30](#)
 - preparing the server [B-29](#)
 - uploading [B-32](#)

G**get-bulk-request operation [26-3](#)****get-next-request operation [26-3, 26-5](#)****get-request operation [26-3, 26-5](#)****get-response operation [26-3](#)****global configuration mode [2-2](#)****global leave, IGMP [18-12](#)****guest VLAN and 802.1x [9-11](#)****guide**

- audience [xxix](#)
- purpose of [xxix](#)

guide mode [1-2](#)**GUIs**

See device manager and Network Assistant

H**hello time**

- MSTP [16-22](#)
- STP [15-20](#)

help, for the command line [2-3](#)**history**

- changing the buffer size [2-6](#)
- described [2-6](#)
- disabling [2-7](#)
- recalling commands [2-6](#)

history table, level and number of syslog messages [25-10](#)**host names, in clusters [5-12](#)****hosts, limit on dynamic ports [12-29](#)****HP OpenView [1-4](#)**

HSRP

- automatic cluster recovery [5-11](#)
- cluster standby group considerations [5-10](#)
- See also clusters, cluster standby group, and standby command switch

HTTP over SSL

- see HTTPS

HTTPS [8-38](#)

- configuring [8-41](#)
- self-signed certificate [8-38](#)

HTTP secure server [8-38](#)

ICMP

- IPv6 [29-4](#)
- time-exceeded messages [32-16](#)
- traceroute and [32-16](#)

ICMP ping

- executing [32-13](#)
- overview [32-13](#)

ICMPv6 [29-4](#)

IDS appliances

- and ingress RSPAN [23-20](#)
- and ingress SPAN [23-13](#)

IEEE 802.1D

- See STP

IEEE 802.1p [14-1](#)

IEEE 802.1Q

- and trunk ports [10-3](#)
- configuration limitations [12-15](#)
- encapsulation [12-14](#)
- native VLAN for untagged traffic [12-19](#)

IEEE 802.1s

- See MSTP

IEEE 802.1w

- See RSTP

IEEE 802.1x

- See port-based authentication

IEEE 802.3ad

- See EtherChannel

IEEE 802.3x flow control [10-14](#)ifIndex values, SNMP [26-6](#)IFS [1-4](#)

IGMP

- configurable leave timer
 - described [18-5](#)
 - enabling [18-11](#)
- flooded multicast traffic
 - controlling the length of time [18-12](#)
 - disabling on an interface [18-13](#)
 - global leave [18-12](#)
 - query solicitation [18-12](#)
 - recovering from flood mode [18-12](#)
- joining multicast group [18-3](#)
- join messages [18-3](#)
- leave processing, enabling [18-10, 30-9](#)
- leaving multicast group [18-5](#)
- queries [18-4](#)
- report suppression
 - described [18-6](#)
 - disabling [18-15, 30-11](#)
- supported versions [18-2](#)
- support for [1-3](#)

IGMP filtering

- configuring [18-24](#)
- default configuration [18-24](#)
- described [18-23](#)
- monitoring [18-28](#)
- support for [1-3](#)

IGMP groups

- configuring filtering [18-27](#)
- setting the maximum number [18-26](#)

IGMP Immediate Leave

- configuration guidelines [18-11](#)
- described [18-5](#)
- enabling [18-10](#)

- IGMP profile
 - applying [18-25](#)
 - configuration mode [18-24](#)
 - configuring [18-25](#)
- IGMP snooping
 - and address aliasing [18-2](#)
 - configuring [18-6](#)
 - default configuration [18-6, 30-5, 30-6](#)
 - definition [18-1](#)
 - enabling and disabling [18-7, 30-6](#)
 - global configuration [18-7](#)
 - Immediate Leave [18-5](#)
 - method [18-8](#)
 - monitoring [18-15, 30-11](#)
 - querier
 - configuration guidelines [18-14](#)
 - configuring [18-14](#)
 - supported versions [18-2](#)
 - support for [1-3](#)
 - VLAN configuration [18-7](#)
- IGMP throttling
 - configuring [18-27](#)
 - default configuration [18-24](#)
 - described [18-24](#)
 - displaying action [18-28](#)
- Immediate Leave, IGMP [18-5](#)
 - enabling [30-9](#)
- inaccessible authentication bypass [9-13](#)
- initial configuration
 - defaults [1-10](#)
 - Express Setup [1-2](#)
 - See also getting started guide and hardware installation guide
- interface
 - number [10-5](#)
 - range macros [10-7](#)
- interface command [10-5](#)
- interface configuration mode [2-3](#)
- interfaces
 - auto-MDIX, configuring [10-15](#)
 - configuration guidelines
 - duplex and speed [10-12](#)
 - configuring
 - procedure [10-5](#)
 - counters, clearing [10-19](#)
 - default configuration [10-9](#)
 - described [10-16](#)
 - descriptive name, adding [10-16](#)
 - displaying information about [10-18](#)
 - flow control [10-14](#)
 - management [1-3](#)
 - monitoring [10-18](#)
 - naming [10-16](#)
 - physical, identifying [10-5](#)
 - range of [10-6](#)
 - restarting [10-19](#)
 - shutting down [10-19](#)
 - speed and duplex, configuring [10-13](#)
 - status [10-18](#)
 - supported [10-4](#)
 - types of [10-1](#)
- interfaces range macro command [10-7](#)
- interface types [10-5](#)
- Internet Protocol version 6
 - See IPv6
- Intrusion Detection System
 - See IDS appliances
- inventory management TLV [21-3, 21-6](#)
- IP ACLs
 - for QoS classification [28-7](#)
- IP addresses
 - 128-bit [29-2](#)
 - candidate or member [5-3, 5-12](#)
 - cluster access [5-2](#)
 - command switch [5-3, 5-10, 5-12](#)
 - discovering [6-26](#)
 - IPv6 [29-2](#)

IP addresses (continued)

- redundant clusters [5-10](#)
- standby command switch [5-10, 5-12](#)

See also IP information

ip igmp profile command [18-24](#)

IP information

- assigned
 - manually [3-10](#)
 - through DHCP-based autoconfiguration [3-3](#)
- default configuration [3-3](#)

IP phones

- and QoS [14-1](#)
- automatic classification and queueing [28-19](#)
- configuring [14-4](#)
- ensuring port security with QoS [28-36](#)
- trusted boundary for QoS [28-36](#)

IP precedence [28-2](#)

IP-precedence-to-DSCP map for QoS [28-53](#)

IP Service Level Agreements

See IP SLAs

IP service levels, analyzing [27-1](#)

IP SLAs

- benefits [27-2](#)
- configuration guidelines [27-5](#)
- Control Protocol [27-3](#)
- default configuration [27-5](#)
- definition [27-1](#)
- measuring network performance [27-2](#)
- monitoring [27-7](#)
- operation [27-3](#)
- responder
 - described [27-3](#)
 - enabling [27-6](#)
- response time [27-4](#)
- SNMP support [27-2](#)
- supported metrics [27-2](#)

IP traceroute

- executing [32-16](#)
- overview [32-15](#)

IPv4 and IPv6

- differences [29-2](#)
- dual protocol stacks [29-5](#)

IPv6

- addresses [29-2](#)
- address formats [29-2](#)
- advantages [29-2](#)
- applications [29-5](#)
- autoconfiguration [29-4](#)
- configuring static routes [29-9](#)
- default configuration [29-8](#)
- defined [29-1](#)
- ICMP [29-4](#)
- ICMP rate limiting [29-8](#)
- monitoring [29-11](#)
- neighbor discovery [29-4](#)
- reasons for [29-1](#)
- SDM templates [29-6, 30-1](#)
- supported features [29-3](#)

J

join messages, IGMP [18-3](#)

L**LACP**

See EtherChannel

Layer 2 frames, classification with CoS [28-2](#)

Layer 2 interfaces, default configuration [10-9](#)

Layer 2 traceroute

- and ARP [32-15](#)
- and CDP [32-14](#)
- broadcast traffic [32-14](#)
- described [32-14](#)
- IP addresses and subnets [32-15](#)
- MAC addresses and VLANs [32-15](#)
- multicast traffic [32-15](#)

Layer 2 traceroute (continued)

- multiple devices on a port [32-15](#)
- unicast traffic [32-14](#)
- usage guidelines [32-14](#)

Layer 3 packets, classification methods [28-2](#)

LDAP [4-2](#)

LEDs, switch

- See hardware installation guide

lightweight directory access protocol

- See LDAP

line configuration mode [2-3](#)

Link Aggregation Control Protocol

- See EtherChannel

link failure, detecting unidirectional [16-8](#)

Link Layer Discovery Protocol

- See CDP

link local unicast addresses [29-3](#)

links, unidirectional [22-1](#)

link-state tracking

- configuring [31-19](#)
- described [31-17](#)

LLDP

- configuring [21-3](#)
 - characteristics [21-4](#)
 - default configuration [21-3](#)
- disabling and enabling
 - globally [21-5](#)
 - on an interface [21-5](#)
- monitoring and maintaining [21-7](#)
- overview [21-1](#)
- supported TLVs [21-2](#)
- switch stack considerations [21-2](#)
- transmission timer and holdtime, setting [21-4](#)

LLDP-MED

- configuring
 - procedures [21-3](#)
 - TLVs [21-6](#)
- monitoring and maintaining [21-7](#)

LLDP-MED (continued)

- overview [21-1, 21-2](#)
- supported TLVs [21-2](#)

LLDP Media Endpoint Discovery

- See LLDP-MED

local SPAN [23-2](#)

location TLV [21-3, 21-6](#)

login authentication

- with RADIUS [8-23](#)
- with TACACS+ [8-14](#)

login banners [6-17](#)

log messages

- See system message logging

Long-Reach Ethernet (LRE) technology [1-14](#)

loop guard

- described [17-9](#)
- enabling [17-15](#)
- support for [1-6](#)

LRE profiles, considerations in switch clusters [5-14](#)

M

MAC/PHY configuration status TLV [21-2](#)

MAC addresses

- aging time [6-21](#)
- and VLAN association [6-20](#)
- building the address table [6-20](#)
- default configuration [6-21](#)
- discovering [6-26](#)
- displaying [6-26](#)
- dynamic
 - learning [6-20](#)
 - removing [6-22](#)
- static
 - adding [6-24](#)
 - allowing [6-25](#)
 - characteristics of [6-24](#)
 - dropping [6-25](#)
 - removing [6-24](#)

- MAC address notification, support for [1-10](#)
- MAC address-to-VLAN mapping [12-24](#)
- MAC extended access lists
 - configuring for QoS [28-43](#)
 - for QoS classification [28-5](#)
- macros
 - See Smartports macros
- magic packet [9-15](#)
- manageability features [1-4](#)
- management access
 - in-band
 - browser session [1-5](#)
 - CLI session [1-5](#)
 - device manager [1-5](#)
 - SNMP [1-5](#)
 - out-of-band console port connection [1-5](#)
- management address TLV [21-2](#)
- management options
 - CLI [2-1](#)
 - clustering [1-2](#)
 - CNS [4-1](#)
 - Network Assistant [1-2](#)
 - overview [1-3](#)
- management VLAN
 - considerations in switch clusters [5-7](#)
 - discovery through different management VLANs [5-7](#)
- mapping tables for QoS
 - configuring
 - CoS-to-DSCP [28-52](#)
 - DSCP [28-51](#)
 - DSCP-to-CoS [28-55](#)
 - DSCP-to-DSCP-mutation [28-56](#)
 - IP-precedence-to-DSCP [28-53](#)
 - policed-DSCP [28-54](#)
 - described [28-11](#)
- marking
 - action with aggregate policers [28-49](#)
 - described [28-4, 28-8](#)
- maximum aging time
 - MSTP [16-23](#)
 - STP [15-21](#)
- maximum hop count, MSTP [16-24](#)
- membership mode, VLAN port [12-3](#)
- member switch
 - automatic discovery [5-4](#)
 - defined [5-2](#)
 - managing [5-14](#)
 - passwords [5-12](#)
 - recovering from lost connectivity [32-11](#)
 - requirements [5-3](#)
 - See also candidate switch, cluster standby group, and standby command switch
- messages, to users through banners [6-17](#)
- MIBs
 - accessing files with FTP [A-3](#)
 - location of files [A-3](#)
 - overview [26-1](#)
 - SNMP interaction with [26-4](#)
 - supported [A-1](#)
- mirroring traffic for analysis [23-1](#)
- mismatches, autonegotiation [32-11](#)
- module number [10-5](#)
- monitoring
 - cables for unidirectional links [22-1](#)
 - CDP [20-4](#)
 - features [1-10](#)
 - IGMP
 - filters [18-28](#)
 - snooping [18-15, 30-11](#)
 - interfaces [10-18](#)
 - IP SLAs operations [27-7](#)
 - IPv6 [29-11](#)
 - multicast router interfaces [18-16, 30-12](#)
 - MVR [18-23](#)
 - network traffic for analysis with probe [23-2](#)

monitoring (continued)

port

blocking 19-18

protection 19-18

SFP status 10-18, 32-12

speed and duplex mode 10-13

traffic flowing among switches 24-1

traffic suppression 19-17

VLANs 12-13

VMPS 12-28

VTP 13-16

MSTP

boundary ports

configuration guidelines 16-15

described 16-6

BPDU filtering

described 17-3

enabling 17-12

BPDU guard

described 17-2

enabling 17-11

CIST, described 16-3

CIST regional root 16-3

CIST root 16-5

configuration guidelines 16-15, 17-10

configuring

forward-delay time 16-23

hello time 16-22

link type for rapid convergence 16-24

maximum aging time 16-23

maximum hop count 16-24

MST region 16-16

neighbor type 16-25

path cost 16-20

port priority 16-19

root switch 16-17

secondary root switch 16-18

switch priority 16-21

MSTP (continued)

CST

defined 16-3

operations between regions 16-4

default configuration 16-14

default optional feature configuration 17-9

displaying status 16-26

enabling the mode 16-16

EtherChannel guard

described 17-7

enabling 17-14

extended system ID

effects on root switch 16-17

effects on secondary root switch 16-18

unexpected behavior 16-17

IEEE 802.1s

implementation 16-6

port role naming change 16-7

terminology 16-5

instances supported 15-9

interface state, blocking to forwarding 17-2

interoperability and compatibility among modes 15-10

interoperability with IEEE 802.1D

described 16-8

restarting migration process 16-25

IST

defined 16-3

master 16-3

operations within a region 16-3

loop guard

described 17-9

enabling 17-15

mapping VLANs to MST instance 16-16

MSTP (continued)

- MST region
 - CIST [16-3](#)
 - configuring [16-16](#)
 - described [16-2](#)
 - hop-count mechanism [16-5](#)
 - IST [16-3](#)
 - supported spanning-tree instances [16-2](#)
- optional features supported [1-6](#)
- overview [16-2](#)
- Port Fast
 - described [17-2](#)
 - enabling [17-10](#)
- preventing root switch selection [17-8](#)
- root guard
 - described [17-8](#)
 - enabling [17-15](#)
- root switch
 - configuring [16-17](#)
 - effects of extended system ID [16-17](#)
 - unexpected behavior [16-17](#)
- shutdown Port Fast-enabled port [17-2](#)
- status, displaying [16-26](#)
- multicast groups
 - Immediate Leave [18-5](#)
 - joining [18-3](#)
 - leaving [18-5](#)
 - static joins [18-10, 30-8](#)
- multicast router interfaces, monitoring [18-16, 30-12](#)
- multicast router ports, adding [18-9, 30-8](#)
- multicast storm [19-1](#)
- multicast storm-control command [19-4](#)
- multicast television application [18-18](#)
- multicast VLAN [18-17](#)
- Multicast VLAN Registration
 - See MVR

MVR

- and address aliasing [18-20](#)
- and IGMPv3 [18-20](#)
- configuration guidelines [18-20](#)
- configuring interfaces [18-21](#)
- default configuration [18-19](#)
- described [18-17](#)
- example application [18-18](#)
- modes [18-21](#)
- monitoring [18-23](#)
- multicast television application [18-18](#)
- setting global parameters [18-20](#)
- support for [1-3](#)

N**NAC**

- critical authentication [9-13, 9-33](#)
- IEEE 802.1x authentication using a RADIUS server [9-37](#)
- IEEE 802.1x validation using RADIUS server [9-37](#)
- inaccessible authentication bypass [9-33](#)
- Layer 2 IEEE 802.1x validation [1-8, 9-37](#)
- Layer 2 IEEE802.1x validation [9-17](#)

NameSpace Mapper

See NSM

native VLAN

- configuring [12-19](#)
- default [12-19](#)

neighbor discovery, IPv6 [29-4](#)**Network Admission Control**

See NAC

Network Admission Control Software Configuration Guide [9-39, 9-40](#)**Network Assistant**

- benefits [1-1](#)
- described [1-3](#)
- downloading image files [1-2](#)
- guide mode [1-2](#)

Network Assistant (continued)

- management options 1-2
- requirements xxx
- upgrading a switch B-23
- wizards 1-2

network configuration examples

- increasing network performance 1-13
- long-distance, high-bandwidth transport 1-17
- providing network services 1-13
- server aggregation and Linux server cluster 1-15
- small to medium-sized network 1-16

network design

- performance 1-13
- services 1-13

network management

- CDP 20-1
- RMON 24-1
- SNMP 26-1

network performance, measuring with IP SLAs 27-2

network policy TLV 21-2, 21-6

Network Time Protocol

See NTP

no commands 2-4

nonhierarchical policy maps

described 28-9

nontrunking mode 12-15

normal-range VLANs 12-4

- configuration guidelines 12-5
- configuration modes 12-6
- configuring 12-4
- defined 12-1

note, described xxx

NSM 4-3

NTP

associations

- authenticating 6-4
- defined 6-2
- enabling broadcast messages 6-6
- peer 6-5
- server 6-5

default configuration 6-4

displaying the configuration 6-11

overview 6-2

restricting access

- creating an access group 6-8
- disabling NTP services per interface 6-10

source IP address, configuring 6-10

stratum 6-2

support for 1-4

synchronizing devices 6-5

time

- services 6-2
- synchronizing 6-2

O

optimizing system resources 7-1

options, management 1-3

out-of-profile markdown 1-9

P

packet modification, with QoS 28-18

PAGP

See EtherChannel

passwords

- default configuration 8-2
- disabling recovery of 8-5
- encrypting 8-3
- for security 1-7
- in clusters 5-13

passwords (continued)

- overview 8-1
 - recovery of 32-3
 - setting
 - enable 8-3
 - enable secret 8-3
 - Telnet 8-6
 - with usernames 8-6
 - VTP domain 13-8
- path cost
- MSTP 16-20
 - STP 15-18
- PC (passive command switch) 5-9
- performance, network design 1-13
- performance features 1-2
- persistent self-signed certificate 8-38
- per-VLAN spanning-tree plus
- See PVST+
- physical ports 10-2
- PIM-DVMRP, as snooping method 18-8
- ping
- character output description 32-13
 - executing 32-13
 - overview 32-13
- policed-DSCP map for QoS 28-54
- policers
- configuring
 - for each matched traffic class 28-46
 - for more than one traffic class 28-49
 - described 28-4
 - displaying 28-69
 - number of 28-32
 - types of 28-9
- policing
- described 28-4
 - token-bucket algorithm 28-9

policy maps for QoS

- characteristics of 28-46
- described 28-7
- displaying 28-70

nonhierarchical on physical ports

- described 28-9

Port Aggregation Protocol

- See EtherChannel

port-based authentication

- accounting 9-8
- authentication server
 - defined 9-2
 - RADIUS server 9-2
- client, defined 9-2
- configuration guidelines 9-20
- configuring
 - 802.1x authentication 9-22
 - guest VLAN 9-30
 - host mode 9-25
 - inaccessible authentication bypass 9-33
 - manual re-authentication of a client 9-26
 - periodic re-authentication 9-25
 - quiet period 9-26
 - RADIUS server 9-25
 - RADIUS server parameters on the switch 9-24
 - restricted VLAN 9-31
 - switch-to-client frame-retransmission number 9-28
 - switch-to-client retransmission time 9-27
- default configuration 9-19
- described 9-1
- device roles 9-2
- displaying statistics 9-41
- EAPOL-start frame 9-5
- EAP-request/identity frame 9-5
- EAP-response/identity frame 9-5
- encapsulation 9-3

port-based authentication (continued)

- guest VLAN
 - configuration guidelines 9-11, 9-12
 - described 9-11
- host mode 9-7
- inaccessible authentication bypass
 - configuring 9-33
 - described 9-13
 - guidelines 9-21
- initiation and message exchange 9-5
- magic packet 9-15
- method lists 9-22
- multiple-hosts mode, described 9-8
- ports
 - authorization state and dot1x port-control command 9-7
 - authorized and unauthorized 9-7
 - critical 9-13
 - voice VLAN 9-14
- port security
 - and voice VLAN 9-15
 - described 9-14
 - interactions 9-15
 - multiple-hosts mode 9-8
- resetting to default values 9-41
- statistics, displaying 9-41
- switch
 - as proxy 9-3
 - RADIUS client 9-3
- upgrading from a previous release 9-22
- VLAN assignment
 - AAA authorization 9-22
 - characteristics 9-10
 - configuration tasks 9-10
 - described 9-9

port-based authentication (continued)

- voice VLAN
 - described 9-14
 - PVID 9-14
 - VVID 9-14
 - wake-on-LAN, described 9-15
- port blocking 1-3, 19-7
- port-channel
 - See EtherChannel
- port description TLV 21-2
- Port Fast
 - described 17-2
 - enabling 17-10
 - mode, spanning tree 12-25
 - support for 1-6
- port membership modes, VLAN 12-3
- port priority
 - MSTP 16-19
 - STP 15-16
- ports
 - access 10-2
 - blocking 19-7
 - dual-purpose uplink 10-4
 - dynamic access 12-3
 - protected 19-5
 - secure 19-8
 - static-access 12-3, 12-10
 - switch 10-2
 - trunks 12-3, 12-14
 - VLAN assignments 12-10
- port security
 - aging 19-16
 - and QoS trusted boundary 28-36
 - configuring 19-11
 - default configuration 19-10
 - described 19-8
 - displaying 19-18
 - on trunk ports 19-13
 - sticky learning 19-9

port security (continued)

- violations [19-9](#)
- with other features [19-10](#)
- port-shutdown response, VMPS [12-24](#)
- port VLAN ID TLV [21-2](#)
- power management TLV [21-2, 21-6](#)
- preferential treatment of traffic
 - See QoS
- preventing unauthorized access [8-1](#)
- priority
 - overriding CoS [14-6](#)
 - trusting CoS [14-6](#)
- private VLAN edge ports
 - See protected ports
- privileged EXEC mode [2-2](#)
- privilege levels
 - changing the default for lines [8-9](#)
 - command switch [5-15](#)
 - exiting [8-9](#)
 - logging into [8-9](#)
 - mapping on member switches [5-15](#)
 - overview [8-2, 8-7](#)
 - setting a command with [8-8](#)
- protected ports [1-7, 19-5](#)
- pruning, VTP
 - disabling
 - in VTP domain [13-14](#)
 - on a port [12-19](#)
 - enabling
 - in VTP domain [13-14](#)
 - on a port [12-19](#)
 - examples [13-5](#)
 - overview [13-4](#)
- pruning-eligible list
 - changing [12-19](#)
 - for VTP pruning [13-4](#)
 - VLANs [13-14](#)

PVST+

- described [15-9](#)
- IEEE 802.1Q trunking interoperability [15-10](#)
- instances supported [15-9](#)

Q**QoS**

- and MQC commands [28-1](#)
- auto-QoS
 - categorizing traffic [28-20](#)
 - configuration and defaults display [28-29](#)
 - configuration guidelines [28-25](#)
 - described [28-19](#)
 - disabling [28-26](#)
 - displaying generated commands [28-26](#)
 - displaying the initial configuration [28-29](#)
 - effects on running configuration [28-24](#)
 - egress queue defaults [28-20](#)
 - enabling for VoIP [28-25](#)
 - example configuration [28-27](#)
 - ingress queue defaults [28-20](#)
 - list of generated commands [28-21](#)
- basic model [28-4](#)
- classification
 - class maps, described [28-7](#)
 - defined [28-4](#)
 - DSCP transparency, described [28-38](#)
 - flowchart [28-6](#)
 - forwarding treatment [28-3](#)
 - in frames and packets [28-3](#)
 - IP ACLs, described [28-5, 28-7](#)
 - MAC ACLs, described [28-5, 28-7](#)
 - options for IP traffic [28-5](#)
 - options for non-IP traffic [28-5](#)
 - policy maps, described [28-7](#)
 - trust DSCP, described [28-5](#)
 - trusted CoS, described [28-5](#)
 - trust IP precedence, described [28-5](#)

QoS (continued)

- class maps
 - configuring 28-44
 - displaying 28-69
- configuration guidelines
 - auto-QoS 28-25
 - standard QoS 28-32
- configuring
 - aggregate policers 28-49
 - auto-QoS 28-19
 - default port CoS value 28-36
 - DSCP maps 28-51
 - DSCP transparency 28-38
 - DSCP trust states bordering another domain 28-38
 - egress queue characteristics 28-62
 - ingress queue characteristics 28-57
 - IP extended ACLs 28-42
 - IP standard ACLs 28-41
 - MAC ACLs 28-43
 - port trust states within the domain 28-34
 - trusted boundary 28-36
- default auto configuration 28-20
- default standard configuration 28-30
- displaying statistics 28-69
- DSCP transparency 28-38
- egress queues
 - allocating buffer space 28-62
 - buffer allocation scheme, described 28-17
 - configuring shaped weights for SRR 28-66
 - configuring shared weights for SRR 28-67
 - described 28-4
 - displaying the threshold map 28-65
 - flowchart 28-16
 - mapping DSCP or CoS values 28-65
 - scheduling, described 28-4
 - setting WTD thresholds 28-62
 - WTD, described 28-18
- enabling globally 28-33

QoS (continued)

- flowcharts
 - classification 28-6
 - egress queueing and scheduling 28-16
 - ingress queueing and scheduling 28-14
 - policing and marking 28-10
- implicit deny 28-7
- ingress queues
 - allocating bandwidth 28-60
 - allocating buffer space 28-59
 - buffer and bandwidth allocation, described 28-15
 - configuring shared weights for SRR 28-60
 - configuring the priority queue 28-61
 - described 28-4
 - displaying the threshold map 28-59
 - flowchart 28-14
 - mapping DSCP or CoS values 28-58
 - priority queue, described 28-15
 - scheduling, described 28-4
 - setting WTD thresholds 28-58
 - WTD, described 28-15
- IP phones
 - automatic classification and queueing 28-19
 - detection and trusted settings 28-19, 28-36
- limiting bandwidth on egress interface 28-68
- mapping tables
 - CoS-to-DSCP 28-52
 - displaying 28-69
 - DSCP-to-CoS 28-55
 - DSCP-to-DSCP-mutation 28-56
 - IP-precedence-to-DSCP 28-53
 - policed-DSCP 28-54
 - types of 28-11
- marked-down actions 28-48
- marking, described 28-4, 28-8
- overview 28-1
- packet modification 28-18

QoS (continued)

- configuring [28-48, 28-50](#)
 - described [28-8](#)
 - displaying [28-69](#)
 - number of [28-32](#)
 - types of [28-9](#)
 - policies, attaching to an interface [28-8](#)
 - described [28-4, 28-8](#)
 - token bucket algorithm [28-9](#)
 - characteristics of [28-46](#)
 - displaying [28-70](#)
 - nonhierarchical on physical ports [28-46](#)
 - QoS label, defined [28-4](#)
 - configuring egress characteristics [28-62](#)
 - configuring ingress characteristics [28-57](#)
 - high priority (expedite) [28-18, 28-68](#)
 - location of [28-12](#)
 - SRR, described [28-13](#)
 - WTD, described [28-12](#)
 - rewrites [28-18](#)
 - support for [1-9](#)
 - bordering another domain [28-38](#)
 - described [28-5](#)
 - trusted device [28-36](#)
 - within the domain [28-34](#)
 - quality of service
 - See QoS
 - queries, IGMP [18-4](#)
 - query solicitation, IGMP [18-12](#)

R**RADIUS**

- attributes
 - vendor-proprietary [8-31](#)
 - vendor-specific [8-29](#)
 - configuring
 - accounting [8-28](#)
 - authentication [8-23](#)
 - authorization [8-27](#)
 - communication, global [8-21, 8-29](#)
 - communication, per-server [8-20, 8-21](#)
 - multiple UDP ports [8-20](#)
 - default configuration [8-20](#)
 - defining AAA server groups [8-25](#)
 - displaying the configuration [8-31](#)
 - identifying the server [8-20](#)
 - in clusters [5-14](#)
 - limiting the services to the user [8-27](#)
 - method list, defined [8-19](#)
 - operation of [8-19](#)
 - overview [8-18](#)
 - suggested network environments [8-18](#)
 - support for [1-8](#)
 - tracking services accessed by user [8-28](#)
 - range
 - macro [10-7](#)
 - of interfaces [10-6](#)
 - rapid convergence [16-10](#)
 - rapid per-VLAN spanning-tree plus
 - See rapid PVST+
 - rapid PVST+
 - described [15-9](#)
 - IEEE 802.1Q trunking interoperability [15-10](#)
 - instances supported [15-9](#)
 - Rapid Spanning Tree Protocol
 - See RSTP
 - rcommand command [5-14](#)

RCP

configuration files

downloading [B-17](#)overview [B-15](#)preparing the server [B-16](#)uploading [B-18](#)

image files

deleting old image [B-36](#)downloading [B-35](#)preparing the server [B-33](#)uploading [B-37](#)reconfirmation interval, VMPS, changing [12-27](#)reconfirming dynamic VLAN membership [12-27](#)recovery procedures [32-1](#)

redundancy

EtherChannel [31-3](#)

STP

backbone [15-8](#)path cost [12-22](#)port priority [12-20](#)redundant links and UplinkFast [17-13](#)reloading software [3-16](#)

Remote Authentication Dial-In User Service

See RADIUS

Remote Copy Protocol

See RCP

Remote Network Monitoring

See RMON

Remote SPAN

See RSPAN

remote SPAN [23-2](#)

report suppression, IGMP

described [18-6](#)disabling [18-15, 30-11](#)

requirements

cluster [xxx](#)device manager [xxx](#)Network Assistant [xxx](#)resetting a UDLD-shutdown interface [22-6](#)

responder, IP SLAs

described [27-3](#)enabling [27-6](#)response time, measuring with IP SLAs [27-4](#)

restricted VLAN

configuring [9-31](#)described [9-12](#)using with IEEE 802.1x [9-12](#)

restricting access

NTP services [6-8](#)overview [8-1](#)passwords and privilege levels [8-2](#)RADIUS [8-17](#)TACACS+ [8-10](#)retry count, VMPS, changing [12-28](#)

RFC

1112, IP multicast and IGMP [18-2](#)1157, SNMPv1 [26-2](#)1305, NTP [6-2](#)1757, RMON [24-2](#)1901, SNMPv2C [26-2](#)1902 to 1907, SNMPv2 [26-2](#)2236, IP multicast and IGMP [18-2](#)2273-2275, SNMPv3 [26-2](#)

RMON

default configuration [24-3](#)displaying status [24-6](#)enabling alarms and events [24-3](#)groups supported [24-2](#)overview [24-1](#)

statistics

collecting group Ethernet [24-5](#)collecting group history [24-5](#)support for [1-10](#)

root guard

described [17-8](#)enabling [17-15](#)support for [1-6](#)

root switch

MSTP 16-17

STP 15-14

RSPAN

characteristics 23-7

configuration guidelines 23-16

default configuration 23-9

defined 23-2

destination ports 23-6

displaying status 23-22

interaction with other features 23-8

monitored ports 23-5

monitoring ports 23-6

overview 1-10, 23-1

received traffic 23-4

sessions

creating 23-16

defined 23-3

limiting source traffic to specific VLANs 23-21

specifying monitored ports 23-16

with ingress traffic enabled 23-20

source ports 23-5

transmitted traffic 23-5

VLAN-based 23-6

RSTP

active topology 16-9

BPDU

format 16-12

processing 16-13

designated port, defined 16-9

designated switch, defined 16-9

interoperability with IEEE 802.1D

described 16-8

restarting migration process 16-25

topology changes 16-13

overview 16-8

port roles

described 16-9

synchronized 16-11

RSTP (continued)

proposal-agreement handshake process 16-10

rapid convergence

described 16-10

edge ports and Port Fast 16-10

point-to-point links 16-10, 16-24

root ports 16-10

root port, defined 16-9

See also MSTP

running configuration

replacing B-19, B-20

rolling back B-19, B-20

running configuration, saving 3-10

S

SC (standby command switch) 5-9

scheduled reloads 3-16

SDM

described 7-1

templates

configuring 7-2

number of 7-1

SDM template

configuration guidelines 7-2

configuring 7-2

types of 7-1

secure HTTP client

configuring 8-43

displaying 8-43

secure HTTP server

configuring 8-41

displaying 8-43

secure MAC addresses

deleting 19-15

maximum number of 19-9

types of 19-8

secure ports, configuring 19-8

secure remote connections 8-33

Secure Shell

See SSH

Secure Socket Layer

See SSL

security, port 19-8

security features 1-7

sequence numbers in log messages 25-8

server mode, VTP 13-3

service-provider network, MSTP and RSTP 16-1

set-request operation 26-5

setup program

failed command switch replacement 32-10

replacing failed command switch 32-8

severity levels, defining in system messages 25-8

SFPs

monitoring status of 10-18, 32-12

security and identification 32-12

status, displaying 32-12

shaped round robin

See SRR

show and more command output, filtering 2-10

show cdp traffic command 20-5

show cluster members command 5-14

show configuration command 10-16

show forward command 32-20

show interfaces command 10-13, 10-16

show lldp traffic command 21-8

show platform forward command 32-20

show running-config command

interface description in 10-16

shutdown command on interfaces 10-19

Simple Network Management Protocol

See SNMP

Smartports macros

applying Cisco-default macros 11-6

applying global parameter values 11-5, 11-6

applying macros 11-5

applying parameter values 11-5, 11-7

configuration guidelines 11-2

Smartports macros (continued)

creating 11-4

default configuration 11-2

defined 11-1

displaying 11-8

tracing 11-3

website 11-2

SNAP 20-1

SNMP

accessing MIB variables with 26-4

agent

described 26-4

disabling 26-8

and IP SLAs 27-2

authentication level 26-11

community strings

configuring 26-8

for cluster switches 26-4

overview 26-4

configuration examples 26-17

default configuration 26-7

engine ID 26-7

groups 26-7, 26-10

host 26-7

ifIndex values 26-6

in-band management 1-5

in clusters 5-13

informs

and trap keyword 26-12

described 26-5

differences from traps 26-5

disabling 26-15

enabling 26-15

limiting access by TFTP servers 26-16

limiting system log messages to NMS 25-10

manager functions 1-4, 26-3

managing clusters with 5-15

SNMP (continued)

MIBs

location of [A-3](#)supported [A-1](#)notifications [26-5](#)overview [26-1, 26-4](#)security levels [26-3](#)status, displaying [26-18](#)system contact and location [26-15](#)trap manager, configuring [26-14](#)

traps

described [26-3, 26-5](#)differences from informs [26-5](#)disabling [26-15](#)enabling [26-12](#)enabling MAC address notification [6-22](#)overview [26-1, 26-5](#)types of [26-12](#)users [26-7, 26-10](#)versions supported [26-2](#)SNMPv1 [26-2](#)SNMPv2C [26-2](#)SNMPv3 [26-2](#)snooping, IGMP [18-1](#)

software images

location in flash [B-24](#)recovery procedures [32-2](#)scheduling reloads [3-16](#)tar file format, described [B-24](#)

See also downloading and uploading

source-and-destination-IP address based forwarding,
EtherChannel [31-7](#)source-and-destination MAC address forwarding,
EtherChannel [31-6](#)source-IP address based forwarding, EtherChannel [31-7](#)source-MAC address forwarding, EtherChannel [31-6](#)**SPAN**configuration guidelines [23-10](#)default configuration [23-9](#)destination ports [23-6](#)displaying status [23-22](#)interaction with other features [23-8](#)monitored ports [23-5](#)monitoring ports [23-6](#)overview [1-10, 23-1](#)ports, restrictions [19-11](#)received traffic [23-4](#)

sessions

configuring ingress forwarding [23-14, 23-21](#)creating [23-10](#)defined [23-3](#)limiting source traffic to specific VLANs [23-14](#)removing destination (monitoring) ports [23-12](#)specifying monitored ports [23-10](#)with ingress traffic enabled [23-13](#)source ports [23-5](#)transmitted traffic [23-5](#)VLAN-based [23-6](#)spanning tree and native VLANs [12-15](#)

Spanning Tree Protocol

See STP

SPAN traffic [23-4](#)

SRR

configuring

shaped weights on egress queues [28-66](#)shared weights on egress queues [28-67](#)shared weights on ingress queues [28-60](#)described [28-13](#)shaped mode [28-13](#)shared mode [28-13](#)support for [1-9](#)

SSH

- configuring [8-34](#)
- cryptographic software image [8-33](#)
- described [1-5, 8-33](#)
- encryption methods [8-34](#)
- user authentication methods, supported [8-34](#)

SSL

- configuration guidelines [8-40](#)
- configuring a secure HTTP client [8-43](#)
- configuring a secure HTTP server [8-41](#)
- cryptographic software image [8-37](#)
- described [8-37](#)
- monitoring [8-43](#)

standby command switch

- configuring
- considerations [5-10](#)
- defined [5-2](#)
- priority [5-9](#)
- requirements [5-3](#)
- virtual IP address [5-10](#)

See also cluster standby group and HSRP

standby group, cluster

See cluster standby group and HSRP

startup configuration

- booting
 - manually [3-13](#)
 - specific image [3-14](#)
- clearing [B-19](#)
- configuration file
 - automatically downloading [3-12](#)
 - specifying the filename [3-12](#)
- default boot configuration [3-12](#)

stateless autoconfiguration [29-4](#)

static access ports

- assigning to VLAN [12-10](#)
- defined [10-3, 12-3](#)

static addresses

See addresses

static MAC addressing [1-7](#)

static routes

- configuring for IPv6 [29-9](#)

static VLAN membership [12-2](#)

statistics

- 802.1x [9-41](#)
- CDP [20-4](#)
- interface [10-18](#)
- LLDP [21-7](#)
- LLDP-MED [21-7](#)
- QoS ingress and egress [28-69](#)
- RMON group Ethernet [24-5](#)
- RMON group history [24-5](#)
- SNMP input and output [26-18](#)
- VTP [13-16](#)

sticky learning [19-9](#)

storm control

- configuring [19-3](#)
- described [19-1](#)
- disabling [19-5](#)
- displaying [19-18](#)
- support for [1-3](#)
- thresholds [19-1](#)

STP

accelerating root port selection [17-4](#)

BackboneFast

- described [17-5](#)
- disabling [17-14](#)
- enabling [17-13](#)

BPDU filtering

- described [17-3](#)
- disabling [17-12](#)
- enabling [17-12](#)

BPDU guard

- described [17-2](#)
- disabling [17-12](#)
- enabling [17-11](#)

BPDU message exchange [15-3](#)configuration guidelines [15-12, 17-10](#)

STP (continued)

- configuring
 - forward-delay time 15-21
 - hello time 15-20
 - maximum aging time 15-21
 - path cost 15-18
 - port priority 15-16
 - root switch 15-14
 - secondary root switch 15-16
 - spanning-tree mode 15-13
 - switch priority 15-19
 - transmit hold-count 15-22
- counters, clearing 15-22
- default configuration 15-11
- default optional feature configuration 17-9
- designated port, defined 15-3
- designated switch, defined 15-3
- detecting indirect link failures 17-5
- disabling 15-14
- displaying status 15-22
- EtherChannel guard
 - described 17-7
 - disabling 17-14
 - enabling 17-14
- extended system ID
 - effects on root switch 15-14
 - effects on the secondary root switch 15-16
 - overview 15-4
 - unexpected behavior 15-14
- features supported 1-6
- IEEE 802.1D and bridge ID 15-4
- IEEE 802.1D and multicast addresses 15-8
- IEEE 802.1t and VLAN identifier 15-4
- inferior BPDU 15-3
- instances supported 15-9
- interface state, blocking to forwarding 17-2

STP (continued)

- interface states
 - blocking 15-6
 - disabled 15-7
 - forwarding 15-5, 15-6
 - learning 15-6
 - listening 15-6
 - overview 15-4
- interoperability and compatibility among modes 15-10
- limitations with IEEE 802.1Q trunks 15-10
- load sharing
 - overview 12-20
 - using path costs 12-22
 - using port priorities 12-20
- loop guard
 - described 17-9
 - enabling 17-15
- modes supported 15-9
- multicast addresses, effect of 15-8
- optional features supported 1-6
- overview 15-2
- path costs 12-22
- Port Fast
 - described 17-2
 - enabling 17-10
- port priorities 12-21
- preventing root switch selection 17-8
- protocols supported 15-9
- redundant connectivity 15-8
- root guard
 - described 17-8
 - enabling 17-15
- root port, defined 15-3
- root switch
 - configuring 15-14
 - effects of extended system ID 15-4, 15-14
 - election 15-3
 - unexpected behavior 15-14

STP (continued)

- shutdown Port Fast-enabled port [17-2](#)
- status, displaying [15-22](#)
- superior BPDU [15-3](#)
- timers, described [15-20](#)
- UplinkFast
 - described [17-3](#)
 - enabling [17-13](#)
- stratum, NTP [6-2](#)
- success response, VMPS [12-24](#)
- summer time [6-13](#)
- SunNet Manager [1-4](#)
- switch clustering technology [5-1](#)
 - See also clusters, switch
- switch console port [1-5](#)
- Switch Database Management
 - See SDM
- Switched Port Analyzer
 - See SPAN
- switched ports [10-2](#)
- switchport block multicast command [19-7](#)
- switchport block unicast command [19-7](#)
- switchport protected command [19-6](#)
- switch priority
 - MSTP [16-21](#)
 - STP [15-19](#)
- switch software features [1-1](#)
- syslog
 - See system message logging
- system capabilities TLV [21-2](#)
- system clock
 - configuring
 - daylight saving time [6-13](#)
 - manually [6-11](#)
 - summer time [6-13](#)
 - time zones [6-12](#)
 - displaying the time and date [6-12](#)
 - overview [6-1](#)
 - See also NTP

- system description TLV [21-2](#)
- system message logging
 - default configuration [25-3](#)
 - defining error message severity levels [25-8](#)
 - disabling [25-4](#)
 - displaying the configuration [25-13](#)
 - enabling [25-4](#)
 - facility keywords, described [25-13](#)
 - level keywords, described [25-9](#)
 - limiting messages [25-10](#)
 - message format [25-2](#)
 - overview [25-1](#)
 - sequence numbers, enabling and disabling [25-8](#)
 - setting the display destination device [25-5](#)
 - synchronizing log messages [25-6](#)
 - syslog facility [1-10](#)
 - time stamps, enabling and disabling [25-7](#)
 - UNIX syslog servers
 - configuring the daemon [25-12](#)
 - configuring the logging facility [25-12](#)
 - facilities supported [25-13](#)
- system name
 - default configuration [6-15](#)
 - default setting [6-15](#)
 - manual configuration [6-15](#)
 - See also DNS
- system name TLV [21-2](#)
- system prompt, default setting [6-14](#), [6-15](#)
- system resources, optimizing [7-1](#)

T

- TACACS+
 - accounting, defined [8-11](#)
 - authentication, defined [8-11](#)
 - authorization, defined [8-11](#)

TACACS+ (continued)

- configuring
 - accounting 8-17
 - authentication key 8-13
 - authorization 8-16
 - login authentication 8-14
- default configuration 8-13
- displaying the configuration 8-17
- identifying the server 8-13
- in clusters 5-14
- limiting the services to the user 8-16
- operation of 8-12
- overview 8-10
- support for 1-8
- tracking services accessed by user 8-17

tar files

- creating B-6
- displaying the contents of B-7
- extracting B-7
- image file format B-24

TDR 1-10**Telnet**

- accessing management interfaces 2-10
- number of connections 1-5
- setting a password 8-6

templates, SDM 7-1**temporary self-signed certificate 8-38****Terminal Access Controller Access Control System Plus**

See TACACS+

terminal lines, setting a password 8-6**TFTP**

- configuration files
 - downloading B-11
 - preparing the server B-10
 - uploading B-12
- configuration files in base directory 3-6
- configuring for autoconfiguration 3-6

TFTP (continued)

- image files
 - deleting B-28
 - downloading B-27
 - preparing the server B-26
 - uploading B-28
- limiting access by servers 26-16
- TFTP server 1-4
- threshold, traffic level 19-2
- time
 - See NTP and system clock
- Time Domain Reflector
 - See TDR
- time stamps in log messages 25-7
- time zones 6-12
- TLVs
 - defined 21-2
 - LLDP 21-2
 - LLDP-MED 21-2
- Token Ring VLANs
 - support for 12-5
 - VTP support 13-4
- ToS 1-9
- traceroute, Layer 2
 - and ARP 32-15
 - and CDP 32-14
 - broadcast traffic 32-14
 - described 32-14
 - IP addresses and subnets 32-15
 - MAC addresses and VLANs 32-15
 - multicast traffic 32-15
 - multiple devices on a port 32-15
 - unicast traffic 32-14
 - usage guidelines 32-14
- traceroute command 32-16
 - See also IP traceroute
- traffic
 - blocking flooded 19-7
- traffic policing 1-9

- traffic suppression [19-1](#)
 - transmit hold-count
 - see STP
 - transparent mode, VTP [13-3, 13-12](#)
 - trap-door mechanism [3-2](#)
 - traps
 - configuring MAC address notification [6-22](#)
 - configuring managers [26-12](#)
 - defined [26-3](#)
 - enabling [6-22, 26-12](#)
 - notification types [26-12](#)
 - overview [26-1, 26-5](#)
 - troubleshooting
 - connectivity problems [32-12, 32-14, 32-15](#)
 - detecting unidirectional links [22-1](#)
 - displaying crash information [32-21](#)
 - setting packet forwarding [32-20](#)
 - SFP security and identification [32-12](#)
 - show forward command [32-20](#)
 - with CiscoWorks [26-4](#)
 - with debug commands [32-18](#)
 - with ping [32-13](#)
 - with system message logging [25-1](#)
 - with traceroute [32-15](#)
 - trunk failover
 - See link-state tracking
 - trunking encapsulation [1-7](#)
 - trunk ports
 - configuring [12-17](#)
 - defined [10-3, 12-3](#)
 - trunks
 - allowed-VLAN list [12-18](#)
 - load sharing
 - setting STP path costs [12-22](#)
 - using STP port priorities [12-20, 12-21](#)
 - native VLAN for untagged traffic [12-19](#)
 - parallel [12-22](#)
 - pruning-eligible list [12-19](#)
 - to non-DTP device [12-14](#)
 - trusted boundary for QoS [28-36](#)
 - trusted port states
 - between QoS domains [28-38](#)
 - classification options [28-5](#)
 - ensuring port security for IP phones [28-36](#)
 - support for [1-9](#)
 - within a QoS domain [28-34](#)
 - trustpoints, CA [8-38](#)
 - twisted-pair Ethernet, detecting unidirectional links [22-1](#)
 - type of service
 - See ToS
-
- ## U
- UDLD
 - configuration guidelines [22-4](#)
 - default configuration [22-4](#)
 - disabling
 - globally [22-5](#)
 - on fiber-optic interfaces [22-5](#)
 - per interface [22-5](#)
 - echoing detection mechanism [22-2](#)
 - enabling
 - globally [22-5](#)
 - per interface [22-5](#)
 - link-detection mechanism [22-1](#)
 - neighbor database [22-2](#)
 - overview [22-1](#)
 - resetting an interface [22-6](#)
 - status, displaying [22-6](#)
 - support for [1-6](#)
 - unauthorized ports with IEEE 802.1x [9-7](#)
 - unicast MAC address filtering [1-4](#)
 - and adding static addresses [6-25](#)
 - and broadcast MAC addresses [6-25](#)
 - and CPU packets [6-25](#)
 - and multicast addresses [6-25](#)
 - and router MAC addresses [6-25](#)

unicast MAC address filtering 1-4 (continued)

- configuration guidelines 6-25

- described 6-25

- unicast storm 19-1

- unicast storm control command 19-4

- unicast traffic, blocking 19-7

- UniDirectional Link Detection protocol

- See UDLD

- UNIX syslog servers

- daemon configuration 25-12

- facilities supported 25-13

- message logging configuration 25-12

- unrecognized Type-Length-Value (TLV) support 13-4

- upgrading a Catalyst 2950 switch

- configuration compatibility issues C-1

- differences in configuration commands C-1

- feature behavior incompatibilities C-5

- incompatible command messages C-1

- recommendations C-1

- upgrading information

- See release notes

- upgrading software images

- See downloading

- UplinkFast

- described 17-3

- disabling 17-13

- enabling 17-13

- support for 1-6

- uploading

- configuration files

- preparing B-10, B-13, B-16

- reasons for B-9

- using FTP B-14

- using RCP B-18

- using TFTP B-21

uploading (continued)

- image files

- preparing B-26, B-29, B-33

- reasons for B-23

- using FTP B-32

- using RCP B-37

- using TFTP B-28

- user EXEC mode 2-2

- username-based authentication 8-6

V

- version-dependent transparent mode 13-4

- virtual IP address

- cluster standby group 5-10

- command switch 5-10

- vlan.dat file 12-4

- VLAN 1, disabling on a trunk port 12-18

- VLAN 1 minimization 12-18

- vlan-assignment response, VMPS 12-24

- VLAN configuration

- at bootup 12-7

- saving 12-7

- VLAN configuration mode 2-2, 12-6

- VLAN database

- and startup configuration file 12-7

- and VTP 13-1

- VLAN configuration saved in 12-6

- VLANs saved in 12-4

- vlan database command 12-6

- VLAN filtering and SPAN 23-6

- vlan global configuration command 12-6

- VLAN ID, discovering 6-26

- VLAN management domain 13-2

- VLAN Management Policy Server

- See VMPS

- VLAN membership

- confirming 12-27

- modes 12-3

VLAN Query Protocol

See VQP

VLANs

- adding 12-8
- adding to VLAN database 12-8
- aging dynamic addresses 15-9
- allowed on trunk 12-18
- and spanning-tree instances 12-2, 12-6, 12-12
- configuration guidelines, extended-range VLANs 12-12
- configuration guidelines, normal-range VLANs 12-5
- configuration options 12-6
- configuring 12-1
- configuring IDs 1006 to 4094 12-12
- creating in config-vlan mode 12-8
- creating in VLAN configuration mode 12-9
- default configuration 12-7
- deleting 12-9
- described 10-2, 12-1
- displaying 12-13
- extended-range 12-1, 12-11
- features 1-7
- illustrated 12-2
- limiting source traffic with RSPAN 23-21
- limiting source traffic with SPAN 23-14
- modifying 12-8
- multicast 18-17
- native, configuring 12-19
- normal-range 12-1, 12-4
- number supported 1-7
- parameters 12-4
- port membership modes 12-3
- static-access ports 12-10
- STP and IEEE 802.1Q trunks 15-10
- supported 12-2
- Token Ring 12-5
- traffic between 12-2
- VTP modes 13-3

VLAN Trunking Protocol

See VTP

VLAN trunks 12-14

VMPS

- administering 12-28
- configuration example 12-29
- configuration guidelines 12-25
- default configuration 12-25
- description 12-23
- dynamic port membership
 - described 12-24
 - reconfirming 12-27
 - troubleshooting 12-29
- entering server address 12-26
- mapping MAC addresses to VLANs 12-24
- monitoring 12-28
- reconfirmation interval, changing 12-27
- reconfirming membership 12-27
- retry count, changing 12-28

voice-over-IP 14-1

voice VLAN

- Cisco 7960 phone, port connections 14-1
- configuration guidelines 14-3
- configuring IP phones for data traffic
 - override CoS of incoming frame 14-6
 - trust CoS priority of incoming frame 14-6
- configuring ports for voice traffic in
 - 802.1p priority tagged frames 14-5
 - 802.1Q frames 14-4
- connecting to an IP phone 14-4
- default configuration 14-3
- described 14-1
- displaying 14-6
- IP phone data traffic, described 14-2
- IP phone voice traffic, described 14-2

VQP 1-7, 12-23

VTP

- adding a client to a domain [13-14](#)
- advertisements [12-16, 13-3](#)
- and extended-range VLANs [13-1](#)
- and normal-range VLANs [13-1](#)
- client mode, configuring [13-11](#)
- configuration
 - global configuration mode [13-7](#)
 - guidelines [13-8](#)
 - privileged EXEC mode [13-7](#)
 - requirements [13-9](#)
 - saving [13-7](#)
 - VLAN configuration mode [13-7](#)
- configuration mode options [13-7](#)
- configuration requirements [13-9](#)
- configuration revision number
 - guideline [13-14](#)
 - resetting [13-15](#)
- configuring
 - client mode [13-11](#)
 - server mode [13-9](#)
 - transparent mode [13-12](#)
- consistency checks [13-4](#)
- default configuration [13-6](#)
- described [13-1](#)
- disabling [13-12](#)
- domain names [13-8](#)
- domains [13-2](#)
- modes
 - client [13-3, 13-11](#)
 - server [13-3, 13-9](#)
 - transitions [13-3](#)
 - transparent [13-3, 13-12](#)
- monitoring [13-16](#)
- passwords [13-8](#)

VTP (continued)

- pruning
 - disabling [13-14](#)
 - enabling [13-14](#)
 - examples [13-5](#)
 - overview [13-4](#)
 - support for [1-7](#)
- pruning-eligible list, changing [12-19](#)
- server mode, configuring [13-9](#)
- statistics [13-16](#)
- support for [1-7](#)
- Token Ring support [13-4](#)
- transparent mode, configuring [13-12](#)
- using [13-1](#)
- version, guidelines [13-8](#)
- Version 1 [13-4](#)
- Version 2
 - configuration guidelines [13-8](#)
 - disabling [13-13](#)
 - enabling [13-13](#)
 - overview [13-4](#)

W

- web authentication
 - configuring [9-38 to 9-40](#)
 - described [1-7, 9-17](#)
 - fallback for IEEE 802.1x [9-39](#)
- weighted tail drop
 - See WTD
- wizards [1-2](#)
- WTD
 - described [28-12](#)
 - setting thresholds
 - egress queue-sets [28-62](#)
 - ingress queues [28-58](#)
 - support for [1-9](#)

×

Xmodem protocol [32-2](#)