



## INDEX

### A

- abbreviating commands [4](#)
- AC (command switch) [9](#)
- access-class command [34](#)
- access control entries
  - See ACEs
- access-denied response, VMPS [25](#)
- access groups, applying IPv4 ACLs to interfaces [35](#)
- accessing
  - clusters, switch [12](#)
  - command switches [10](#)
  - member switches [12](#)
  - switch clusters [12](#)
- access lists
  - See ACLs
- access ports
  - in switch clusters [8](#)
- access ports, defined [2](#)
- accounting
  - with 802.1x [40](#)
  - with IEEE 802.1x [9](#)
  - with RADIUS [28](#)
  - with TACACS+ [11, 17](#)
- ACEs
  - and QoS [7](#)
  - defined [20](#)
  - Ethernet [20](#)
  - IP [20](#)
- ACLs
  - ACEs [20](#)
  - any keyword [27](#)
  - applying
    - time ranges to [32](#)
    - to an interface [34](#)
    - to QoS [7](#)
  - classifying traffic for QoS [40](#)
  - comments in [33](#)
  - compiling [35](#)
  - defined [19, 23](#)
  - examples of [35, 40](#)
  - extended IP, configuring for QoS classification [41](#)
  - extended IPv4
    - creating [26](#)
    - matching criteria [23](#)
  - hardware and software handling [35](#)
  - host keyword [28](#)
  - IP
    - creating [23](#)
    - fragments and QoS guidelines [31](#)
    - implicit deny [25, 29, 31](#)
    - implicit masks [25](#)
    - matching criteria [23](#)
    - undefined [35](#)
  - IPv4
    - applying to interfaces [34](#)
    - creating [23](#)
    - matching criteria [23](#)
    - named [30](#)
    - numbers [24](#)
    - terminal lines, setting on [34](#)
    - unsupported features [22](#)
  - MAC extended [37, 42](#)
  - matching [23, 35](#)
  - monitoring [40](#)
  - named, IPv4 [30](#)

- number per QoS class map [31](#)
- QoS [7, 40](#)
- resequencing entries [30](#)
- standard IP, configuring for QoS classification [40](#)
- standard IPv4
  - creating [25](#)
  - matching criteria [23](#)
- support for [9](#)
- support in hardware [35](#)
- time ranges [32](#)
- unsupported features, IPv4 [22](#)
- active link [4, 5, 6](#)
- active links [2](#)
- active traffic monitoring, IP SLAs [1](#)
- address aliasing [2](#)
- addresses
  - displaying the MAC address table [27](#)
  - dynamic
    - accelerated aging [8](#)
    - changing the aging time [21](#)
    - default aging [8](#)
    - defined [19](#)
    - learning [20](#)
    - removing [21](#)
  - IPv6 [2](#)
  - MAC, discovering [27](#)
  - multicast, STP address management [8](#)
  - static
    - adding and removing [24](#)
    - defined [19](#)
- address resolution [27](#)
- Address Resolution Protocol
  - See ARP
- advertisements
  - CDP [1](#)
  - LLDP [2](#)
  - VTP [17, 3](#)
- aggregatable global unicast addresses [3](#)
- aggregated ports
  - See EtherChannel
- aggregate policers [48](#)
- aggregate policing [11](#)
- aging, accelerating [8](#)
- aging time
  - accelerated
    - for MSTP [23](#)
    - for STP [8, 21](#)
  - MAC address table [21](#)
  - maximum
    - for MSTP [23, 24](#)
    - for STP [21, 22](#)
- alarms, RMON [3](#)
- allowed-VLAN list [19](#)
- AP1250 (Cisco wireless access point) [4](#)
- ARP
  - defined [5, 27](#)
  - table
    - address resolution [27](#)
    - managing [27](#)
- attributes, RADIUS
  - vendor-proprietary [31](#)
  - vendor-specific [29](#)
- authentication
  - local mode with AAA [32](#)
  - NTP associations [4](#)
  - RADIUS
    - key [21](#)
    - login [23](#)
  - TACACS+
    - defined [11](#)
    - key [13](#)
    - login [14](#)
  - See also port-based authentication
- authentication failed VLAN
  - See restricted VLAN
- authoritative time source, described [2](#)

- authorization
    - with RADIUS [27](#)
    - with TACACS+ [11, 16](#)
  - authorized ports with IEEE 802.1x [8](#)
  - autoconfiguration [3](#)
  - automatic discovery
    - considerations
      - beyond a noncandidate device [7](#)
      - brand new switches [8](#)
      - connectivity [4](#)
      - different VLANs [6](#)
      - management VLANs [7](#)
      - non-CDP-capable devices [6](#)
      - noncluster-capable devices [6](#)
    - in switch clusters [4](#)
    - See also CDP
  - automatic QoS
    - See QoS
  - automatic recovery, clusters [9](#)
    - See also HSRP
  - auto-MDIX
    - configuring [20](#)
    - described [20](#)
  - autonegotiation
    - duplex mode [3](#)
    - interface configuration guidelines [17](#)
    - mismatches [11](#)
  - autosensing, port speed [3](#)
  - auxiliary VLAN
    - See voice VLAN
  - availability, features [6](#)
- 
- B**
- BackboneFast
    - described [5](#)
    - disabling [14](#)
    - enabling [13](#)
    - support for [7](#)
  - backup interfaces
    - See Flex Links
  - backup links [2](#)
  - banners
    - configuring
      - login [18](#)
      - message-of-the-day login [18](#)
    - default configuration [17](#)
    - when displayed [17](#)
  - Berkeley r-tools replacement [44](#)
  - binding table, DHCP snooping
    - See DHCP snooping binding database
  - blocking packets [7](#)
  - booting
    - boot loader, function of [2](#)
    - boot process [1](#)
    - manually [17](#)
    - specific image [18](#)
  - boot loader
    - accessing [18](#)
    - described [2](#)
    - environment variables [18](#)
    - prompt [18](#)
    - trap-door mechanism [2](#)
  - BPDU
    - error-disabled state [2](#)
    - filtering [3](#)
    - RSTP format [12](#)
  - BPDU filtering
    - described [3](#)
    - disabling [12](#)
    - enabling [12](#)
    - support for [7](#)
  - BPDU guard
    - described [2](#)
    - disabling [12](#)
    - enabling [11](#)
    - support for [7](#)

bridge protocol data unit

See BPDU

broadcast storm-control command 4

broadcast storms 1

## C

cables, monitoring for unidirectional links 1

candidate switch

automatic discovery 4

defined 3

requirements 3

See also command switch, cluster standby group, and member switch

CA trustpoint

configuring 40

defined 38

CDP

and trusted boundary 35

automatic discovery in switch clusters 4

configuring 2

default configuration 2

defined with LLDP 1

described 1

disabling for routing device 3 to 4

enabling and disabling

on an interface 4

on a switch 3

monitoring 4

overview 1

power negotiation extensions 5

support for 5

transmission timer and holdtime, setting 2

updates 2

CGMP

as IGMP snooping learning method 8

joining multicast group 3

CipherSuites 39

Cisco 7960 IP Phone 1

Cisco AP1250 wireless access point 4

Cisco Discovery Protocol

See CDP

Cisco intelligent power management 5

Cisco IOS File System

See IFS

Cisco IOS IP Service Level Agreements (SLAs) responder 4

Cisco IOS IP SLAs 1

CiscoWorks 2000 4

CIST regional root

See MSTP

CIST root

See MSTP

civic location 3

class maps for QoS

configuring 43

described 7

displaying 68

class of service

See CoS

clearing interfaces 28

CLI

abbreviating commands 4

command modes 1

configuration logging 5

described 4

editing features

enabling and disabling 7

keystroke editing 7

wrapped lines 9

error messages 5

filtering command output 10

getting help 3

history

changing the buffer size 6

described 6

disabling 7

recalling commands 6

- managing clusters [14](#)
- no and default forms of commands [4](#)
- client mode, VTP [3](#)
- clock
  - See system clock
- clusters, switch
  - accessing [12](#)
  - automatic discovery [4](#)
  - automatic recovery [9](#)
  - benefits [2](#)
  - compatibility [4](#)
  - described [1](#)
  - LRE profile considerations [13](#)
  - managing
    - through CLI [14](#)
    - through SNMP [14](#)
  - planning [4](#)
  - planning considerations
    - automatic discovery [4](#)
    - automatic recovery [9](#)
    - CLI [14](#)
    - host names [12](#)
    - IP addresses [12](#)
    - LRE profiles [13](#)
    - passwords [12](#)
    - RADIUS [13](#)
    - SNMP [13,14](#)
    - TACACS+ [13](#)
  - See also candidate switch, command switch, cluster standby group, member switch, and standby command switch
- cluster standby group
  - automatic recovery [11](#)
  - considerations [10](#)
  - defined [2](#)
  - requirements [3](#)
  - virtual IP address [10](#)
  - See also HSRP
- CNS [5](#)
  - Configuration Engine
    - configID, deviceID, hostname [3](#)
    - configuration service [2](#)
    - described [1](#)
    - event service [3](#)
  - embedded agents
    - described [5](#)
    - enabling automated configuration [6](#)
    - enabling configuration agent [9](#)
    - enabling event agent [7](#)
  - management functions [5](#)
- Coarse Wave Division Multiplexer
  - See CWDM SFPs
- command-line interface
  - See CLI
- command modes [1](#)
- commands
  - abbreviating [4](#)
  - no and default [4](#)
- commands, setting privilege levels [8](#)
- command switch
  - accessing [10](#)
  - active (AC) [9](#)
  - configuration conflicts [11](#)
  - defined [2](#)
  - passive (PC) [9](#)
  - password privilege levels [14](#)
  - priority [9](#)
  - recovery
    - from command-switch failure [9,7](#)
    - from lost member connectivity [11](#)
  - redundant [9](#)
  - replacing
    - with another switch [9](#)
    - with cluster member [8](#)

- requirements [3](#)
- standby (SC) [9](#)
- See also candidate switch, cluster standby group, member switch, and standby command switch
- community strings
  - configuring [13, 8](#)
  - for cluster switches [4](#)
  - in clusters [13](#)
  - overview [4](#)
  - SNMP [13](#)
- compatibility, feature [12](#)
- config.text [16](#)
- configurable leave timer, IGMP [5](#)
- configuration, initial
  - defaults [13](#)
  - Express Setup [2](#)
- configuration changes, logging [10](#)
- configuration conflicts, recovering from lost member connectivity [11](#)
- configuration examples, network [16](#)
- configuration files
  - archiving [18](#)
  - clearing the startup configuration [18](#)
  - creating using a text editor [9](#)
  - default name [16](#)
  - deleting a stored configuration [18](#)
  - described [7](#)
  - downloading
    - automatically [16](#)
    - preparing [9, 12, 15](#)
    - reasons for [7](#)
    - using FTP [12](#)
    - using RCP [16](#)
    - using TFTP [10](#)
  - guidelines for creating and using [8](#)
  - guidelines for replacing and rolling back [19](#)
  - invalid combinations when copying [4](#)
  - limiting TFTP server access [15](#)
  - obtaining with DHCP [8](#)
  - password recovery disable considerations [5](#)
  - replacing a running configuration [18, 19](#)
  - rolling back a running configuration [18, 19](#)
  - specifying the filename [16](#)
  - system contact and location information [15](#)
  - types and location [8](#)
  - uploading
    - preparing [9, 12, 15](#)
    - reasons for [7](#)
    - using FTP [13](#)
    - using RCP [17](#)
    - using TFTP [10](#)
- configuration logger [10](#)
- configuration logging [5](#)
- configuration replacement [18](#)
- configuration rollback [18](#)
- configuration settings, saving [14](#)
- configure terminal command [10](#)
- configuring port-based authentication violation modes [32](#)
- configuring small-frame arrival rate [5](#)
- config-vlan mode [2, 7](#)
- conflicts, configuration [11](#)
- connections, secure remote [33](#)
- connectivity problems [13, 14, 16](#)
- consistency checks in VTP Version 2 [4](#)
- console port, connecting to [10](#)
- control protocol, IP SLAs [4](#)
- corrupted software, recovery steps with Xmodem [2](#)
- CoS
  - in Layer 2 frames [2](#)
  - override priority [6](#)
  - trust priority [6](#)
- CoS input queue threshold map for QoS [14](#)
- CoS output queue threshold map for QoS [17](#)
- CoS-to-DSCP map for QoS [51](#)
- counters, clearing interface [28](#)
- CPU utilization, troubleshooting [23](#)
- crashinfo file [22](#)
- critical authentication, IEEE 802.1x [43](#)

cryptographic software image

SSH 33

SSL 37

CWDM SFPs 20

## D

daylight saving time 13

debugging

enabling all system diagnostics 19

enabling for a specific feature 19

redirecting error message output 20

using commands 18

default commands 4

default configuration

802.1x 26

auto-QoS 19

banners 17

booting 16

CDP 2

DHCP 6

DHCP option 82 6

DHCP snooping 6

DHCP snooping binding database 6

DNS 16

EtherChannel 10

Ethernet interfaces 14

Flex Links 8, 9

IGMP filtering 24

IGMP snooping 6, 5, 6

IGMP throttling 24

initial switch information 3

IP SLAs 5

IPv6 7

Layer 2 interfaces 14

LLDP 3

MAC address table 20

MAC address-table move update 9

MSTP 14

MVR 19

NTP 4

optional spanning-tree configuration 9

password and privilege level 2

RADIUS 20

RMON 3

RSPAN 9

SDM template 2

SNMP 6

SPAN 9

SSL 40

standard QoS 28

STP 11

system message logging 3

system name and prompt 15

TACACS+ 13

UDLD 4

VLAN, Layer 2 Ethernet interfaces 17

VLANs 8

VMPS 26

voice VLAN 3

VTP 6

default gateway 14

default router preference

See DRP

deleting VLANs 10

denial-of-service attack 1

description command 25

designing your network, examples 16

destination addresses

in IPv4 ACLs 27

destination-IP address-based forwarding, EtherChannel 8

destination-MAC address forwarding, EtherChannel 8

detecting indirect link failures, STP 5

device 22

device discovery protocol 1

- device manager
  - benefits [2](#)
  - described [2, 4](#)
  - in-band management [6](#)
  - upgrading a switch [22](#)
- DHCP
  - Cisco IOS server database
    - configuring [9](#)
  - enabling
    - relay agent [7](#)
- DHCP-based autoconfiguration
  - client request message exchange [4](#)
  - configuring
    - client side [3](#)
    - DNS [7](#)
    - relay device [7](#)
    - server side [6](#)
    - TFTP server [7](#)
  - example [9](#)
  - lease options
    - for IP address information [6](#)
    - for receiving the configuration file [6](#)
  - overview [3](#)
  - relationship to BOOTP [3](#)
  - relay support [5](#)
  - support for [5](#)
- DHCP-based autoconfiguration and image update
  - configuring [11 to 13](#)
  - understanding [4 to 5](#)
- DHCP binding table
  - See DHCP snooping binding database
- DHCP option 82
  - circuit ID suboption [5](#)
  - configuration guidelines [6](#)
  - default configuration [6](#)
  - displaying [10](#)
  - overview [3](#)
  - packet format, suboption
    - circuit ID [5](#)
    - remote ID [5](#)
  - remote ID suboption [5](#)
- DHCP server port-based address allocation
  - configuration guidelines [12](#)
  - default configuration [12](#)
  - described [11](#)
  - displaying [15](#)
  - enabling [12](#)
- DHCP server port-based address assignment
  - support for [5](#)
- DHCP snooping
  - accepting untrusted packets form edge switch [3, 8](#)
  - configuration guidelines [6](#)
  - default configuration [6](#)
  - displaying binding tables [10](#)
  - message exchange process [4](#)
  - option 82 data insertion [3](#)
  - trusted interface [2](#)
  - untrusted interface [2](#)
  - untrusted messages [2](#)
- DHCP snooping binding database
  - adding bindings [9](#)
  - clearing agent statistics [10](#)
  - configuring [9](#)
  - default configuration [6](#)
  - deleting
    - binding file [10](#)
    - bindings [10](#)
    - database agent [10](#)
  - displaying [10](#)
  - enabling [9](#)
  - renewing database [10](#)
  - resetting
    - delay value [10](#)
    - timeout value [10](#)
- DHCP snooping binding table
  - See DHCP snooping binding database

- DHCPv6
  - support for [12](#)
- Differentiated Services architecture, QoS [2](#)
- Differentiated Services Code Point [2](#)
- directed unicast requests [5](#)
- directories
  - changing [3](#)
  - creating and removing [3](#)
  - displaying the working [3](#)
- discovery, clusters
  - See automatic discovery
- DNS
  - and DHCP-based autoconfiguration [7](#)
  - default configuration [16](#)
  - displaying the configuration [17](#)
  - in IPv6 [3](#)
  - overview [15](#)
  - setting up [16](#)
  - support for [5](#)
- domain names
  - DNS [15](#)
  - VTP [8](#)
- Domain Name System
  - See DNS
- downloading
  - configuration files
    - preparing [9, 12, 15](#)
    - reasons for [7](#)
    - using FTP [12](#)
    - using RCP [16](#)
    - using TFTP [10](#)
  - image files
    - deleting old image [26](#)
    - preparing [24, 27, 31](#)
    - reasons for [22](#)
    - using CMS [2](#)
    - using FTP [28](#)
    - using HTTP [2, 22](#)
    - using RCP [32](#)
  - using TFTP [24](#)
  - using the device manager or Network Assistant [22](#)
- DRP
  - configuring [9](#)
  - described [4](#)
  - IPv6 [4](#)
  - support for [12](#)
- DSCP [11, 2](#)
- DSCP input queue threshold map for QoS [14](#)
- DSCP output queue threshold map for QoS [17](#)
- DSCP-to-CoS map for QoS [54](#)
- DSCP-to-DSCP-mutation map for QoS [55](#)
- DSCP transparency [36](#)
- DTP [8, 15](#)
- dual-action detection [5](#)
- dual IPv4 and IPv6 templates [5](#)
- dual protocol stacks
  - IPv4 and IPv6 [5](#)
  - SDM templates supporting [5](#)
- dual-purpose uplinks
  - defined [4](#)
  - LEDs [4](#)
  - link selection [4, 15](#)
  - setting the type [15](#)
- dynamic access ports
  - characteristics [4](#)
  - configuring [27](#)
  - defined [3](#)
- dynamic addresses
  - See addresses
- dynamic auto trunking mode [16](#)
- dynamic desirable trunking mode [16](#)
- Dynamic Host Configuration Protocol
  - See DHCP-based autoconfiguration

## dynamic port VLAN membership

- described [25](#)
- reconfirming [28](#)
- troubleshooting [30](#)
- types of connections [27](#)

## Dynamic Trunking Protocol

See DTP

**E**

## editing features

- enabling and disabling [7](#)
- keystrokes used [7](#)
- wrapped lines [9](#)

ELIN location [3](#)enable password [3](#)enable secret password [3](#)encryption, CipherSuite [39](#)encryption for passwords [3](#)enhanced PoE [4,5](#)environment variables, function of [19](#)error-disabled state, BPDU [2](#)error messages during command entry [5](#)

## EtherChannel

- automatic creation of [4,6](#)
- channel groups
  - binding physical and logical interfaces [3](#)
  - numbering of [3](#)
- configuration guidelines [10](#)
- configuring Layer 2 interfaces [11](#)
- default configuration [10](#)
- described [2](#)
- displaying status [17](#)
- forwarding methods [7,13](#)
- IEEE 802.3ad, described [6](#)
- interaction
  - with STP [10](#)
  - with VLANs [11](#)
- LACP

described [6](#)

displaying status [17](#)

hot-standby ports [15](#)

interaction with other features [7](#)

modes [6](#)

port priority [16](#)

system priority [16](#)

load balancing [7,13](#)

## PAGP

- aggregate-port learners [14](#)
- compatibility with Catalyst 1900 [14](#)
- described [4](#)
- displaying status [17](#)
- interaction with other features [6](#)
- interaction with virtual switches [5](#)
- learn method and priority configuration [14](#)
- modes [5](#)
- support for [3](#)
- with dual-action detection [5](#)

## port-channel interfaces

- described [3](#)
- numbering of [3](#)

port groups [3](#)

support for [3](#)

## EtherChannel guard

- described [7](#)
- disabling [14](#)
- enabling [14](#)

## Ethernet VLANs

- adding [8](#)
- defaults and ranges [8](#)
- modifying [8](#)

EUI [3](#)events, RMON [3](#)

## examples

network configuration [16](#)

expedite queue for QoS [66](#)Express Setup [2](#)

See also getting started guide

- extended crashinfo file [22](#)
  - extended-range VLANs
    - configuration guidelines [13](#)
    - configuring [12](#)
    - creating [13](#)
    - defined [1](#)
  - extended system ID
    - MSTP [17](#)
    - STP [4, 14](#)
  - extended universal identifier
    - See EUI
  - Extensible Authentication Protocol over LAN [1](#)
- 
- F**
- fa0 interface [6](#)
  - Fast Convergence [3](#)
  - features, incompatible [12](#)
  - fiber-optic, detecting unidirectional links [1](#)
  - files
    - basic crashinfo
      - description [22](#)
      - location [22](#)
    - copying [4](#)
    - crashinfo, description [22](#)
    - deleting [4](#)
    - displaying the contents of [7](#)
    - extended crashinfo
      - description [22](#)
      - location [22](#)
    - tar
      - creating [5](#)
      - displaying the contents of [5](#)
      - extracting [6](#)
      - image file format [23](#)
  - file system
    - displaying available file systems [2](#)
    - displaying file information [2](#)
    - local file system names [1](#)
    - network file system names [4](#)
    - setting the default [2](#)
  - filtering
    - non-IP traffic [37](#)
    - show and more command output [10](#)
  - filtering show and more command output [10](#)
  - filters, IP
    - See ACLs, IP
  - flash device, number of [1](#)
  - Flex Link Multicast Fast Convergence [3](#)
  - Flex Links
    - configuration guidelines [9](#)
    - configuring [9, 10](#)
    - configuring preferred VLAN [12](#)
    - configuring VLAN load balancing [11](#)
    - default configuration [8](#)
    - description [2](#)
    - link load balancing [2](#)
    - monitoring [15](#)
    - VLANs [2](#)
  - flooded traffic, blocking [8](#)
  - flow-based packet classification [11](#)
  - flowcharts
    - QoS classification [6](#)
    - QoS egress queueing and scheduling [16](#)
    - QoS ingress queueing and scheduling [13](#)
    - QoS policing and marking [10](#)
  - flowcontrol
    - configuring [19](#)
    - described [19](#)
  - forward-delay time
    - MSTP [23](#)
    - STP [21](#)
  - FTP
    - accessing MIB files [3](#)
    - configuration files
      - downloading [12](#)
      - overview [11](#)

- preparing the server [12](#)
- uploading [13](#)
- image files
  - deleting old image [30](#)
  - downloading [28](#)
  - preparing the server [27](#)
  - uploading [30](#)

---

## G

- general query [5](#)
- Generating IGMP Reports [4](#)
- get-bulk-request operation [3](#)
- get-next-request operation [3, 4](#)
- get-request operation [3, 4](#)
- get-response operation [3](#)
- global configuration mode [2](#)
- global leave, IGMP [12](#)
- guest VLAN and 802.1x [12](#)
- guide mode [2](#)
- GUIs

See device manager and Network Assistant

---

## H

- hello time
  - MSTP [22](#)
  - STP [20](#)
- help, for the command line [3](#)
- history
  - changing the buffer size [6](#)
  - described [6](#)
  - disabling [7](#)
  - recalling commands [6](#)
- history table, level and number of syslog messages [10](#)
- host names, in clusters [12](#)
- hosts, limit on dynamic ports [30](#)
- HP OpenView [4](#)

## HSRP

- automatic cluster recovery [11](#)
- cluster standby group considerations [10](#)
- See also clusters, cluster standby group, and standby command switch

## HTTP over SSL

- see HTTPS

## HTTPS [38](#)

- configuring [41](#)
- self-signed certificate [38](#)

## HTTP secure server [38](#)

---

## I

## ICMP

- IPv6 [3](#)
- time-exceeded messages [16](#)
- traceroute and [16](#)

## ICMP ping

- executing [13](#)
- overview [13](#)

## ICMPv6 [3](#)

## IDS appliances

- and ingress RSPAN [20](#)
- and ingress SPAN [13](#)

## IEEE 802.1D

- See STP

## IEEE 802.1p [1](#)

## IEEE 802.1Q

- and trunk ports [3](#)
- configuration limitations [16](#)
- encapsulation [15](#)
- native VLAN for untagged traffic [20](#)

## IEEE 802.1s

- See MSTP

## IEEE 802.1w

- See RSTP

## IEEE 802.1x

- See port-based authentication

- IEEE 802.3ad
  - See EtherChannel
- IEEE 802.3af
  - See PoE
- IEEE 802.3x flow control **19**
- ifIndex values, SNMP **5**
- IFS **5**
- IGMP
  - configurable leave timer
    - described **5**
    - enabling **10**
  - flooded multicast traffic
    - controlling the length of time **11**
    - disabling on an interface **12**
    - global leave **12**
    - query solicitation **12**
    - recovering from flood mode **12**
  - joining multicast group **3**
  - join messages **3**
  - leave processing, enabling **10, 9**
  - leaving multicast group **5**
  - queries **4**
  - report suppression
    - described **6**
    - disabling **15, 11**
  - supported versions **2**
  - support for **3**
- IGMP filtering
  - configuring **24**
  - default configuration **24**
  - described **23**
  - monitoring **28**
  - support for **4**
- IGMP groups
  - configuring filtering **27**
  - setting the maximum number **26**
- IGMP Immediate Leave
  - configuration guidelines **10**
  - described **5**
  - enabling **10**
- IGMP profile
  - applying **25**
  - configuration mode **24**
  - configuring **25**
- IGMP snooping
  - and address aliasing **2**
  - configuring **6**
  - default configuration **6, 5, 6**
  - definition **1**
  - enabling and disabling **7, 6**
  - global configuration **7**
  - Immediate Leave **5**
  - method **8**
  - monitoring **15, 11**
  - querier
    - configuration guidelines **13**
    - configuring **13**
  - supported versions **2**
  - support for **3**
  - VLAN configuration **7**
- IGMP throttling
  - configuring **27**
  - default configuration **24**
  - described **24**
  - displaying action **28**
- Immediate Leave, IGMP **5**
  - enabling **9**
- inaccessible authentication bypass **14**
- initial configuration
  - defaults **13**
  - Express Setup **2**
- interface
  - number **9**
  - range macros **12**
- interface command **9 to 10**

- interface configuration mode [3](#)
- interfaces
  - auto-MDIX, configuring [20](#)
  - configuration guidelines
    - duplex and speed [17](#)
  - configuring
    - procedure [10](#)
  - counters, clearing [28](#)
  - default configuration [14](#)
  - described [25](#)
  - descriptive name, adding [25](#)
  - displaying information about [27](#)
  - flow control [19](#)
  - management [4](#)
  - monitoring [27](#)
  - naming [25](#)
  - physical, identifying [9](#)
  - range of [10](#)
  - restarting [29](#)
  - shutting down [29](#)
  - speed and duplex, configuring [18](#)
  - status [27](#)
  - supported [9](#)
  - types of [1](#)
- interfaces range macro command [12](#)
- interface types [9](#)
- Internet Protocol version 6
  - See IPv6
- Intrusion Detection System
  - See IDS appliances
- inventory management TLV [2, 6](#)
- IP ACLs
  - for QoS classification [7](#)
  - implicit deny [25, 29](#)
  - implicit masks [25](#)
  - named [30](#)
  - undefined [35](#)
- IP addresses
  - 128-bit [2](#)
  - candidate or member [3, 12](#)
  - cluster access [2](#)
  - command switch [3, 10, 12](#)
  - discovering [27](#)
  - IPv6 [2](#)
  - redundant clusters [10](#)
  - standby command switch [10, 12](#)
  - See also IP information
- ip igmp profile command [24](#)
- IP information
  - assigned
    - manually [14](#)
    - through DHCP-based autoconfiguration [3](#)
  - default configuration [3](#)
- IP phones
  - and QoS [1](#)
  - automatic classification and queuing [19](#)
  - configuring [4](#)
  - ensuring port security with QoS [35](#)
  - trusted boundary for QoS [35](#)
- IP precedence [2](#)
- IP-precedence-to-DSCP map for QoS [52](#)
- IP protocols in ACLs [27](#)
- IP Service Level Agreements
  - See IP SLAs
- IP service levels, analyzing [1](#)
- IP SLAs
  - benefits [2](#)
  - configuration guidelines [5](#)
  - Control Protocol [4](#)
  - default configuration [5](#)
  - definition [1](#)
  - measuring network performance [3](#)
  - monitoring [6](#)
  - operation [3](#)

- responder
  - described [4](#)
  - enabling [6](#)
- response time [4](#)
- SNMP support [2](#)
- supported metrics [2](#)

#### IP traceroute

- executing [17](#)
- overview [16](#)

#### IPv4 ACLs

- applying to interfaces [34](#)
- extended, creating [26](#)
- named [30](#)
- standard, creating [25](#)

#### IPv4 and IPv6

- dual protocol stacks [4](#)

#### IPv6

- addresses [2](#)
- address formats [2](#)
- applications [4](#)
- assigning address [7](#)
- autoconfiguration [4](#)
- configuring static routes [11](#)
- default configuration [7](#)
- default router preference (DRP) [4](#)
- defined [1](#)
- forwarding [7](#)
- ICMP [3](#)
- monitoring [12](#)
- neighbor discovery [3](#)
- SDM templates [1](#)
- Stateless Autoconfiguration [4](#)
- supported features [2](#)
- understanding static routes [5](#)

## J

- join messages, IGMP [3](#)

## L

#### LACP

- See EtherChannel

- Layer 2 frames, classification with CoS [2](#)

- Layer 2 interfaces, default configuration [14](#)

#### Layer 2 traceroute

- and ARP [15](#)
- and CDP [15](#)
- broadcast traffic [14](#)
- described [14](#)
- IP addresses and subnets [15](#)
- MAC addresses and VLANs [15](#)
- multicast traffic [15](#)
- multiple devices on a port [15](#)
- unicast traffic [14](#)
- usage guidelines [15](#)

#### Layer 3 interfaces

- assigning IPv6 addresses to [7](#)

- Layer 3 packets, classification methods [2](#)

- LDAP [2](#)

- Leaking IGMP Reports [4](#)

#### LEDs, switch

- See hardware installation guide

- lightweight directory access protocol

- See LDAP

- line configuration mode [3](#)

- Link Aggregation Control Protocol

- See EtherChannel

- link failure, detecting unidirectional [8](#)

- Link Layer Discovery Protocol

- See CDP

- link local unicast addresses [3](#)

- link redundancy

- See Flex Links

- links, unidirectional [1](#)

- link-state tracking

- configuring [20](#)

- described [18](#)

## LLDP

- configuring [3](#)
  - characteristics [4](#)
  - default configuration [3](#)
- disabling and enabling
  - globally [4](#)
  - on an interface [5](#)
- monitoring and maintaining [7](#)
- overview [1](#)
- supported TLVs [2](#)
- switch stack considerations [2](#)
- transmission timer and holdtime, setting [4](#)

## LLDP-MED

- configuring
  - procedures [3](#)
  - TLVs [6](#)
- monitoring and maintaining [7](#)
- overview [1,2](#)
- supported TLVs [2](#)

## LLDP Media Endpoint Discovery

See LLDP-MED

local SPAN [2](#)location TLV [3,6](#)

## login authentication

- with RADIUS [23](#)
- with TACACS+ [14](#)

login banners [17](#)

## log messages

See system message logging

Long-Reach Ethernet (LRE) technology [17](#)

## loop guard

- described [9](#)
- enabling [15](#)
- support for [7](#)

LRE profiles, considerations in switch clusters [13](#)**M**

## MAB inactivity timer

- default setting [26](#)
- range [29](#)

MAC/PHY configuration status TLV [2](#)

## MAC addresses

- aging time [21](#)
- and VLAN association [20](#)
- building the address table [20](#)
- default configuration [20](#)
- disabling learning on a VLAN [26](#)
- discovering [27](#)
- displaying [27](#)
- dynamic
  - learning [20](#)
  - removing [21](#)
- in ACLs [37](#)
- static
  - adding [24](#)
  - allowing [25,27](#)
  - characteristics of [24](#)
  - dropping [25](#)
  - removing [24](#)

MAC address learning [5](#)MAC address learning, disabling on a VLAN [26](#)MAC address notification, support for [13](#)

## MAC address-table move update

- configuration guidelines [9](#)
- configuring [13](#)
- default configuration [9](#)
- description [7](#)
- monitoring [15](#)

MAC address-to-VLAN mapping [25](#)MAC authentication bypass [11](#)

## MAC extended access lists

- applying to Layer 2 interfaces [39](#)
- configuring for QoS [42](#)
- creating [37](#)

- defined [37](#)
  - for QoS classification [5](#)
- macros
  - See Smartports macros
- magic packet [17](#)
- manageability features [5](#)
- management access
  - in-band
    - browser session [6](#)
    - CLI session [6](#)
    - device manager [6](#)
    - SNMP [6](#)
  - out-of-band console port connection [6](#)
- management address TLV [2](#)
- management options
  - CLI [1](#)
  - clustering [3](#)
  - CNS [1](#)
  - Network Assistant [2](#)
  - overview [4](#)
- management VLAN
  - considerations in switch clusters [7](#)
  - discovery through different management VLANs [7](#)
- mapping tables for QoS
  - configuring
    - CoS-to-DSCP [51](#)
    - DSCP [50](#)
    - DSCP-to-CoS [54](#)
    - DSCP-to-DSCP-mutation [55](#)
    - IP-precedence-to-DSCP [52](#)
    - policed-DSCP [53](#)
  - described [10](#)
- marking
  - action with aggregate policers [48](#)
  - described [4, 8](#)
- matching, IPv4 ACLs [23](#)
- maximum aging time
  - MSTP [23](#)
  - STP [21](#)
- maximum hop count, MSTP [24](#)
- maximum number of allowed devices, port-based authentication [29](#)
- MDA
  - configuration guidelines [20 to 21](#)
  - described [9, 20](#)
  - exceptions with authentication process [5](#)
- membership mode, VLAN port [3](#)
- member switch
  - automatic discovery [4](#)
  - defined [2](#)
  - managing [14](#)
  - passwords [12](#)
  - recovering from lost connectivity [11](#)
  - requirements [3](#)
  - See also candidate switch, cluster standby group, and standby command switch
- messages, to users through banners [17](#)
- MIBs
  - accessing files with FTP [3](#)
  - location of files [3](#)
  - overview [1](#)
  - SNMP interaction with [4](#)
  - supported [1](#)
- mirroring traffic for analysis [1](#)
- mismatches, autonegotiation [11](#)
- module number [9](#)
- monitoring
  - access groups [40](#)
  - cables for unidirectional links [1](#)
  - CDP [4](#)
  - features [13](#)
  - Flex Links [15](#)
  - IGMP
    - filters [28](#)
    - snooping [15, 11](#)
  - interfaces [27](#)
  - IP SLAs operations [6](#)
  - IPv4 ACL configuration [40](#)

- IPv6 [12](#)
- MAC address-table move update [15](#)
- multicast router interfaces [16, 11](#)
- MVR [23](#)
- network traffic for analysis with probe [2](#)
- port
  - blocking [18](#)
  - protection [18](#)
- SFP status [28, 13](#)
- speed and duplex mode [18](#)
- traffic flowing among switches [1](#)
- traffic suppression [18](#)
- VLANs [14](#)
- VMPS [29](#)
- VTP [16](#)
- mrouter Port [3](#)
- mrouter port [5](#)
- MSTP
  - boundary ports
    - configuration guidelines [15](#)
    - described [6](#)
  - BPDU filtering
    - described [3](#)
    - enabling [12](#)
  - BPDU guard
    - described [2](#)
    - enabling [11](#)
  - CIST, described [3](#)
  - CIST regional root [3](#)
  - CIST root [5](#)
  - configuration guidelines [15, 10](#)
  - configuring
    - forward-delay time [23](#)
    - hello time [22](#)
    - link type for rapid convergence [24](#)
    - maximum aging time [23](#)
    - maximum hop count [24](#)
    - MST region [16](#)
    - neighbor type [25](#)
    - path cost [20](#)
    - port priority [19](#)
    - root switch [17](#)
    - secondary root switch [18](#)
    - switch priority [21](#)
  - CST
    - defined [3](#)
    - operations between regions [4](#)
  - default configuration [14](#)
  - default optional feature configuration [9](#)
  - displaying status [26](#)
  - enabling the mode [16](#)
  - EtherChannel guard
    - described [7](#)
    - enabling [14](#)
  - extended system ID
    - effects on root switch [17](#)
    - effects on secondary root switch [18](#)
    - unexpected behavior [17](#)
  - IEEE 802.1s
    - implementation [6](#)
    - port role naming change [7](#)
    - terminology [5](#)
  - instances supported [9](#)
  - interface state, blocking to forwarding [2](#)
  - interoperability and compatibility among modes [10](#)
  - interoperability with IEEE 802.1D
    - described [8](#)
    - restarting migration process [25](#)
  - IST
    - defined [3](#)
    - master [3](#)
    - operations within a region [3](#)
  - loop guard
    - described [9](#)
    - enabling [15](#)
  - mapping VLANs to MST instance [16](#)

- MST region
  - CIST [3](#)
  - configuring [16](#)
  - described [2](#)
  - hop-count mechanism [5](#)
  - IST [3](#)
  - supported spanning-tree instances [2](#)
- optional features supported [7](#)
- overview [2](#)
- Port Fast
  - described [2](#)
  - enabling [10](#)
- preventing root switch selection [8](#)
- root guard
  - described [8](#)
  - enabling [15](#)
- root switch
  - configuring [17](#)
  - effects of extended system ID [17](#)
  - unexpected behavior [17](#)
- shutdown Port Fast-enabled port [2](#)
- status, displaying [26](#)
- multicast groups
  - Immediate Leave [5](#)
  - joining [3](#)
  - leaving [5](#)
  - static joins [9,7](#)
- multicast router interfaces, monitoring [16,11](#)
- multicast router ports, adding [9,8](#)
- multicast storm [1](#)
- multicast storm-control command [4](#)
- multicast television application [17](#)
- multicast VLAN [16](#)
- Multicast VLAN Registration
  - See MVR
- multidomain authentication
  - See MDA

- MVR
  - and address aliasing [20](#)
  - and IGMPv3 [20](#)
  - configuration guidelines [19](#)
  - configuring interfaces [21](#)
  - default configuration [19](#)
  - described [16](#)
  - example application [17](#)
  - modes [20](#)
  - monitoring [23](#)
  - multicast television application [17](#)
  - setting global parameters [20](#)
  - support for [4](#)

---

## N

- NAC
  - critical authentication [14,43](#)
  - IEEE 802.1x authentication using a RADIUS server [48](#)
  - IEEE 802.1x validation using RADIUS server [48](#)
  - inaccessible authentication bypass [43](#)
  - Layer 2 IEEE 802.1x validation [10,19,48](#)
- named IPv4 ACLs [30](#)
- NameSpace Mapper
  - See NSM
- native VLAN
  - configuring [20](#)
  - default [20](#)
- neighbor discovery, IPv6 [3](#)
- Network Admission Control
  - See NAC
- Network Admission Control Software Configuration Guide [50,51](#)
- Network Assistant
  - benefits [2](#)
  - described [4](#)
  - downloading image files [2](#)
  - guide mode [2](#)

- management options [2](#)
- upgrading a switch [22](#)
- wizards [2](#)
- network configuration examples
  - increasing network performance [16](#)
  - long-distance, high-bandwidth transport [20](#)
  - providing network services [16](#)
  - server aggregation and Linux server cluster [18](#)
  - small to medium-sized network [19](#)
- network design
  - performance [16](#)
  - services [16](#)
- network management
  - CDP [1](#)
  - RMON [1](#)
  - SNMP [1](#)
- network performance, measuring with IP SLAs [3](#)
- network policy TLV [2,6](#)
- Network Time Protocol
  - See NTP
- no commands [4](#)
- nonhierarchical policy maps
  - described [9](#)
- non-IP traffic filtering [37](#)
- nontrunking mode [16](#)
- normal-range VLANs [4](#)
  - configuration guidelines [6](#)
  - configuration modes [6](#)
  - configuring [4](#)
  - defined [1](#)
- NSM [3](#)
- NTP
  - associations
    - authenticating [4](#)
    - defined [2](#)
    - enabling broadcast messages [6](#)
    - peer [5](#)
    - server [5](#)
  - default configuration [4](#)

- displaying the configuration [11](#)
- overview [2](#)
- restricting access
  - creating an access group [8](#)
  - disabling NTP services per interface [10](#)
- source IP address, configuring [10](#)
- stratum [2](#)
- support for [5](#)
- synchronizing devices [5](#)
- time
  - services [2](#)
  - synchronizing [2](#)

---

## O

- optimizing system resources [1](#)
- options, management [4](#)
- out-of-profile markdown [11](#)

---

## P

- packet modification, with QoS [18](#)
- PAgP
  - See EtherChannel
- passwords
  - default configuration [2](#)
  - disabling recovery of [5](#)
  - encrypting [3](#)
  - for security [9](#)
  - in clusters [12](#)
  - overview [1](#)
  - recovery of [3](#)
  - setting
    - enable [3](#)
    - enable secret [3](#)
    - Telnet [6](#)
    - with usernames [6](#)
  - VTP domain [8](#)

- path cost
  - MSTP [20](#)
  - STP [18](#)
- PC (passive command switch) [9](#)
- performance, network design [16](#)
- performance features [3](#)
- persistent self-signed certificate [38](#)
- per-VLAN spanning-tree plus
  - See PVST+
- physical ports [2](#)
- PIM-DVMRP, as snooping method [8](#)
- ping
  - character output description [14](#)
  - executing [13](#)
  - overview [13](#)
- PoE
  - auto mode [6](#)
  - CDP with power consumption, described [4](#)
  - CDP with power negotiation, described [5](#)
  - Cisco intelligent power management [5](#)
  - configuring [21](#)
  - cutoff power
    - determining [7](#)
  - cutoff-power
    - support for [7](#)
  - devices supported [4](#)
  - enhanced [5](#)
    - supported watts per port [4](#)
  - high-power devices operating in low-power mode [5](#)
  - IEEE power classification levels [5](#)
  - monitoring [7](#)
  - monitoring power [24](#)
  - policing power consumption [24](#)
  - policing power usage [7](#)
  - power budgeting [22](#)
  - power consumption [8, 22](#)
  - powered-device detection and initial power allocation [5](#)
  - power management modes [6](#)
    - power monitoring [7](#)
    - power negotiation extensions to CDP [5](#)
    - power sensing [7](#)
    - standards supported [4](#)
    - static mode [6](#)
    - supported watts per port [4](#)
    - total available power [8](#)
    - troubleshooting [11](#)
- policed-DSCP map for QoS [53](#)
- policers
  - configuring
    - for each matched traffic class [45](#)
    - for more than one traffic class [48](#)
  - described [4](#)
  - displaying [68](#)
  - number of [31](#)
  - types of [9](#)
- policing
  - described [4](#)
  - token-bucket algorithm [9](#)
- policy maps for QoS
  - characteristics of [45](#)
  - described [7](#)
  - displaying [68](#)
  - nonhierarchical on physical ports
    - described [9](#)
- port ACLs, described [20](#)
- Port Aggregation Protocol
  - See EtherChannel
- port-based authentication
  - accounting [9](#)
  - authentication server
    - defined [3](#)
    - RADIUS server [3](#)
  - client, defined [3](#)
  - configuration guidelines [27](#)
  - configuring
    - 802.1x authentication [32](#)
    - guest VLAN [41](#)

- host mode [35](#)
- inaccessible authentication bypass [43](#)
- manual re-authentication of a client [37](#)
- periodic re-authentication [36](#)
- quiet period [37](#)
- RADIUS server [35](#)
- RADIUS server parameters on the switch [34](#)
- restricted VLAN [41](#)
- switch-to-client frame-retransmission number [38, 39](#)
- switch-to-client retransmission time [38](#)
- violation mode [17](#)
- violation modes [32](#)
- default configuration [26](#)
- described [1](#)
- device roles [3](#)
- displaying statistics [53](#)
- EAPOL-start frame [6](#)
- EAP-request/identity frame [6](#)
- EAP-response/identity frame [6](#)
- encapsulation [3](#)
- guest VLAN
  - configuration guidelines [13, 14](#)
  - described [12](#)
- host mode [8](#)
- inaccessible authentication bypass
  - configuring [43](#)
  - described [14](#)
  - guidelines [28](#)
- initiation and message exchange [6](#)
- magic packet [17](#)
- maximum number of allowed devices per port [29](#)
- method lists [32](#)
- multiple-hosts mode, described [9](#)
- ports
  - authorization state and dot1x port-control command [8](#)
  - authorized and unauthorized [8](#)
  - critical [14](#)
  - voice VLAN [16](#)
- port security
  - and voice VLAN [17](#)
  - described [16](#)
  - interactions [16](#)
  - multiple-hosts mode [9](#)
- readiness check
  - configuring [29](#)
  - described [11, 29](#)
- resetting to default values [53](#)
- statistics, displaying [53](#)
- switch
  - as proxy [3](#)
  - RADIUS client [3](#)
- upgrading from a previous release [29](#)
- VLAN assignment
  - AAA authorization [33](#)
  - characteristics [11](#)
  - configuration tasks [12](#)
  - described [11](#)
- voice aware 802.1x security
  - configuring [31](#)
  - described [21, 30](#)
- voice VLAN
  - described [16](#)
  - PVID [16](#)
  - VVID [16](#)
- wake-on-LAN, described [17](#)
- with ACLs and RADIUS Filter-Id attribute [24](#)
- port blocking [3, 7](#)
- port-channel
  - See EtherChannel
- port description TLV [2](#)
- Port Fast
  - described [2](#)
  - enabling [10](#)
  - mode, spanning tree [26](#)
  - support for [7](#)

- port membership modes, VLAN [3](#)
- port priority
  - MSTP [19](#)
  - STP [16](#)
- ports
  - access [2](#)
  - blocking [7](#)
  - dual-purpose uplink [4](#)
  - dynamic access [4](#)
  - protected [6](#)
  - secure [8](#)
  - static-access [3,11](#)
  - switch [2](#)
  - trunks [3,15](#)
  - VLAN assignments [11](#)
- port security
  - aging [17](#)
  - and QoS trusted boundary [35](#)
  - configuring [12](#)
  - default configuration [11](#)
  - described [8](#)
  - displaying [18](#)
  - on trunk ports [14](#)
  - sticky learning [9](#)
  - violations [10](#)
  - with other features [11](#)
- port-shutdown response, VMPS [25](#)
- port VLAN ID TLV [2](#)
- power management TLV [2,6](#)
- Power over Ethernet
  - See PoE
- preemption, default configuration [8](#)
- preemption delay, default configuration [9](#)
- preferential treatment of traffic
  - See QoS
- preventing unauthorized access [1](#)
- primary links [2](#)
- priority
  - overriding CoS [6](#)
  - trusting CoS [6](#)
- private VLAN edge ports
  - See protected ports
- privileged EXEC mode [2](#)
- privilege levels
  - changing the default for lines [9](#)
  - command switch [14](#)
  - exiting [9](#)
  - logging into [9](#)
  - mapping on member switches [14](#)
  - overview [2,7](#)
  - setting a command with [8](#)
- protected ports [9,6](#)
- proxy reports [4](#)
- pruning, VTP
  - disabling
    - in VTP domain [14](#)
    - on a port [20](#)
  - enabling
    - in VTP domain [14](#)
    - on a port [20](#)
  - examples [5](#)
  - overview [4](#)
- pruning-eligible list
  - changing [20](#)
  - for VTP pruning [4](#)
  - VLANs [14](#)
- PVST+
  - described [9](#)
  - IEEE 802.1Q trunking interoperability [10](#)
  - instances supported [9](#)

---

## Q

- QoS
  - and MQC commands [1](#)
  - auto-QoS

- categorizing traffic [19](#)
- configuration and defaults display [27](#)
- configuration guidelines [24](#)
- described [19](#)
- disabling [25](#)
- displaying generated commands [25](#)
- displaying the initial configuration [27](#)
- effects on running configuration [24](#)
- egress queue defaults [20](#)
- enabling for VoIP [25](#)
- example configuration [26](#)
- ingress queue defaults [20](#)
- list of generated commands [21](#)
- basic model [4](#)
- classification
  - class maps, described [7](#)
  - defined [4](#)
  - DSCP transparency, described [36](#)
  - flowchart [6](#)
  - forwarding treatment [3](#)
  - in frames and packets [3](#)
  - IP ACLs, described [5,7](#)
  - MAC ACLs, described [5,7](#)
  - options for IP traffic [5](#)
  - options for non-IP traffic [5](#)
  - policy maps, described [7](#)
  - trust DSCP, described [5](#)
  - trusted CoS, described [5](#)
  - trust IP precedence, described [5](#)
- class maps
  - configuring [43](#)
  - displaying [68](#)
- configuration guidelines
  - auto-QoS [24](#)
  - standard QoS [31](#)
- configuring
  - aggregate policers [48](#)
  - auto-QoS [19](#)
  - default port CoS value [34](#)
  - DSCP maps [50](#)
  - DSCP transparency [36](#)
  - DSCP trust states bordering another domain [37](#)
  - egress queue characteristics [60](#)
  - ingress queue characteristics [56](#)
  - IP extended ACLs [41](#)
  - IP standard ACLs [40](#)
  - MAC ACLs [42](#)
  - port trust states within the domain [33](#)
  - trusted boundary [35](#)
- default auto configuration [19](#)
- default standard configuration [28](#)
- displaying statistics [68](#)
- DSCP transparency [36](#)
- egress queues
  - allocating buffer space [61](#)
  - buffer allocation scheme, described [16](#)
  - configuring shaped weights for SRR [64](#)
  - configuring shared weights for SRR [65](#)
  - described [4](#)
  - displaying the threshold map [64](#)
  - flowchart [16](#)
  - mapping DSCP or CoS values [63](#)
  - scheduling, described [4](#)
  - setting WTD thresholds [61](#)
  - WTD, described [17](#)
- enabling globally [32](#)
- flowcharts
  - classification [6](#)
  - egress queueing and scheduling [16](#)
  - ingress queueing and scheduling [13](#)
  - policing and marking [10](#)
- implicit deny [7](#)
- ingress queues
  - allocating bandwidth [58](#)
  - allocating buffer space [58](#)
  - buffer and bandwidth allocation, described [14](#)
  - configuring shared weights for SRR [58](#)
  - configuring the priority queue [59](#)

- described [4](#)
- displaying the threshold map [57](#)
- flowchart [13](#)
- mapping DSCP or CoS values [57](#)
- priority queue, described [14](#)
- scheduling, described [4](#)
- setting WTD thresholds [57](#)
- WTD, described [14](#)

IP phones

- automatic classification and queuing [19](#)
- detection and trusted settings [19, 35](#)

limiting bandwidth on egress interface [67](#)

mapping tables

- CoS-to-DSCP [51](#)
- displaying [68](#)
- DSCP-to-CoS [54](#)
- DSCP-to-DSCP-mutation [55](#)
- IP-precedence-to-DSCP [52](#)
- policed-DSCP [53](#)
- types of [10](#)

marked-down actions [47](#)

marking, described [4, 8](#)

overview [2](#)

packet modification [18](#)

policers

- configuring [47, 49](#)
- described [8](#)
- displaying [68](#)
- number of [31](#)
- types of [9](#)

policies, attaching to an interface [8](#)

policing

- described [4, 8](#)
- token bucket algorithm [9](#)

policy maps

- characteristics of [45](#)
- displaying [68](#)
- nonhierarchical on physical ports [45](#)

QoS label, defined [4](#)

queues

- configuring egress characteristics [60](#)
- configuring ingress characteristics [56](#)
- high priority (expedite) [18, 66](#)
- location of [11](#)
- SRR, described [12](#)
- WTD, described [12](#)

rewrites [18](#)

support for [11](#)

trust states

- bordering another domain [37](#)
- described [5](#)
- trusted device [35](#)
- within the domain [33](#)

quality of service

- See QoS

queries, IGMP [4](#)

query solicitation, IGMP [12](#)

---

## R

RADIUS

attributes

- vendor-proprietary [31](#)
- vendor-specific [29](#)

configuring

- accounting [28](#)
- authentication [23](#)
- authorization [27](#)
- communication, global [21, 29](#)
- communication, per-server [20, 21](#)
- multiple UDP ports [20](#)

default configuration [20](#)

defining AAA server groups [25](#)

displaying the configuration [32](#)

identifying the server [20](#)

in clusters [13](#)

limiting the services to the user [27](#)

method list, defined [19](#)

- operation of [19](#)
- overview [18](#)
- suggested network environments [18](#)
- support for [10](#)
- tracking services accessed by user [28](#)
- range
  - macro [12](#)
  - of interfaces [11](#)
- rapid convergence [10](#)
- rapid per-VLAN spanning-tree plus
  - See rapid PVST+
- rapid PVST+
  - described [9](#)
  - IEEE 802.1Q trunking interoperability [10](#)
  - instances supported [9](#)
- Rapid Spanning Tree Protocol
  - See RSTP
- rcommand command [14](#)
- RCP
  - configuration files
    - downloading [16](#)
    - overview [14](#)
    - preparing the server [15](#)
    - uploading [17](#)
  - image files
    - deleting old image [34](#)
    - downloading [32](#)
    - preparing the server [31](#)
    - uploading [34](#)
- readiness check
  - port-based authentication
    - configuring [29](#)
    - described [11, 29](#)
- reconfirmation interval, VMPS, changing [28](#)
- reconfirming dynamic VLAN membership [28](#)
- recovery procedures [1](#)
- redundancy
  - EtherChannel [3](#)
  - STP
    - backbone [8](#)
    - path cost [23](#)
    - port priority [21](#)
- redundant links and UplinkFast [13](#)
- reloading software [20](#)
- Remote Authentication Dial-In User Service
  - See RADIUS
- Remote Copy Protocol
  - See RCP
- Remote Network Monitoring
  - See RMON
- Remote SPAN
  - See RSPAN
- remote SPAN [2](#)
- report suppression, IGMP
  - described [6](#)
  - disabling [15, 11](#)
- resequencing ACL entries [30](#)
- resetting a UDLD-shutdown interface [6](#)
- responder, IP SLAs
  - described [4](#)
  - enabling [6](#)
- response time, measuring with IP SLAs [4](#)
- restricted VLAN
  - configuring [41](#)
  - described [13](#)
  - using with IEEE 802.1x [13](#)
- restricting access
  - NTP services [8](#)
  - overview [1](#)
  - passwords and privilege levels [2](#)
  - RADIUS [17](#)
  - TACACS+ [10](#)
- retry count, VMPS, changing [29](#)
- RFC
  - 1112, IP multicast and IGMP [2](#)
  - 1157, SNMPv1 [2](#)
  - 1305, NTP [2](#)
  - 1757, RMON [2](#)

- 1901, SNMPv2C [2](#)
  - 1902 to 1907, SNMPv2 [2](#)
  - 2236, IP multicast and IGMP [2](#)
  - 2273-2275, SNMPv3 [2](#)
  - RMON
    - default configuration [3](#)
    - displaying status [6](#)
    - enabling alarms and events [3](#)
    - groups supported [2](#)
    - overview [1](#)
    - statistics
      - collecting group Ethernet [5](#)
      - collecting group history [5](#)
    - support for [13](#)
  - root guard
    - described [8](#)
    - enabling [15](#)
    - support for [7](#)
  - root switch
    - MSTP [17](#)
    - STP [14](#)
  - RSPAN
    - characteristics [7](#)
    - configuration guidelines [16](#)
    - default configuration [9](#)
    - defined [2](#)
    - destination ports [6](#)
    - displaying status [23](#)
    - interaction with other features [8](#)
    - monitored ports [5](#)
    - monitoring ports [6](#)
    - overview [13, 1](#)
    - received traffic [4](#)
    - sessions
      - creating [17](#)
      - defined [3](#)
      - limiting source traffic to specific VLANs [22](#)
      - specifying monitored ports [17](#)
      - with ingress traffic enabled [20](#)
    - source ports [5](#)
    - transmitted traffic [5](#)
    - VLAN-based [6](#)
  - RSTP
    - active topology [9](#)
  - BPDU
    - format [12](#)
    - processing [13](#)
  - designated port, defined [9](#)
  - designated switch, defined [9](#)
  - interoperability with IEEE 802.1D
    - described [8](#)
    - restarting migration process [25](#)
    - topology changes [13](#)
  - overview [8](#)
  - port roles
    - described [9](#)
    - synchronized [11](#)
  - proposal-agreement handshake process [10](#)
  - rapid convergence
    - described [10](#)
    - edge ports and Port Fast [10](#)
    - point-to-point links [10, 24](#)
    - root ports [10](#)
  - root port, defined [9](#)
  - See also MSTP
  - running configuration
    - replacing [18, 19](#)
    - rolling back [18, 19](#)
  - running configuration, saving [14](#)
- 
- S**
- SC (standby command switch) [9](#)
  - scheduled reloads [20](#)
  - SCP
    - and SSH [44](#)
    - configuring [45](#)

- SDM
  - described [1](#)
  - templates
    - configuring [3](#)
    - number of [1](#)
- SDM template
  - configuration guidelines [2](#)
  - configuring [2](#)
  - types of [1](#)
- Secure Copy Protocol
- secure HTTP client
  - configuring [43](#)
  - displaying [44](#)
- secure HTTP server
  - configuring [42](#)
  - displaying [44](#)
- secure MAC addresses
  - deleting [16](#)
  - maximum number of [9](#)
  - types of [9](#)
- secure ports, configuring [8](#)
- secure remote connections [33](#)
- Secure Shell
  - See SSH
- Secure Socket Layer
  - See SSL
- security, port [8](#)
- security features [8](#)
- See SCP
- sequence numbers in log messages [8](#)
- server mode, VTP [3](#)
- service-provider network, MSTP and RSTP [1](#)
- set-request operation [4](#)
- setup program
  - failed command switch replacement [9](#)
  - replacing failed command switch [8](#)
- severity levels, defining in system messages [8](#)
- SFPs
  - monitoring status of [28, 13](#)
  - security and identification [12](#)
  - status, displaying [13](#)
- shaped round robin
  - See SRR
- show access-lists hw-summary command [35](#)
- show and more command output, filtering [10](#)
- show cdp traffic command [5](#)
- show cluster members command [14](#)
- show configuration command [25](#)
- show forward command [20](#)
- show interfaces command [18, 25](#)
- show interfaces switchport [4](#)
- show lldp traffic command [7](#)
- show platform forward command [20](#)
- show running-config command
  - displaying ACLs [34, 35](#)
  - interface description in [25](#)
- shutdown command on interfaces [29](#)
- Simple Network Management Protocol
  - See SNMP
- small-frame arrival rate, configuring [5](#)
- Smartports macros
  - applying Cisco-default macros [6](#)
  - applying global parameter values [5, 6](#)
  - applying macros [5](#)
  - applying parameter values [5, 7](#)
  - configuration guidelines [2](#)
  - creating [4](#)
  - default configuration [2](#)
  - defined [1](#)
  - displaying [8](#)
  - tracing [3](#)
- SNAP [1](#)
- SNMP
  - accessing MIB variables with [4](#)
  - agent
    - described [3](#)
    - disabling [7](#)
  - and IP SLAs [2](#)

- authentication level [10](#)
- community strings
  - configuring [8](#)
  - for cluster switches [4](#)
  - overview [4](#)
- configuration examples [16](#)
- default configuration [6](#)
- engine ID [7](#)
- groups [6,9](#)
- host [6](#)
- ifIndex values [5](#)
- in-band management [6](#)
- in clusters [13](#)
- informs
  - and trap keyword [11](#)
  - described [5](#)
  - differences from traps [5](#)
  - disabling [15](#)
  - enabling [15](#)
- limiting access by TFTP servers [15](#)
- limiting system log messages to NMS [10](#)
- manager functions [4,3](#)
- managing clusters with [14](#)
- MIBs
  - location of [3](#)
  - supported [1](#)
- notifications [5](#)
- overview [1,4](#)
- security levels [3](#)
- status, displaying [17](#)
- system contact and location [15](#)
- trap manager, configuring [13](#)
- traps
  - described [3,5](#)
  - differences from informs [5](#)
  - disabling [15](#)
  - enabling [11](#)
  - enabling MAC address notification [21](#)
  - overview [1,4](#)
  - types of [11](#)
  - users [6,9](#)
  - versions supported [2](#)
- SNMP and Syslog Over IPv6 [5](#)
- SNMPv1 [2](#)
- SNMPv2C [2](#)
- SNMPv3 [2](#)
- snooping, IGMP [1](#)
- software images
  - location in flash [22](#)
  - recovery procedures [2](#)
  - scheduling reloads [20](#)
  - tar file format, described [23](#)
  - See also downloading and uploading
- source addresses
  - in IPv4 ACLs [27](#)
- source-and-destination-IP address based forwarding, EtherChannel [8](#)
- source-and-destination MAC address forwarding, EtherChannel [8](#)
- source-IP address based forwarding, EtherChannel [8](#)
- source-MAC address forwarding, EtherChannel [7](#)
- SPAN
  - configuration guidelines [10](#)
  - default configuration [9](#)
  - destination ports [6](#)
  - displaying status [23](#)
  - interaction with other features [8](#)
  - monitored ports [5](#)
  - monitoring ports [6](#)
  - overview [13,1](#)
  - ports, restrictions [12](#)
  - received traffic [4](#)
  - sessions
    - configuring ingress forwarding [14,21](#)
    - creating [10](#)
    - defined [3](#)
    - limiting source traffic to specific VLANs [15](#)

- removing destination (monitoring) ports [12](#)
  - specifying monitored ports [10](#)
  - with ingress traffic enabled [13](#)
- source ports [5](#)
- transmitted traffic [5](#)
- VLAN-based [6](#)
- spanning tree and native VLANs [16](#)
- Spanning Tree Protocol
  - See STP
- SPAN traffic [4](#)
- SRR
  - configuring
    - shaped weights on egress queues [64](#)
    - shared weights on egress queues [65](#)
    - shared weights on ingress queues [58](#)
  - described [12](#)
  - shaped mode [13](#)
  - shared mode [13](#)
  - support for [12](#)
- SSH
  - configuring [34](#)
  - cryptographic software image [33](#)
  - described [6,33](#)
  - encryption methods [34](#)
  - user authentication methods, supported [34](#)
- SSL
  - configuration guidelines [40](#)
  - configuring a secure HTTP client [43](#)
  - configuring a secure HTTP server [41](#)
  - cryptographic software image [37](#)
  - described [37](#)
  - monitoring [44](#)
- standby command switch
  - configuring
  - considerations [10](#)
  - defined [2](#)
  - priority [9](#)
  - requirements [3](#)
  - virtual IP address [10](#)
  - See also cluster standby group and HSRP
- standby group, cluster
  - See cluster standby group and HSRP
- standby links [2](#)
- startup configuration
  - booting
    - manually [17](#)
    - specific image [18](#)
  - clearing [18](#)
  - configuration file
    - automatically downloading [16](#)
    - specifying the filename [16](#)
  - default boot configuration [16](#)
- static access ports
  - assigning to VLAN [11](#)
  - defined [3](#)
- static addresses
  - See addresses
- static MAC addressing [9](#)
- static routes
  - configuring for IPv6 [11](#)
  - understanding [5](#)
- static VLAN membership [2](#)
- statistics
  - 802.1x [53](#)
  - CDP [4](#)
  - interface [28](#)
  - LLDP [7](#)
  - LLDP-MED [7](#)
  - QoS ingress and egress [68](#)
  - RMON group Ethernet [5](#)
  - RMON group history [5](#)
  - SNMP input and output [17](#)
  - VTP [16](#)
- sticky learning [9](#)

- storm control
  - configuring [3](#)
  - described [1](#)
  - disabling [5](#)
  - displaying [18](#)
  - support for [3](#)
  - thresholds [1](#)
- STP
  - accelerating root port selection [4](#)
  - BackboneFast
    - described [5](#)
    - disabling [14](#)
    - enabling [13](#)
  - BPDU filtering
    - described [3](#)
    - disabling [12](#)
    - enabling [12](#)
  - BPDU guard
    - described [2](#)
    - disabling [12](#)
    - enabling [11](#)
  - BPDU message exchange [3](#)
  - configuration guidelines [12, 10](#)
  - configuring
    - forward-delay time [21](#)
    - hello time [20](#)
    - maximum aging time [21](#)
    - path cost [18](#)
    - port priority [16](#)
    - root switch [14](#)
    - secondary root switch [16](#)
    - spanning-tree mode [13](#)
    - switch priority [19](#)
    - transmit hold-count [22](#)
  - counters, clearing [22](#)
  - default configuration [11](#)
  - default optional feature configuration [9](#)
  - designated port, defined [3](#)
  - designated switch, defined [3](#)
  - detecting indirect link failures [5](#)
  - disabling [14](#)
  - displaying status [22](#)
  - EtherChannel guard
    - described [7](#)
    - disabling [14](#)
    - enabling [14](#)
  - extended system ID
    - effects on root switch [14](#)
    - effects on the secondary root switch [16](#)
    - overview [4](#)
    - unexpected behavior [14](#)
  - features supported [7](#)
  - IEEE 802.1D and bridge ID [4](#)
  - IEEE 802.1D and multicast addresses [8](#)
  - IEEE 802.1t and VLAN identifier [4](#)
  - inferior BPDU [3](#)
  - instances supported [9](#)
  - interface state, blocking to forwarding [2](#)
  - interface states
    - blocking [5](#)
    - disabled [7](#)
    - forwarding [5, 6](#)
    - learning [6](#)
    - listening [6](#)
    - overview [4](#)
  - interoperability and compatibility among modes [10](#)
  - limitations with IEEE 802.1Q trunks [10](#)
  - load sharing
    - overview [21](#)
    - using path costs [23](#)
    - using port priorities [21](#)
  - loop guard
    - described [9](#)
    - enabling [15](#)
  - modes supported [9](#)
  - multicast addresses, effect of [8](#)
  - optional features supported [7](#)
  - overview [2](#)

- path costs [23](#)
- Port Fast
  - described [2](#)
  - enabling [10](#)
- port priorities [22](#)
- preventing root switch selection [8](#)
- protocols supported [9](#)
- redundant connectivity [8](#)
- root guard
  - described [8](#)
  - enabling [15](#)
- root port, defined [3](#)
- root switch
  - configuring [14](#)
  - effects of extended system ID [4, 14](#)
  - election [3](#)
  - unexpected behavior [14](#)
- shutdown Port Fast-enabled port [2](#)
- status, displaying [22](#)
- superior BPDU [3](#)
- timers, described [20](#)
- UplinkFast
  - described [3](#)
  - enabling [13](#)
- stratum, NTP [2](#)
- success response, VMPS [25](#)
- summer time [13](#)
- SunNet Manager [4](#)
- supported watts per port [4](#)
- switch [2](#)
- switch clustering technology [1](#)
  - See also clusters, switch
- switch console port [6](#)
- Switch Database Management
  - See SDM
- Switched Port Analyzer
  - See SPAN
- switched ports [2](#)
- switchport backup interface [4, 5](#)
- switchport block multicast command [8](#)
- switchport block unicast command [8](#)
- switchport protected command [7](#)
- switch priority
  - MSTP [21](#)
  - STP [19](#)
- switch software features [1](#)
- syslog
  - See system message logging
- system capabilities TLV [2](#)
- system clock
  - configuring
    - daylight saving time [13](#)
    - manually [11](#)
    - summer time [13](#)
    - time zones [12](#)
  - displaying the time and date [12](#)
  - overview [1](#)
  - See also NTP
- system description TLV [2](#)
- system message logging
  - default configuration [3](#)
  - defining error message severity levels [8](#)
  - disabling [4](#)
  - displaying the configuration [14](#)
  - enabling [4](#)
  - facility keywords, described [14](#)
  - level keywords, described [9](#)
  - limiting messages [10](#)
  - message format [2](#)
  - overview [1](#)
  - sequence numbers, enabling and disabling [8](#)
  - setting the display destination device [5](#)
  - synchronizing log messages [6](#)
  - syslog facility [13](#)
  - time stamps, enabling and disabling [7](#)

- UNIX syslog servers
    - configuring the daemon [12](#)
    - configuring the logging facility [13](#)
    - facilities supported [14](#)
  - system name
    - default configuration [15](#)
    - default setting [15](#)
    - manual configuration [15](#)
    - See also DNS
  - system name TLV [2](#)
  - system prompt, default setting [14, 15](#)
  - system resources, optimizing [1](#)
- 
- T**
- TACACS+
    - accounting, defined [11](#)
    - authentication, defined [11](#)
    - authorization, defined [11](#)
    - configuring
      - accounting [17](#)
      - authentication key [13](#)
      - authorization [16](#)
      - login authentication [14](#)
    - default configuration [13](#)
    - displaying the configuration [17](#)
    - identifying the server [13](#)
    - in clusters [13](#)
    - limiting the services to the user [16](#)
    - operation of [12](#)
    - overview [10](#)
    - support for [10](#)
    - tracking services accessed by user [17](#)
  - tar files
    - creating [5](#)
    - displaying the contents of [5](#)
    - extracting [6](#)
    - image file format [23](#)
  - TDR [13](#)
  - Telnet
    - accessing management interfaces [10](#)
    - number of connections [6](#)
    - setting a password [6](#)
  - templates, SDM [1](#)
  - temporary self-signed certificate [38](#)
  - Terminal Access Controller Access Control System Plus
    - See TACACS+
  - terminal lines, setting a password [6](#)
  - TFTP
    - configuration files
      - downloading [10](#)
      - preparing the server [9](#)
      - uploading [10](#)
    - configuration files in base directory [7](#)
    - configuring for autoconfiguration [7](#)
    - image files
      - deleting [26](#)
      - downloading [24](#)
      - preparing the server [24](#)
      - uploading [26](#)
    - limiting access by servers [15](#)
  - TFTP server [5](#)
  - threshold, traffic level [2](#)
  - time
    - See NTP and system clock
  - Time Domain Reflector
    - See TDR
  - time-range command [32](#)
  - time ranges in ACLs [32](#)
  - time stamps in log messages [7](#)
  - time zones [12](#)
  - TLVs
    - defined [2](#)
    - LLDP [2](#)
    - LLDP-MED [2](#)
  - Token Ring VLANs
    - support for [5](#)
    - VTP support [4](#)

- ToS [11](#)
  - traceroute, Layer 2
    - and ARP [15](#)
    - and CDP [15](#)
    - broadcast traffic [14](#)
    - described [14](#)
    - IP addresses and subnets [15](#)
    - MAC addresses and VLANs [15](#)
    - multicast traffic [15](#)
    - multiple devices on a port [15](#)
    - unicast traffic [14](#)
    - usage guidelines [15](#)
  - traceroute command [17](#)
    - See also IP traceroute
  - traffic
    - blocking flooded [8](#)
    - fragmented [21](#)
    - unfragmented [21](#)
  - traffic policing [11](#)
  - traffic suppression [1](#)
  - transmit hold-count
    - see STP
  - transparent mode, VTP [3, 12](#)
  - trap-door mechanism [2](#)
  - traps
    - configuring MAC address notification [21](#)
    - configuring managers [11](#)
    - defined [3](#)
    - enabling [21, 11](#)
    - notification types [11](#)
    - overview [1, 4](#)
  - troubleshooting
    - connectivity problems [13, 14, 16](#)
    - CPU utilization [23](#)
    - detecting unidirectional links [1](#)
    - displaying crash information [22](#)
    - setting packet forwarding [20](#)
    - SFP security and identification [12](#)
    - show forward command [20](#)
    - with CiscoWorks [4](#)
    - with debug commands [18](#)
    - with ping [13](#)
    - with system message logging [1](#)
    - with traceroute [16](#)
  - trunk failover
    - See link-state tracking
  - trunking encapsulation [8](#)
  - trunk ports
    - configuring [18](#)
    - defined [3](#)
  - trunks
    - allowed-VLAN list [19](#)
    - load sharing
      - setting STP path costs [23](#)
      - using STP port priorities [21, 22](#)
    - native VLAN for untagged traffic [20](#)
    - parallel [23](#)
    - pruning-eligible list [20](#)
    - to non-DTP device [15](#)
  - trusted boundary for QoS [35](#)
  - trusted port states
    - between QoS domains [37](#)
    - classification options [5](#)
    - ensuring port security for IP phones [35](#)
    - support for [11](#)
    - within a QoS domain [33](#)
  - trustpoints, CA [38](#)
  - twisted-pair Ethernet, detecting unidirectional links [1](#)
  - type of service
    - See ToS
- 
- ## U
- UDLD
    - configuration guidelines [4](#)
    - default configuration [4](#)

- disabling
    - globally [5](#)
    - on fiber-optic interfaces [5](#)
    - per interface [5](#)
  - echoing detection mechanism [2](#)
  - enabling
    - globally [5](#)
    - per interface [5](#)
  - link-detection mechanism [1](#)
  - neighbor database [2](#)
  - overview [1](#)
  - resetting an interface [6](#)
  - status, displaying [6](#)
  - support for [6](#)
  - unauthorized ports with IEEE 802.1x [8](#)
  - unicast MAC address filtering [5](#)
    - and adding static addresses [25](#)
    - and broadcast MAC addresses [25](#)
    - and CPU packets [25](#)
    - and multicast addresses [25](#)
    - and router MAC addresses [25](#)
    - configuration guidelines [25](#)
    - described [25](#)
  - unicast storm [1](#)
  - unicast storm control command [4](#)
  - unicast traffic, blocking [8](#)
  - UniDirectional Link Detection protocol
    - See UDLD
  - UNIX syslog servers
    - daemon configuration [12](#)
    - facilities supported [14](#)
    - message logging configuration [13](#)
  - unrecognized Type-Length-Value (TLV) support [4](#)
  - upgrading a Catalyst 2950 switch
    - configuration compatibility issues [1](#)
    - differences in configuration commands [1](#)
    - feature behavior incompatibilities [5](#)
    - incompatible command messages [1](#)
    - recommendations [1](#)
  - upgrading software images
    - See downloading
  - UplinkFast
    - described [3](#)
    - disabling [13](#)
    - enabling [13](#)
    - support for [7](#)
  - uploading
    - configuration files
      - preparing [9, 12, 15](#)
      - reasons for [7](#)
      - using FTP [13](#)
      - using RCP [17](#)
      - using TFTP [10](#)
    - image files
      - preparing [24, 27, 31](#)
      - reasons for [22](#)
      - using FTP [30](#)
      - using RCP [34](#)
      - using TFTP [26](#)
  - user EXEC mode [2](#)
  - username-based authentication [6](#)
- 
- ## V
- version-dependent transparent mode [4](#)
  - virtual IP address
    - cluster standby group [10](#)
    - command switch [10](#)
  - virtual switches and PAGP [5](#)
  - vlan.dat file [4](#)
  - VLAN 1, disabling on a trunk port [19](#)
  - VLAN 1 minimization [19](#)
  - vlan-assignment response, VMPS [25](#)
  - VLAN configuration
    - at bootup [7](#)
    - saving [7](#)
  - VLAN configuration mode [2, 7](#)

- VLAN database
  - and startup configuration file [7](#)
  - and VTP [1](#)
  - VLAN configuration saved in [7](#)
  - VLANs saved in [4](#)
- vlan database command [7](#)
- VLAN filtering and SPAN [6](#)
- vlan global configuration command [7](#)
- VLAN ID, discovering [27](#)
- VLAN load balancing on flex links [2](#)
  - configuration guidelines [9](#)
- VLAN management domain [2](#)
- VLAN Management Policy Server
  - See VMPS
- VLAN membership
  - confirming [28](#)
  - modes [3](#)
- VLAN Query Protocol
  - See VQP
- VLANs
  - adding [8](#)
  - adding to VLAN database [8](#)
  - aging dynamic addresses [9](#)
  - allowed on trunk [19](#)
  - and spanning-tree instances [3, 6, 13](#)
  - configuration guidelines, extended-range VLANs [13](#)
  - configuration guidelines, normal-range VLANs [6](#)
  - configuration options [6](#)
  - configuring [1](#)
  - configuring IDs 1006 to 4094 [13](#)
  - creating in config-vlan mode [9](#)
  - creating in VLAN configuration mode [10](#)
  - default configuration [8](#)
  - deleting [10](#)
  - described [2, 1](#)
  - displaying [14](#)
  - extended-range [1, 12](#)
  - features [8](#)
  - illustrated [2](#)
  - limiting source traffic with RSPAN [22](#)
  - limiting source traffic with SPAN [15](#)
  - modifying [8](#)
  - multicast [16](#)
  - native, configuring [20](#)
  - normal-range [1, 4](#)
  - number supported [8](#)
  - parameters [5](#)
  - port membership modes [3](#)
  - static-access ports [11](#)
  - STP and IEEE 802.1Q trunks [10](#)
  - supported [2](#)
  - Token Ring [5](#)
  - traffic between [2](#)
  - VTP modes [3](#)
- VLAN Trunking Protocol
  - See VTP
- VLAN trunks [15](#)
- VMPS
  - administering [29](#)
  - configuration example [30](#)
  - configuration guidelines [26](#)
  - default configuration [26](#)
  - description [24](#)
  - dynamic port membership
    - described [25](#)
    - reconfirming [28](#)
    - troubleshooting [30](#)
  - entering server address [27](#)
  - mapping MAC addresses to VLANs [25](#)
  - monitoring [29](#)
  - reconfirmation interval, changing [28](#)
  - reconfirming membership [28](#)
  - retry count, changing [29](#)
- voice aware 802.1x security
  - port-based authentication
    - configuring [31](#)
    - described [21, 30](#)
- voice-over-IP [1](#)

- voice VLAN
  - Cisco 7960 phone, port connections [1](#)
  - configuration guidelines [3](#)
  - configuring IP phones for data traffic
    - override CoS of incoming frame [6](#)
    - trust CoS priority of incoming frame [6](#)
  - configuring ports for voice traffic in
    - 802.1p priority tagged frames [5](#)
    - 802.1Q frames [5](#)
  - connecting to an IP phone [4](#)
  - default configuration [3](#)
  - described [1](#)
  - displaying [7](#)
  - IP phone data traffic, described [2](#)
  - IP phone voice traffic, described [2](#)
- VQP [8, 24](#)
- VTP
  - adding a client to a domain [14](#)
  - advertisements [17, 3](#)
  - and extended-range VLANs [2](#)
  - and normal-range VLANs [2](#)
  - client mode, configuring [11](#)
  - configuration
    - global configuration mode [7](#)
    - guidelines [8](#)
    - privileged EXEC mode [7](#)
    - requirements [9](#)
    - saving [7](#)
    - VLAN configuration mode [7](#)
  - configuration mode options [7](#)
  - configuration requirements [9](#)
  - configuration revision number
    - guideline [14](#)
    - resetting [15](#)
  - configuring
    - client mode [11](#)
    - server mode [9](#)
    - transparent mode [12](#)
  - consistency checks [4](#)
  - default configuration [6](#)
  - described [1](#)
  - disabling [12](#)
  - domain names [8](#)
  - domains [2](#)
  - modes
    - client [3, 11](#)
    - server [3, 9](#)
    - transitions [3](#)
    - transparent [3, 12](#)
  - monitoring [16](#)
  - passwords [8](#)
  - pruning
    - disabling [14](#)
    - enabling [14](#)
    - examples [5](#)
    - overview [4](#)
    - support for [8](#)
  - pruning-eligible list, changing [20](#)
  - server mode, configuring [9](#)
  - statistics [16](#)
  - support for [8](#)
  - Token Ring support [4](#)
  - transparent mode, configuring [12](#)
  - using [1](#)
  - version, guidelines [8](#)
  - Version 1 [4](#)
  - Version 2
    - configuration guidelines [8](#)
    - disabling [13](#)
    - enabling [13](#)
    - overview [4](#)

---

## W

- web authentication [11](#)
  - configuring [49 to 51, 52 to ??](#)
  - described [8, 21](#)
  - fallback for IEEE 802.1x [50](#)

weighted tail drop

See WTD

wireless access point, Cisco AP1250 [4](#)

wizards [2](#)

WTD

described [12](#)

setting thresholds

    egress queue-sets [61](#)

    ingress queues [57](#)

support for [12](#)

---

## X

Xmodem protocol [2](#)