



INDEX

A

- AAA down policy, NAC Layer 2 IP validation [10](#)
- abbreviating commands [4](#)
- ABRs [24](#)
- AC (command switch) [10](#)
- access-class command [19](#)
- access control entries
 - See ACEs
- access control entry (ACE) [3](#)
- access-denied response, VMPS [28](#)
- access groups
 - applying IPv4 ACLs to interfaces [20](#)
 - Layer 2 [20](#)
 - Layer 3 [20](#)
- accessing
 - clusters, switch [13](#)
 - command switches [11](#)
 - member switches [13](#)
 - switch clusters [13](#)
- access lists
 - See ACLs
- access ports
 - and Layer 2 protocol tunneling [11](#)
 - defined [3](#)
 - in switch clusters [9](#)
- access template [1](#)
- accounting
 - with 802.1x [45](#)
 - with IEEE 802.1x [12](#)
 - with RADIUS [28](#)
 - with TACACS+ [11, 17](#)
- ACEs
 - and QoS [7](#)
 - defined [2](#)
 - Ethernet [2](#)
 - IP [2](#)
- ACLs
 - ACEs [2](#)
 - any keyword [12](#)
 - applying
 - on bridged packets [38](#)
 - on multicast packets [40](#)
 - on routed packets [39](#)
 - on switched packets [38](#)
 - time ranges to [16](#)
 - to an interface [19, 8](#)
 - to IPv6 interfaces [8](#)
 - to QoS [7](#)
 - classifying traffic for QoS [43](#)
 - comments in [18](#)
 - compiling [22](#)
 - defined [1, 7](#)
 - examples of [22, 43](#)
 - extended IP, configuring for QoS classification [44](#)
 - extended IPv4
 - creating [10](#)
 - matching criteria [7](#)
 - hardware and software handling [21](#)
 - host keyword [12](#)
- IP
 - creating [7](#)
 - fragments and QoS guidelines [33](#)
 - implicit deny [9, 13, 15](#)
 - implicit masks [9](#)

- matching criteria [7](#)
 - undefined [20](#)
- IPv4
 - applying to interfaces [19](#)
 - creating [7](#)
 - matching criteria [7](#)
 - named [14](#)
 - numbers [8](#)
 - terminal lines, setting on [18](#)
 - unsupported features [6](#)
- IPv6
 - applying to interfaces [8](#)
 - configuring [3,4](#)
 - displaying [9](#)
 - interactions with other features [4](#)
 - limitations [3](#)
 - matching criteria [3](#)
 - named [3](#)
 - precedence of [2](#)
 - supported [2](#)
 - unsupported features [3](#)
- Layer 4 information in [37](#)
- logging messages [8](#)
- MAC extended [27,45](#)
- matching [7,20,3](#)
- monitoring [40,9](#)
- named, IPv4 [14](#)
- named, IPv6 [3](#)
- names [4](#)
- number per QoS class map [33](#)
- port [2](#)
- precedence of [2](#)
- QoS [7,43](#)
- resequencing entries [14](#)
- router [2](#)
- router ACLs and VLAN map configuration guidelines [37](#)
- standard IP, configuring for QoS classification [43](#)
- standard IPv4
 - creating [9](#)
 - matching criteria [7](#)
 - support for [9](#)
 - support in hardware [21](#)
 - time ranges [16](#)
 - types supported [2](#)
 - unsupported features, IPv4 [6](#)
 - unsupported features, IPv6 [3](#)
 - using router ACLs with VLAN maps [36](#)
 - VLAN maps
 - configuration guidelines [30](#)
 - configuring [29](#)
- active link [4,5,6](#)
- active links [2](#)
- active router [1](#)
- active traffic monitoring, IP SLAs [1](#)
- address aliasing [2](#)
- addresses
 - displaying the MAC address table [27](#)
 - dynamic
 - accelerated aging [8](#)
 - changing the aging time [21](#)
 - default aging [8](#)
 - defined [19](#)
 - learning [20](#)
 - removing [22](#)
 - IPv6 [2](#)
 - MAC, discovering [28](#)
 - multicast
 - group address range [3](#)
 - STP address management [8](#)
 - static
 - adding and removing [24](#)
 - defined [19](#)
- address resolution [28,8](#)
- Address Resolution Protocol
 - See ARP
- adjacency tables, with CEF [87](#)

- administrative distances
 - defined [99](#)
 - OSPF [30](#)
 - routing protocol defaults [89](#)
- advertisements
 - CDP [1](#)
 - LLDP [1, 2](#)
 - RIP [19](#)
 - VTP [19, 3](#)
- aggregatable global unicast addresses [3](#)
- aggregate addresses, BGP [57](#)
- aggregated ports
 - See EtherChannel
- aggregate policers [58](#)
- aggregate policing [11](#)
- aging, accelerating [8](#)
- aging time
 - accelerated
 - for MSTP [23](#)
 - for STP [8, 21](#)
 - MAC address table [21](#)
 - maximum
 - for MSTP [23, 24](#)
 - for STP [21, 22](#)
- alarms, RMON [3](#)
- allowed-VLAN list [21](#)
- application engines, redirecting traffic to [1](#)
- area border routers
 - See ABRs
- area routing
 - IS-IS [61](#)
 - ISO IGRP [61](#)
- ARP
 - configuring [9](#)
 - defined [5, 28, 8](#)
 - encapsulation [9](#)
 - static cache configuration [9](#)
- table
 - address resolution [28](#)
 - managing [28](#)
- ASBRs [24](#)
- AS-path filters, BGP [51](#)
- asymmetrical links, and IEEE 802.1Q tunneling [4](#)
- attributes, RADIUS
 - vendor-proprietary [31](#)
 - vendor-specific [29](#)
- attribute-value pairs [11, 13, 17, 26](#)
- authentication
 - EIGRP [38](#)
 - HSRP [10](#)
 - local mode with AAA [36](#)
 - NTP associations [4](#)
 - open1x [25](#)
 - RADIUS
 - key [21](#)
 - login [23](#)
 - TACACS+
 - defined [11](#)
 - key [13](#)
 - login [14](#)
 - See also port-based authentication
- authentication compatibility with Catalyst 6000 switches [8](#)
- authentication failed VLAN
 - See restricted VLAN
- authentication keys, and routing protocols [99](#)
- authentication manager
 - CLI commands [8](#)
 - compatibility with older 802.1x CLI commands [8 to 9](#)
 - overview [7](#)
- authoritative time source, described [2](#)
- authorization
 - with RADIUS [27](#)
 - with TACACS+ [11, 16](#)
- authorized ports with IEEE 802.1x [9](#)
- autoconfiguration [3](#)

- auto enablement [26](#)
 - automatic discovery
 - considerations
 - beyond a noncandidate device [7](#)
 - brand new switches [9](#)
 - connectivity [4](#)
 - different VLANs [6](#)
 - management VLANs [7](#)
 - non-CDP-capable devices [6](#)
 - noncluster-capable devices [6](#)
 - routed ports [8](#)
 - in switch clusters [4](#)
 - See also CDP
 - automatic QoS
 - See QoS
 - automatic recovery, clusters [10](#)
 - See also HSRP
 - auto-MDIX
 - configuring [21](#)
 - described [21](#)
 - autonegotiation
 - duplex mode [3](#)
 - interface configuration guidelines [18](#)
 - mismatches [11](#)
 - autonomous system boundary routers
 - See ASBRs
 - autonomous systems, in BGP [45](#)
 - Auto-RP, described [6](#)
 - autosensing, port speed [3](#)
 - Auto Smartports macros
 - built-in macros [2,4](#)
 - configuration guidelines [3](#)
 - default configuration [2](#)
 - defined [1](#)
 - displaying [14](#)
 - enabling [3](#)
 - event triggers [6](#)
 - IOS shell [1,9](#)
 - mapping [4](#)
 - user-defined macros [9](#)
 - autostate exclude [5](#)
 - Auto Smartports macros
 - See also Smartports macros
 - auxiliary VLAN
 - See voice VLAN
 - availability, features [7](#)
-
- B**
- BackboneFast
 - described [5](#)
 - disabling [14](#)
 - enabling [13](#)
 - support for [7](#)
 - backup interfaces
 - See Flex Links
 - backup links [2](#)
 - backup static routing, configuring [12](#)
 - banners
 - configuring
 - login [18](#)
 - message-of-the-day login [18](#)
 - default configuration [17](#)
 - when displayed [17](#)
 - Berkeley r-tools replacement [48](#)
 - BGP
 - aggregate addresses [57](#)
 - aggregate routes, configuring [57](#)
 - CIDR [57](#)
 - clear commands [60](#)
 - community filtering [54](#)
 - configuring neighbors [55](#)
 - default configuration [43](#)
 - described [42](#)
 - enabling [45](#)
 - monitoring [60](#)
 - multipath support [49](#)

- neighbors, types of [45](#)
 - path selection [49](#)
 - peers, configuring [55](#)
 - prefix filtering [53](#)
 - resetting sessions [47](#)
 - route dampening [59](#)
 - route maps [51](#)
 - route reflectors [58](#)
 - routing domain confederation [58](#)
 - routing session with multi-VRF CE [81](#)
 - show commands [60](#)
 - supernets [57](#)
 - support for [12](#)
 - Version 4 [42](#)
 - binding cluster group and HSRP group [12](#)
 - binding database
 - address, DHCP server
 - See DHCP, Cisco IOS server database
 - DHCP snooping
 - See DHCP snooping binding database
 - bindings
 - address, Cisco IOS DHCP server [6](#)
 - DHCP snooping database [6](#)
 - IP source guard [15](#)
 - binding table, DHCP snooping
 - See DHCP snooping binding database
 - blocking packets [7](#)
 - Boolean expressions in tracked lists [4](#)
 - booting
 - boot loader, function of [2](#)
 - boot process [2](#)
 - manually [17](#)
 - specific image [18](#)
 - boot loader
 - accessing [18](#)
 - described [2](#)
 - environment variables [18](#)
 - prompt [18](#)
 - trap-door mechanism [2](#)
 - bootstrap router (BSR), described [7](#)
 - Border Gateway Protocol
 - See BGP
 - BPDU
 - error-disabled state [2](#)
 - filtering [3](#)
 - RSTP format [12](#)
 - BPDU filtering
 - described [3](#)
 - disabling [12](#)
 - enabling [12](#)
 - support for [7](#)
 - BPDU guard
 - described [2](#)
 - disabling [12](#)
 - enabling [11](#)
 - support for [7](#)
 - bridged packets, ACLs on [38](#)
 - bridge groups
 - See fallback bridging
 - bridge protocol data unit
 - See BPDU
 - broadcast flooding [16](#)
 - broadcast packets
 - directed [13](#)
 - flooded [13](#)
 - broadcast storm-control command [4](#)
 - broadcast storms [1, 13](#)
-
- ## C
- cables, monitoring for unidirectional links [1](#)
 - candidate switch
 - automatic discovery [4](#)
 - defined [3](#)
 - requirements [3](#)
 - See also command switch, cluster standby group, and member switch

- Catalyst 6000 switches
 - authentication compatibility [8](#)
- CA trustpoint
 - configuring [45](#)
 - defined [43](#)
- CDP
 - and trusted boundary [39](#)
 - automatic discovery in switch clusters [4](#)
 - configuring [2](#)
 - default configuration [2](#)
 - defined with LLDP [1](#)
 - described [1](#)
 - disabling for routing device [3 to 4](#)
 - enabling and disabling
 - on an interface [4](#)
 - on a switch [3](#)
 - Layer 2 protocol tunneling [8](#)
 - monitoring [4](#)
 - overview [1](#)
 - power negotiation extensions [7](#)
 - support for [5](#)
 - transmission timer and holdtime, setting [2](#)
 - updates [2](#)
- CEF
 - defined [86](#)
 - enabling [87](#)
 - IPv6 [18](#)
- CGMP
 - as IGMP snooping learning method [8](#)
 - clearing cached group entries [60](#)
 - enabling server support [43](#)
 - joining multicast group [3](#)
 - overview [9](#)
 - server support only [9](#)
 - switch support of [4](#)
- CIDR [57](#)
- CipherSuites [44](#)
- Cisco 7960 IP Phone [1](#)
- Cisco Discovery Protocol
 - See CDP
- Cisco Express Forwarding
 - See CEF
- Cisco Group Management Protocol
 - See CGMP
- Cisco intelligent power management [7](#)
- Cisco IOS DHCP server
 - See DHCP, Cisco IOS DHCP server
- Cisco IOS File System
 - See IFS
- Cisco IOS IP SLAs [1](#)
- Cisco Secure ACS
 - attribute-value pairs for downloadable ACLs [17](#)
 - attribute-value pairs for redirect URL [17](#)
- Cisco Secure ACS configuration guide [57](#)
- CiscoWorks 2000 [5, 4](#)
- CISP [25](#)
- CIST regional root
 - See MSTP
- CIST root
 - See MSTP
- civic location [3](#)
- classless interdomain routing
 - See CIDR
- classless routing [6](#)
- class maps for QoS
 - configuring [46](#)
 - described [7](#)
 - displaying [78](#)
- class of service
 - See CoS
- clearing interfaces [30](#)
- CLI
 - abbreviating commands [4](#)
 - command modes [1](#)
 - configuration logging [5](#)
 - described [5](#)
 - editing features

- enabling and disabling [7](#)
 - keystroke editing [7](#)
 - wrapped lines [9](#)
- error messages [5](#)
- filtering command output [10](#)
- getting help [3](#)
- history
 - changing the buffer size [6](#)
 - described [6](#)
 - disabling [7](#)
 - recalling commands [6](#)
- managing clusters [15](#)
- no and default forms of commands [4](#)
- Client Information Signalling Protocol
 - See CISP
- client mode, VTP [3](#)
- client processes, tracking [1](#)
- CLNS
 - See ISO CLNS
- clock
 - See system clock
- clusters, switch
 - accessing [13](#)
 - automatic discovery [4](#)
 - automatic recovery [10](#)
 - benefits [2](#)
 - compatibility [4](#)
 - described [1](#)
 - LRE profile considerations [14](#)
 - managing
 - through CLI [15](#)
 - through SNMP [15](#)
 - planning [4](#)
 - planning considerations
 - automatic discovery [4](#)
 - automatic recovery [10](#)
 - CLI [15](#)
 - host names [13](#)
 - IP addresses [13](#)
 - LRE profiles [14](#)
 - passwords [13](#)
 - RADIUS [14](#)
 - SNMP [14, 15](#)
 - TACACS+ [14](#)

See also candidate switch, command switch, cluster standby group, member switch, and standby command switch

- cluster standby group
 - and HSRP group [12](#)
 - automatic recovery [12](#)
 - considerations [11](#)
 - defined [2](#)
 - requirements [3](#)
 - virtual IP address [11](#)

See also HSRP

- CNS [5](#)
- Configuration Engine
 - configID, deviceID, hostname [3](#)
 - configuration service [2](#)
 - described [1](#)
 - event service [3](#)
- embedded agents
 - described [5](#)
 - enabling automated configuration [6](#)
 - enabling configuration agent [9](#)
 - enabling event agent [7](#)
 - management functions [5](#)
- Coarse Wave Division Multiplexer
 - See CWDM SFPs
- command-line interface
 - See CLI
- command modes [1](#)
- commands
 - abbreviating [4](#)
 - no and default [4](#)
- commands, setting privilege levels [8](#)

- command switch
 - accessing [11](#)
 - active (AC) [10](#)
 - configuration conflicts [11](#)
 - defined [2](#)
 - passive (PC) [10](#)
 - password privilege levels [15](#)
 - priority [10](#)
 - recovery
 - from command-switch failure [10, 7](#)
 - from lost member connectivity [11](#)
 - redundant [10](#)
 - replacing
 - with another switch [10](#)
 - with cluster member [8](#)
 - requirements [3](#)
 - standby (SC) [10](#)
 - See also candidate switch, cluster standby group, member switch, and standby command switch
- community list, BGP [54](#)
- community ports [2](#)
- community strings
 - configuring [14, 8](#)
 - for cluster switches [4](#)
 - in clusters [14](#)
 - overview [4](#)
 - SNMP [14](#)
- community VLANs [2, 3](#)
- compatibility, feature [12](#)
- config.text [16](#)
- configurable leave timer, IGMP [6](#)
- configuration, initial
 - defaults [14](#)
 - Express Setup [2](#)
- configuration changes, logging [10](#)
- configuration conflicts, recovering from lost member connectivity [11](#)
- configuration examples, network [17](#)
- configuration files
 - archiving [19](#)
 - clearing the startup configuration [19](#)
 - creating using a text editor [10](#)
 - default name [16](#)
 - deleting a stored configuration [19](#)
 - described [8](#)
 - downloading
 - automatically [16](#)
 - preparing [10, 13, 16](#)
 - reasons for [8](#)
 - using FTP [13](#)
 - using RCP [17](#)
 - using TFTP [11](#)
 - guidelines for creating and using [9](#)
 - guidelines for replacing and rolling back [21](#)
 - invalid combinations when copying [5](#)
 - limiting TFTP server access [16](#)
 - obtaining with DHCP [8](#)
 - password recovery disable considerations [5](#)
 - replacing a running configuration [19, 20](#)
 - rolling back a running configuration [19, 20](#)
 - specifying the filename [16](#)
 - system contact and location information [16](#)
 - types and location [10](#)
 - uploading
 - preparing [10, 13, 16](#)
 - reasons for [9](#)
 - using FTP [14](#)
 - using RCP [18](#)
 - using TFTP [12](#)
- configuration guidelines, multi-VRF CE [74](#)
- configuration logger [10](#)
- configuration logging [5](#)
- configuration replacement [19](#)
- configuration rollback [19](#)
- configuration settings, saving [15](#)
- configure terminal command [11](#)
- configuring port-based authentication violation modes [36](#)

- configuring small-frame arrival rate [5](#)
 - config-vlan mode [2, 7](#)
 - conflicts, configuration [11](#)
 - connections, secure remote [38](#)
 - connectivity problems [13, 15, 16](#)
 - consistency checks in VTP Version 2 [4](#)
 - console port, connecting to [10](#)
 - content-routing technology
 - See WCCP
 - control protocol, IP SLAs [4](#)
 - corrupted software, recovery steps with Xmodem [2](#)
 - CoS
 - in Layer 2 frames [2](#)
 - override priority [6](#)
 - trust priority [6](#)
 - CoS input queue threshold map for QoS [16](#)
 - CoS output queue threshold map for QoS [18](#)
 - CoS-to-DSCP map for QoS [60](#)
 - counters, clearing interface [30](#)
 - CPU utilization, troubleshooting [24](#)
 - crashinfo file [23](#)
 - critical authentication, IEEE 802.1x [49](#)
 - cryptographic software image
 - Kerberos [32](#)
 - SSH [37](#)
 - SSL [42](#)
 - customer edge devices [72](#)
 - CWDM SFPs [23](#)
-
- D**
- DAACL
 - See downloadable ACL
 - daylight saving time [13](#)
 - debugging
 - enabling all system diagnostics [20](#)
 - enabling for a specific feature [19](#)
 - redirecting error message output [20](#)
 - using commands [19](#)
 - default commands [4](#)
 - default configuration
 - 802.1x [30](#)
 - auto-QoS [20](#)
 - banners [17](#)
 - BGP [43](#)
 - booting [16](#)
 - CDP [2](#)
 - DHCP [8](#)
 - DHCP option 82 [8](#)
 - DHCP snooping [8](#)
 - DHCP snooping binding database [8](#)
 - DNS [16](#)
 - dynamic ARP inspection [5](#)
 - EIGRP [34](#)
 - EtherChannel [9](#)
 - Ethernet interfaces [15](#)
 - fallback bridging [3](#)
 - Flex Links [8](#)
 - HSRP [5](#)
 - IEEE 802.1Q tunneling [4](#)
 - IGMP [38](#)
 - IGMP filtering [24](#)
 - IGMP snooping [7, 5, 6](#)
 - IGMP throttling [24](#)
 - initial switch information [3](#)
 - IP addressing, IP routing [4](#)
 - IP multicast routing [10](#)
 - IP SLAs [6](#)
 - IP source guard [16](#)
 - IPv6 [10](#)
 - IS-IS [63](#)
 - Layer 2 interfaces [15](#)
 - Layer 2 protocol tunneling [11](#)
 - LLDP [4](#)
 - MAC address table [21](#)
 - MAC address-table move update [8](#)
 - MSDP [4](#)
 - MSTP [14](#)

- multi-VRF CE [74](#)
- MVR [19](#)
- NTP [4](#)
- optional spanning-tree configuration [9](#)
- OSPF [25](#)
- password and privilege level [2](#)
- PIM [10](#)
- private VLANs [6](#)
- RADIUS [20](#)
- RIP [19](#)
- RMON [3](#)
- RSPAN [9](#)
- SDM template [3](#)
- SNMP [6](#)
- SPAN [9](#)
- SSL [45](#)
- standard QoS [30](#)
- STP [11](#)
- system message logging [3](#)
- system name and prompt [15](#)
- TACACS+ [13](#)
- UDLD [4](#)
- VLAN, Layer 2 Ethernet interfaces [19](#)
- VLANs [8](#)
- VMPS [29](#)
- voice VLAN [3](#)
- VTP [6](#)
- WCCP [5](#)
- default gateway [14, 11](#)
- default networks [89](#)
- default router preference
 - See [DRP](#)
- default routes [89](#)
- default routing [2](#)
- deleting VLANs [10](#)
- denial-of-service attack [1](#)
- description command [24](#)
- designing your network, examples [17](#)
- destination addresses
 - in IPv4 ACLs [11](#)
 - in IPv6 ACLs [5, 6](#)
- destination-IP address-based forwarding, EtherChannel [7](#)
- destination-MAC address forwarding, EtherChannel [7](#)
- detecting indirect link failures, STP [5](#)
- device [23](#)
- device discovery protocol [1](#)
- device manager
 - benefits [2](#)
 - described [2, 4](#)
 - in-band management [6](#)
 - upgrading a switch [23](#)
- DHCP
 - Cisco IOS server database
 - configuring [14](#)
 - default configuration [8](#)
 - described [6](#)
 - DHCP for IPv6
 - See [DHCPv6](#)
 - enabling
 - relay agent [10](#)
 - server [10](#)
- DHCP-based autoconfiguration
 - client request message exchange [4](#)
 - configuring
 - client side [3](#)
 - DNS [7](#)
 - relay device [8](#)
 - server side [6](#)
 - server-side [10](#)
 - TFTP server [7](#)
 - example [9](#)
 - lease options
 - for IP address information [6](#)
 - for receiving the configuration file [6](#)
 - overview [3](#)
 - relationship to BOOTP [4](#)
 - relay support [5, 12](#)
 - support for [5](#)

- DHCP-based autoconfiguration and image update
 - configuring [11 to 13](#)
 - understanding [5](#)
- DHCP binding database
 - See DHCP snooping binding database
- DHCP binding table
 - See DHCP snooping binding database
- DHCP object tracking, configuring primary interface [11](#)
- DHCP option 82
 - circuit ID suboption [5](#)
 - configuration guidelines [9](#)
 - default configuration [8](#)
 - displaying [15](#)
 - forwarding address, specifying [10](#)
 - helper address [10](#)
 - overview [3](#)
 - packet format, suboption
 - circuit ID [5](#)
 - remote ID [5](#)
 - remote ID suboption [5](#)
- DHCP server port-based address allocation
 - configuration guidelines [20](#)
 - default configuration [19](#)
 - described [19](#)
 - displaying [22](#)
 - enabling [20](#)
- DHCP server port-based address assignment
 - support for [5](#)
- DHCP snooping
 - accepting untrusted packets form edge switch [3, 12](#)
 - and private VLANs [13](#)
 - binding database
 - See DHCP snooping binding database
 - configuration guidelines [9](#)
 - default configuration [8](#)
 - displaying binding tables [15](#)
 - message exchange process [4](#)
 - option 82 data insertion [3](#)
 - trusted interface [2](#)
 - untrusted interface [2](#)
 - untrusted messages [2](#)
- DHCP snooping binding database
 - adding bindings [14](#)
 - binding file
 - format [7](#)
 - location [6](#)
 - bindings [6](#)
 - clearing agent statistics [15](#)
 - configuration guidelines [9](#)
 - configuring [14](#)
 - default configuration [8](#)
 - deleting
 - binding file [14](#)
 - bindings [15](#)
 - database agent [14](#)
 - described [6](#)
 - displaying [15](#)
 - binding entries [15](#)
 - status and statistics [15](#)
 - enabling [14](#)
 - entry [6](#)
 - renewing database [15](#)
 - resetting
 - delay value [14](#)
 - timeout value [14](#)
- DHCP snooping binding table
 - See DHCP snooping binding database
- DHCPv6
 - configuration guidelines [14](#)
 - default configuration [14](#)
 - described [6](#)
 - enabling client function [17](#)
 - enabling DHCPv6 server function [15](#)
 - support for [12](#)
- Differentiated Services architecture, QoS [2](#)
- Differentiated Services Code Point [2](#)
- Diffusing Update Algorithm (DUAL) [33](#)
- directed unicast requests [5](#)

- directories
 - changing [4](#)
 - creating and removing [4](#)
 - displaying the working [4](#)
- discovery, clusters
 - See automatic discovery
- Distance Vector Multicast Routing Protocol
 - See DVMRP
- distance-vector protocols [3](#)
- distribute-list command [98](#)
- DNS
 - and DHCP-based autoconfiguration [7](#)
 - default configuration [16](#)
 - displaying the configuration [17](#)
 - in IPv6 [4](#)
 - overview [15](#)
 - setting up [16](#)
 - support for [5](#)
- DNS-based SSM mapping [18, 20](#)
- domain names
 - DNS [15](#)
 - VTP [8](#)
- Domain Name System
 - See DNS
- domains, ISO IGRP routing [62](#)
- dot1q-tunnel switchport mode [18](#)
- double-tagged packets
 - IEEE 802.1Q tunneling [2](#)
 - Layer 2 protocol tunneling [10](#)
- downloadable ACL [16, 17, 57](#)
- downloading
 - configuration files
 - preparing [10, 13, 16](#)
 - reasons for [8](#)
 - using FTP [13](#)
 - using RCP [17](#)
 - using TFTP [11](#)
 - image files
 - deleting old image [27](#)
 - preparing [25, 29, 33](#)
 - reasons for [23](#)
 - using CMS [2](#)
 - using FTP [30](#)
 - using HTTP [2, 23](#)
 - using RCP [34](#)
 - using TFTP [26](#)
 - using the device manager or Network Assistant [23](#)
- drop threshold for Layer 2 protocol packets [11](#)
- DRP
 - configuring [12](#)
 - described [4](#)
 - IPv6 [4](#)
 - support for [12](#)
- DSCP [11, 2](#)
- DSCP input queue threshold map for QoS [16](#)
- DSCP output queue threshold map for QoS [18](#)
- DSCP-to-CoS map for QoS [64](#)
- DSCP-to-DSCP-mutation map for QoS [65](#)
- DSCP transparency [40](#)
- DTP [8, 17](#)
- dual-action detection [5](#)
- DUAL finite state machine, EIGRP [34](#)
- dual IPv4 and IPv6 templates [2, 5, 6](#)
- dual protocol stacks
 - IPv4 and IPv6 [6](#)
 - SDM templates supporting [6](#)
- dual-purpose uplinks
 - defined [6](#)
 - LEDs [6](#)
 - link selection [6, 16](#)
 - setting the type [16](#)
- DVMRP
 - autosummarization
 - configuring a summary address [57](#)
 - disabling [59](#)
 - connecting PIM domain to DVMRP router [50](#)
 - enabling unicast routing [53](#)

- interoperability
 - with Cisco devices [48](#)
 - with Cisco IOS software [9](#)
- mrinfo requests, responding to [52](#)
- neighbors
 - advertising the default route to [51](#)
 - discovery with Probe messages [48](#)
 - displaying information [52](#)
 - prevent peering with nonpruning [55](#)
 - rejecting nonpruning [54](#)
- overview [8](#)
- routes
 - adding a metric offset [59](#)
 - advertising all [59](#)
 - advertising the default route to neighbors [51](#)
 - caching DVMRP routes learned in report messages [53](#)
 - changing the threshold for syslog messages [56](#)
 - deleting [60](#)
 - displaying [61](#)
 - favoring one over another [59](#)
 - limiting the number injected into MBONE [56](#)
 - limiting unicast route advertisements [48](#)
- routing table [9](#)
- source distribution tree, building [9](#)
- support for [12](#)
- tunnels
 - configuring [50](#)
 - displaying neighbor information [52](#)
- dynamic access ports
 - characteristics [3](#)
 - configuring [30](#)
 - defined [3](#)
- dynamic addresses
 - See addresses
- dynamic ARP inspection
 - ARP cache poisoning [1](#)
 - ARP requests, described [1](#)
 - ARP spoofing attack [1](#)
- clearing
 - log buffer [14](#)
 - statistics [14](#)
- configuration guidelines [6](#)
- configuring
 - ACLs for non-DHCP environments [8](#)
 - in DHCP environments [7](#)
 - log buffer [12](#)
 - rate limit for incoming ARP packets [4, 10](#)
- default configuration [5](#)
- denial-of-service attacks, preventing [10](#)
- described [1](#)
- DHCP snooping binding database [2](#)
- displaying
 - ARP ACLs [14](#)
 - configuration and operating state [14](#)
 - log buffer [14](#)
 - statistics [14](#)
 - trust state and rate limit [14](#)
- error-disabled state for exceeding rate limit [4](#)
- function of [2](#)
- interface trust states [3](#)
- log buffer
 - clearing [14](#)
 - configuring [12](#)
 - displaying [14](#)
- logging of dropped packets, described [4](#)
- man-in-the middle attack, described [2](#)
- network security issues and interface trust states [3](#)
- priority of ARP ACLs and DHCP snooping entries [4](#)
- rate limiting of ARP packets
 - configuring [10](#)
 - described [4](#)
 - error-disabled state [4](#)
- statistics
 - clearing [14](#)
 - displaying [14](#)
- validation checks, performing [11](#)
- dynamic auto trunking mode [18](#)

dynamic desirable trunking mode [18](#)
 Dynamic Host Configuration Protocol
 See DHCP-based autoconfiguration
 dynamic port VLAN membership
 described [28](#)
 reconfirming [31](#)
 troubleshooting [33](#)
 types of connections [30](#)
 dynamic routing [3](#)
 ISO CLNS [61](#)
 Dynamic Trunking Protocol
 See DTP

E

EBGP [41](#)

editing features

 enabling and disabling [7](#)
 keystrokes used [7](#)
 wrapped lines [9](#)

EIGRP

 authentication [38](#)
 components [33](#)
 configuring [36](#)
 default configuration [34](#)
 definition [33](#)
 interface parameters, configuring [37](#)
 monitoring [40](#)
 stub routing [39](#)

ELIN location [3](#)

embedded event manager

 actions [4](#)
 configuring [1, 5](#)
 displaying information [7](#)
 environmental variables [5](#)
 event detectors [2](#)
 policies [4](#)
 registering and defining an applet [5](#)

 registering and defining a TCL script [6](#)
 understanding [1](#)

enable password [3](#)

enable secret password [3](#)

encryption, CipherSuite [44](#)

encryption for passwords [3](#)

Enhanced IGRP

 See EIGRP

enhanced object tracking

 backup static routing [12](#)

 commands [1](#)

 defined [1](#)

 DHCP primary interface [11](#)

 HSRP [7](#)

 IP routing state [2](#)

 IP SLAs [9](#)

 line-protocol state [2](#)

 network monitoring with IP SLAs [11](#)

 routing policy, configuring [12](#)

 static route primary interface [10](#)

 tracked lists [3](#)

enhanced object tracking static routing [10](#)

environmental variables, embedded event manager [5](#)

environment variables, function of [19](#)

equal-cost routing [12, 88](#)

error-disabled state, BPDU [2](#)

error messages during command entry [5](#)

EtherChannel

 automatic creation of [4, 5](#)

 channel groups

 binding physical and logical interfaces [3](#)

 numbering of [3](#)

 configuration guidelines [9](#)

 configuring

 Layer 2 interfaces [10](#)

 Layer 3 physical interfaces [14](#)

 Layer 3 port-channel logical interfaces [13](#)

 default configuration [9](#)

 described [2](#)

- displaying status [20](#)
 - forwarding methods [7, 16](#)
 - IEEE 802.3ad, described [5](#)
 - interaction
 - with STP [10](#)
 - with VLANs [10](#)
 - LACP
 - described [5](#)
 - displaying status [20](#)
 - hot-standby ports [18](#)
 - interaction with other features [6](#)
 - modes [6](#)
 - port priority [19](#)
 - system priority [19](#)
 - Layer 3 interface [3](#)
 - load balancing [7, 16](#)
 - logical interfaces, described [3](#)
 - PAgP
 - aggregate-port learners [16](#)
 - compatibility with Catalyst 1900 [17](#)
 - described [4](#)
 - displaying status [20](#)
 - interaction with other features [5](#)
 - interaction with virtual switches [5](#)
 - learn method and priority configuration [16](#)
 - modes [4](#)
 - support for [3](#)
 - with dual-action detection [5](#)
 - port-channel interfaces
 - described [3](#)
 - numbering of [3](#)
 - port groups [6](#)
 - support for [3](#)
 - EtherChannel guard
 - described [7](#)
 - disabling [14](#)
 - enabling [14](#)
 - Ethernet VLANs
 - adding [9](#)
 - defaults and ranges [8](#)
 - modifying [9](#)
 - EUI [3](#)
 - event detectors, embedded event manager [2](#)
 - events, RMON [3](#)
 - examples
 - network configuration [17](#)
 - expedite queue for QoS [76](#)
 - Express Setup [2](#)
 - See also getting started guide
 - extended crashinfo file [23](#)
 - extended-range VLANs
 - configuration guidelines [13](#)
 - configuring [12](#)
 - creating [13](#)
 - creating with an internal VLAN ID [15](#)
 - defined [1](#)
 - extended system ID
 - MSTP [17](#)
 - STP [4, 14](#)
 - extended universal identifier
 - See EUI
 - Extensible Authentication Protocol over LAN [1](#)
 - external BGP
 - See EBGp
 - external neighbors, BGP [45](#)
-
- F**
- fa0 interface [6](#)
 - fallback bridging
 - and protected ports [3](#)
 - bridge groups
 - creating [3](#)
 - described [1](#)
 - displaying [10](#)
 - function of [2](#)
 - number supported [4](#)
 - removing [4](#)

- bridge table
 - clearing [10](#)
 - displaying [10](#)
 - configuration guidelines [3](#)
 - connecting interfaces with [10](#)
 - default configuration [3](#)
 - described [1](#)
 - frame forwarding
 - flooding packets [2](#)
 - forwarding packets [2](#)
 - overview [1](#)
 - protocol, unsupported [3](#)
 - STP
 - disabling on an interface [9](#)
 - forward-delay interval [8](#)
 - hello BPDU interval [7](#)
 - interface priority [6](#)
 - keepalive messages [2](#)
 - maximum-idle interval [9](#)
 - path cost [6](#)
 - VLAN-bridge spanning-tree priority [5](#)
 - VLAN-bridge STP [2](#)
 - support for [12](#)
 - SVIs and routed ports [1](#)
 - unsupported protocols [3](#)
 - VLAN-bridge STP [10](#)
- Fast Convergence [3](#)
- features, incompatible [12](#)
- FIB [87](#)
- fiber-optic, detecting unidirectional links [1](#)
- files
 - basic crashinfo
 - description [23](#)
 - location [23](#)
 - copying [5](#)
 - crashinfo, description [23](#)
 - deleting [5](#)
 - displaying the contents of [8](#)
 - extended crashinfo
 - description [23](#)
 - location [23](#)
 - tar
 - creating [6](#)
 - displaying the contents of [7](#)
 - extracting [7](#)
 - image file format [24](#)
- file system
 - displaying available file systems [2](#)
 - displaying file information [3](#)
 - local file system names [1](#)
 - network file system names [5](#)
 - setting the default [3](#)
- filtering
 - in a VLAN [29](#)
 - IPv6 traffic [3, 8](#)
 - non-IP traffic [27](#)
 - show and more command output [10](#)
- filtering show and more command output [10](#)
- filters, IP
 - See ACLs, IP
- flash device, number of [1](#)
- flexible authentication ordering
 - configuring [59](#)
 - overview [24](#)
- Flex Link Multicast Fast Convergence [3](#)
- Flex Links
 - configuration guidelines [8](#)
 - configuring [9](#)
 - configuring preferred VLAN [12](#)
 - configuring VLAN load balancing [11](#)
 - default configuration [8](#)
 - description [1](#)
 - link load balancing [2](#)
 - monitoring [14](#)
 - VLANs [2](#)
- flooded traffic, blocking [8](#)
- flow-based packet classification [11](#)

flowcharts

- QoS classification [6](#)
- QoS egress queueing and scheduling [17](#)
- QoS ingress queueing and scheduling [15](#)
- QoS policing and marking [10](#)

flowcontrol

- configuring [20](#)
- described [20](#)

forward-delay time

- MSTP [23](#)
- STP [21](#)

Forwarding Information Base

- See FIB

forwarding nonroutable protocols [1](#)

FTP

- accessing MIB files [3](#)
- configuration files
 - downloading [13](#)
 - overview [12](#)
 - preparing the server [13](#)
 - uploading [14](#)
- image files
 - deleting old image [31](#)
 - downloading [30](#)
 - preparing the server [29](#)
 - uploading [31](#)

G

- general query [5](#)
- Generating IGMP Reports [3](#)
- get-bulk-request operation [3](#)
- get-next-request operation [3,4](#)
- get-request operation [3,4](#)
- get-response operation [3](#)
- global configuration mode [2](#)
- global leave, IGMP [13](#)
- guest VLAN and 802.1x [17](#)
- guide mode [2](#)

GUIs

- See device manager and Network Assistant

H

hardware limitations and Layer 3 interfaces [26](#)

hello time

- MSTP [22](#)
- STP [20](#)

help, for the command line [3](#)

hierarchical policy maps [8](#)

- configuration guidelines [33](#)
- configuring [52](#)
- described [11](#)

history

- changing the buffer size [6](#)
- described [6](#)
- disabling [7](#)
- recalling commands [6](#)

history table, level and number of syslog messages [10](#)

host names, in clusters [13](#)

host ports

- configuring [11](#)
- kinds of [2](#)

hosts, limit on dynamic ports [33](#)

Hot Standby Router Protocol

- See HSRP

HP OpenView [5](#)

HSRP

- authentication string [10](#)
- automatic cluster recovery [12](#)
- binding to cluster group [12](#)
- cluster standby group considerations [11](#)
- command-switch redundancy [1,7](#)
- configuring [4](#)
- default configuration [5](#)
- definition [1](#)
- guidelines [5](#)
- monitoring [13](#)

- object tracking [7](#)
 - overview [1](#)
 - priority [8](#)
 - routing redundancy [12](#)
 - support for ICMP redirect messages [12](#)
 - timers [10](#)
 - tracking [8](#)
 - See also clusters, cluster standby group, and standby command switch
 - HSRP for IPv6
 - configuring [24](#)
 - guidelines [23](#)
 - HTTP over SSL
 - see HTTPS
 - HTTPS [42](#)
 - configuring [46](#)
 - self-signed certificate [43](#)
 - HTTP secure server [42](#)
-
- IBPG [41](#)
 - ICMP
 - IPv6 [4](#)
 - redirect messages [11](#)
 - support for [12](#)
 - time-exceeded messages [17](#)
 - traceroute and [17](#)
 - unreachable messages [19](#)
 - unreachable messages and IPv6 [4](#)
 - unreachables and ACLs [21](#)
 - ICMP Echo operation
 - configuring [12](#)
 - IP SLAs [11](#)
 - ICMP ping
 - executing [14](#)
 - overview [13](#)
 - ICMP Router Discovery Protocol
 - See IRDP
 - ICMPv6 [4](#)
 - IDS appliances
 - and ingress RSPAN [20](#)
 - and ingress SPAN [13](#)
 - IEEE 802.1D
 - See STP
 - IEEE 802.1p [1](#)
 - IEEE 802.1Q
 - and trunk ports [3](#)
 - configuration limitations [19](#)
 - encapsulation [16](#)
 - native VLAN for untagged traffic [23](#)
 - tunneling
 - compatibility with other features [6](#)
 - defaults [4](#)
 - described [1](#)
 - tunnel ports with other features [6](#)
 - IEEE 802.1s
 - See MSTP
 - IEEE 802.1w
 - See RSTP
 - IEEE 802.1x
 - See port-based authentication
 - IEEE 802.3ad
 - See EtherChannel
 - IEEE 802.3af
 - See PoE
 - IEEE 802.3x flow control [20](#)
 - ifIndex values, SNMP [5](#)
 - IFS [5](#)
 - IGMP
 - configurable leave timer
 - described [6](#)
 - enabling [11](#)
 - configuring the switch
 - as a member of a group [38](#)
 - statically connected member [42](#)
 - controlling access to groups [39](#)
 - default configuration [38](#)

- deleting cache entries [61](#)
- displaying groups [61](#)
- fast switching [42](#)
- flooded multicast traffic
 - controlling the length of time [12](#)
 - disabling on an interface [13](#)
 - global leave [13](#)
 - query solicitation [13](#)
 - recovering from flood mode [13](#)
- host-query interval, modifying [40](#)
- joining multicast group [3](#)
- join messages [3](#)
- leave processing, enabling [10, 8](#)
- leaving multicast group [5](#)
- multicast reachability [38](#)
- overview [3](#)
- queries [4](#)
- report suppression
 - described [6](#)
 - disabling [15, 11](#)
- supported versions [3](#)
- support for [4](#)
- Version 1
 - changing to Version 2 [40](#)
 - described [3](#)
- Version 2
 - changing to Version 1 [40](#)
 - described [3](#)
 - maximum query response time value [42](#)
 - pruning groups [42](#)
 - query timeout value [41](#)
- IGMP filtering
 - configuring [24](#)
 - default configuration [24](#)
 - described [23](#)
 - monitoring [28](#)
 - support for [4](#)
- IGMP groups
 - configuring filtering [27](#)
 - setting the maximum number [26](#)
- IGMP helper [4, 6](#)
- IGMP Immediate Leave
 - configuration guidelines [11](#)
 - described [5](#)
 - enabling [10](#)
- IGMP profile
 - applying [26](#)
 - configuration mode [24](#)
 - configuring [25](#)
- IGMP snooping
 - and address aliasing [2](#)
 - configuring [6](#)
 - default configuration [7, 5, 6](#)
 - definition [2](#)
 - enabling and disabling [7, 6](#)
 - global configuration [7](#)
 - Immediate Leave [5](#)
 - method [8](#)
 - monitoring [15, 11](#)
 - querier
 - configuration guidelines [14](#)
 - configuring [14](#)
 - supported versions [3](#)
 - support for [4](#)
 - VLAN configuration [8](#)
- IGMP throttling
 - configuring [27](#)
 - default configuration [24](#)
 - described [24](#)
 - displaying action [28](#)
- IGP [24](#)
- Immediate Leave, IGMP [5](#)
 - enabling [8](#)
- inaccessible authentication bypass [19](#)
- initial configuration
 - defaults [14](#)
 - Express Setup [2](#)

- interface
 - number [11](#)
 - range macros [13](#)
- interface command [10 to 11](#)
- interface configuration mode [3](#)
- interfaces
 - auto-MDIX, configuring [21](#)
 - configuration guidelines
 - duplex and speed [18](#)
 - configuring
 - procedure [11](#)
 - counters, clearing [30](#)
 - default configuration [15](#)
 - described [24](#)
 - descriptive name, adding [24](#)
 - displaying information about [29](#)
 - flow control [20](#)
 - management [4](#)
 - monitoring [29](#)
 - naming [24](#)
 - physical, identifying [10](#)
 - range of [11](#)
 - restarting [31](#)
 - shutting down [31](#)
 - speed and duplex, configuring [18](#)
 - status [29](#)
 - supported [10](#)
 - types of [1](#)
- interfaces range macro command [13](#)
- interface types [10](#)
- Interior Gateway Protocol
 - See IGP
- internal BGP
 - See IBGP
- internal neighbors, BGP [45](#)
- Internet Control Message Protocol
 - See ICMP
- Internet Group Management Protocol
 - See IGMP
- Internet Protocol version 6
 - See IPv6
- Inter-Switch Link
 - See ISL
- inter-VLAN routing [12, 2](#)
- Intrusion Detection System
 - See IDS appliances
- inventory management TLV [2, 6](#)
- IOS shell
 - See Auto Smartports macros
- IP ACLs
 - for QoS classification [7](#)
 - implicit deny [9, 13](#)
 - implicit masks [9](#)
 - named [14](#)
 - undefined [20](#)
- IP addresses
 - 128-bit [2](#)
 - candidate or member [3, 13](#)
 - classes of [5](#)
 - cluster access [2](#)
 - command switch [3, 11, 13](#)
 - default configuration [4](#)
 - discovering [28](#)
 - for IP routing [4](#)
 - IPv6 [2](#)
 - MAC address association [8](#)
 - monitoring [17](#)
 - redundant clusters [11](#)
 - standby command switch [11, 13](#)
 - See also IP information
- IP base image [1](#)
- IP broadcast address [15](#)
- ip cef distributed command [87](#)
- IP directed broadcasts [13](#)
- ip igmp profile command [24](#)

- IP information
 - assigned
 - manually [14](#)
 - through DHCP-based autoconfiguration [3](#)
 - default configuration [3](#)
- IP multicast routing
 - addresses
 - all-hosts [3](#)
 - all-multicast-routers [3](#)
 - host group address range [3](#)
 - administratively-scoped boundaries, described [45](#)
 - and IGMP snooping [2](#)
 - Auto-RP
 - adding to an existing sparse-mode cloud [25](#)
 - benefits of [25](#)
 - clearing the cache [61](#)
 - configuration guidelines [11](#)
 - filtering incoming RP announcement messages [28](#)
 - overview [6](#)
 - preventing candidate RP spoofing [28](#)
 - preventing join messages to false RPs [27](#)
 - setting up in a new internetwork [25](#)
 - using with BSR [33](#)
 - bootstrap router
 - configuration guidelines [11](#)
 - configuring candidate BSRs [31](#)
 - configuring candidate RPs [32](#)
 - defining the IP multicast boundary [30](#)
 - defining the PIM domain border [29](#)
 - overview [7](#)
 - using with Auto-RP [33](#)
 - Cisco implementation [2](#)
 - configuring
 - basic multicast routing [11](#)
 - IP multicast boundary [45](#)
 - default configuration [10](#)
 - enabling
 - multicast forwarding [12](#)
 - PIM mode [13](#)
 - group-to-RP mappings
 - Auto-RP [6](#)
 - BSR [7](#)
- MBONE
 - deleting sdr cache entries [61](#)
 - described [44](#)
 - displaying sdr cache [62](#)
 - enabling sdr listener support [45](#)
 - limiting DVMRP routes advertised [56](#)
 - limiting sdr cache entry lifetime [45](#)
 - SAP packets for conference session announcement [44](#)
 - Session Directory (sdr) tool, described [44](#)
- monitoring
 - packet rate loss [62](#)
 - peering devices [62](#)
 - tracing a path [62](#)
- multicast forwarding, described [7](#)
- PIMv1 and PIMv2 interoperability [10](#)
- protocol interaction [2](#)
- reverse path check (RPF) [7](#)
- routing table
 - deleting [61](#)
 - displaying [61](#)
- RP
 - assigning manually [23](#)
 - configuring Auto-RP [25](#)
 - configuring PIMv2 BSR [29](#)
 - monitoring mapping information [33](#)
 - using Auto-RP and BSR [33](#)
- statistics, displaying system and network [61](#)
- See also CGMP
- See also DVMRP
- See also IGMP
- See also PIM
- IP phones
 - and QoS [1](#)
 - automatic classification and queuing [20](#)

- configuring [4](#)
 - ensuring port security with QoS [38](#)
 - trusted boundary for QoS [38](#)
- IP precedence [2](#)
- IP-precedence-to-DSCP map for QoS [62](#)
- IP protocols
 - in ACLs [11](#)
 - routing [12](#)
- IP routes, monitoring [100](#)
- IP routing
 - connecting interfaces with [10](#)
 - disabling [18](#)
 - enabling [18](#)
- IP Service Level Agreements
 - See IP SLAs
- IP service levels, analyzing [1](#)
- IP services image [1](#)
- IP SLAs
 - benefits [2](#)
 - configuration guidelines [6](#)
 - configuring object tracking [9](#)
 - Control Protocol [4](#)
 - default configuration [6](#)
 - definition [1](#)
 - ICMP echo operation [11](#)
 - measuring network performance [3](#)
 - monitoring [13](#)
 - multioperations scheduling [5](#)
 - object tracking [9](#)
 - operation [3](#)
 - reachability tracking [9](#)
 - responder
 - described [4](#)
 - enabling [8](#)
 - response time [4](#)
 - scheduling [5](#)
 - SNMP support [2](#)
 - supported metrics [2](#)
 - threshold monitoring [6](#)
 - track object monitoring agent, configuring [11](#)
 - track state [9](#)
 - UDP jitter operation [9](#)
- IP source guard
 - and 802.1x [17](#)
 - and DHCP snooping [15](#)
 - and EtherChannels [17](#)
 - and port security [17](#)
 - and private VLANs [17](#)
 - and routed ports [17](#)
 - and TCAM entries [17](#)
 - and trunk interfaces [17](#)
 - and VRF [17](#)
 - binding configuration
 - automatic [15](#)
 - manual [15](#)
 - binding table [15](#)
 - configuration guidelines [17](#)
 - default configuration [16](#)
 - described [15](#)
 - disabling [18](#)
 - displaying
 - bindings [19](#)
 - configuration [19](#)
 - enabling [17](#)
 - filtering
 - source IP address [16](#)
 - source IP and MAC address [16](#)
 - source IP address filtering [16](#)
 - source IP and MAC address filtering [16](#)
 - static bindings
 - adding [17](#)
 - deleting [18](#)
- IP traceroute
 - executing [17](#)
 - overview [16](#)
- IP unicast routing
 - address resolution [8](#)
 - administrative distances [89, 99](#)

- ARP [8](#)
- assigning IP addresses to Layer 3 interfaces [5](#)
- authentication keys [99](#)
- broadcast
 - address [15](#)
 - flooding [16](#)
 - packets [13](#)
 - storms [13](#)
- classless routing [6](#)
- configuring static routes [88](#)
- default
 - addressing configuration [4](#)
 - gateways [11](#)
 - networks [89](#)
 - routes [89](#)
 - routing [2](#)
- directed broadcasts [13](#)
- disabling [18](#)
- dynamic routing [3](#)
- enabling [18](#)
- EtherChannel Layer 3 interface [3](#)
- IGP [24](#)
- inter-VLAN [2](#)
- IP addressing
 - classes [5](#)
 - configuring [4](#)
- IPv6 [3](#)
- IRDP [11](#)
- Layer 3 interfaces [3](#)
- MAC address and IP address [8](#)
- passive interfaces [97](#)
- protocols
 - distance-vector [3](#)
 - dynamic [3](#)
 - link-state [3](#)
- proxy ARP [8](#)
- redistribution [90](#)
- reverse address resolution [8](#)
- routed ports [3](#)
- static routing [3](#)
- steps to configure [4](#)
- subnet mask [5](#)
- subnet zero [6](#)
- supernet [6](#)
- UDP [14](#)
- with SVIs [3](#)
- See also BGP
- See also EIGRP
- See also OSPF
- See also RIP
- IPv4 ACLs
 - applying to interfaces [19](#)
 - extended, creating [10](#)
 - named [14](#)
 - standard, creating [9](#)
- IPv4 and IPv6
 - dual protocol stacks [5](#)
- IPv6
 - ACLs
 - displaying [9](#)
 - limitations [3](#)
 - matching criteria [3](#)
 - port [2](#)
 - precedence [2](#)
 - router [2](#)
 - supported [2](#)
 - addresses [2](#)
 - address formats [2](#)
 - applications [5](#)
 - assigning address [10](#)
 - autoconfiguration [5](#)
 - CEFv6 [18](#)
 - configuring static routes [19](#)
 - default configuration [10](#)
 - default router preference (DRP) [4](#)
 - defined [1](#)
 - Enhanced Interior Gateway Routing Protocol (EIGRP) IPv6 [7](#)

- EIGRP IPv6 Commands [7](#)
 - Router ID [7](#)
- feature limitations [8](#)
- features not supported [8](#)
- forwarding [10](#)
- ICMP [4](#)
- monitoring [26](#)
- neighbor discovery [4](#)
- OSPF [6](#)
- path MTU discovery [4](#)
- SDM templates [2, 1](#)
- Stateless Autoconfiguration [5](#)
 - supported features [2](#)
 - switch limitations [8](#)
 - understanding static routes [6](#)
- IPv6 traffic, filtering [3](#)
- IRDP
 - configuring [12](#)
 - definition [11](#)
 - support for [12](#)
- IS-IS
 - addresses [62](#)
 - area routing [61](#)
 - default configuration [63](#)
 - monitoring [71](#)
 - show commands [71](#)
 - system routing [61](#)
- ISL
 - and IPv6 [3](#)
 - and trunk ports [3](#)
 - encapsulation [8, 16](#)
 - trunking with IEEE 802.1 tunneling [5](#)
- ISO CLNS
 - clear commands [71](#)
 - dynamic routing protocols [61](#)
 - monitoring [71](#)
 - NETs [61](#)
 - NSAPs [61](#)
 - OSI standard [61](#)

- ISO IGRP
 - area routing [61](#)
 - system routing [61](#)
- isolated port [2](#)
- isolated VLANs [2, 3](#)

J

- join messages, IGMP [3](#)

K

- KDC
 - described [32](#)
 - See also Kerberos
- keepalive messages [2](#)
- Kerberos
 - authenticating to
 - boundary switch [35](#)
 - KDC [35](#)
 - network services [35](#)
 - configuration examples [32](#)
 - configuring [35](#)
 - credentials [32](#)
 - cryptographic software image [32](#)
 - described [32](#)
 - KDC [32](#)
 - operation [34](#)
 - realm [34](#)
 - server [34](#)
 - support for [10](#)
 - switch as trusted third party [32](#)
 - terms [33](#)
 - TGT [34](#)
 - tickets [32](#)
- key distribution center
 - See KDC

L

l2protocol-tunnel command [13](#)

LACP

Layer 2 protocol tunneling [9](#)

See EtherChannel

Layer 2 frames, classification with CoS [2](#)

Layer 2 interfaces, default configuration [15](#)

Layer 2 protocol tunneling

configuring [10](#)

configuring for EtherChannels [14](#)

default configuration [11](#)

defined [8](#)

guidelines [11](#)

Layer 2 traceroute

and ARP [16](#)

and CDP [15](#)

broadcast traffic [15](#)

described [15](#)

IP addresses and subnets [16](#)

MAC addresses and VLANs [15](#)

multicast traffic [15](#)

multiple devices on a port [16](#)

unicast traffic [15](#)

usage guidelines [15](#)

Layer 3 features [12](#)

Layer 3 interfaces

assigning IP addresses to [5](#)

assigning IPv4 and IPv6 addresses to [13](#)

assigning IPv6 addresses to [11](#)

changing from Layer 2 mode [5, 78, 79](#)

types of [3](#)

Layer 3 packets, classification methods [2](#)

LDAP [2](#)

Leaking IGMP Reports [4](#)

LEDs, switch

See hardware installation guide

lightweight directory access protocol

See LDAP

line configuration mode [3](#)

Link Aggregation Control Protocol

See EtherChannel

link failure, detecting unidirectional [7](#)

Link Layer Discovery Protocol

See CDP

link local unicast addresses [3](#)

link redundancy

See Flex Links

links, unidirectional [1](#)

link state advertisements (LSAs) [28](#)

link-state protocols [3](#)

link-state tracking

configuring [23](#)

described [21](#)

LLDP

configuring [4](#)

characteristics [5](#)

default configuration [4](#)

enabling [5](#)

monitoring and maintaining [10](#)

overview [1](#)

supported TLVs [2](#)

switch stack considerations [2](#)

transmission timer and holdtime, setting [5](#)

LLDP-MED

configuring

procedures [4](#)

TLVs [6](#)

monitoring and maintaining [10](#)

overview [1, 2](#)

supported TLVs [2](#)

LLDP Media Endpoint Discovery

See LLDP-MED

load balancing [4](#)

local SPAN [2](#)

location TLV [3, 6](#)

logging messages, ACL [8](#)

- login authentication
 - with RADIUS [23](#)
 - with TACACS+ [14](#)
 - login banners [17](#)
 - log messages
 - See system message logging
 - Long-Reach Ethernet (LRE) technology [18](#)
 - loop guard
 - described [9](#)
 - enabling [15](#)
 - support for [7](#)
 - LRE profiles, considerations in switch clusters [14](#)
-
- ## M
- MAB
 - See MAC authentication bypass
 - MAB aging timer [8](#)
 - MAB inactivity timer
 - default setting [31](#)
 - range [33](#)
 - MAC/PHY configuration status TLV [2](#)
 - MAC addresses
 - aging time [21](#)
 - and VLAN association [20](#)
 - building the address table [20](#)
 - default configuration [21](#)
 - disabling learning on a VLAN [27](#)
 - discovering [28](#)
 - displaying [27](#)
 - displaying in the IP source binding table [19](#)
 - dynamic
 - learning [20](#)
 - removing [22](#)
 - in ACLs [27](#)
 - IP address association [8](#)
 - static
 - adding [24](#)
 - allowing [26, 27](#)
 - characteristics of [24](#)
 - dropping [25](#)
 - removing [24](#)
 - MAC address learning [5](#)
 - MAC address learning, disabling on a VLAN [27](#)
 - MAC address notification, support for [13](#)
 - MAC address-table move update
 - configuration guidelines [8](#)
 - configuring [12](#)
 - default configuration [8](#)
 - description [6](#)
 - monitoring [14](#)
 - MAC address-to-VLAN mapping [28](#)
 - MAC authentication bypass [33](#)
 - configuring [53](#)
 - overview [14](#)
 - See MAB
 - MAC extended access lists
 - applying to Layer 2 interfaces [28](#)
 - configuring for QoS [45](#)
 - creating [27](#)
 - defined [27](#)
 - for QoS classification [5](#)
 - macros
 - See Auto Smartports macros
 - See Smartports macros
 - magic packet [22](#)
 - manageability features [5](#)
 - management access
 - in-band
 - browser session [6](#)
 - CLI session [6](#)
 - device manager [6](#)
 - SNMP [6](#)
 - out-of-band console port connection [6](#)
 - management address TLV [2](#)
 - management options
 - CLI [1](#)
 - clustering [3](#)

- CNS [1](#)
- Network Assistant [2](#)
- overview [4](#)
- management VLAN
 - considerations in switch clusters [7](#)
 - discovery through different management VLANs [7](#)
- mapping tables for QoS
 - configuring
 - CoS-to-DSCP [60](#)
 - DSCP [60](#)
 - DSCP-to-CoS [64](#)
 - DSCP-to-DSCP-mutation [65](#)
 - IP-precedence-to-DSCP [62](#)
 - policed-DSCP [63](#)
 - described [12](#)
- marking
 - action with aggregate policers [58](#)
 - described [4, 8](#)
- matching
 - IPv6 ACLs [3](#)
- matching, IPv4 ACLs [7](#)
- maximum aging time
 - MSTP [23](#)
 - STP [21](#)
- maximum hop count, MSTP [24](#)
- maximum number of allowed devices, port-based authentication [33](#)
- maximum-paths command [49, 88](#)
- MDA
 - configuration guidelines [11 to 12](#)
 - described [9, 11](#)
 - exceptions with authentication process [5](#)
- membership mode, VLAN port [3](#)
- member switch
 - automatic discovery [4](#)
 - defined [2](#)
 - managing [15](#)
 - passwords [13](#)
 - recovering from lost connectivity [11](#)
 - requirements [3](#)
 - See also candidate switch, cluster standby group, and standby command switch
- messages, to users through banners [17](#)
- metrics, in BGP [49](#)
- metric translations, between routing protocols [93](#)
- metro tags [2](#)
- MHSRP [4](#)
- MIBs
 - accessing files with FTP [3](#)
 - location of files [3](#)
 - overview [1](#)
 - SNMP interaction with [4](#)
 - supported [1](#)
- mirroring traffic for analysis [1](#)
- mismatches, autonegotiation [11](#)
- module number [11](#)
- monitoring
 - access groups [40](#)
 - BGP [60](#)
 - cables for unidirectional links [1](#)
 - CDP [4](#)
 - CEF [87](#)
 - EIGRP [40](#)
 - fallback bridging [10](#)
 - features [13](#)
 - Flex Links [14](#)
 - HSRP [13](#)
 - IEEE 802.1Q tunneling [17](#)
 - IGMP
 - filters [28](#)
 - snooping [15, 11](#)
 - interfaces [29](#)
 - IP
 - address tables [17](#)
 - multicast routing [60](#)
 - routes [100](#)
 - IP SLAs operations [13](#)
 - IPv4 ACL configuration [40](#)

- IPv6 [26](#)
- IPv6 ACL configuration [9](#)
- IS-IS [71](#)
- ISO CLNS [71](#)
- Layer 2 protocol tunneling [17](#)
- MAC address-table move update [14](#)
- MSDP peers [18](#)
- multicast router interfaces [16, 11](#)
- multi-VRF CE [86](#)
- MVR [23](#)
- network traffic for analysis with probe [2](#)
- object tracking [12](#)
- OSPF [32](#)
- port
 - blocking [19](#)
 - protection [19](#)
- private VLANs [14](#)
- RP mapping information [33](#)
- SFP status [30, 13](#)
- source-active messages [18](#)
- speed and duplex mode [19](#)
- SSM mapping [21](#)
- traffic flowing among switches [1](#)
- traffic suppression [19](#)
- tunneling [17](#)
- VLAN
 - filters [41](#)
 - maps [41](#)
- VLANs [16](#)
- VMPS [32](#)
- VTP [16](#)
- mrouter Port [3](#)
- mrouter port [5](#)
- MSDP
 - benefits of [3](#)
 - clearing MSDP connections and statistics [18](#)
 - controlling source information
 - forwarded by switch [11](#)
 - originated by switch [8](#)
 - received by switch [13](#)
 - default configuration [4](#)
 - dense-mode regions
 - sending SA messages to [16](#)
 - specifying the originating address [17](#)
 - filtering
 - incoming SA messages [14](#)
 - SA messages to a peer [12](#)
 - SA requests from a peer [10](#)
 - join latency, defined [6](#)
 - meshed groups
 - configuring [15](#)
 - defined [15](#)
 - originating address, changing [17](#)
 - overview [1](#)
 - peer-RPF flooding [2](#)
 - peers
 - configuring a default [4](#)
 - monitoring [18](#)
 - peering relationship, overview [1](#)
 - requesting source information from [8](#)
 - shutting down [15](#)
 - source-active messages
 - caching [6](#)
 - clearing cache entries [18](#)
 - defined [2](#)
 - filtering from a peer [10](#)
 - filtering incoming [14](#)
 - filtering to a peer [12](#)
 - limiting data with TTL [13](#)
 - monitoring [18](#)
 - restricting advertised sources [9](#)
 - support for [12](#)
- MSTP
 - boundary ports
 - configuration guidelines [15](#)
 - described [6](#)
 - BPDU filtering

- described [3](#)
- enabling [12](#)
- BPDU guard
 - described [2](#)
 - enabling [11](#)
- CIST, described [3](#)
- CIST regional root [3](#)
- CIST root [5](#)
- configuration guidelines [15, 10](#)
- configuring
 - forward-delay time [23](#)
 - hello time [22](#)
 - link type for rapid convergence [24](#)
 - maximum aging time [23](#)
 - maximum hop count [24](#)
 - MST region [16](#)
 - neighbor type [25](#)
 - path cost [20](#)
 - port priority [19](#)
 - root switch [17](#)
 - secondary root switch [18](#)
 - switch priority [21](#)
- CST
 - defined [3](#)
 - operations between regions [3](#)
- default configuration [14](#)
- default optional feature configuration [9](#)
- displaying status [26](#)
- enabling the mode [16](#)
- EtherChannel guard
 - described [7](#)
 - enabling [14](#)
- extended system ID
 - effects on root switch [17](#)
 - effects on secondary root switch [18](#)
 - unexpected behavior [17](#)
- IEEE 802.1s
 - implementation [6](#)
 - port role naming change [6](#)
- terminology [5](#)
- instances supported [9](#)
- interface state, blocking to forwarding [2](#)
- interoperability and compatibility among modes [10](#)
- interoperability with IEEE 802.1D
 - described [8](#)
 - restarting migration process [25](#)
- IST
 - defined [2](#)
 - master [3](#)
 - operations within a region [3](#)
- loop guard
 - described [9](#)
 - enabling [15](#)
- mapping VLANs to MST instance [16](#)
- MST region
 - CIST [3](#)
 - configuring [16](#)
 - described [2](#)
 - hop-count mechanism [5](#)
 - IST [2](#)
 - supported spanning-tree instances [2](#)
- optional features supported [7](#)
- overview [2](#)
- Port Fast
 - described [2](#)
 - enabling [10](#)
- preventing root switch selection [8](#)
- root guard
 - described [8](#)
 - enabling [15](#)
- root switch
 - configuring [17](#)
 - effects of extended system ID [17](#)
 - unexpected behavior [17](#)
- shutdown Port Fast-enabled port [2](#)
- status, displaying [26](#)
- multiauth mode
 - See multiple-authentication mode

- multicast groups
 - Immediate Leave [5](#)
 - joining [3](#)
 - leaving [5](#)
 - static joins [10, 7](#)
- multicast packets
 - ACLs on [40](#)
 - blocking [8](#)
- multicast router interfaces, monitoring [16, 11](#)
- multicast router ports, adding [9, 8](#)
- Multicast Source Discovery Protocol
 - See MSDP
- multicast storm [1](#)
- multicast storm-control command [4](#)
- multicast television application [17](#)
- multicast VLAN [17](#)
- Multicast VLAN Registration
 - See MVR
- multidomain authentication
 - See MDA
- multioperations scheduling, IP SLAs [5](#)
- multiple authentication [12](#)
- multiple authentication mode
 - configuring [40](#)
- Multiple HSRP
 - See MHSRP
- multiple VPN routing/forwarding in customer edge devices
 - See multi-VRF CE
- multi-VRF CE
 - configuration example [82](#)
 - configuration guidelines [74](#)
 - configuring [74](#)
 - default configuration [74](#)
 - defined [72](#)
 - displaying [86](#)
 - monitoring [86](#)
 - network components [74](#)

- packet-forwarding process [73](#)
- support for [12](#)

MVR

- and address aliasing [20](#)
- and IGMPv3 [20](#)
- configuration guidelines [19](#)
- configuring interfaces [21](#)
- default configuration [19](#)
- described [17](#)
- example application [17](#)
- modes [20](#)
- monitoring [23](#)
- multicast television application [17](#)
- setting global parameters [20](#)
- support for [4](#)

N

NAC

- AAA down policy [10](#)
- critical authentication [19, 49](#)
- IEEE 802.1x authentication using a RADIUS server [54](#)
- IEEE 802.1x validation using RADIUS server [54](#)
- inaccessible authentication bypass [10, 49](#)
- Layer 2 IEEE 802.1x validation [10, 24, 54](#)
- Layer 2 IP validation [10](#)

named IPv4 ACLs [14](#)

NameSpace Mapper

- See NSM

native VLAN

- and IEEE 802.1Q tunneling [4](#)
- configuring [23](#)
- default [23](#)

NEAT

- configuring [55](#)
- overview [25](#)

neighbor discovery, IPv6 [4](#)

neighbor discovery/recovery, EIGRP [33](#)

- neighbors, BGP [55](#)
- Network Admission Control
 - NAC
- Network Admission Control Software Configuration Guide [62, 63](#)
- Network Assistant
 - benefits [2](#)
 - described [4](#)
 - downloading image files [2](#)
 - guide mode [2](#)
 - management options [2](#)
 - upgrading a switch [23](#)
 - wizards [2](#)
- network configuration examples
 - increasing network performance [17](#)
 - large network [21](#)
 - long-distance, high-bandwidth transport [23](#)
 - providing network services [17](#)
 - server aggregation and Linux server cluster [19](#)
 - small to medium-sized network [20](#)
- network design
 - performance [17](#)
 - services [17](#)
- Network Edge Access Toplogy
 - See NEAT
- network management
 - CDP [1](#)
 - RMON [1](#)
 - SNMP [1](#)
- network performance, measuring with IP SLAs [3](#)
- network policy TLV [2, 7](#)
- Network Time Protocol
 - See NTP
- no commands [4](#)
- nonhierarchical policy maps
 - configuration guidelines [33](#)
 - described [9](#)
- non-IP traffic filtering [27](#)
- nontrunking mode [18](#)
- normal-range VLANs [4](#)
 - configuration guidelines [6](#)
 - configuration modes [7](#)
 - configuring [4](#)
 - defined [1](#)
- no switchport command [4](#)
- not-so-stubby areas
 - See NSSA
- NSAPs, as ISO IGRP addresses [62](#)
- NSF Awareness
 - IS-IS [64](#)
- NSM [3](#)
- NSSA, OSPF [28](#)
- NTP
 - associations
 - authenticating [4](#)
 - defined [2](#)
 - enabling broadcast messages [6](#)
 - peer [5](#)
 - server [5](#)
 - default configuration [4](#)
 - displaying the configuration [11](#)
 - overview [2](#)
 - restricting access
 - creating an access group [8](#)
 - disabling NTP services per interface [10](#)
 - source IP address, configuring [10](#)
 - stratum [2](#)
 - support for [5](#)
 - synchronizing devices [5](#)
 - time
 - services [2](#)
 - synchronizing [2](#)

O

- object tracking
 - HSRP [7](#)
 - IP SLAs [9](#)

- IP SLAs, configuring [9](#)
 - monitoring [12](#)
 - online diagnostics
 - overview [1](#)
 - running tests [3](#)
 - understanding [1](#)
 - open1x
 - configuring [60](#)
 - open1x authentication
 - overview [25](#)
 - Open Shortest Path First
 - See OSPF
 - optimizing system resources [1](#)
 - options, management [4](#)
 - OSPF
 - area parameters, configuring [28](#)
 - configuring [26](#)
 - default configuration
 - metrics [30](#)
 - route [30](#)
 - settings [25](#)
 - described [24](#)
 - for IPv6 [6](#)
 - interface parameters, configuring [27](#)
 - LSA group pacing [31](#)
 - monitoring [32](#)
 - router IDs [32](#)
 - route summarization [29](#)
 - support for [12](#)
 - virtual links [30](#)
 - out-of-profile markdown [11](#)
-
- P**
- packet modification, with QoS [19](#)
 - PAgP
 - Layer 2 protocol tunneling [9](#)
 - See EtherChannel
 - parallel paths, in routing tables [88](#)
 - passive interfaces
 - configuring [97](#)
 - OSPF [30](#)
 - passwords
 - default configuration [2](#)
 - disabling recovery of [5](#)
 - encrypting [3](#)
 - for security [8](#)
 - in clusters [13](#)
 - overview [1](#)
 - recovery of [3](#)
 - setting
 - enable [3](#)
 - enable secret [3](#)
 - Telnet [6](#)
 - with usernames [6](#)
 - VTP domain [8](#)
 - path cost
 - MSTP [20](#)
 - STP [18](#)
 - path MTU discovery [4](#)
 - PBR
 - defined [94](#)
 - enabling [95](#)
 - fast-switched policy-based routing [97](#)
 - local policy-based routing [97](#)
 - PC (passive command switch) [10](#)
 - peers, BGP [55](#)
 - percentage thresholds in tracked lists [6](#)
 - performance, network design [17](#)
 - performance features [3](#)
 - persistent self-signed certificate [43](#)
 - per-user ACLs and Filter-Ids [8](#)
 - per-VLAN spanning-tree plus
 - See PVST+
 - PE to CE routing, configuring [81](#)
 - physical ports [2](#)
 - PIM
 - default configuration [10](#)

- dense mode
 - overview [4](#)
 - rendezvous point (RP), described [5](#)
 - RPF lookups [8](#)
- displaying neighbors [61](#)
- enabling a mode [13](#)
- overview [4](#)
- router-query message interval, modifying [36](#)
- shared tree and source tree, overview [34](#)
- shortest path tree, delaying the use of [35](#)
- sparse mode
 - join messages and shared tree [5](#)
 - overview [5](#)
 - prune messages [5](#)
 - RPF lookups [8](#)
- stub routing
 - configuration guidelines [22](#)
 - displaying [61](#)
 - enabling [22](#)
 - overview [5](#)
- support for [12](#)
- versions
 - interoperability [10](#)
 - troubleshooting interoperability problems [34](#)
 - v2 improvements [4](#)
- PIM-DVMRP, as snooping method [8](#)
- ping
 - character output description [14](#)
 - executing [14](#)
 - overview [13](#)
- PoE
 - auto mode [8](#)
 - CDP with power consumption, described [7](#)
 - CDP with power negotiation, described [7](#)
 - Cisco intelligent power management [7](#)
 - configuring [22](#)
 - devices supported [7](#)
 - high-power devices operating in low-power mode [7](#)
 - IEEE power classification levels [8](#)
 - power budgeting [23](#)
 - power consumption [23](#)
 - powered-device detection and initial power allocation [7](#)
 - power management modes [8](#)
 - power negotiation extensions to CDP [7](#)
 - standards supported [7](#)
 - static mode [9](#)
 - troubleshooting [12](#)
- policed-DSCP map for QoS [63](#)
- policers
 - configuring
 - for each matched traffic class [48](#)
 - for more than one traffic class [58](#)
 - described [4](#)
 - displaying [78](#)
 - number of [34](#)
 - types of [9](#)
- policing
 - described [4](#)
 - hierarchical
 - See hierarchical policy maps
 - token-bucket algorithm [9](#)
- policy-based routing
 - See PBR
- policy maps for QoS
 - characteristics of [48](#)
 - described [7](#)
 - displaying [78](#)
 - hierarchical [8](#)
 - hierarchical on SVIs
 - configuration guidelines [33](#)
 - configuring [52](#)
 - described [11](#)
 - nonhierarchical on physical ports
 - configuration guidelines [33](#)
 - described [9](#)

- port ACLs
 - defined [2](#)
 - types of [3](#)
- Port Aggregation Protocol
 - See EtherChannel
- port-based authentication
 - accounting [12](#)
 - authentication server
 - defined [3](#)
 - RADIUS server [3](#)
 - client, defined [2](#)
 - configuration guidelines [31](#)
 - configuring
 - 802.1x authentication [37](#)
 - guest VLAN [46](#)
 - host mode [40](#)
 - inaccessible authentication bypass [49](#)
 - manual re-authentication of a client [42](#)
 - periodic re-authentication [41](#)
 - quiet period [42](#)
 - RADIUS server [39](#)
 - RADIUS server parameters on the switch [38](#)
 - restricted VLAN [47](#)
 - switch-to-client frame-retransmission number [44](#)
 - switch-to-client retransmission time [43](#)
 - violation modes [36](#)
 - default configuration [30](#)
 - described [1](#)
 - device roles [2](#)
 - displaying statistics [65](#)
 - downloadable ACLs and redirect URLs
 - configuring [57 to 59](#)
 - overview [16 to 17](#)
 - EAPOL-start frame [5](#)
 - EAP-request/identity frame [5](#)
 - EAP-response/identity frame [5](#)
 - encapsulation [3](#)
 - flexible authentication ordering
 - configuring [59](#)
 - overview [24](#)
 - guest VLAN
 - configuration guidelines [18, 19](#)
 - described [17](#)
 - host mode [10](#)
 - inaccessible authentication bypass
 - configuring [49](#)
 - described [19](#)
 - guidelines [32](#)
 - initiation and message exchange [5](#)
 - magic packet [22](#)
 - maximum number of allowed devices per port [33](#)
 - method lists [37](#)
 - multiple authentication [12](#)
 - per-user ACLs
 - AAA authorization [37](#)
 - configuration tasks [16](#)
 - described [15](#)
 - RADIUS server attributes [15](#)
 - ports
 - authorization state and dot1x port-control command [9](#)
 - authorized and unauthorized [9](#)
 - critical [19](#)
 - voice VLAN [21](#)
 - port security
 - and voice VLAN [22](#)
 - described [21](#)
 - interactions [21](#)
 - multiple-hosts mode [10](#)
 - readiness check
 - configuring [34](#)
 - described [14, 34](#)
 - resetting to default values [65](#)
 - statistics, displaying [65](#)
 - switch
 - as proxy [3](#)
 - RADIUS client [3](#)

- switch supplicant
 - configuring [55](#)
 - overview [25](#)
- upgrading from a previous release [26](#)
- VLAN assignment
 - AAA authorization [37](#)
 - characteristics [14](#)
 - configuration tasks [15](#)
 - described [14](#)
- voice aware 802.1x security
 - configuring [35](#)
 - described [25, 35](#)
- voice VLAN
 - described [21](#)
 - PVID [21](#)
 - VVID [21](#)
- wake-on-LAN, described [22](#)
- port-based authentication methods, supported [7](#)
- port blocking [4, 7](#)
- port-channel
 - See EtherChannel
- port description TLV [2](#)
- Port Fast
 - described [2](#)
 - enabling [10](#)
 - mode, spanning tree [29](#)
 - support for [7](#)
- port membership modes, VLAN [3](#)
- port priority
 - MSTP [19](#)
 - STP [17](#)
- ports
 - access [3](#)
 - blocking [7](#)
 - dual-purpose uplink [6](#)
 - dynamic access [3](#)
 - IEEE 802.1Q tunnel [4](#)
 - protected [6](#)
 - routed [4](#)
 - secure [8](#)
 - static-access [3, 11](#)
 - switch [2](#)
 - trunks [3, 16](#)
 - VLAN assignments [11](#)
- port security
 - aging [17](#)
 - and private VLANs [18](#)
 - and QoS trusted boundary [38](#)
 - configuring [13](#)
 - default configuration [11](#)
 - described [8](#)
 - displaying [19](#)
 - enabling [18](#)
 - on trunk ports [14](#)
 - sticky learning [9](#)
 - violations [10](#)
 - with other features [11](#)
- port-shutdown response, VMPS [28](#)
- port VLAN ID TLV [2](#)
- power management TLV [2, 7](#)
- Power over Ethernet
 - See PoE
- preemption, default configuration [8](#)
- preemption delay, default configuration [8](#)
- preferential treatment of traffic
 - See QoS
- prefix lists, BGP [53](#)
- preventing unauthorized access [1](#)
- primary interface for object tracking, DHCP, configuring [11](#)
- primary interface for static routing, configuring [10](#)
- primary links [2](#)
- primary VLANs [1, 3](#)
- priority
 - HSRP [8](#)
 - overriding CoS [6](#)
 - trusting CoS [6](#)

private VLAN edge ports

See protected ports

private VLANs

across multiple switches 4

and SDM template 4

and SVIs 5

benefits of 1

community ports 2

community VLANs 2,3

configuration guidelines 6,8

configuration tasks 6

configuring 9

default configuration 6

end station access to 3

IP addressing 3

isolated port 2

isolated VLANs 2,3

mapping 13

monitoring 14

ports

community 2

configuration guidelines 8

configuring host ports 11

configuring promiscuous ports 12

described 4

isolated 2

promiscuous 2

primary VLANs 1,3

promiscuous ports 2

secondary VLANs 2

subdomains 1

traffic in 5

privileged EXEC mode 2

privilege levels

changing the default for lines 9

command switch 15

exiting 9

logging into 9

mapping on member switches 15

overview 2,7

setting a command with 8

promiscuous ports

configuring 12

defined 2

protected ports 8,6

protocol-dependent modules, EIGRP 34

Protocol-Independent Multicast Protocol

See PIM

provider edge devices 72

proxy ARP

configuring 10

definition 8

with IP routing disabled 11

proxy reports 3

pruning, VTP

disabling

in VTP domain 14

on a port 23

enabling

in VTP domain 14

on a port 23

examples 5

overview 4

pruning-eligible list

changing 23

for VTP pruning 4

VLANs 14

PVST+

described 9

IEEE 802.1Q trunking interoperability 10

instances supported 9

Q

QoS

and MQC commands 1

auto-QoS

categorizing traffic 20

- configuration and defaults display [29](#)
- configuration guidelines [25](#)
- described [20](#)
- disabling [27](#)
- displaying generated commands [27](#)
- displaying the initial configuration [29](#)
- effects on running configuration [25](#)
- egress queue defaults [21](#)
- enabling for VoIP [27](#)
- example configuration [28](#)
- ingress queue defaults [21](#)
- list of generated commands [22](#)
- basic model [4](#)
- classification
 - class maps, described [7](#)
 - defined [4](#)
 - DSCP transparency, described [40](#)
 - flowchart [6](#)
 - forwarding treatment [3](#)
 - in frames and packets [3](#)
 - IP ACLs, described [5,7](#)
 - MAC ACLs, described [5,7](#)
 - options for IP traffic [5](#)
 - options for non-IP traffic [5](#)
 - policy maps, described [7](#)
 - trust DSCP, described [5](#)
 - trusted CoS, described [5](#)
 - trust IP precedence, described [5](#)
- class maps
 - configuring [46](#)
 - displaying [78](#)
- configuration guidelines
 - auto-QoS [25](#)
 - standard QoS [33](#)
- configuring
 - aggregate policers [58](#)
 - auto-QoS [20](#)
 - default port CoS value [38](#)
 - DSCP maps [60](#)
 - DSCP transparency [40](#)
 - DSCP trust states bordering another domain [40](#)
 - egress queue characteristics [70](#)
 - ingress queue characteristics [66](#)
 - IP extended ACLs [44](#)
 - IP standard ACLs [43](#)
 - MAC ACLs [45](#)
 - policy maps, hierarchical [52](#)
 - port trust states within the domain [36](#)
 - trusted boundary [38](#)
- default auto configuration [20](#)
- default standard configuration [30](#)
- displaying statistics [78](#)
- DSCP transparency [40](#)
- egress queues
 - allocating buffer space [71](#)
 - buffer allocation scheme, described [17](#)
 - configuring shaped weights for SRR [74](#)
 - configuring shared weights for SRR [75](#)
 - described [4](#)
 - displaying the threshold map [74](#)
 - flowchart [17](#)
 - mapping DSCP or CoS values [73](#)
 - scheduling, described [4](#)
 - setting WTD thresholds [71](#)
 - WTD, described [18](#)
- enabling globally [35](#)
- flowcharts
 - classification [6](#)
 - egress queueing and scheduling [17](#)
 - ingress queueing and scheduling [15](#)
 - policing and marking [10](#)
- implicit deny [7](#)
- ingress queues
 - allocating bandwidth [68](#)
 - allocating buffer space [68](#)
 - buffer and bandwidth allocation, described [16](#)
 - configuring shared weights for SRR [68](#)
 - configuring the priority queue [69](#)

- described 4
 - displaying the threshold map 67
 - flowchart 15
 - mapping DSCP or CoS values 67
 - priority queue, described 16
 - scheduling, described 4
 - setting WTD thresholds 67
 - WTD, described 16
 - IP phones
 - automatic classification and queueing 20
 - detection and trusted settings 20, 38
 - limiting bandwidth on egress interface 77
 - mapping tables
 - CoS-to-DSCP 60
 - displaying 78
 - DSCP-to-CoS 64
 - DSCP-to-DSCP-mutation 65
 - IP-precedence-to-DSCP 62
 - policed-DSCP 63
 - types of 12
 - marked-down actions 50, 55
 - marking, described 4, 8
 - overview 2
 - packet modification 19
 - policers
 - configuring 50, 55, 58
 - described 8
 - displaying 78
 - number of 34
 - types of 9
 - policies, attaching to an interface 8
 - policing
 - described 4, 8
 - token bucket algorithm 9
 - policy maps
 - characteristics of 48
 - displaying 78
 - hierarchical 8
 - hierarchical on SVIs 52
 - nonhierarchical on physical ports 48
 - QoS label, defined 4
 - queues
 - configuring egress characteristics 70
 - configuring ingress characteristics 66
 - high priority (expedite) 19, 76
 - location of 13
 - SRR, described 14
 - WTD, described 13
 - rewrites 19
 - support for 11
 - trust states
 - bordering another domain 40
 - described 5
 - trusted device 38
 - within the domain 36
 - quality of service
 - See QoS
 - queries, IGMP 4
 - query solicitation, IGMP 13
-
- ## R
- ### RADIUS
- attributes
 - vendor-proprietary 31
 - vendor-specific 29
 - configuring
 - accounting 28
 - authentication 23
 - authorization 27
 - communication, global 21, 29
 - communication, per-server 20, 21
 - multiple UDP ports 20
 - default configuration 20
 - defining AAA server groups 25
 - displaying the configuration 32
 - identifying the server 20
 - in clusters 14

- limiting the services to the user [27](#)
- method list, defined [19](#)
- operation of [19](#)
- overview [18](#)
- server load balancing [31](#)
- suggested network environments [18](#)
- support for [10](#)
- tracking services accessed by user [28](#)
- range
 - macro [13](#)
 - of interfaces [12](#)
- rapid convergence [10](#)
- rapid per-VLAN spanning-tree plus
 - See rapid PVST+
- rapid PVST+
 - described [9](#)
 - IEEE 802.1Q trunking interoperability [10](#)
 - instances supported [9](#)
- Rapid Spanning Tree Protocol
 - See RSTP
- RARP [8](#)
- rcommand command [15](#)
- RCP
 - configuration files
 - downloading [17](#)
 - overview [15](#)
 - preparing the server [16](#)
 - uploading [18](#)
 - image files
 - deleting old image [36](#)
 - downloading [34](#)
 - preparing the server [33](#)
 - uploading [36](#)
- reachability, tracking IP SLAs IP host [9](#)
- readiness check
 - port-based authentication
 - configuring [34](#)
 - described [14, 34](#)
- reconfirmation interval, VMPS, changing [31](#)
- reconfirming dynamic VLAN membership [31](#)
- recovery procedures [1](#)
- redirect URL [16, 17, 57](#)
- redundancy
 - EtherChannel [3](#)
 - HSRP [1](#)
 - STP
 - backbone [8](#)
 - path cost [26](#)
 - port priority [24](#)
- redundant links and UplinkFast [13](#)
- reliable transport protocol, EIGRP [33](#)
- reloading software [20](#)
- Remote Authentication Dial-In User Service
 - See RADIUS
- Remote Copy Protocol
 - See RCP
- Remote Network Monitoring
 - See RMON
- Remote SPAN
 - See RSPAN
- remote SPAN [2](#)
- report suppression, IGMP
 - described [6](#)
 - disabling [15, 11](#)
- resequencing ACL entries [14](#)
- resets, in BGP [47](#)
- resetting a UDLD-shutdown interface [6](#)
- responder, IP SLAs
 - described [4](#)
 - enabling [8](#)
- response time, measuring with IP SLAs [4](#)
- restricted VLAN
 - configuring [47](#)
 - described [18](#)
 - using with IEEE 802.1x [18](#)
- restricting access
 - NTP services [8](#)
 - overview [1](#)

- passwords and privilege levels [2](#)
- RADIUS [17](#)
- TACACS+ [10](#)
- retry count, VMPS, changing [32](#)
- reverse address resolution [8](#)
- Reverse Address Resolution Protocol
 - See RARP
- RFC
 - 1058, RIP [18](#)
 - 1112, IP multicast and IGMP [2](#)
 - 1157, SNMPv1 [2](#)
 - 1163, BGP [40](#)
 - 1166, IP addresses [5](#)
 - 1253, OSPF [24](#)
 - 1267, BGP [40](#)
 - 1305, NTP [2](#)
 - 1587, NSSAs [24](#)
 - 1757, RMON [2](#)
 - 1771, BGP [40](#)
 - 1901, SNMPv2C [2](#)
 - 1902 to 1907, SNMPv2 [2](#)
 - 2236, IP multicast and IGMP [2](#)
 - 2273-2275, SNMPv3 [2](#)
- RIP
 - advertisements [19](#)
 - authentication [21](#)
 - configuring [20](#)
 - default configuration [19](#)
 - described [19](#)
 - for IPv6 [6](#)
 - hop counts [19](#)
 - split horizon [22](#)
 - summary addresses [22](#)
 - support for [12](#)
- RMON
 - default configuration [3](#)
 - displaying status [6](#)
 - enabling alarms and events [3](#)
 - groups supported [2](#)
 - overview [1](#)
 - statistics
 - collecting group Ethernet [5](#)
 - collecting group history [5](#)
 - support for [13](#)
- root guard
 - described [8](#)
 - enabling [15](#)
 - support for [7](#)
- root switch
 - MSTP [17](#)
 - STP [14](#)
- route calculation timers, OSPF [30](#)
- route dampening, BGP [59](#)
- routed packets, ACLs on [39](#)
- routed ports
 - configuring [3](#)
 - defined [4](#)
 - in switch clusters [8](#)
 - IP addresses on [26, 4](#)
- route-map command [96](#)
- route maps
 - BGP [51](#)
 - policy-based routing [94](#)
- router ACLs
 - defined [2](#)
 - types of [4](#)
- route reflectors, BGP [58](#)
- router ID, OSPF [32](#)
- route selection, BGP [49](#)
- route summarization, OSPF [29](#)
- route targets, VPN [74](#)
- routing
 - default [2](#)
 - dynamic [3](#)
 - redistribution of information [90](#)
 - static [3](#)
- routing domain confederation, BGP [58](#)

- Routing Information Protocol
 - See RIP
 - routing protocol administrative distances [89](#)
 - RSPAN
 - characteristics [8](#)
 - configuration guidelines [16](#)
 - default configuration [9](#)
 - defined [2](#)
 - destination ports [7](#)
 - displaying status [23](#)
 - interaction with other features [8](#)
 - monitored ports [5](#)
 - monitoring ports [7](#)
 - overview [13, 1](#)
 - received traffic [4](#)
 - sessions
 - creating [17](#)
 - defined [3](#)
 - limiting source traffic to specific VLANs [22](#)
 - specifying monitored ports [17](#)
 - with ingress traffic enabled [20](#)
 - source ports [5](#)
 - transmitted traffic [5](#)
 - VLAN-based [6](#)
 - RSTP
 - active topology [9](#)
 - BPDU
 - format [12](#)
 - processing [13](#)
 - designated port, defined [9](#)
 - designated switch, defined [9](#)
 - interoperability with IEEE 802.1D
 - described [8](#)
 - restarting migration process [25](#)
 - topology changes [13](#)
 - overview [8](#)
 - port roles
 - described [9](#)
 - synchronized [11](#)
 - proposal-agreement handshake process [10](#)
 - rapid convergence
 - described [10](#)
 - edge ports and Port Fast [10](#)
 - point-to-point links [10, 24](#)
 - root ports [10](#)
 - root port, defined [9](#)
 - See also MSTP
 - running configuration
 - replacing [19, 20](#)
 - rolling back [19, 20](#)
 - running configuration, saving [15](#)
-
- ## S
- SC (standby command switch) [10](#)
 - scheduled reloads [20](#)
 - scheduling, IP SLAs operations [5](#)
 - SCP
 - and SSH [49](#)
 - configuring [49](#)
 - SDM
 - described [1](#)
 - templates
 - configuring [4](#)
 - number of [1](#)
 - SDM template [3](#)
 - configuration guidelines [3](#)
 - configuring [3](#)
 - dual IPv4 and IPv6 [2](#)
 - types of [1](#)
 - secondary VLANs [2](#)
 - Secure Copy Protocol
 - secure HTTP client
 - configuring [47](#)
 - displaying [48](#)
 - secure HTTP server
 - configuring [46](#)
 - displaying [48](#)

- secure MAC addresses
 - deleting [16](#)
 - maximum number of [10](#)
 - types of [9](#)
- secure ports, configuring [8](#)
- secure remote connections [38](#)
- Secure Shell
 - See SSH
- Secure Socket Layer
 - See SSL
- security, port [8](#)
- security features [8](#)
- See SCP
- sequence numbers in log messages [8](#)
- server mode, VTP [3](#)
- service-provider network, MSTP and RSTP [1](#)
- service-provider networks
 - and customer VLANs [2](#)
 - and IEEE 802.1Q tunneling [1](#)
 - Layer 2 protocols across [8](#)
 - Layer 2 protocol tunneling for EtherChannels [9](#)
- set-request operation [4](#)
- setup program
 - failed command switch replacement [10](#)
 - replacing failed command switch [8](#)
- severity levels, defining in system messages [8](#)
- SFPs
 - monitoring status of [30, 13](#)
 - security and identification [12](#)
 - status, displaying [13](#)
- shaped round robin
 - See SRR
- Shell functions
 - See Auto Smartports macros
- Shell triggers
 - See Auto Smartports macros
- show access-lists hw-summary command [21](#)
- show and more command output, filtering [10](#)
- show cdp traffic command [5](#)
- show cluster members command [15](#)
- show configuration command [24](#)
- show forward command [20](#)
- show interfaces command [19, 24](#)
- show interfaces switchport [4](#)
- show l2protocol command [13, 15, 16](#)
- show lldp traffic command [11](#)
- show platform forward command [20](#)
- show running-config command
 - displaying ACLs [19, 20, 31, 34](#)
 - interface description in [24](#)
- shutdown command on interfaces [31](#)
- shutdown threshold for Layer 2 protocol packets [11](#)
- Simple Network Management Protocol
 - See SNMP
- small-frame arrival rate, configuring [5](#)
- Smartports macros
 - applying Cisco-default macros [12](#)
 - applying global parameter values [13](#)
 - configuration guidelines [12](#)
 - default configuration [11](#)
 - defined [1](#)
 - displaying [14](#)
 - tracing [12](#)
- SNAP [1](#)
- SNMP
 - accessing MIB variables with [4](#)
 - agent
 - described [3](#)
 - disabling [7](#)
 - and IP SLAs [2](#)
 - authentication level [10](#)
 - community strings
 - configuring [8](#)
 - for cluster switches [4](#)
 - overview [4](#)
 - configuration examples [17](#)
 - default configuration [6](#)
 - engine ID [7](#)

- groups [6,9](#)
 - host [6](#)
 - ifIndex values [5](#)
 - in-band management [6](#)
 - in clusters [14](#)
 - informs
 - and trap keyword [11](#)
 - described [5](#)
 - differences from traps [5](#)
 - disabling [15](#)
 - enabling [15](#)
 - limiting access by TFTP servers [16](#)
 - limiting system log messages to NMS [10](#)
 - manager functions [5,3](#)
 - managing clusters with [15](#)
 - MIBs
 - location of [3](#)
 - supported [1](#)
 - notifications [5](#)
 - overview [1,4](#)
 - security levels [3](#)
 - setting CPU threshold notification [15](#)
 - status, displaying [18](#)
 - system contact and location [16](#)
 - trap manager, configuring [13](#)
 - traps
 - described [3,5](#)
 - differences from informs [5](#)
 - disabling [15](#)
 - enabling [11](#)
 - enabling MAC address notification [22](#)
 - overview [1,4](#)
 - types of [11](#)
 - users [6,9](#)
 - versions supported [2](#)
- SNMP and Syslog Over IPv6 [7](#)
- SNMPv1 [2](#)
- SNMPv2C [2](#)
- SNMPv3 [2](#)
- snooping, IGMP [2](#)
- software images
 - location in flash [24](#)
 - recovery procedures [2](#)
 - scheduling reloads [20](#)
 - tar file format, described [24](#)
 - See also downloading and uploading
- source addresses
 - in IPv4 ACLs [11](#)
 - in IPv6 ACLs [5,6](#)
- source-and-destination-IP address based forwarding, EtherChannel [7](#)
- source-and-destination MAC address forwarding, EtherChannel [7](#)
- source-IP address based forwarding, EtherChannel [7](#)
- source-MAC address forwarding, EtherChannel [7](#)
- Source-specific multicast
 - See SSM
- SPAN
 - configuration guidelines [10](#)
 - default configuration [9](#)
 - destination ports [7](#)
 - displaying status [23](#)
 - interaction with other features [8](#)
 - monitored ports [5](#)
 - monitoring ports [7](#)
 - overview [13,1](#)
 - ports, restrictions [12](#)
 - received traffic [4](#)
 - sessions
 - configuring ingress forwarding [14,21](#)
 - creating [11](#)
 - defined [3](#)
 - limiting source traffic to specific VLANs [15](#)
 - removing destination (monitoring) ports [12](#)
 - specifying monitored ports [11](#)
 - with ingress traffic enabled [13](#)
 - source ports [5](#)
 - transmitted traffic [5](#)

- VLAN-based 6
- spanning tree and native VLANs 19
- Spanning Tree Protocol
 - See STP
- SPAN traffic 4
- split horizon, RIP 22
- SRR
 - configuring
 - shaped weights on egress queues 74
 - shared weights on egress queues 75
 - shared weights on ingress queues 68
 - described 14
 - shaped mode 14
 - shared mode 14
 - support for 11
- SSH
 - configuring 39
 - cryptographic software image 37
 - described 6, 38
 - encryption methods 38
 - user authentication methods, supported 38
- SSL
 - configuration guidelines 45
 - configuring a secure HTTP client 47
 - configuring a secure HTTP server 46
 - cryptographic software image 42
 - described 42
 - monitoring 48
- SSM
 - address management restrictions 15
 - CGMP limitations 15
 - components 13
 - configuration guidelines 15
 - configuring 13, 16
 - differs from Internet standard multicast 14
 - IGMP snooping 15
 - IGMPv3 13
 - IGMPv3 Host Signalling 15
 - IP address range 14
 - monitoring 16
 - operations 14
 - PIM 13
 - state maintenance limitations 16
 - SSM mapping 16
 - configuration guidelines 17
 - configuring 16, 19
 - DNS-based 18, 20
 - monitoring 21
 - overview 17
 - restrictions 17
 - static 18, 19
 - static traffic forwarding 20
 - standby command switch
 - configuring
 - considerations 11
 - defined 2
 - priority 10
 - requirements 3
 - virtual IP address 11
 - See also cluster standby group and HSRP
 - standby group, cluster
 - See cluster standby group and HSRP
 - standby ip command 6
 - standby links 2
 - standby router 1
 - standby timers, HSRP 10
 - startup configuration
 - booting
 - manually 17
 - specific image 18
 - clearing 19
 - configuration file
 - automatically downloading 16
 - specifying the filename 16
 - default boot configuration 16
 - static access ports
 - assigning to VLAN 11
 - defined 3

- static addresses
 - See addresses
- static IP routing [12](#)
- static MAC addressing [8](#)
- static route primary interface, configuring [10](#)
- static routes
 - configuring [88](#)
 - configuring for IPv6 [19](#)
 - understanding [6](#)
- static routing [3](#)
- static routing support, enhanced object tracking [10](#)
- static SSM mapping [18, 19](#)
- static traffic forwarding [20](#)
- static VLAN membership [2](#)
- statistics
 - 802.1x [65](#)
 - CDP [4](#)
 - interface [29](#)
 - IP multicast routing [61](#)
 - LLDP [10](#)
 - LLDP-MED [10](#)
 - NMSP [10](#)
 - OSPF [32](#)
 - QoS ingress and egress [78](#)
 - RMON group Ethernet [5](#)
 - RMON group history [5](#)
 - SNMP input and output [18](#)
 - VTP [16](#)
- sticky learning [9](#)
- storm control
 - configuring [3](#)
 - described [1](#)
 - disabling [5](#)
 - displaying [19](#)
 - support for [3](#)
 - thresholds [1](#)
- STP
 - accelerating root port selection [4](#)
 - BackboneFast
 - described [5](#)
 - disabling [14](#)
 - enabling [13](#)
 - BPDUs filtering
 - described [3](#)
 - disabling [12](#)
 - enabling [12](#)
 - BPDUs guard
 - described [2](#)
 - disabling [12](#)
 - enabling [11](#)
 - BPDUs message exchange [3](#)
 - configuration guidelines [12, 10](#)
 - configuring
 - forward-delay time [21](#)
 - hello time [20](#)
 - maximum aging time [21](#)
 - path cost [18](#)
 - port priority [17](#)
 - root switch [14](#)
 - secondary root switch [16](#)
 - spanning-tree mode [13](#)
 - switch priority [19](#)
 - transmit hold-count [22](#)
 - counters, clearing [22](#)
 - default configuration [11](#)
 - default optional feature configuration [9](#)
 - designated port, defined [3](#)
 - designated switch, defined [3](#)
 - detecting indirect link failures [5](#)
 - disabling [14](#)
 - displaying status [22](#)
 - EtherChannel guard
 - described [7](#)
 - disabling [14](#)
 - enabling [14](#)
 - extended system ID
 - effects on root switch [14](#)
 - effects on the secondary root switch [16](#)

- overview 4
 - unexpected behavior 15
- features supported 7
- IEEE 802.1D and bridge ID 4
- IEEE 802.1D and multicast addresses 8
- IEEE 802.1t and VLAN identifier 4
- inferior BPDU 3
- instances supported 9
- interface state, blocking to forwarding 2
- interface states
 - blocking 5
 - disabled 7
 - forwarding 5, 6
 - learning 6
 - listening 6
 - overview 4
- interoperability and compatibility among modes 10
- keepalive messages 2
- Layer 2 protocol tunneling 8
- limitations with IEEE 802.1Q trunks 10
- load sharing
 - overview 24
 - using path costs 26
 - using port priorities 24
- loop guard
 - described 9
 - enabling 15
- modes supported 9
- multicast addresses, effect of 8
- optional features supported 7
- overview 2
- path costs 26
- Port Fast
 - described 2
 - enabling 10
- port priorities 25
- preventing root switch selection 8
- protocols supported 9
- redundant connectivity 8
- root guard
 - described 8
 - enabling 15
- root port, defined 3
- root switch
 - configuring 15
 - effects of extended system ID 4, 14
 - election 3
 - unexpected behavior 15
- shutdown Port Fast-enabled port 2
- status, displaying 22
- superior BPDU 3
- timers, described 20
- UplinkFast
 - described 3
 - enabling 13
- VLAN-bridge 10
- stratum, NTP 2
- stub areas, OSPF 28
- stub routing, EIGRP 39
- subdomains, private VLAN 1
- subnet mask 5
- subnet zero 6
- success response, VMPS 28
- summer time 13
- SunNet Manager 5
- supernet 6
- supported port-based authentication methods 7
- Smartports macros
 - See also Auto Smartports macros
- SVI autostate exclude
 - configuring 27
 - defined 5
- SVI link state 5
- SVIs
 - and IP unicast routing 3
 - and router ACLs 4
 - connecting VLANs 9
 - defined 4

- routing between VLANs [2](#)
 - switch [2](#)
 - switch clustering technology [1](#)
 - See also clusters, switch
 - switch console port [6](#)
 - Switch Database Management
 - See SDM
 - switched packets, ACLs on [38](#)
 - Switched Port Analyzer
 - See SPAN
 - switched ports [2](#)
 - switchport backup interface [4, 5](#)
 - switchport block multicast command [8](#)
 - switchport block unicast command [8](#)
 - switchport command [15](#)
 - switchport mode dot1q-tunnel command [6](#)
 - switchport protected command [7](#)
 - switch priority
 - MSTP [21](#)
 - STP [19](#)
 - switch software features [1](#)
 - switch virtual interface
 - See SVI
 - synchronization, BGP [45](#)
 - syslog
 - See system message logging
 - system capabilities TLV [2](#)
 - system clock
 - configuring
 - daylight saving time [13](#)
 - manually [11](#)
 - summer time [13](#)
 - time zones [12](#)
 - displaying the time and date [12](#)
 - overview [1](#)
 - See also NTP
 - system description TLV [2](#)
 - system message logging
 - default configuration [3](#)
 - defining error message severity levels [8](#)
 - disabling [4](#)
 - displaying the configuration [13](#)
 - enabling [4](#)
 - facility keywords, described [13](#)
 - level keywords, described [9](#)
 - limiting messages [10](#)
 - message format [2](#)
 - overview [1](#)
 - sequence numbers, enabling and disabling [8](#)
 - setting the display destination device [5](#)
 - synchronizing log messages [6](#)
 - syslog facility [13](#)
 - time stamps, enabling and disabling [7](#)
 - UNIX syslog servers
 - configuring the daemon [12](#)
 - configuring the logging facility [12](#)
 - facilities supported [13](#)
 - system MTU
 - and IS-IS LSPs [66](#)
 - system MTU and IEEE 802.1Q tunneling [5](#)
 - system name
 - default configuration [15](#)
 - default setting [15](#)
 - manual configuration [15](#)
 - See also DNS
 - system name TLV [2](#)
 - system prompt, default setting [14, 15](#)
 - system resources, optimizing [1](#)
 - system routing
 - IS-IS [61](#)
 - ISO IGRP [61](#)
-
- ## T
- TACACS+
 - accounting, defined [11](#)
 - authentication, defined [11](#)
 - authorization, defined [11](#)

- configuring
 - accounting 17
 - authentication key 13
 - authorization 16
 - login authentication 14
 - default configuration 13
 - displaying the configuration 17
 - identifying the server 13
 - in clusters 14
 - limiting the services to the user 16
 - operation of 12
 - overview 10
 - support for 10
 - tracking services accessed by user 17
- tagged packets
- IEEE 802.1Q 3
 - Layer 2 protocol 8
- tar files
- creating 6
 - displaying the contents of 7
 - extracting 7
 - image file format 24
- TCL script, registering and defining with embedded event manager 6
- TDR 14
- Telnet
- accessing management interfaces 10
 - number of connections 6
 - setting a password 6
- templates, SDM 1
- temporary self-signed certificate 43
- Terminal Access Controller Access Control System Plus
- See TACACS+
- terminal lines, setting a password 6
- TFTP
- configuration files
 - downloading 11
 - preparing the server 10
 - uploading 12
 - configuration files in base directory 7
 - configuring for autoconfiguration 7
 - image files
 - deleting 27
 - downloading 26
 - preparing the server 25
 - uploading 28
 - limiting access by servers 16
- TFTP server 5
- threshold, traffic level 2
- threshold monitoring, IP SLAs 6
- time
- See NTP and system clock
- Time Domain Reflector
- See TDR
- time-range command 16
- time ranges in ACLs 16
- time stamps in log messages 7
- time zones 12
- TLVs
- defined 1
 - LLDP 2
 - LLDP-MED 2
- Token Ring VLANs
- support for 6
 - VTP support 4
- ToS 11
- traceroute, Layer 2
- and ARP 16
 - and CDP 15
 - broadcast traffic 15
 - described 15
 - IP addresses and subnets 16
 - MAC addresses and VLANs 15
 - multicast traffic 15
 - multiple devices on a port 16
 - unicast traffic 15
 - usage guidelines 15
- traceroute command 17

- See also IP traceroute
- tracked lists
 - configuring [3](#)
 - types [3](#)
- tracked objects
 - by Boolean expression [4](#)
 - by threshold percentage [6](#)
 - by threshold weight [5](#)
- tracking interface line-protocol state [2](#)
- tracking IP routing state [2](#)
- tracking objects [1](#)
- tracking process [1](#)
- track state, tracking IP SLAs [9](#)
- traffic
 - blocking flooded [8](#)
 - fragmented [5](#)
 - fragmented IPv6 [2](#)
 - unfragmented [5](#)
- traffic policing [11](#)
- traffic suppression [1](#)
- transmit hold-count
 - see STP
- transparent mode, VTP [3, 12](#)
- trap-door mechanism [2](#)
- traps
 - configuring MAC address notification [22](#)
 - configuring managers [11](#)
 - defined [3](#)
 - enabling [22, 11](#)
 - notification types [11](#)
 - overview [1, 4](#)
- troubleshooting
 - connectivity problems [13, 15, 16](#)
 - CPU utilization [24](#)
 - detecting unidirectional links [1](#)
 - displaying crash information [23](#)
 - PIMv1 and PIMv2 interoperability problems [34](#)
 - setting packet forwarding [20](#)
 - SFP security and identification [12](#)
 - show forward command [20](#)
 - with CiscoWorks [4](#)
 - with debug commands [19](#)
 - with ping [13](#)
 - with system message logging [1](#)
 - with traceroute [16](#)
- trunk failover
 - See link-state tracking
- trunking encapsulation [8](#)
- trunk ports
 - configuring [20](#)
 - defined [3](#)
 - encapsulation [21, 25, 27](#)
- trunks
 - allowed-VLAN list [21](#)
 - configuring [21, 25, 27](#)
 - ISL [16](#)
 - load sharing
 - setting STP path costs [26](#)
 - using STP port priorities [24, 25](#)
 - native VLAN for untagged traffic [23](#)
 - parallel [26](#)
 - pruning-eligible list [23](#)
 - to non-DTP device [17](#)
- trusted boundary for QoS [38](#)
- trusted port states
 - between QoS domains [40](#)
 - classification options [5](#)
 - ensuring port security for IP phones [38](#)
 - support for [11](#)
 - within a QoS domain [36](#)
- trustpoints, CA [42](#)
- tunneling
 - defined [1](#)
 - IEEE 802.1Q [1](#)
 - Layer 2 protocol [8](#)
- tunnel ports
 - defined [4](#)
 - described [3, 1](#)

IEEE 802.1Q, configuring [6](#)
 incompatibilities with other features [6](#)
 twisted-pair Ethernet, detecting unidirectional links [1](#)
 type of service
 See ToS

U

UDLD

configuration guidelines [4](#)
 default configuration [4](#)
 disabling
 globally [5](#)
 on fiber-optic interfaces [5](#)
 per interface [5](#)
 echoing detection mechanism [2](#)
 enabling
 globally [5](#)
 per interface [5](#)
 Layer 2 protocol tunneling [10](#)
 link-detection mechanism [1](#)
 neighbor database [2](#)
 overview [1](#)
 resetting an interface [6](#)
 status, displaying [6](#)
 support for [7](#)
 UDP, configuring [14](#)
 UDP jitter, configuring [9](#)
 UDP jitter operation, IP SLAs [9](#)
 unauthorized ports with IEEE 802.1x [9](#)
 unicast MAC address filtering [5](#)
 and adding static addresses [25](#)
 and broadcast MAC addresses [25](#)
 and CPU packets [25](#)
 and multicast addresses [25](#)
 and router MAC addresses [25](#)
 configuration guidelines [25](#)
 described [25](#)
 unicast storm [1](#)

unicast storm control command [4](#)
 unicast traffic, blocking [8](#)
 UniDirectional Link Detection protocol
 See UDLD
 UNIX syslog servers
 daemon configuration [12](#)
 facilities supported [13](#)
 message logging configuration [12](#)
 unrecognized Type-Length-Value (TLV) support [4](#)
 upgrading software images
 See downloading
 UplinkFast
 described [3](#)
 disabling [13](#)
 enabling [13](#)
 support for [7](#)
 uploading
 configuration files
 preparing [10, 13, 16](#)
 reasons for [9](#)
 using FTP [14](#)
 using RCP [18](#)
 using TFTP [12](#)
 image files
 preparing [25, 29, 33](#)
 reasons for [23](#)
 using FTP [31](#)
 using RCP [36](#)
 using TFTP [28](#)
 User Datagram Protocol
 See UDP
 user EXEC mode [2](#)
 username-based authentication [6](#)

V

version-dependent transparent mode [4](#)
 virtual IP address
 cluster standby group [11](#)

- command switch [11](#)
- Virtual Private Network
 - See VPN
- virtual router [1,2](#)
- virtual switches and PAgP [5](#)
- vlan.dat file [5](#)
- VLAN 1, disabling on a trunk port [22](#)
- VLAN 1 minimization [22](#)
- VLAN ACLs
 - See VLAN maps
- vlan-assignment response, VMPS [28](#)
- VLAN configuration
 - at bootup [8](#)
 - saving [8](#)
- VLAN configuration mode [2,7](#)
- VLAN database
 - and startup configuration file [8](#)
 - and VTP [1](#)
 - VLAN configuration saved in [7](#)
 - VLANs saved in [4](#)
- vlan database command [7](#)
- vlan dot1q tag native command [5](#)
- VLAN filtering and SPAN [6](#)
- vlan global configuration command [7](#)
- VLAN ID, discovering [28](#)
- VLAN link state [5](#)
- VLAN load balancing on flex links [2](#)
 - configuration guidelines [8](#)
- VLAN management domain [2](#)
- VLAN Management Policy Server
 - See VMPS
- VLAN map entries, order of [30](#)
- VLAN maps
 - applying [34](#)
 - common uses for [34](#)
 - configuration guidelines [30](#)
 - configuring [29](#)
 - creating [31](#)
 - defined [2](#)
 - denying access to a server example [35](#)
 - denying and permitting packets [31](#)
 - displaying [41](#)
 - examples of ACLs and VLAN maps [32](#)
 - removing [34](#)
 - support for [9](#)
 - wiring closet configuration example [35](#)
- VLAN membership
 - confirming [31](#)
 - modes [3](#)
- VLAN Query Protocol
 - See VQP
- VLANs
 - adding [9](#)
 - adding to VLAN database [9](#)
 - aging dynamic addresses [9](#)
 - allowed on trunk [21](#)
 - and spanning-tree instances [3,6,13](#)
 - configuration guidelines, extended-range VLANs [13](#)
 - configuration guidelines, normal-range VLANs [6](#)
 - configuration options [7](#)
 - configuring [1](#)
 - configuring IDs 1006 to 4094 [13](#)
 - connecting through SVIs [9](#)
 - creating in config-vlan mode [9](#)
 - creating in VLAN configuration mode [10](#)
 - customer numbering in service-provider networks [3](#)
 - default configuration [8](#)
 - deleting [10](#)
 - described [2,1](#)
 - displaying [16](#)
 - extended-range [1,12](#)
 - features [7](#)
 - illustrated [2](#)
 - internal [13](#)
 - limiting source traffic with RSPAN [22](#)
 - limiting source traffic with SPAN [15](#)
 - modifying [9](#)
 - multicast [17](#)

- native, configuring [23](#)
- normal-range [1, 4](#)
- number supported [7](#)
- parameters [5](#)
- port membership modes [3](#)
- static-access ports [11](#)
- STP and IEEE 802.1Q trunks [10](#)
- supported [2](#)
- Token Ring [6](#)
- traffic between [2](#)
- VLAN-bridge STP [10, 2](#)
- VTP modes [3](#)
- VLAN Trunking Protocol
 - See VTP
- VLAN trunks [16](#)
- VMPS
 - administering [32](#)
 - configuration example [33](#)
 - configuration guidelines [29](#)
 - default configuration [29](#)
 - description [27](#)
 - dynamic port membership
 - described [28](#)
 - reconfirming [31](#)
 - troubleshooting [33](#)
 - entering server address [30](#)
 - mapping MAC addresses to VLANs [28](#)
 - monitoring [32](#)
 - reconfirmation interval, changing [31](#)
 - reconfirming membership [31](#)
 - retry count, changing [32](#)
- voice aware 802.1x security
 - port-based authentication
 - configuring [35](#)
 - described [25, 35](#)
- voice-over-IP [1](#)
- voice VLAN
 - Cisco 7960 phone, port connections [1](#)
 - configuration guidelines [3](#)
 - configuring IP phones for data traffic
 - override CoS of incoming frame [6](#)
 - trust CoS priority of incoming frame [6](#)
 - configuring ports for voice traffic in
 - 802.1p priority tagged frames [5](#)
 - 802.1Q frames [5](#)
 - connecting to an IP phone [4](#)
 - default configuration [3](#)
 - described [1](#)
 - displaying [7](#)
 - IP phone data traffic, described [2](#)
 - IP phone voice traffic, described [2](#)
- VPN
 - configuring routing in [80](#)
 - forwarding [74](#)
 - in service provider networks [71](#)
 - routes [72](#)
- VPN routing and forwarding table
 - See VRF
- VQP [7, 27](#)
- VRF
 - defining [74](#)
 - tables [71](#)
- VRF-aware services
 - ARP [77](#)
 - configuring [77](#)
 - ftp [80](#)
 - HSRP [78](#)
 - ping [78](#)
 - SNMP [78](#)
 - syslog [79](#)
 - tftp [80](#)
 - traceroute [80](#)
 - uRPF [79](#)
- VTP
 - adding a client to a domain [14](#)
 - advertisements [19, 3](#)
 - and extended-range VLANs [1](#)
 - and normal-range VLANs [1](#)

- client mode, configuring [11](#)
 - configuration
 - global configuration mode [7](#)
 - guidelines [8](#)
 - privileged EXEC mode [7](#)
 - requirements [9](#)
 - saving [7](#)
 - VLAN configuration mode [7](#)
 - configuration mode options [7](#)
 - configuration requirements [9](#)
 - configuration revision number
 - guideline [14](#)
 - resetting [15](#)
 - configuring
 - client mode [11](#)
 - server mode [9](#)
 - transparent mode [12](#)
 - consistency checks [4](#)
 - default configuration [6](#)
 - described [1](#)
 - disabling [12](#)
 - domain names [8](#)
 - domains [2](#)
 - Layer 2 protocol tunneling [8](#)
 - modes
 - client [3,11](#)
 - server [3,9](#)
 - transitions [3](#)
 - transparent [3,12](#)
 - monitoring [16](#)
 - passwords [8](#)
 - pruning
 - disabling [14](#)
 - enabling [14](#)
 - examples [5](#)
 - overview [4](#)
 - support for [8](#)
 - pruning-eligible list, changing [23](#)
 - server mode, configuring [9](#)
 - statistics [16](#)
 - support for [8](#)
 - Token Ring support [4](#)
 - transparent mode, configuring [12](#)
 - using [1](#)
 - version, guidelines [8](#)
 - Version 1 [4](#)
 - Version 2
 - configuration guidelines [8](#)
 - disabling [13](#)
 - enabling [13](#)
 - overview [4](#)
-
- ## W
- WCCP
 - authentication [3](#)
 - configuration guidelines [5](#)
 - default configuration [5](#)
 - described [1](#)
 - displaying [9](#)
 - dynamic service groups [3](#)
 - enabling [6](#)
 - features unsupported [4](#)
 - forwarding method [3](#)
 - Layer-2 header rewrite [3](#)
 - MD5 security [3](#)
 - message exchange [2](#)
 - monitoring and maintaining [9](#)
 - negotiation [3](#)
 - packet redirection [3](#)
 - packet-return method [3](#)
 - redirecting traffic received from a client [6](#)
 - setting the password [6](#)
 - unsupported WCCPv2 features [4](#)
 - web authentication [14](#)
 - configuring [60 to 63, 64 to ??](#)
 - described [8, 26](#)
 - fallback for IEEE 802.1x [62](#)

Web Cache Communication Protocol

See WCCP

weighted tail drop

See WTD

weight thresholds in tracked lists [5](#)

wired location service

configuring [9](#)

displaying [10](#)

location TLV [3](#)

understanding [3](#)

wizards [2](#)

WTD

described [13](#)

setting thresholds

egress queue-sets [71](#)

ingress queues [67](#)

support for [11](#)

X

Xmodem protocol [2](#)