



# CISCO TELEPRESENCE SYSTEM T3 MAINTENANCE AND CLEANING



## VACUUM CLEANING

After any vacuum cleaning of the room, verify that no power cables have loosened—check the table legs and the main systems.

**Caution!** The vacuum cleaner must never be connected to any of the PC power outlets of the table!

## TOUCH COLLABORATION DISPLAY

The screens should be cleaned using the screen cleaning kit that comes with the system.

## MAIN VIDEO DISPLAY

The screens should be cleaned using the screen cleaning kit that comes with the system.

## TABLE

Use a mild detergent, typically one made for glass cleaning and the microfibre cloth that comes with the system.

## T3 FLOOR STRUCTURE COVERS

Clean with a detergent made for glass cleaning and the microfibre cloth that comes with the system. Apply the detergent to the cloth only. Do not spray directly on the system.

## T3 SYSTEM ENCLOSURES

Clean with a detergent made for glass cleaning and the microfibre cloth that comes with the system. Apply the detergent to the cloth only. Do not spray directly on the system.

## BLUE GLASS WALLS

Clean with a detergent made for glass cleaning and the microfibre cloth that comes with the system.

## MDF BORDERS (ALUMINIUM)

Clean with a detergent made for glass cleaning and the microfibre cloth that comes with the system.

The objective of this documentation is to provide the reader with assistance in using and configuring the product. The specifications for the product and the information in this Guide are subject to change at any time, without notice, by Cisco. Every effort has been made to supply complete and accurate information in this Guide; however, Cisco assumes no responsibility or liability for any errors or inaccuracies that may appear in this document.

All trademarks used in this document are the property of their respective holders.

This Guide may be reproduced in its entirety, including all copyright and intellectual property notices, in limited quantities in connection with the use of this product. Except for the limited exception set forth in the previous sentence, no part of this Guide may be reproduced, stored in a retrieval system, or transmitted, in any form, or by any means, electronically, mechanically, by photocopying, or otherwise, without the prior written permission of Cisco.

[www.cisco.com](http://www.cisco.com)

© 2010–2011 Cisco Inc.

78-19801-02 Cisco TelePresence System T3  
MAINTENANCE AND CLEANING Dec. 2011

## REPLACING FLUIDS AND CLOTHS

Whenever needed, the microfibre cleaning cloth should be replaced by a microfibre cloth designed for glass cleaning.

Screen cleaning kit should be replaced by 3M Screen and Keyboard Cleaner or a kit of similar type and performance.

## REPLACING LAMPS AND BULBS

### Spot bulb:

- Osram Halostar Starlite 64432 S 35W 12V GY6.35 FS1  
Observe the manufacturer's handling instructions.

### Fluorescent lamp:

#### For US:

- FH 21 W/830 HE 4050300464800 21 1900 LUMILUX Warm White 80...89 16 849 40

#### For Europe:

- FQ 39 W/830 HO 4050300453552 39 3100 LUMILUX Warm White 80...89 16 849 40 (older versions)
- FH 21 W/830 HE 4050300464800 21 1900 LUMILUX Warm White 80...89 16 849 40 (current version).

Type number is printed on the lamp. Observe the manufacturer's handling instructions.

**Doc cam bulb:** Halogen 150W, 24V, G6.35. Observe the manufacturer's handling instructions.

## STORING THE MAINTENANCE TOOLS

The cleaning kit can be conveniently stored in the shelf located in the right system base module.