



Information Relocated - Call Agent Controlled Mode for RFC 2833 DTMF Relay Feature Module

Revised: August 14, 2007

For the latest information on this Cisco BTS 10200 Softswitch feature, see:

Information	Link to Information in the Standard Documentation Set	Document Name
Feature descriptions, including interworking, limitations, legacy behavior	http://www.cisco.com/en/US/docs/voice_ip_comm/bts/5.0/feature/description/fd5010nf.html#wp1229630	<i>Network and Subscriber Feature Descriptions</i>
CLI reference data	http://www.cisco.com/en/US/docs/voice_ip_comm/bts/5.0/command/reference/clipc5.pdf	<i>Call Processing Command Line Interface Reference - Call Processing Commands</i>
Troubleshooting events and alarms	http://www.cisco.com/en/US/docs/voice_ip_comm/bts/5.0/troubleshooting/guide/14tg01.html#wp1305264	<i>Troubleshooting Guide</i>
Provisioning procedures for MGW, MGW profiles, enabling DTMF format, etc.	H.323 Gateway - http://www.cisco.com/en/US/docs/voice_ip_comm/bts/5.0/command/guide/h323_41.html#wp1062204	<i>Provisioning Guide</i>



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

© 2007 Cisco Systems, Inc. All rights reserved.

