



SCCP Compatibility Matrix: Cisco Unity Connection, Cisco Unified Communications Manager, and Cisco Unified Communications Manager Express

Revised September 24, 2009

This document lists the supported version combinations for Cisco Unity Connection, the Cisco Unity-CM TSP, and Cisco Unified Communications Manager, and for Cisco Unity Connection, the Cisco Unity-CM TSP, and Cisco Unified Communications Manager Express. It contains the following sections:

- [Supported Version Combinations for Cisco Unity Connection and Cisco Unified Communications Manager, page 2](#)
- [Supported Version Combinations for Cisco Unified Communications Manager Business Edition \(CMBE\), page 3](#)
- [Supported Version Combinations for Cisco Unity Connection and Cisco Unified Communications Manager Express, page 3](#)



Note

The supported version combinations are determined by testing. While other combinations may provide acceptable results to customers, Cisco must test or approve these combinations before they will be supported.

The Cisco Unity-CM TSP is required only when Cisco Unity Connection 1.x is integrated with Cisco Unified CM or Cisco Unified CM Express by Skinny Call Control Protocol (SCCP). Cisco Unity Connection 2.x or later does not use the Cisco Unity-CM TSP.

Cisco Unified CM support patch (sp) releases are not listed in the tables below unless they affect compatibility with Cisco Unity Connection or the Cisco Unity-CM TSP. If not listed, a support patch has the same compatibility as the base release. In addition, rereleased versions—for example, 3.x(xa) rereleased as 3.x(xb)—are assumed to have the same compatibility unless noted.



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

Supported Version Combinations for Cisco Unity Connection and Cisco Unified Communications Manager

Versions of Cisco Unity Connection 2.x or later and Cisco Unified CM are supported only in the combinations listed in [Table 1](#).



Note

To see supported version combinations for Cisco Unity Connection and Cisco Unified CM when installed as Cisco Unified Communications Manager Business Edition (CMBE), see the “[Supported Version Combinations for Cisco Unified Communications Manager Business Edition \(CMBE\)](#)” section on page 3.

Table 1 *Supported Version Combinations for Cisco Unity Connection 2.x or Later and Cisco Unified Communications Manager*

Cisco Unity Connection	Cisco Unified Communications Manager
7.1(3)	7.1(x), 7.0(x), 6.1(x), 6.0(x), 5.1(x), 5.0(x), 4.3(x), 4.2(x), 4.1(3) ¹
7.1(2)	7.1(x), 7.0(x), 6.1(x), 6.0(x), 5.1(x), 5.0(x), 4.3(x), 4.2(x), 4.1(3) ¹
7.0(2)	7.1(x), 7.0(x), 6.1(x), 6.0(x), 5.1(x), 5.0(x), 4.3(x), 4.2(x), 4.1(3) ¹
7.0(1)	7.1(x), 7.0(x), 6.1(x), 6.0(x), 5.1(x), 5.0(x), 4.3(x), 4.2(x), 4.1(3) ¹
2.1(4)	7.1(x), 7.0(x), 6.1(x), 6.0(x), 5.1(x), 5.0(x), 4.3(x), 4.2(x), 4.1(3) ¹
2.1(3)	7.1(x), 7.0(x), 6.1(x), 6.0(x), 5.1(x), 5.0(x), 4.3(x), 4.2(x), 4.1(3) ¹
2.1(2)	7.1(x), 7.0(x), 6.1(x), 6.0(x), 5.1(x), 5.0(x), 4.3(x), 4.2(x), 4.1(3) ¹
2.1(1)	7.1(x), 7.0(x), 6.1(x), 6.0(x), 5.1(x), 5.0(x), 4.3(x), 4.2(x), 4.1(3) ¹
2.0(1)	7.1(x), 7.0(x), 6.1(x), 6.0(x), 5.1(x), 5.0(x), 4.3(x), 4.2(x), 4.1(3) ¹

Footnotes for [Table 1](#)—Cisco Unity Connection 2.x or Later and Cisco Unified Communications Manager

1. Cisco Unified Communications Manager version 4.3(x), 4.2(x), and 4.1(3) are not supported for use with Cisco Unity Connection Phone View.

Versions of Cisco Unity Connection 1.x, the Cisco Unity-CM TSP, and Cisco Unified CM are supported only in the combinations listed in [Table 2](#).

Table 2 *Supported Version Combinations for Cisco Unity Connection 1.x, the Cisco Unity-CM TSP, and Cisco Unified Communications Manager*

Cisco Unity Connection	Cisco Unity-CM TSP	Cisco Unified Communications Manager
1.2(1)	8.3(1)	7.1(x), 7.0(x), 6.1(x), 6.0(x), 5.1(x), 5.0(x), 4.3(x), 4.2(x), 4.1(3), 4.1(2)
	8.2(1)	6.1(x), 6.0(x), 5.1(x), 5.0(x), 4.3(x), 4.2(x), 4.1(3), 4.1(2)
	8.1(3)	5.1(2), 5.1(1), 5.0(4), 5.0(3), 5.0(2), 5.0(1), 4.3(1), 4.2(3), 4.2(2), 4.2(1), 4.1(3), 4.1(2), 4.0(2), 4.0(1)

Table 2 *Supported Version Combinations for Cisco Unity Connection 1.x, the Cisco Unity-CM TSP, and Cisco Unified Communications Manager (continued)*

Cisco Unity Connection	Cisco Unity-CM TSP	Cisco Unified Communications Manager
1.1(1)	8.3(1)	7.1(x), 7.0(x), 6.1(x), 6.0(x), 5.1(x), 5.0(x), 4.3(x), 4.2(x), 4.1(3), 4.1(2)
	8.2(1)	6.1(x), 6.0(x), 5.1(x), 5.0(x), 4.3(x), 4.2(x), 4.1(3), 4.1(2)
	8.1(3)	5.1(2), 5.1(1), 5.0(4), 5.0(3), 5.0(2), 5.0(1), 4.3(1), 4.2(3), 4.2(2), 4.2(1), 4.1(3), 4.1(2), 4.0(2), 4.0(1)
	8.1(2)	5.0(2), 5.0(1), 4.2(3), 4.2(2), 4.2(1), 4.1(3), 4.1(2), 4.0(2), 4.0(1), 3.3(5), 3.3(4), 3.3(3), 3.3(2), 3.3(1)
	8.1(1)	4.2(1), 4.1(3), 4.1(2), 4.0(2), 4.0(1), 3.3(5), 3.3(4), 3.3(3), 3.3(2), 3.3(1)

Supported Version Combinations for Cisco Unified Communications Manager Business Edition (CMBE)

Versions of Cisco Unity Connection and Cisco Unified CM when installed as Cisco Unified Communications Manager Business Edition (CMBE) are supported only in the combinations listed in [Table 3](#).

Table 3 *Supported Version Combinations for Cisco Unified Communications Manager Business Edition (CMBE)*

Cisco Unity Connection Installed as Cisco Unified CMBE	Cisco Unified Communications Manager Installed as Cisco Unified CMBE
7.1(x)	7.1(x)
7.0(x)	7.0(x)
6.1(x)	6.1(x)
6.0(x)	6.0(x)

Supported Version Combinations for Cisco Unity Connection and Cisco Unified Communications Manager Express

Versions of Cisco Unity Connection 2.x or later and Cisco Unified Communications Manager Express are supported only in the combinations listed in [Table 4](#).

Table 4 Supported Version Combinations for Cisco Unity Connection 2.x or Later and Cisco Unified Communications Manager Express

Cisco Unity Connection	Cisco Unified Communications Manager Express
7.1(3)	7.0, 4.3, 4.2, 4.1, 4.0, 3.4 ¹
7.1(2)	7.0, 4.3, 4.2, 4.1, 4.0, 3.4 ¹
7.0(2)	7.0, 4.3, 4.2, 4.1, 4.0, 3.4 ¹
7.0(1)	7.0, 4.3, 4.2, 4.1, 4.0, 3.4 ¹
2.1(4)	7.0, 4.3, 4.2, 4.1, 4.0, 3.4 ¹
2.1(3)	7.0, 4.3, 4.2, 4.1, 4.0, 3.4 ¹
2.1(2)	7.0, 4.3, 4.2, 4.1, 4.0, 3.4 ¹
2.1(1)	7.0, 4.3, 4.2, 4.1, 4.0, 3.4 ¹
2.0(1)	7.0, 4.3, 4.2, 4.1, 4.0, 3.4 ¹

Footnotes for Table 4—Cisco Unity Connection 2.x or Later and Cisco Unified Communications Manager Express

- Integrations with Connection and Cisco Unified CM Express 3.4 are supported only when Cisco Unified CM Express 3.4 is installed on IOS 12.4(6)T1 or later.

Versions of Cisco Unity Connection 1.x, the Cisco Unity-CM TSP, and Cisco Unified Communications Manager Express are supported only in the combinations listed in [Table 5](#).

Table 5 Supported Version Combinations for Cisco Unity Connection 1.x, the Cisco Unity-CM TSP, and Cisco Unified Communications Manager Express

Cisco Unity Connection	Cisco Unity-CM TSP	Cisco Unified Communications Manager Express
1.2(1)	8.3(1), 8.2(1), 8.1(3)	7.0, 4.3, 4.2, 4.1, 4.0, 3.4, ¹ 3.3, 3.2, 3.1
1.1(1)	8.1(2), 8.1(1)	3.4, ¹ 3.3, 3.2, 3.1

Footnotes for Table 5—Cisco Unity Connection 1.x and Cisco Unified Communications Manager Express

- Integrations with Connection and Cisco Unified CM Express 3.4 are supported only when Cisco Unified CM Express 3.4 is installed on IOS 12.4(6)T1 or later.

CCDE, CCENT, CCSI, Cisco Eos, Cisco HealthPresence, Cisco IronPort, the Cisco logo, Cisco Lumin, Cisco Nexus, Cisco Nurse Connect, Cisco Pulse, Cisco StackPower, Cisco StadiumVision, Cisco TelePresence, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flipshare (Design), Flip Ultra, Flip Video (Design), Instant Broadband, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Capital, Cisco Capital (Design), Cisco:Financed (Stylized), Cisco Store, and Flip Gift Card are service marks; and Access Registrar, Aironet, AllTouch, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Continuum, EtherFast, EtherSwitch, Event Center, Explorer, Fast Step, Follow Me Browsing, FormShare, GainMaker, GigaDrive, HomeLink, iLYNX, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, Laser Link, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerKEY, PowerPanels, PowerTV, PowerTV (Design), PowerVu, Prisma, ProConnect, ROSA, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0908R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2005 – 2009 Cisco Systems, Inc. All rights reserved.

