



INDEX

A

alarm definition [1-16](#)

C

call media forking [1-9](#)

call media set attributes [1-8](#)

call mode change [1-8](#)

Cisco Unified Communication IOS Services interface [1-1](#)

configuring for Cisco Unified Communication IOS services [2-1](#)

configuring XCC provider [2-4](#)

configuring XCDR provider [2-8](#)

configuring XSVC provider [2-5](#)

connection states [1-11](#)

I

inbound ports [1-4](#)

interactions

- application, XCC provider, and XCC call [A-4](#)

- application and XCC connection [A-8](#)

- call authorization with a delayed response [A-11](#)

- call authorization with immediate response [A-9](#)

- digit collection with delayed response [A-13](#)

- digit collection with immediate response [A-11](#)

- XCC provider and application [A-1](#)

N

namespace [1-4](#)

R

registered session states [1-4](#)

registering [1-4](#)

S

show voip trunk group [2-20](#)

show wsapi [2-21](#)

source-address (uc-wsapi) [2-24](#)

statistics definition [1-17](#)

T

troubleshooting [2-10](#)

W

WSDL [1-3](#)

X

XCC Call API [1-7](#)

XCC Connection [1-10](#)

XCC Connection API [1-12](#)

XCC Provider [1-5](#)

XCC Provider API [1-6](#)

XCDR CDR API [1-19](#)

XCDR Provider [1-17](#)

XCDR Provider API [1-18](#)

xsvc [2-26](#)

- XSVC Provider [1-13](#)
- XSVC Provider API [1-14](#)
- XSVC Route API [1-15](#)