



Physical and Operating Environment Specifications

The following section describes the technical specifications for the Cisco Wireless IP Phone 7920. [Table C-1](#) shows the physical and operating environment specifications.

Table C-1 *Physical and Operating Environmental Specifications*

Specification	Value or Range
Operating temperature	0° to 45°C (32° to 113°F)
Operating Relative Humidity	10% to 95% (non-condensing)
Storage Temperature	-30° to 60°C (22° to 140°F)
Drop Specification	1 meter to concrete
Thermal Shock	-30 C for 24 hours to up to +70 C for 24 hours
Phone Height	132.1 mm (5.2 in.)
Phone Width	53.3 mm (2.1 in.)
Phone Depth	25.4 mm (1 in.)
Phone Weight (with Standard Battery)	136.1 g (4.8 oz)

Table C-1 Physical and Operating Environmental Specifications (continued)

Specification	Value or Range
Power	<ul style="list-style-type: none"> • 1440/1560mA—Standard lithium ion battery • 1960mA— Extended lithium ion battery • 100-240 VAC, 50-60 Hz, 0.5 A—when using the AC adapter
Distance Requirements	As supported by the 802.11b specification, the Cisco Wireless IP Phones should be within 500 to 1000 feet of an access point
Desktop Charger Height	75 mm (3.0 in.)
Desktop Charger Width	93 mm (3.7 in.)
Desktop Charger Depth	129 mm (5.1 in.)