



# APPENDIX C

## Physical and Operating Environment Specifications

The following section describes the technical specifications for the Cisco Unified Wireless IP Phone 7925G, 7925G-EX, and 7926G. [Table C-1](#) shows the physical and operating environment specifications for the Cisco.

**Table C-1** *Cisco Unified Wireless IP Phone 7926G and 7926G Physical and Operating Environmental Specifications*

Specification	Value or Range
Operating Temperature	0° to 40°C (32° to 104°F)
Operating Relative Humidity	10% to 95% (non-condensing)
Storage Temperature	-30° to 60°C (-22° to 140°F)
Drop Specification	5 ft (1.5 m) to concrete without carrying case
Thermal Shock	-22°F (-30° C) for 24 hours to up to 158°F (+70°C) for 24 hours
Vibration	1.5 Grms maximum, 0.1 in. (2.5 mm) double amplitude at 0.887 octaves per minute from 5-500-5 Hz sweep; 10-minute dwell on three major peaks in each of the three major mutually perpendicular axis
Altitude	Certified for operation from 0 to 6,500 ft (0 to 2km)
Endurance	IP54; MIL810F
Phone Height	5.0 in. (12.7 cm)
Phone Width	2.0 in. (5.2 cm)
Phone Depth	0.8 (2.0 cm)
Phone Weight	4.8 to 5.0 oz. (138 to 143 g) <sup>1</sup>
LCD	2 inches wide with 176 by 220 pixel resolution
Power	AC adapters by geographic region

1. Depends on the weight of the battery pack.

[Table C-2](#) shows the physical and operating environment specifications for the Cisco Wireless IP Phone 7925G-EX.

**Table C-2 Cisco Unified Wireless IP Phone 7925G-EX Physical and Operating Environmental Specifications**

<b>Specification</b>	<b>Value or Range</b>
Operating Temperature	-10 to 50°C (14° to 122°F)
Operating Relative Humidity	10% to 95% (non-condensing)
Storage Temperature	-30° to 60°C (-22° to 140°F)
Drop Specification	5 ft (1.5 m) to concrete without carrying case
Thermal Shock	-22°F (-30° C) for 24 hours to up to 158°F (+70°C) for 24 hours
Vibration	1.5 Grms maximum, 0.1 in. (2.5 mm) double amplitude at 0.887 octaves per minute from 5-500-5 Hz sweep; 10-minute dwell on three major peaks in each of the three major mutually perpendicular axis
Altitude	Certified for operation from 0 to 6,500 ft (0 to 2km)
Endurance	IP64; MIL-STD-810F, Method 516.5, Procedure I
Phone Height	5.0 in. (12.7 cm)
Phone Width	2.0 in. (5.2 cm)
Phone Depth	0.8 (2.0 cm)
Phone Weight	4.8 to 5.0 oz. (138 to 143 g) <sup>1</sup>
LCD	2 inches wide with 176 by 220 pixel resolution
Power	AC adapters by geographic region

1. Depends on the weight of the battery pack.