



## CHAPTER 7

# Viewing Model Information, Status, and Statistics on the Cisco Unified IP Phone

---

This chapter describes how to use the following menus and screens on the Cisco Unified IP Phone 7965G and 7945G to view model information, status messages, network statistics, and firmware information for the phone:

- Model Information screen—Displays hardware and software information about the phone. For more information, see the [“Model Information Screen” section on page 7-2](#).
- Status menu—Provides access to screens that display the status messages, network statistics, and firmware versions. For more information, see the [“Status Menu” section on page 7-2](#).
- Call Statistics screen—Displays counters and statistics for the current call. For more information, see the o.

You can use the information on these screens to monitor the operation of a phone and to assist with troubleshooting.

You can also obtain much of this information, and obtain other related information, remotely through the phone’s web page. For more information, see [Chapter 8, “Monitoring the Cisco Unified IP Phone Remotely.”](#)

For more information about troubleshooting the Cisco Unified IP Phone 7965G and 7945G, see [Chapter 9, “Troubleshooting and Maintenance.”](#)

This chapter includes these topics:

- [Model Information Screen, page 7-2](#)
- [Status Menu, page 7-2](#)
- [Call Statistics Screen, page 7-11](#)

## Model Information Screen

The Model Information screen includes the options that are described in [Table 7-1](#).

To display the Model Information screen, press the **Settings** button and then select **Model Information**.

To exit the Model Information screen, press the **Exit** softkey.

**Table 7-1** Model Information Settings

Option	Description	To Change
Model Number	Model number of the phone.	Display only—Cannot configure.
MAC Address	MAC address of the phone.	Display only—Cannot configure.
Load File	Identifier of the factory-installed load running on the phone.	Display only—Cannot configure.
Boot Load ID	Identifier of the factory-installed load running on the phone.	Display only—Cannot configure.
Serial Number	Serial number of the phone.	Display only—Cannot configure.
CTL	Displays the MD5 hash of the certificate trust list (CTL) file that is installed in the phone. If no CTL file is installed on the phone, this field displays No. (If security is configured for the phone, the CTL file installs automatically when the phone reboots or resets).	For more information about this file, refer to <i>Cisco Unified Communications Manager Security Guide</i> .
MIC	Indicates whether a manufacturing installed certificate (used for the security features) is installed on the phone (Yes) or is not installed on the phone (No).	For information about how to manage the MIC for your phone, refer to the “Using the Certificate Authority Proxy Function” section in <i>Cisco Unified Communications Manager Security Guide</i> .
LSC	Indicates whether a locally significant certificate (used for the security features) is installed on the phone (Yes) or is not installed on the phone (No).	For information about how to manage the LSC for your phone, refer to the “Using the Certificate Authority Proxy Function” section in <i>Cisco Unified Communications Manager Security Guide</i> .
Call Control Protocol	Indicates whether the phone is running under SCCP or SIP.	See the “Using Cisco Unified IP Phones with Different Protocols” section on page 2-11.

## Status Menu

The Status menu includes these options, which provide information about the phone and its operation:

- **Status Messages**—Displays the Status Messages screen, which shows a log of important system messages. For more information, see the “[Status Messages Screen](#)” section on page 7-3.
- **Network Statistics**—Displays the Network Statistics screen, which shows Ethernet traffic statistics. For more information, see the “[Network Statistics Screen](#)” section on page 7-9.
- **Firmware Versions**—Displays the Firmware Versions screen, which shows information about the firmware running on the phone. For more information, see the “[Firmware Versions Screen](#)” section on page 7-10.

- **Expansion Module(s)**—(SCCP phones only) Displays the Expansion Module(s) screen, which shows information about the Cisco Unified IP Phone Expansion Module 7914, if connected to the phone. For more information, see the “[Expansion Module\(s\) Screen \(SCCP Phones Only\)](#)” section on page 7-10.

To display the Status menu, press the **Settings** button and then select **Status**.

To exit the Status menu, press the **Exit** softkey.

## Status Messages Screen

The Status Messages screen displays the 10 most recent status messages that the phone has generated. You can access this screen at any time, even if the phone has not finished starting up. [Table 7-2](#) describes the status messages that might appear. This table also includes actions you can take to address errors.

To display the Status Messages screen, follow these steps:

### Procedure

- 
- |               |                                   |
|---------------|-----------------------------------|
| <b>Step 1</b> | Press the <b>Settings</b> button. |
| <b>Step 2</b> | Select <b>Status</b> .            |
| <b>Step 3</b> | Select <b>Status Messages</b> .   |
-

To remove current status messages, press the **Clear** softkey.

To exit the Status Messages screen, press the **Exit** softkey.

**Table 7-2** Status Messages on the Cisco Unified IP Phone 7965G and 7945G

Message	Description	Possible Explanation and Action
BootP server used	The phone obtained its IP address from a BootP server rather than a DHCP server.	None. This message is informational only.
CFG file not found	The name-based and default configuration file was not found on the TFTP Server.	<p>The configuration file for a phone is created when the phone is added to the Cisco Unified Communications Manager database. If the phone has not been added to the Cisco Unified Communications Manager database, the TFTP server generates a CFG File Not Found response.</p> <ul style="list-style-type: none"> <li>Phone is not registered with Cisco Unified Communications Manager. You must manually add the phone to Cisco Unified Communications Manager if you are not allowing phones to auto-register. See the <a href="#">“Adding Phones with Cisco Unified Communications Manager Administration”</a> section on page 2-11 for details.</li> <li>If you are using DHCP, verify that the DHCP server is pointing to the correct TFTP server.</li> <li>If you are using static IP addresses, check configuration of the TFTP server. See the <a href="#">“Network Configuration Menu”</a> section on page 4-5 for details on assigning a TFTP server.</li> </ul>
CFG TFTP Size Error	The configuration file is too large for file system on the phone.	Power cycle the phone.
Checksum Error	Downloaded software file is corrupted.	Obtain a new copy of the phone firmware and place it in the TFTPPath directory. You should only copy files into this directory when the TFTP server software is shut down, otherwise the files may be corrupted.
CTL Installed	A certificate trust list (CTL) file is installed in the phone.	None. This message is informational only. For more information about the CTL file, refer to <i>Cisco Unified Communications Manager Security Guide</i> .
CTL update failed	The phone could not update its certificate trust list (CTL) file.	Problem with the CTL file on the TFTP server. For more information, refer to <i>Cisco Unified Communications Manager Security Guide</i> .

Table 7-2 Status Messages on the Cisco Unified IP Phone 7965G and 7945G (continued)

Message	Description	Possible Explanation and Action
DHCP timeout	DHCP server did not respond.	<ul style="list-style-type: none"> <li>Network is busy—The errors should resolve themselves when the network load reduces.</li> <li>No network connectivity between the DHCP server and the phone—Verify the network connections.</li> <li>DHCP server is down—Check configuration of DHCP server.</li> <li>Errors persist—Consider assigning a static IP address. See the “<a href="#">Network Configuration Menu</a>” section on page 4-5 for details on assigning a static IP address.</li> </ul>
Dialplan Parsing Error (SIP phones only)	The phone could not parse the dialplan XML file properly.	Problem with the TFTP downloaded dialplan XML file. For more information refer to the <i>Cisco Unified Communications Manager Administration Guide</i> .
Disabled	802.1X Authentication is disabled on the phone.	You can enable 802.1X authentication using the <b>Settings &gt; Security Configuration &gt; 802.1X Authentication</b> option on the phone. For more information, see the “ <a href="#">802.1X Authentication and Status</a> ” section on page 4-34.
DNS timeout	DNS server did not respond.	<ul style="list-style-type: none"> <li>Network is busy—The errors should resolve themselves when the network load reduces.</li> <li>No network connectivity between the DNS server and the phone—Verify the network connections.</li> <li>DNS server is down—Check configuration of DNS server.</li> </ul>
DNS unknown host	DNS could not resolve the name of the TFTP server or Cisco Unified Communications Manager.	<ul style="list-style-type: none"> <li>Verify that the host names of the TFTP server or Cisco Unified Communications Manager are configured properly in DNS.</li> <li>Consider using IP addresses rather than host names.</li> </ul>
Duplicate IP	Another device is using the IP address assigned to the phone.	<ul style="list-style-type: none"> <li>If the phone has a static IP address, verify that you have not assigned a duplicate IP address. See the “<a href="#">Network Configuration Menu</a>” section on page 4-5 section for details.</li> <li>If you are using DHCP, check the DHCP server configuration.</li> </ul>

Table 7-2 Status Messages on the Cisco Unified IP Phone 7965G and 7945G (continued)

Message	Description	Possible Explanation and Action
Error update locale	One or more localization files could not be found in the TFTPPath directory or were not valid. The locale was not changed.	<p>Check that the following files are located within subdirectories in the TFTPPath directory:</p> <ul style="list-style-type: none"> <li>• Located in subdirectory with same name as network locale: <ul style="list-style-type: none"> <li>– tones.xml</li> </ul> </li> <li>• Located in subdirectory with same name as user locale: <ul style="list-style-type: none"> <li>– glyphs.xml</li> <li>– dictionary.xml</li> <li>– kate.xml</li> <li>– dictionary.xml</li> </ul> </li> </ul>
Failed	The phone attempted an 802.1X transaction but authentication failed.	<p>Authentication typically fails because of one of the following:</p> <ul style="list-style-type: none"> <li>• No shared secret is configured in the phone or authentication server</li> <li>• The shared secret configured in the phone and the authentication server do not match</li> <li>• Phone has not been configured in the authentication server</li> </ul>
File auth error	An error occurred when the phone tried to validate the signature of a signed file. This message includes the name of the file that failed.	<ul style="list-style-type: none"> <li>• The file is corrupted. If the file is a phone configuration file, delete the phone from the Cisco Unified Communications Manager database using Cisco Unified Communications Manager Administration. Then add the phone back to the Cisco Unified Communications Manager database using Cisco Unified Communications Manager Administration.</li> <li>• There is a problem with the CTL file and the key for the server from which files are obtained is bad. In this case, run the CTL client and update the CTL file, making sure that the proper TFTP servers are included in this file.</li> </ul>
File not found	The phone cannot locate, on the TFTP server, the phone load file that is specified in the phone configuration file.	Make sure that the phone load file is on the TFTP server and that the entry in the configuration file is correct.
IP address released	The phone has been configured to release its IP address.	The phone remains idle until it is power cycled or you reset the DHCP address. See the <a href="#">“Network Configuration Menu” section on page 4-5</a> section for details.

Table 7-2 Status Messages on the Cisco Unified IP Phone 7965G and 7945G (continued)

Message	Description	Possible Explanation and Action
Load Auth Failed	The phone could not load a configuration file.	Check that: <ul style="list-style-type: none"> <li>• A good version of the configuration file exists on the applicable server.</li> <li>• The phone load file being downloaded has not been altered or renamed.</li> <li>• The phone load type is compatible; for example, you cannot place a DEV load configuration file on a REL-signed phone.</li> </ul>
Load ID incorrect	Load ID of the software file is of the wrong type.	Check the load ID assigned to the phone (from Cisco Unified Communications Manager, choose <b>Device &gt; Phone</b> ). Verify that the load ID is entered correctly.
Load rejected HC	The application that was downloaded is not compatible with the phone's hardware.	Occurs if you were attempting to install a version of software on this phone that did not support hardware changes on this newer phone.  Check the load ID assigned to the phone (from Cisco Unified Communications Manager, choose <b>Device &gt; Phone</b> ). Re-enter the load displayed on the phone. See the <a href="#">“Firmware Versions Screen” section on page 7-10</a> to verify the phone setting.
Load Server is invalid	Indicates an invalid TFTP server IP address or name in the Load Server option.	The Load Server setting is not valid. The Load Server specifies a TFTP server IP address or name from which the phone firmware can be retrieved for upgrades on the phones.  Check the Load Server entry (from Cisco Unified Communications Manager Administration choose <b>Device &gt; Phone</b> ).
No CTL installed	A certificate trust list (CTL) file is not installed in the phone.	Occurs if security is not configured. If security is configured, because the CTL file does not exist on the TFTP server.  For more information, refer to <i>Cisco Unified Communications Manager Security Guide</i> .
No default router	DHCP or static configuration did not specify a default router.	<ul style="list-style-type: none"> <li>• If the phone has a static IP address, verify that the default router has been configured. See the <a href="#">“Network Configuration Menu” section on page 4-5</a> section for details.</li> <li>• If you are using DHCP, the DHCP server has not provided a default router. Check the DHCP server configuration.</li> </ul>

Table 7-2 Status Messages on the Cisco Unified IP Phone 7965G and 7945G (continued)

Message	Description	Possible Explanation and Action
No DNS server IP	A name was specified but DHCP or static IP configuration did not specify a DNS server address.	<ul style="list-style-type: none"> <li>If the phone has a static IP address, verify that the DNS server has been configured. See the “<a href="#">Network Configuration Menu</a>” section on page 4-5 section for details.</li> <li>If you are using DHCP, the DHCP server has not provided a DNS server. Check the DHCP server configuration.</li> </ul>
Programming Error	The phone failed during programming.	Attempt to resolve this error by power cycling the phone. If the problem persists, contact Cisco technical support for additional assistance.
Successful – MD5	The phone attempted an 802.1X transaction and authentication achieved.	The phone achieved 802.1X authentication.
TFTP access error	TFTP server is pointing to a directory that does not exist.	<ul style="list-style-type: none"> <li>If you are using DHCP, verify that the DHCP server is pointing to the correct TFTP server.</li> <li>If you are using static IP addresses, check configuration of TFTP server. See the “<a href="#">Network Configuration Menu</a>” section on page 4-5 for details on assigning a TFTP server.</li> </ul>
TFTP Error	The phone does not recognize an error code provided by the TFTP server.	Contact the Cisco TAC.
TFTP file not found	The requested load file (.bin) was not found in the TFTPPath directory.	Check the load ID assigned to the phone (from Cisco Unified Communications Manager, choose <b>Device &gt; Phone</b> ). Verify that the TFTPPath directory contains a .bin file with this load ID as the name.
TFTP server not authorized	The specified TFTP server could not be found in the phone’s CTL.	<ul style="list-style-type: none"> <li>DHCP server has wrong configuration file for TFTP server.</li> <li>The CTL file was made and then the TFTP server address changed. In this case, regenerate the CTL file.</li> </ul>
TFTP timeout	TFTP server did not respond.	<ul style="list-style-type: none"> <li>Network is busy—The errors should resolve themselves when the network load reduces.</li> <li>No network connectivity between the TFTP server and the phone—Verify the network connections.</li> <li>TFTP server is down—Check configuration of TFTP server.</li> </ul>
Timed Out	Supplicant attempted 802.1X transaction but timed out due the absence of an authenticator.	Authentication typically times out if 802.1X authentication is not configured on the switch.
Version error	The name of the phone load file is incorrect.	Make sure that the phone load file has the correct name.
XmlDefault.cnf.xml, or .cnf.xml corresponding to the phone device name	Name of the configuration file.	None. This is an informational message indicating the name of the configuration file for the phone.

## Network Statistics Screen

The Network Statistics screen displays information about the phone and network performance. [Table 7-3](#) describes the information that appears in this screen.

To display the Network Statistics screen, follow these steps:

### Procedure

- 
- Step 1** Press the **Settings** button.
- Step 2** Select **Status**.
- Step 3** Select **Network Statistics**.
- 

To reset the Rx Frames, Tx Frames, and Rx Broadcasts statistics to 0, press the **Clear** softkey.

To exit the Network Statistics screen, press the **Exit** softkey.

**Table 7-3** Network Statistics Message Components

Item	Description
Rx Frames	Number of packets received by the phone
Tx Frames	Number of packets sent by the phone
Rx Broadcasts	Number of broadcast packets received by the phone
One of the following values: Initialized TCP-timeout CM-closed-TCP TCP-Bad-ACK CM-reset-TCP CM-aborted-TCP CM-NAKed KeepaliveTO Failback Phone-Keypad Phone-Re-IP Reset-Reset Reset-Restart Phone-Reg-Rej Load Rejected HC CM-ICMP-Unreach Phone-Abort	Cause of the last reset of the phone
Elapsed Time	Amount of time that has elapsed since the phone last rebooted
Port 1	Link state and connection of the PC port (for example, <code>Auto 100 Mb Full-Duplex</code> means that the PC port is in a link up state and has auto-negotiated a full-duplex, 100-Mbps connection)

**Table 7-3 Network Statistics Message Components (continued)**

Item	Description
Port 2	Link state and connection of the Network port
DHCP BOUND	Phone is bound to the DHCP server, DHCP parameters are acceptable, and the phone has received a DHCPACK message.

## Firmware Versions Screen

The Firmware Versions screen displays information about the firmware version that is running on the phone. [Table 7-4](#) explains the information that is displayed on this screen.

To display the Firmware Version screen, follow these steps:

### Procedure

- 
- Step 1** Press the **Settings** button.
  - Step 2** Select **Status**.
  - Step 3** Select **Firmware Versions**.
- 

To exit the Firmware Version screen, press the **Exit** softkey.

**Table 7-4 Firmware Version Information**

Item	Description
Load File	Load file running on the phone
App Load ID	Identifies the JAR file running on the phone
JVM Load ID	Identifies the Java Virtual Machine (JVM) running on the phone
OS Load ID	Identifies the operating system running on the phone
Boot Load ID	Identifies the factory-installed load running on the phone
Expansion Module 1 Expansion Module 2	Identifies the load running on the Expansion Module(s), if connected to and SCCP phone
DSP Load ID	Identifies the digital signal processor (DSP) software version used

## Expansion Module(s) Screen (SCCP Phones Only)

The Expansion Module(s) screen displays information about each Cisco Unified IP Phone Expansion Module 7914 that is connected to the phone. This screen appears on SCCP phones only.

[Table 7-5](#) explains the information that is displayed on this screen for each connected expansion module. You can use this information to troubleshoot the expansion module, if necessary. In the Expansion Module(s) screen, a statistic preceded by “A” is for the first expansion module. A statistic preceded by “B” is for the second expansion module.

To display the Expansion Module(s) screen, follow these steps:

### Procedure

- 
- Step 1** Press the **Settings** button.
- Step 2** Select **Status**.
- Step 3** Select **Expansion Module(s)**.
- 

To exit the Expansion Module(s) screen, press the **Exit** softkey.

**Table 7-5**      *Expansion Module Statistics*

Item	Description
Link State	Overall expansion module status
RX Discarded Bytes	Number of bytes discarded due to errors
RX Length Err	Number of packets discarded due to improper length
RX Checksum Err	Number of packets discarded due to invalid checksum information
RX Invalid Message	Number of packets that have been discarded because a message was invalid or unsupported
TX Retransmit	Number of packets that have been retransmitted to the expansion module
TX Buffer Full	Number of packets discarded because the expansion module was not able to accept new messages

## Call Statistics Screen

You can access the Call Statistics screen on the phone to display counters, statistics, and voice-quality metrics in the following ways:

- During call—You can view the call information by rapidly pressing the ? button twice.
- After the call—You can view the call information captured during the last call by displaying the Call Statistics screen.



**Note** You can also remotely view the call statistics information by using a web browser to access the Streaming Statistics web page. This web page contains additional RTCP statistics not available on the phone. For more information about remote monitoring, see [Chapter 8, “Monitoring the Cisco Unified IP Phone Remotely.”](#)

A single call can have multiple voice streams, but data is captured for only the last voice stream. A voice stream is a packet stream between two endpoints. If one endpoint is put on hold, the voice stream stops even though the call is still connected. When the call resumes, a new voice packet stream begins, and the new call data overwrites the former call data.

To display the Call Statistics screen for information about the last voice stream, follow these steps:

### Procedure

- 
- Step 1** Press the **Settings** button.

**Step 2** Select **Status**.

**Step 3** Select **Call Statistics**.

The Call Statistics screen displays these items:

**Table 7-6 Call Statistics Items**

Item	Description
Rcvr Codec	Type of voice stream received (RTP streaming audio from codec): G.729, G.728/iLBC, G.711 u-law, G.711 A-law, or Lin16k.
Sender Codec	Type of voice stream transmitted (RTP streaming audio from codec): G.729, G.728/iLBC, G.711 u-law, G.711 A-law, or Lin16k.
Rcvr Size	Size of voice packets, in milliseconds, in the receiving voice stream (RTP streaming audio).
Sender Size	Size of voice packets, in milliseconds, in the transmitting voice stream.
Rcvr Packets	Number of RTP voice packets received since voice stream was opened. <b>Note</b> This number is not necessarily identical to the number of RTP voice packets received since the call began because the call might have been placed on hold.
Sender Packets	Number of RTP voice packets transmitted since voice stream was opened. <b>Note</b> This number is not necessarily identical to the number of RTP voice packets transmitted since the call began because the call might have been placed on hold.
Avg Jitter	Estimated average RTP packet jitter (dynamic delay that a packet encounters when going through the network) observed since the receiving voice stream was opened.
Max Jitter	Maximum jitter observed since the receiving voice stream was opened.
Rcvr Discarded	Number of RTP packets in the receiving voice stream that have been discarded (bad packets, too late, and so on). <b>Note</b> The phone will discard payload type 19 comfort noise packets that are generated by Cisco Gateways, which will increment this counter.
Rcvr Lost Packets	Missing RTP packets (lost in transit).
<b>Voice Quality Metrics</b>	
MOS LQK	Score that is an objective estimate of the mean opinion score (MOS) for listening quality (LQK) that rates from 5 (excellent) to 1 (bad). This score is based on audible concealment events due to frame loss in the preceding 8-second interval of the voice stream. For more information, see the <a href="#">“Monitoring the Voice Quality of Calls”</a> section on page 9-16. <b>Note</b> The MOS LQK score can vary based on the type of codec that the Cisco Unified IP Phone uses.
Avg MOS LQK	Average MOS LQK score observed for the entire voice stream.
Min MOS LQK	Lowest MOS LQK score observed from start of the voice stream.

**Table 7-6 Call Statistics Items (continued)**

<b>Item</b>	<b>Description</b>
Max MOS LQK	<p>Baseline or highest MOS LQK score observed from start of the voice stream.</p> <p>These codecs provide the following maximum MOS LQK score under normal conditions with no frame loss:</p> <ul style="list-style-type: none"> <li>• G.711 gives 4.5</li> <li>• G.722 gives 4.5</li> <li>• G.728/iLBC gives 3.9</li> <li>• G.729 A/AB gives 3.8</li> </ul>
MOS LQK Version	Version of the Cisco proprietary algorithm used to calculate MOS LQK scores.
Cumulative Conceal Ratio	Total number of concealment frames divided by total number of speech frames received from start of the voice stream.
Interval Conceal Ratio	Ratio of concealment frames to speech frames in preceding 3-second interval of active speech. If using voice activity detection (VAD), a longer interval might be required to accumulate 3 seconds of active speech.
Max Conceal Ratio	Highest interval concealment ratio from start of the voice stream.
Conceal Secs	Number of seconds that have concealment events (lost frames) from the start of the voice stream (includes severely concealed seconds).
Severely Conceal Secs	Number of seconds that have more than 5 percent concealment events (lost frames) from the start of the voice stream.
Latency	Estimate of the network latency, expressed in milliseconds. Represents a running average of the round-trip delay, measured when RTCP receiver report blocks are received.

