



Cisco Unified Web and E-Mail Interaction Manager System Requirements

For Unified Contact Center Express

Release 4.2(1)
July 2007

Americas Headquarters
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
<http://www.cisco.com>
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 527-0883

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

CCVP, the Cisco logo, and the Cisco Square Bridge logo are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networking Academy, Network Registrar, *Packet*, PIX, ProConnect, ScriptShare, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0705R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

Cisco Unified Web and E-Mail Interaction Manager System Requirements: For Unified Contact Center Express
© 2007 Cisco Systems, Inc. All rights reserved.

System requirements

- ▶ [About this guide](#)
- ▶ [Hardware requirements for user desktops](#)
- ▶ [Software requirements for servers](#)
- ▶ [Software requirements for user desktops](#)

Welcome to Cisco® Unified Web and E-Mail Interaction Manager™, multichannel interaction software used by businesses all over the world to build and sustain customer relationships. A unified suite of the industry’s best applications for web and email interaction management, it is the backbone of many innovative contact center and customer service helpdesk organizations.

About this guide

Cisco Unified Web and E-Mail Interaction Manager System Requirements is meant for system administrators, deployment engineers, and installation engineers. It helps you evaluate existing resources and plan purchases for your Cisco Interaction Manager installation, which includes a common platform and one or both of the following applications:

- ▶ Cisco Unified Web Interaction Manager (Unified WIM)
- ▶ Cisco Unified E-Mail Interaction Manager (Unified EIM)

This guide is for installations that are integrated with Cisco Unified Contact Center Express (Unified CCX).

Contents

This guide contains the following information:

- ▶ [“Hardware requirements for user desktops” on page 5](#)
- ▶ [“Software requirements for servers” on page 6](#)
- ▶ [“Software requirements for user desktops” on page 9](#)

To determine hardware requirements for servers, use the following resources:

- ▶ *Cisco Unified Contact Center Express (CCX) Configuration & Ordering Tool*
- ▶ *Cisco Customer Response Solutions (CRS) Software and Hardware Compatibility Guide*

For bandwidth requirements, see the following document:

- ▶ *Cisco Unified Web and E-Mail Interaction Manager Solutions Reference Network Design Guide*

Document conventions

This guide uses the following typographical conventions..

Convention	Indicates
<i>Italic</i>	Emphasis, or the title of a published document.
Bold	Labels of items on the user interface, such as buttons, boxes, and lists.
Monospace	The name of a file or folder, a database table column or value, or a command.
<i>Variable</i>	User-specific text, provided by the user. Or, text that must be typed by the user.

Document conventions

Hardware requirements for user desktops

In this section, we list hardware requirements for the desktop machines of users. While determining hardware needs, in addition to the minimum requirements mentioned here, consider the resources required for other applications that will be running on the desktop at the same time.

Item	Minimum requirements
CPU	Intel® Pentium™ 4 with a clock speed of 2 GHz or higher
RAM	512 MB (256 MB available physical memory for Cisco Interaction Manager)
Hard disk	512 MB for the Temporary Internet Files folder used by Internet Explorer
Screen resolution	1024 x 768 pixels (minimum as well as recommended setting)

Minimum hardware requirements for user desktops

Software requirements for servers

In this section we list software requirements for the server-class machines on which product components are installed. It includes:

- ▶ “Application servers” on page 6
- ▶ “Web servers” on page 7
- ▶ “Services servers” on page 7
- ▶ “Database server” on page 8

Application servers

Item	Requirements
Operating system (OS)	▶ Microsoft® Windows® 2003 Language: English
JDBC driver	Microsoft® SQL Server® 2000 Driver for JDBC™ Service Pack 3 version 2.2.0040
Application Server and servlet engine	BEA® WebLogic Server™ 8.1 SP 6 (included on the Cisco product CD)
Java runtime environment	JDK 1.4.2_11 (Shipped with WebLogic Server 8.1 SP 6)
Cisco Security Agent	Cisco® Security Agent version 4.5
Anti-virus	▶ McAfee® VirusScan® Enterprise version 8.1 or ▶ Symantec® AntiVirus® Corporate Edition 9.0

Software requirements for application servers

Web servers

Item	Requirements
Operating system (OS)	▶ Microsoft® Windows® 2003 Language: English
Web Server	Microsoft® IIS® 6.0
Cisco Security Agent	Cisco® Security Agent version 4.5
Anti-virus	▶ McAfee® VirusScan® Enterprise version 8.1 or ▶ Symantec® AntiVirus® Corporate Edition 9.0

Software requirements for web servers

Services servers

Item	Requirements
Operating system (OS)	▶ Microsoft® Windows® 2003 Language: English
JDBC driver	Microsoft® SQL Server® 2000 Driver for JDBC™ Service Pack 3 version 2.2.0040
Java runtime environment	JRE 1.4.2_11 (included on the Cisco product CD)
Cisco Security Agent	Cisco® Security Agent version 4.5
Anti-virus	▶ McAfee® VirusScan® Enterprise version 8.1 or ▶ Symantec® AntiVirus® Corporate Edition 9.0

Software requirements for services servers

Database server

Item	Requirements
Operating system (OS)	▶ Microsoft® Windows® 2003 Language: English
Database	Microsoft® SQL Server® 2000 SP 4
Cisco Security Agent	Cisco® Security Agent version 4.5
Anti-virus	▶ McAfee® VirusScan® Enterprise version 8.1 or ▶ Symantec® AntiVirus® Corporate Edition 9.0

Software requirements for the database server

Software requirements for user desktops

Item	Requirements
Operating system (OS)	<ul style="list-style-type: none"> ▶ Microsoft® Windows® XP (SP 2 or higher) Languages: Dutch, English, French, German, Italian, Spanish or ▶ Microsoft® Windows® XP (SP 2 or higher) with Multilingual User Interface Pack (MUI) <p>Note: See <i>Cisco Agent Desktop Installation Guide</i> to identify the OS that will work with both Unified Web and E-Mail Interaction Manager and Cisco Agent Desktop (CAD).</p>
Java runtime environment	Sun JVM 1.6 (included on the Cisco product CD)
Web browser	Microsoft® Internet Explorer® 6.0 (SP 2 or higher)
Additional item for web collaboration	MeadCo Security Manager 6,3,434,26 Agents who are assigned Unified WIM licenses are prompted to install this control when they first use Agent Console.
Cisco Security Agent	Cisco® Security Agent version 4.5
Anti-virus	<ul style="list-style-type: none"> ▶ McAfee® VirusScan® Enterprise version 8.1 or ▶ Symantec® AntiVirus® Corporate Edition 9.0

Software requirements for user desktops