



Cisco Customer Voice Portal (CVP) Software Release 3.0(0) Service Release 2 Bill of Materials

Revision 1.7
Last Updated: June 2008

Corporate Headquarters
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
<http://www.cisco.com>
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

Cisco CVP Software Release 3.0(0) Bill of Materials

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES

CCDE, CCENT, Cisco Eos, Cisco Lumin, Cisco Nexus, Cisco StadiumVision, the Cisco logo, DCE, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn is a service mark; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0805R)

Cisco Customer Voice Portal Software Release 3.0(0) Bill of Materials. Copyright © 2006-2007 Cisco Systems, Inc. All rights reserved.

Contents

Overview.....	1
About the CVP 3.0 BOM.....	1
Cisco Media Convergence Servers	1
3 rd Party Software Requirements	2
Hardware/Software Requirements	3
CVP Application Server/CVP Voice Browsers	3
Cisco Customer Voice Portal VoiceXML Server (optional).....	3
Cisco Customer Voice Portal VoiceXML Studio (optional).....	4
Media Server (optional).....	4
ASR/TTS Server (optional)	4
SDDSN (optional)	5
Cisco Contact Services Switch (CSS) (optional)	5
Cisco Gateways.....	6
Cisco Gatekeepers	7
Cisco IPCC	7
Cisco CallManager	7

Overview

This document is the recommended Bill of Materials for Cisco Customer Voice Portal version 3.0(0) (referenced herein as “CVP”). It provides platform hardware specifications and compatible 3rd party software version requirements across the major components of the Cisco CVP platform.

Requirements for the CVP systems are listed by major component, both basic CVP nodes and corresponding options, including multi-media servers. Hardware specifications are supplied for these components.

The Cisco CVP product is, by design, highly scalable and is configured across multiple deployment and call routing scenarios. Optimal sizing and component configuration for a given deployment will vary based on a number of factors, including agent capacity, call rate and call flow model(s), and other factors. Cisco strongly recommends consultation with your Cisco Certified Partner or with Cisco World Wide Voice Practice / Advanced Services prior to specific deployment selection.

The hardware specifications supplied herein for CPU processor power, memory and disk storage requirements, and related parameters represent systems minimally configured for adequate performance in the given size category. As specified, such systems will afford a margin for reasonable incremental growth within the bounds of that category. While it is likely that lower capacity hardware would provide adequate performance in many scenarios, the specifications as stated are those on which the CVP product is qualified by Cisco prior to release.

Note: Using hardware with higher performance than recommended does not necessarily result in greater call handling capacity.

About the CVP 3.0 BOM

The software versions referenced in this Bill of Materials represent the current supported versions for the CVP 3.0 solution. However, Cisco will continue to support customers who deployed ISN systems using earlier supported versions.

Information regarding previous supported versions can be found in the Bill of Materials for Cisco Enterprise Contact Routing--Release 5.0(0) at: <http://www.cisco.com/univercd/cc/td/doc/product/icm/ccubom/ccubom.pdf> or in the CVP Tech Reference, which can be found by clicking "Product specifications" at <http://www.in.cisco.com/voice/products/cvp.shtml>.

Cisco Media Convergence Servers

Supplied hardware options include the Cisco Media Convergence Servers (MCS) platform, a Cisco supplied and qualified server platform built using components from several leading server hardware vendors. The available MCS platform for CVP 3.0 at this writing is the 7845-H1-3.0-CCI. The BOM provides a mapping of CVP component server requirements to the appropriate MCS model across the configuration range.

The Cisco Media Convergence Server (MCS) Network Teaming Driver is not supported with CVP 3.0.

More information on Cisco 7800 Series Media Convergence Servers may be found at the following Cisco.com link: <http://www.cisco.com/en/US/products/hw/voiceapp/ps378/index.html>

3rd Party Software Requirements

Node	All Nodes
Software	<p>Remote Administration:</p> <p>Symantec pcANYWHERE 11.0 VNC 4.0 Windows Terminal Services (server administration only – no Application GUI access)</p> <p>Virus protection: McAfee VirusScan Enterprise 8.0i Symantec AntiVirus Corporate Edition 9.0 Trend 5.5.8</p> <p>Microsoft Internet Explorer 6.0 Service Pack 1 (minimum)</p> <p>Intrusion Prevention System: Cisco Security Agent for Cisco Customer Voice Portal: http://www.cisco.com/kobayashi/sw-center/contact_center/csa/ (Note: CSA is not supported for Terminal Services)</p> <p>Optional: WinZIP Adobe Acrobat Reader</p>

Hardware/Software Requirements

CVP Application Server/CVP Voice Browsers

Node	CVP Application Server/CVP Voice Browser
Cisco Media Convergence Servers (MCS)	MCS-7845-H1-3.0-CC1 Note: The MCS hardware is an option. Equivalent or faster servers from HP are also supported.
Minimum Recommended Hardware	2 x 2.6GHz or greater Intel "Xeon" class processors 2000+ MB RAM 18.2+ GB usable disk space Internal CD-ROM or DVD-ROM drive 1 x 10/100/1000 Ethernet ports
Operating System	Microsoft Windows 2000 Server with Service Pack 4 Note: Microsoft provides as an option the Integrated Service pack that simultaneously installs the operating system and SP4. Cisco does not support the Integrated Service Pack method. Apply SP4 only after Windows 2000 Server has been installed. Cisco IP Telephony (IPT) Operating System 2000.2.7 (supported only on the MCS and the HP equivalent machines). Note: To apply the latest Operating System Service Upgrade Release, go to http://www.cisco.com/cgi-bin/tablebuild.pl/cmva-3des
Additional Items	Application Server machines require the Windows 2000 Internet Information Admin Service (IIS), World Wide Web Publishing Services and SNMP (Simple Network Management Protocol).

Cisco Customer Voice Portal VoiceXML Server (optional)

Node	CVP VoiceXML Server
Cisco Media Convergence Servers (MCS)	MCS-7845-H1-3.0-CC1 Note: The MCS hardware is an option. Equivalent or faster servers from HP are also supported.
Minimum Recommended Hardware	2 x 2.6GHz or greater Intel "Xeon" class processors 2000+ MB RAM 18.2+ GB usable disk space Internal CD-ROM or DVD-ROM drive 1 x 10/100/1000 Ethernet ports
Operating System	Microsoft Windows 2000 Server with Service Pack 4
Additional Items	Cisco supports only the Apache Tomcat Java Application Server for CVP VoiceXML Server. SNMP is optional for logging and reporting.

Cisco Customer Voice Portal VoiceXML Studio (optional)

Node	CVP VoiceXML Studio
Minimum Recommended Hardware	800 MHz Intel Pentium III (or equivalent) 256 MB minimum memory, 512 MB recommended 100 MB minimum free hard disk space, 2 GB recommended 1024 x 768 minimum display (when using the CVP VoiceXML Builder)
Operating System	Microsoft Windows 2000 Server with Service Pack 4

Media Server (optional)

Node	Media Server
Minimum Recommended Hardware	Use vendor recommended hardware.
Additional information	<p>A minimum of 10MB should be available for CVP system media files (Cisco-provided .wav files of numbers, days, months, currency types, etc. in English, and Latin American Spanish).</p> <p>Note: Any additional media files will require additional space.</p> <p>To maximize Voice Browser and Application Server performance, <i>do not</i> install the Media Server on the same machine as the Voice Browser and/or Application Server.</p> <p>Note: This restriction applies to the Comprehensive and Advanced Speech deployment models. If you are using the Queue and Transfer deployment model, you may install the Media Server on the same machine as the Voice Browser and/or Application Server. For more information about the CVP deployment models, refer to the <i>Cisco Customer Voice Portal (CVP) Release 3.0 Product Description</i>.</p>

ASR/TTS Server (optional)

Note: This section provides information on vendors and software versions that have had extensive interoperability testing between CVP and ASR/TTS products. These tests exercised system functionality but not ASR/TTS product availability or sizing. For availability and sizing data on ASR/TTS servers, contact the vendor or their recommended partners.

	ASR/TTS Server
Recommended Hardware	Use vendor recommended hardware.
Recommended Software	Scansoft: OSMS 2.0.4 OSR 2.0.9 Speechify 3.0.1 Nuance 8.5 SR8b Nuance Vocalizer 3.0.8 (MRCP variant)

SDDSN (optional)

Node	SDDSN Machine
Cisco Media Convergence Servers (MCS)	MCS-7825H-3.0-CC1 Note: MCS class machines are not required to host SDDSN. However, using a MCS machine allows approximately 50 connections to SDDSN clients, such as the CVP Application Server and the CVP Voice Browser.
Recommended Hardware	2.6GHz or greater Intel "Xeon" class processors 2000+ MB RAM 18.2+ GB usable disk space Internal CD-ROM or DVD-ROM drive 1 x 10/100/1000 Ethernet ports Note: This level of hardware is not required to host SDDSN. However, using this hardware allows approximately 50 connections to SDDSN clients, such as the CVP Application Server and the CVP Voice Browser
Operating System	SDDSN machines should have Microsoft Windows 2000 pre-installed. These machines also must have the SNMP services, which is no longer loaded by default with SP3.

Cisco Contact Services Switch (CSS) (optional)

Node	CSS Machine
Minimum Recommended Hardware	Cisco CCS 11500
Recommended Software	WebNS 7.30

Cisco Gateways

	Gateways
Hardware options	17xx 36xx 37xx 3825 3845 5350* 5400 HPX 5850eRSC * The XM series is not supported.
Software options	IOS 12.3(11)T4 ¹ (Or later T. For example, IOS 12.3(11)T6) IOS 12.3(11)T10 or later T IOS 12.4(13) [supported as of CVP 3.0 SR 2] IP PLUS software feature set 1. An upgrade to an IOS version that is not explicitly stated in this Hardware and System Software Specification requires approval from CVP engineering.

Cisco Gatekeepers

	Gatekeepers
Hardware options	2xxx 3xxx
Software options	IOS 12.3(11)T3 or later T IOS 12.3(11)T10 or later T IOS 12.4(13) [supported as of CVP 3.0 SR 2] IP/H323 Software feature set

Cisco IPCC

	IPCC
IPCC versions that are compatible with CVP 3.0	6.0 7.0 SR3 [supported as of CVP 3.0 SR2] Note: All versions must be installed with the latest Service Release
Additional Information	If Cisco CallManager is to be part of the configuration, refer to the CallManager table for version requirements.

Cisco CallManager

	Cisco CallManager
Cisco CallManager versions that are compatible with CVP 3.0	CCM 4.0 (for IPCC version 6.0) CCM 4.1(3) [supported as of CVP3.0 SR2]