



Release Notes for Cisco 7000 Family for Cisco IOS Release 12.4 SW

July 20, 2007

Cisco IOS Release 12.4(11)SW3

These release notes for the Cisco 7000 family describe the enhancements provided in Cisco IOS Release 12.4(11)SW3. Cisco IOS Release 12.4(11)SW3 supports the IP Transfer Point (ITP) product on Cisco 7200 and 7301 series routers and uses the ITP functionality of Cisco IOS Release 12.2(25)SW8 as its base. Cisco IOS Release 12.4(11)SW3 is not a general purpose release. These release notes are updated as needed.

For a list of the software caveats that apply to Cisco IOS Release 12.4(11)SW3, see the “[Caveats for Cisco IOS Release 12.4 SW](#)” section on [page 9](#) and *Caveats for Cisco IOS Release 12.4T*. The caveats document is updated for every maintenance release and is located on [Cisco.com](#).

Use these release notes with *Cross-Platform Release Notes for Cisco IOS Release 12.4T* located on [Cisco.com](#).

Cisco recommends that you view the field notices for this release to see if your software or hardware platforms are affected. If you have an account on Cisco.com, you can find field notices at http://www.cisco.com/warp/customer/tech_tips/index/fn.html. If you do not have a Cisco.com login account, you can find field notices at http://www.cisco.com/warp/public/tech_tips/index/fn.html.

Contents

These release notes describe the following topics:

- [Inheritance Information, page 2](#)
- [System Requirements, page 3](#)
- [New and Changed Information, page 6](#)
- [MIBs, page 9](#)
- [Caveats for Cisco IOS Release 12.4 SW, page 9](#)
- [Related Documentation, page 13](#)
- [Obtaining Documentation, page 21](#)



- [Documentation Feedback, page 23](#)
- [Obtaining Technical Assistance, page 24](#)
- [Obtaining Additional Publications and Information, page 26](#)

Inheritance Information

Cisco IOS Release 12.4(11)SW3 is based on Cisco IOS Release 12.4(11)T. All features in Cisco IOS Release 12.4(11)T are in Cisco IOS Release 12.4(11)SW3.

[Table 1](#) lists sections of the *Cross-Platform Release Notes for Cisco IOS Release 12.4T* that apply to Cisco IOS Release 12.4(11)SW3.

Table 1 *References for the Cross-Platform Release Notes for Cisco IOS Release 12.4T*

Topic	Location
<ul style="list-style-type: none"> • Introductory information about the Cisco 7200 and Cisco 7301 series routers • Hardware Supported • Feature Set Tables 	<p>On Cisco.com at:</p> <p>Products & Services > IOS Software > Cisco IOS Software Releases 12.4T > General Information> Release Notes > Cross-Platform Release Notes for Cisco IOS Release 12.4T, Part 2 > Platform-Specific Information</p> <p>Or at:</p> <p>http://www.cisco.com/en/US/products/ps6441/prod_release_note09186a00804a19a2.html</p>
<ul style="list-style-type: none"> • Determining the Software Version • Upgrading to a New Software Release 	<p>On Cisco.com at:</p> <p>Products & Services > IOS Software > Cisco IOS Software Releases 12.4T > General Information> Release Notes > Cross-Platform Release Notes for Cisco IOS Release 12.4T, Part 1 > System Requirements</p> <p>Or at:</p> <p>http://www.cisco.com/en/US/products/ps6441/prod_release_note09186a00804a19ec.html</p>

Table 1 References for the Cross-Platform Release Notes for Cisco IOS Release 12.4T

Topic	Location
<ul style="list-style-type: none"> • Feature Descriptions (New and Changed Information) • MIBs • Important Notes 	<p>On Cisco.com at:</p> <p>Products & Services > IOS Software > Cisco IOS Software Releases 12.4T > General Information> Release Notes > Cross-Platform Release Notes for Cisco IOS Release 12.4T, Part 3 > New Features and Important Notes</p> <p>Or at:</p> <p>http://www.cisco.com/en/US/products/ps6441/prod_release_note09186a00804a19ae.html</p>
<ul style="list-style-type: none"> • Related Documentation • Obtaining Documentation • Obtaining Technical Assistance 	<p>On Cisco.com at:</p> <p>Products & Services > IOS Software > Cisco IOS Software Releases 12.4T > General Information> Release Notes > Cross-Platform Release Notes for Cisco IOS Release 12.2T, Part 4 > Related Documentation</p> <p>Or at:</p> <p>http://www.cisco.com/en/US/products/ps6441/prod_release_note09186a00804a196b.html</p>

System Requirements

This section describes the system requirements for Cisco IOS Release 12.4(11)SW and includes the following sections:

- [Memory Recommendations](#), page 3
- [Supported Hardware](#), page 4
- [Determining the Software Version](#), page 4
- [Upgrading to a New Software Release](#), page 4
- [Feature Set Tables](#), page 5

Memory Recommendations

Table 2 Memory Recommendations for Cisco IOS Release 12.4(11)SW

Platforms	Feature Sets	Image Name	Software Image	Flash Memory Recommended	DRAM Memory Recommended	Runs From
Cisco 7200	IP Standard Feature Set	IP Transfer Point	c7200-itpk9-mz	32 MB Flash	256 MB DRAM	FLASH
Cisco 7301	IP Standard Feature Set	IP Transfer Point	c7301-itpk9-mz	32 MB Flash	256 MB DRAM	FLASH

Supported Hardware

Cisco IOS Release 12.4(11)SW supports the following Cisco 7000 platforms:

- Cisco 7200 series routers
- Cisco 7301 series routers

For detailed descriptions of the new hardware features, see the “[New and Changed Information](#)” section on page 6.

Determining the Software Version

To determine the version of Cisco IOS software running on your Cisco 7200 or Cisco 7301 series router, log in to the router and enter the **show version EXEC** command. For example:

```
Router> show version
Cisco Internetwork Operating System Software
IOS (tm) 7301 Software (c7301-itpk9-mz), Version 12.4(11)SW3, RELEASE SOFTWARE
```

Upgrading to a New Software Release

For information about selecting a new Cisco IOS software release, please refer to *How to Choose a Cisco IOS Software Release* at:

http://www.cisco.com/warp/public/130/choosing_ios.shtml

For information about upgrading to a new software release, refer to the appropriate platform-specific document:

- Cisco 7200 Series, 7300 Series, 7400 Series, and 7500 Series Routers
http://www.cisco.com/en/US/products/hw/routers/ps133/products_tech_note09186a0080094c07.shtml

For *Cisco IOS Upgrade Ordering Instructions*, refer to the document at the following location:

http://www.cisco.com/warp/public/cc/pd/iosw/prodlit/957_pp.htm

To choose a new Cisco IOS software release by comparing feature support or memory requirements, use Cisco Feature Navigator. Cisco Feature Navigator is a web-based tool that enables you to determine which Cisco IOS and Catalyst OS software images support a specific set of features and which features are supported in a specific Cisco IOS image. You can search by feature or by feature set (software image). Under the release section, you can compare Cisco IOS software releases side by side to display both the features unique to each software release and the features that the releases have in common.

Cisco Feature Navigator is updated regularly when major Cisco IOS software releases and technology releases occur. For the most current information, go to the Cisco Feature Navigator home page at the following URL:

<http://www.cisco.com/go/fn>

To choose a new Cisco IOS software release based on information about defects that affect that software, use Bug Toolkit at:

http://www.cisco.com/cgi-bin/Support/Bugtool/launch_bugtool.pl.

Feature Set Tables

The Cisco IOS software is packaged in feature sets consisting of software images—depending on the platform. Each feature set contains a specific set of Cisco IOS features.

Cisco IOS Release 12.4(11)SW3 supports the same feature sets as Cisco IOS Release 12.4(11)T, but Cisco IOS Release 12.4(11)SW3 can include new features supported by the Cisco 7200 and Cisco 7301 series routers.



Caution

Cisco IOS images with strong encryption (including, but not limited to, 168-bit Triple Data Encryption Standard [3DES] data encryption feature sets) are subject to United States government export controls and have limited distribution. Strong encryption images to be installed outside the United States are likely to require an export license. Customer orders may be denied or subject to delay because of United States government regulations. When applicable, purchaser and user must obtain local import and use authorizations for all encryption strengths. Please contact your sales representative or distributor for more information, or send an e-mail to export@cisco.com.

Cisco IOS software images are subject to deferral. Cisco recommends that you view the deferral notices at the following location to determine if your software release is affected:

<http://www.cisco.com/kobayashi/sw-center/sw-ios-advisories.shtml>

Table 3 lists the features and feature sets supported by the Cisco 7200 and Cisco 7301 series routers in Cisco IOS Release 12.4(11)SW and uses the following conventions:

- Yes—The feature is supported in the software image.
- No—The feature is not supported in the software image.
- In—The number in the “In” column indicates the Cisco IOS release in which the feature was introduced. For example, a “3” would mean a feature was introduced in 12.4(11)SW3. If a cell in this column is empty, the feature was included in the initial base release.



Note

These release notes are not cumulative and list only features that are new to Cisco IOS Release 12.4(11)SW. The parent release for Cisco IOS Release 12.4(11)SW is Cisco IOS Release 12.4(11)T. For information about inherited features, refer to Cisco.com or Cisco Feature Navigator. For Cisco.com, either go to [Cisco.com](http://www.cisco.com) and select the appropriate software release under **Products and Service** and **IOS Software** or go to <http://www.cisco.com/univercd/home/index.htm> and select the appropriate software release under **Cisco IOS Software** and **Release Notes**. You can use the Cisco Feature Navigator tool at <http://www.cisco.com/go/fn>.

Table 3 Feature List by Feature Set for the Cisco 7000 Family Routers

Features	In	Software Images by Feature Sets	
		c7200-itpk9-mz	c7301-itpk9-mz
C-Link Backup Routing of M3UA/SUA Traffic		Yes	Yes
Enhanced Loadsharing	2	Yes	Yes
GWS SCCP Error Return		Yes	Yes
Integrated GWS and MLR Triggers	2	Yes	Yes
MLR SCCP Error Return		Yes	Yes

Table 3 Feature List by Feature Set for the Cisco 7000 Family Routers

Features	In	Software Images by Feature Sets	
		c7200-itpk9-mz	c7301-itpk9-mz
Multiple HSL PVCs per Physical ATM interface		Yes	Yes
SCCP/MAP Address Modification for SRI-SM Messages		Yes	Yes

New and Changed Information

The following sections list the new hardware and software features supported by the Cisco 7200 and Cisco 7301 series routers for Cisco IOS Release 12.4(11)SW.

New Hardware Features in Release 12.4(11)SW3

There are no new software features supported in Cisco IOS Release 12.4(11)SW3.

New Software Features in Release 12.4(11)SW3

There are no new software features supported in Cisco IOS Release 12.4(11)SW3.

New Hardware Features in Release 12.4(11)SW2

There are no new software features supported in Cisco IOS Release 12.4(11)SW2.

New Software Features in Release 12.4(11)SW2

The following new software features are supported by the Cisco 7200 and Cisco 7301 series routers for Cisco IOS Release 12.4(11)SW2:

- [Enhanced Loadsharing, page 6](#)
- [Integrated GWS and MLR Triggers, page 7](#)

Enhanced Loadsharing

The Enhanced Loadsharing feature creates a 3-bit hash from a subset of bits (6 each) taken from the Originating Point Code (OPC) and Destination Point Code (DPC). Concatenating this hash with the SLS yields a 7-bit value that is then used to select a link (SLC) from a 128 entry SLS->SLC mapping table. This results in a much more even load distribution among available links.

The feature also allows flexibility in choosing the subset of bits from the OPC and DPC using the `opc-shift` and `dpc-shift` parameters and simultaneous configuration of `sls-shift`, at the global and/or linkset level.

Refer to the following document for more information about Enhanced Loadsharing:

IP Transfer Point

Integrated GWS and MLR Triggers

In Cisco IOS 12.4(11)SW2 and later releases, Multi Layer Routing (MLR) triggers and Gateway Screening (GWS) are integrated. GWS determines which packets are intercepted by MLR. You can configure MLR triggers using the GWS infrastructure, GWS tables, and MLR variables.

Refer to the following document for more information about Integrated GWS and MLR Triggers:

IP Transfer Point

New Hardware Features in Release 12.4(11)SW1

There are no new hardware features supported in Cisco IOS Release 12.4(11)SW1.

New Software Features in Release 12.4(11)SW1

There are no new software features supported in Cisco IOS Release 12.4(11)SW1.

New Hardware Features in Release 12.4(11)SW

There are no new hardware features supported in Cisco IOS Release 12.4(11)SW.

New Software Features in Release 12.4(11)SW

The following new software features are supported by the Cisco 7200 and Cisco 7301 series routers for Cisco IOS Release 12.4(11)SW:

- [C-Link Backup Routing of M3UA/SUA Traffic, page 7](#)
- [GWS SCCP Error Return, page 8](#)
- [MLR SCCP Error Return, page 8](#)
- [Multiple HSL PVCs per Physical ATM interface, page 8](#)
- [SCCP/MAP Address Modification for SRI-SM Messages, page 8](#)

C-Link Backup Routing of M3UA/SUA Traffic

Cisco IOS Release 12.4(11)SW supports a C-link Backup Routing feature that provides backup routing to MTP3 User Adaptation Layer (M3UA) and SCCP User Adaptation (SUA) application servers (ASs). It uses a Message Transfer Part Level 3 (MTP3)/M2PA linkset to a remote signaling gateway (SG) serving the same ASs over Stream Control Transmission Protocol (SCTP)/IP. This configurable software feature is available to any IP Transfer Point (ITP) running a sigtran protocol (M3UA and/or SUA) and offloaded MTP3. The remote SG that is reachable through the C-link may be another ITP, or any SG serving the same ASs.

Refer to the following document for more information about C-link Backup Routing:

IP Transfer Point (ITP)

GWS SCCP Error Return

Cisco IOS Release 12.4(11)SW allows you to configure Gateway Screening (GWS) to return a unitdata service (UDTS) to the source of the Signaling Connection Control Part (SCCP) packet when the SCCP packet is dropped. You configure a return UDTS when you define the gateway screening action set in enhanced GWS.

Refer to the following document for more information about the GWS SCCP error return feature:

IP Transfer Point (ITP)

MLR SCCP Error Return

Cisco IOS Release 12.4(11)SW allows you to configure Multi Layer Routing (MLR) to return a unitdata service (UDTS) to the source of the Signaling Connection Control Part (SCCP) packet when the SCCP packet is blocked. You configure this by specifying an optional `sccp-error` parameter on block results in MLR rules and MLR address tables.

Refer to the following document for more information about the MLR SCCP error return feature:

IP Transfer Point (ITP)

Multiple HSL PVCs per Physical ATM interface

Cisco IOS Release 12.4(11)SW allows multiple High Speed Link (HSL) permanent virtual circuits (PVCs) per physical Asynchronous Transfer Mode (ATM) interface. This is done through the support of subinterface configuration on the ATM link. Prior to Cisco IOS Release 12.4(11)SW, you could only configure the ATM interface, not any subinterfaces. The ability to create additional subinterfaces allows for more qssals, since only one qssal is allowed per interface or subinterface.

Refer to the following document for more information about the multiple HSL PVCs feature:

IP Transfer Point (ITP)

SCCP/MAP Address Modification for SRI-SM Messages

Cisco IOS Release 12.4(11)SW permits Signaling Connection Control Part (SCCP) and MAP address modification using a Multi-Layer Routing (MLR) **modify-profile**. MLR currently supports modifying only the service center address (`orig-smsc`) and the calling party address (`CgPA`) for SRI-SM messages.

With Cisco IOS Release 12.4(11)SW, the user can also now optionally configure the desired action for failed modifications using the **modify-failure** command within the MLR options submode. A user can also configure the **preserve-opc** function within the global MLR options submode. The **preserve-opc** function retains the original Originating Point Code (OPC). The user may configure MLR to return a unitdata service (UDTS) to the source of the SCCP packet when the SCCP packet is blocked by specifying an optional **sccp-error** parameter on block results.

Refer to the following document for more information about SCCP and MAP address modification:

IP Transfer Point (ITP)

MIBs

To locate and download MIBs for selected platforms, Cisco IOS releases, and feature sets, use Cisco MIB Locator found at the following URL:

<http://tools.cisco.com/ITDIT/MIBS/servlet/index>

If Cisco MIB Locator does not support the MIB information that you need, you can also obtain a list of supported MIBs and download MIBs from the Cisco MIBs page at the following URL:

<http://www.cisco.com/public/sw-center/netmgmt/cmtk/mibs.shtml>

To access Cisco MIB Locator, you must have an account on Cisco.com. If you have forgotten or lost your account information, send a blank e-mail to cco-locksmith@cisco.com. An automatic check will verify that your e-mail address is registered with Cisco.com. If the check is successful, account details with a new random password will be e-mailed to you. Qualified users can establish an account on Cisco.com by following the directions found at this URL:

<http://tools.cisco.com/RPF/register/register.do>

Caveats for Cisco IOS Release 12.4 SW

Caveats describe unexpected behavior in Cisco IOS software releases. Severity 1 caveats are the most serious caveats; severity 2 caveats are less serious. Severity 3 caveats are moderate caveats, and only select severity 3 caveats are included in the caveats document.

This section contains open and resolved caveats for the current Cisco IOS maintenance release.

All caveats in Cisco IOS Release 12.4(11)T that apply to the Cisco 7200 and Cisco 7301 series routers are also in Cisco IOS Release 12.4(11)SW.

For information on caveats in Cisco IOS Release 12.4(11)T, see *Caveats for Cisco IOS Release 12.4T*, which lists severity 1 and 2 caveats and select severity 3 caveats and is located on [Cisco.com](http://www.cisco.com).



Note

If you have an account on Cisco.com, you can also use the Bug Toolkit to find select caveats of any severity. To reach the Bug Toolkit, **log in** to [Cisco.com](http://www.cisco.com) and click **Products and Services > Cisco IOS Software > Cisco IOS Software Releases 12.2 > Troubleshooting > Bug Toolkit**. Another option is to go to http://www.cisco.com/cgi-bin/Support/Bugtool/launch_bugtool.pl. (If the defect that you have requested cannot be displayed, this may be due to one or more of the following reasons: the defect number does not exist, the defect does not have a customer-visible description yet, or the defect has been marked Cisco Confidential.)

The *Dictionary of Internetworking Terms and Acronyms* contains definitions of acronyms that are not defined in this document:

<http://www.cisco.com/univercd/cc/td/doc/cisintwk/ita/index.htm>

Table 4 Caveats Reference for 12.4(11)SW

DDTS Number	Software Release Caveat Corrected	Caveat Open
CSCsd85587	12.4(11)SW1	No
CSCsg11686	12.4(11)SW2	No
CSCsg27676	12.4(11)SW2	No
CSCsh595601	12.4(11)SW2	No
CSCsh69956	12.4(11)SW2	No
CSCsi60319	12.4(11)SW2	No
CSCsi68841	12.4(11)SW3	No
CSCsj44081	12.4(11)SW3	No
CSCsj53415	12.4(11)SW3	No

Open Caveats—Cisco IOS Release 12.4(11)SW3

This section documents possible unexpected behavior by Cisco IOS Release 12.4(11)SW3 and describes only severity 1 and 2 caveats and select severity 3 caveats.

There are no known open caveats for Cisco IOS Release 12.4(11)SW3.

Resolved Caveats—Cisco IOS Release 12.4(11)SW3

All the caveats listed in this section are resolved in Cisco IOS Release 12.4(11)SW3. This section describes only severity 1 and 2 caveats and select severity 3 caveats.

- CSCsi68841
After configuring a cs7 group, ITP crashes during normal traffic processing.
There are no known workarounds.
- CSCsj44081
Improper use of data structures occurs in Cisco IOS. The Cisco IOS software has been enhanced with the introduction of additional software checks to signal the improper use of data structures. The %DATACORRUPTION-1-DATAINCONSISTENCY error message is now preceded by a timestamp, and the error message is then followed by a traceback.
There are no known workarounds.
- CSCsj53415
When traffic goes through global title translation (GTT), which results in the traffic going to an xUA application server (AS), but the traffic is blocked by outbound Gateway Screening (GWS), the buffer is lost. Eventually all buffers are exhausted, and the links fail and do not recover. The **show buffers** command displays an extremely large number of cs7 buffers and an extremely large number of misses in the global pool. The cs7 buffers keep increasing until the links fail.

Workaround: To prevent the problem, remove the outbound GWS rule. If the links fail, you must reload the individual line card that contains the inbound links, or reload the entire router.

Open Caveats—Cisco IOS Release 12.4(11)SW2

This section documents possible unexpected behavior by Cisco IOS Release 12.4(11)SW2 and describes only severity 1 and 2 caveats and select severity 3 caveats.

There are no known open caveats for Cisco IOS Release 12.4(11)SW2.

Resolved Caveats—Cisco IOS Release 12.4(11)SW2

All the caveats listed in this section are resolved in Cisco IOS Release 12.4(11)SW2. This section describes only severity 1 and 2 caveats and select severity 3 caveats.

- CSCsg11686

ITP sends an SIE instead of an SIN when a failed link is reactivating.

This issue occurs when a linkset has two links and one of the links is brought out of service (for example, as a result of a remote disconnect). Although the linkset status remains "available" when the failed link is re-activated, the ITP sends an SIE instead of an SIN (as shown by the increase of the OMLSSU_XMIT_SIECount by 1 for the failed link in the output of **show cs7 mtp2 statistics** command). Because one link is still available, an SIN should be sent instead of an SIE.

There are no known workarounds.

- CSCsg27676

The Signaling Gateway Mate Protocol (SGMP) link between ITP mates may fail when an Application Server Process (ASP) becomes active.

This issue occurs when an ASP configured for a loadshare bindings Application Server (AS) becomes active, and thousands of ASP bindings exist on the ITP.

There are no known workarounds.

- CSCsh59560

Cisco IP Transfer Point (ITP) running Cisco IOS Release 12.4(11)SW reports the Message Transfer Part Level 3 (MTP3) route as Avail, but the destination is reported as INACC.

This issue occurs during a system boot while processing a large route table because the MTP3 restart may not complete before the mtp3 timers expire. As a result, the system may be in an intermediate state where routes are available but the destination is inaccessible.

Workaround: Reduce the number of routes to 8000 total routes/4000 destinations.

- CSCsh69956

Syslog messages and Simple Network Management Protocol (SNMP) traps are not generated for clock transitions on the Inverse Multiplexing over ATM (IMA) port adapter.

There are no known workarounds.

- CSCsi60319

The responding Home Location Register (HLR) E.164 address is not returned to the Short Message Peer-to-Peer (SMPP) client when handling error responses from an HLR.

This condition only affects the Multimedia Message Service Center (MMSC) gateway feature when clients submit a GetIMSI request and an HLR responds with an error.

There are no known workarounds.

Open Caveats—Cisco IOS Release 12.4(11)SW1

This section documents possible unexpected behavior by Cisco IOS Release 12.4(11)SW1 and describes only severity 1 and 2 caveats and select severity 3 caveats.

- CSCsh59560

Cisco IP Transfer Point (ITP) running Cisco IOS Release 12.4(11)SW reports the Message Transfer Part Level 3 (MTP3) route as Avail, but the destination is reported as INACC.

This issue occurs during a system boot while processing a large route table because the MTP3 restart may not complete before the mtp3 timers expire. As a result, the system may be in an intermediate state where routes are available but the destination is inaccessible.

Workaround: Reduce the number of routes 8000 total routes/4000 destinations.

Resolved Caveats—Cisco IOS Release 12.4(11)SW1

All the caveats listed in this section are resolved in Cisco IOS Release 12.4(11)SW1. This section describes only severity 1 and 2 caveats and select severity 3 caveats.

- CSCsd85587

A vulnerability has been discovered in a third party cryptographic library which is used by a number of Cisco products. This vulnerability may be triggered when a malformed Abstract Syntax Notation One (ASN.1) object is parsed. Due to the nature of the vulnerability it may be possible, in some cases, to trigger this vulnerability without a valid certificate or valid application-layer credentials (such as a valid username or password).

Successful repeated exploitation of any of these vulnerabilities may lead to a sustained Denial-of-Service (DoS); however, vulnerabilities are not known to compromise either the confidentiality or integrity of the data or the device. These vulnerabilities are not believed to allow an attacker will not be able to decrypt any previously encrypted information.

The vulnerable cryptographic library is used in the following Cisco products:

- Cisco IOS, documented as Cisco bug ID CSCsd85587
- Cisco IOS XR, documented as Cisco bug ID CSCsg41084
- Cisco PIX and ASA Security Appliances, documented as Cisco bug ID CSCse91999
- Cisco Unified CallManager, documented as Cisco bug ID CSCsg44348
- Cisco Firewall Service Module (FWSM)

This vulnerability is also being tracked by CERT/CC as VU#754281.

Cisco has made free software available to address this vulnerability for affected customers. There are no workarounds available to mitigate the effects of the vulnerability.

This advisory is posted at <http://www.cisco.com/warp/public/707/cisco-sa-20070522-crypto.shtml>.



Note

Another related advisory is posted together with this Advisory. It also describes vulnerabilities related to cryptography that affect Cisco IOS. A combined software table for Cisco IOS only is available at <http://www.cisco.com/warp/public/707/cisco-sa-20070522-cry-bundle.shtml> and can be used to choose a software release which fixes all security vulnerabilities published as of May 22, 2007. The related advisory is published at <http://www.cisco.com/warp/public/707/cisco-sa-20070522-SSL.shtml>.

Open Caveats—Cisco IOS Release 12.4(11)SW

This section documents possible unexpected behavior by Cisco IOS Release 12.4(11)SW and describes only severity 1 and 2 caveats and select severity 3 caveats.

- CSCsh59560

Cisco IP Transfer Point (ITP) running Cisco IOS Release 12.4(11)SW reports the Message Transfer Part Level 3 (MTP3) route as Avail, but the destination is reported as INACC.

This issue occurs during a system boot while processing a large route table because the MTP3 restart may not complete before the mtp3 timers expire. As a result, the system may be in an intermediate state where routes are available but the destination is inaccessible.

Workaround: Reduce the number of routes 8000 total routes/4000 destinations.

Resolved Caveats—Cisco IOS Release 12.4(11)SW

All the caveats listed in this section are resolved in Cisco IOS Release 12.4(11)SW. This section describes only severity 1 and 2 caveats and select severity 3 caveats.

There are no known resolved caveats for Cisco IOS Release 12.4(11)SW.

Related Documentation

The following sections describe the documentation available for the Cisco 7200 and Cisco 7301 series routers. These documents consist of hardware and software installation guides, Cisco IOS configuration guides and command references, system error messages, feature modules, and other documents.

Documentation is available as printed manuals or electronic documents, except for feature modules, which are available online on [Cisco.com](http://www.cisco.com) and <http://www.cisco.com/univercd/home/index.htm>.

Use these release notes with these documents:

- [Release-Specific Documents, page 13](#)
- [Platform-Specific Documents, page 14](#)
- [Cisco IOS Release 12.4T Documentation Set, page 15](#)

Release-Specific Documents

The following documents are specific to Cisco IOS Release 12.4 T and are located on [Cisco.com](http://www.cisco.com) and <http://www.cisco.com/univercd/home/index.htm>:

- *Cross-Platform Release Notes for Cisco IOS Release 12.4 T*

On [Cisco.com](http://www.cisco.com) at:

Technical Support & Documentation > Documentation > Cisco IOS Software > Cisco IOS Software Releases 12.4T > General Information > Release Notes

On <http://www.cisco.com/univercd/home/index.htm> at:

Cisco IOS Software > Cisco IOS Release 12.4T > Release Notes

- Product bulletins, field notices, and other release-specific documents at <http://www.cisco.com/univercd/home/index.htm>

- *Caveats for Cisco IOS Release 12.4 T*

As a supplement to the caveats listed in “[Caveats for Cisco IOS Release 12.4 SW](#)” in these release notes, see *Caveats for Cisco IOS Release 12.4 T*, which contains caveats applicable to all platforms for all maintenance releases of Cisco IOS Release 12.4 T.

On [Cisco.com](#) at:

Technical Support & Documentation > Documentation > Cisco IOS Software > Cisco IOS Software Releases 12.4T > General Information > Release Notes > Cross-Platform Release Notes for Cisco IOS Release 12.4T, Part 5: Caveats

On <http://www.cisco.com/univercd/home/index.htm> at:

Cisco IOS Software > Cisco IOS Release 12.4T > Release Notes > Cross-Platform Release Notes for Cisco IOS Release 12.4T, Part 5: Caveats



Note

If you have an account on [Cisco.com](#), you can also use the Bug Toolkit to find select caveats of any severity. To reach the Bug Toolkit, **log in** to [Cisco.com](#) and click **Technical Support & Documentation > Tools & Resources > Bug Toolkit**. Another option is to go to http://www.cisco.com/cgi-bin/Support/Bugtool/launch_bugtool.pl. (If the defect that you have requested cannot be displayed, this may be due to one or more of the following reasons: the defect number does not exist, the defect does not have a customer-visible description yet, or the defect has been marked Cisco Confidential.)

Platform-Specific Documents

These documents are available for the Cisco 7200 and Cisco 7301 series routers on [Cisco.com](#):

- *Cisco 7200 VXR Installation and Configuration Guide*
- *Cisco 7200 Routers Quick Start Guide*
- *Cisco 7301 Installation and Configuration Guide*
- *Cisco 7301 Router Quick Start Guide*

On [Cisco.com](#) at:

Products & Services: Technical Support and Documentation: Documentation: Routers: Cisco 7200 Series Routers

On <http://www.cisco.com/univercd/home/index.htm> at:

Cisco Product Documentation: Routers

Cisco IOS Release 12.4T Documentation Set

Table 5 lists the Cisco IOS Release 12.4T configuration guides and command references.



Note

Some of the configuration guides in the following table reference Cisco IOS Release 12.4 versions of these documents. In these instances, no distinct Cisco IOS Release 12.4T version of the guide exists and the necessary configuration information is in the Cisco IOS Release 12.4 version of the document. Keep in mind that Cisco IOS Release 12.4(11)SW is based on Cisco IOS Release **12.4(11)T**. All features in Cisco IOS Release **12.4(11)T** are in Cisco IOS Release 12.4(11)SW. **The references to Cisco IOS Release 12.4 configuration guides in the following table do not indicate that all features in Cisco IOS Release 12.4 are in Cisco IOS Release 12.4(11)SW.**

Table 5 Cisco IOS Release 12.4T Configuration Guides and Command References

Configuration Guide and Command Reference Titles	Description
IP	
Cisco IOS BGP Configuration Guide , Release 12.4T	The configuration guide describes configuration tasks to configure various advanced Border Gateway Protocol (BGP) features, such as BGP next-hop address tracking, BGP Nonstop Forwarding (NSF) awareness, and route dampening. BGP is an interdomain routing protocol designed to provide loop-free routing between organizations.
Cisco IOS DHCP Configuration Guide , Release 12.4T	The configuration guide describes the concepts and the tasks needed to configure the Cisco IOS Dynamic Host Configuration Protocol (DHCP).
Cisco IOS IP Addressing Services Configuration Guide , Release 12.4 Cisco IOS IP Addressing Services Command Reference , Release 12.4T	The configuration guide is a task-oriented guide to configuring IP addressing and services, including Network Address Translation (NAT), Domain Name System (DNS), and Dynamic Host Configuration Protocol (DHCP). The command reference provides detailed information about the commands used in the configuration guide.
Cisco IOS IP Application Services Configuration Guide , Release 12.4T Cisco IOS Application Services Command Reference , Release 12.4T	The configuration guide is a task-oriented guide to configuring IP application services, including IP access lists, Web Cache Communication Protocol (WCCP), Gateway Load Balancing Protocol (GLBP), Server Load Balancing (SLB), Hot Standby Router Protocol (HSRP), and Virtual Router Redundancy Protocol (VRRP). The command reference provides detailed information about the commands used in the configuration guide.
Cisco IOS IP Mobility Configuration Guide , Release 12.4 Cisco IOS IP Mobility Command Reference , Release 12.4T	The configuration guide is a task-oriented guide to configuring Mobile IP and Cisco Mobile Networks. The command reference provides detailed information about the commands used in the configuration guide.
Cisco IOS IP Multicast Configuration Guide , Release 12.4 Cisco IOS IP Multicast Command Reference , Release 12.4T	The configuration guide is a task-oriented guide to configuring IP multicast, including Protocol Independent Multicast (PIM), Internet Group Management Protocol (IGMP), Distance Vector Multicast Routing Protocol (DVMRP), and Multicast Source Discovery Protocol (MSDP). The command reference provides detailed information about the commands used in the configuration guide.

Table 5 Cisco IOS Release 12.4T Configuration Guides and Command References (Continued)

Configuration Guide and Command Reference Titles	Description
<p>Cisco IOS IP Routing Protocols Configuration Guide, Release 12.4</p> <p>Cisco IOS IP Routing Protocols Command Reference, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring IP routing protocols, including Border Gateway Protocol (BGP), Intermediate System-to-Intermediate System (IS-IS), and Open Shortest Path First (OSPF). The command reference provides detailed information about the commands used in the configuration guide.</p>
<p>Cisco IOS IP Switching Configuration Guide, Release 12.4</p> <p>Cisco IOS IP Switching Command Reference, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring IP switching features, including Cisco Express Forwarding (CEF), fast switching, and Multicast Distributed Switching (MDS). The command reference provides detailed information about the commands used in the configuration guide.</p>
<p>Cisco IOS IPv6 Configuration Guide, Release 12.4T</p> <p>Cisco IOS IPv6 Command Reference, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring IP version 6 (IPv6), including IPv6 broadband access, IPv6 data-link layer, IPv6 multicast routing, IPv6 quality of service (QoS), IPv6 routing, IPv6 services and management, and IPv6 tunnel services. The command reference provides detailed information about the commands used in the configuration guide.</p>
<p>Cisco IOS NAT Configuration Guide, Release 12.4T</p>	<p>The configuration guide contains configuration documentation for s configuring NAT for IP address conservation and using application level gateways with NAT.</p>
<p>Cisco IOS Optimized Edge Routing Configuration Guide, Release 12.4T</p> <p>Cisco IOS Optimized Edge Routing Command Reference, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring Optimized Edge Routing (OER) features, including OER prefix learning, OER prefix monitoring, OER operational modes, and OER policy configuration. The command reference provides detailed information about the commands used in the configuration guide.</p>
Security and VPN	
<p>Cisco IOS Security Configuration Guide, Release 12.4T</p> <p>Cisco IOS Security Command Reference, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring various aspects of security, including terminal access security, network access security, accounting, traffic filters, router access, and network data encryption with router authentication. The command reference provides detailed information about the commands used in the configuration guide.</p>
QoS	
<p>Cisco IOS Quality of Service Solutions Configuration Guide, Release 12.4T</p> <p>Cisco IOS Quality of Service Solutions Command Reference, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring quality of service (QoS) features, including traffic classification and marking, traffic policing and shaping, congestion management, congestion avoidance, and signaling. The command reference provides detailed information about the commands used in the configuration guide.</p>
LAN Switching	
<p>Cisco IOS LAN Switching Configuration Guide, Release 12.4</p> <p>Cisco IOS LAN Switching Command Reference, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to local-area network (LAN) switching features, including configuring routing between virtual LANs (VLANs) using Inter-Switch Link (ISL) encapsulation, IEEE 802.10 encapsulation, and IEEE 802.1Q encapsulation. The command reference provides detailed information about the commands used in the configuration guide.</p>

Table 5 Cisco IOS Release 12.4T Configuration Guides and Command References (Continued)

Configuration Guide and Command Reference Titles	Description
Multiprotocol Label Switching (MPLS)	
<p><i>Cisco IOS Multiprotocol Label Switching Configuration Guide</i>, Release 12.4</p> <p><i>Cisco IOS Multiprotocol Label Switching Command Reference</i>, Release 12.4T</p>	The configuration guide is a task-oriented guide to configuring Multiprotocol Label Switching (MPLS), including MPLS Label Distribution Protocol, MPLS traffic engineering, and MPLS Virtual Private Networks (VPNs). The command reference provides detailed information about the commands used in the configuration guide.
Network Management	
<p><i>Cisco IOS IP SLAs Monitoring Technology Configuration Guide</i>, Release 12.4</p> <p><i>Cisco IOS IP SLAs Command Reference</i>, Release 12.4T</p>	The configuration guide is a task-oriented guide to configuring the Cisco IOS IP Service Level Assurances (IP SLAs) feature. The command reference provides detailed information about the commands used in the configuration guide.
<p><i>Cisco IOS NetFlow Configuration Guide</i>, Release 12.4T</p> <p><i>Cisco IOS NetFlow Command Reference</i>, Release 12.4T</p>	The configuration guide is a task-oriented guide to NetFlow features, including configuring NetFlow to analyze network traffic data, configuring NetFlow aggregation caches and export features, and configuring Simple Network Management Protocol (SNMP) and NetFlow MIB features. The command reference provides detailed information about the commands used in the configuration guide.
<p><i>Cisco IOS Network Management Configuration Guide</i>, Release 12.4</p> <p><i>Cisco IOS Network Management Command Reference</i>, Release 12.4T</p>	The configuration guide is a task-oriented guide to network management features, including performing basic system management, performing troubleshooting and fault management, configuring Cisco Discovery Protocol (CDP), configuring Cisco Networking Services (CNS), configuring DistributedDirector, and configuring Simple Network Management Protocol (SNMP). The command reference provides detailed information about the commands used in the configuration guide.
Voice	
<p><i>Cisco CallManager and Cisco IOS Interoperability Configuration Guide</i>, Release 12.4T</p>	The configuration guide provides configuration information about Cisco IOS voice features for Cisco Unified CallManager and Cisco IOS Interoperability.
<p><i>Cisco IOS Voice Configuration Library</i></p> <p><i>Cisco IOS Voice Command Reference</i></p>	The configuration library is a task-oriented collection of configuration guides, application guides, a troubleshooting guide, feature documents, a library preface, a voice glossary, and more. It also covers Cisco IOS support for voice call control protocols, interoperability, physical and virtual interface management, and troubleshooting. In addition, the library includes documentation for IP telephony applications. The command reference provides detailed information about the commands used in the configuration library.
Wireless / Mobility	
<p><i>Cisco IOS Mobile Wireless Gateway GPRS Support Node Configuration Guide</i>, Release 12.4</p> <p><i>Cisco IOS Mobile Wireless Gateway GPRS Support Node Command Reference</i>, Release 12.4T</p>	The configuration guide is a task-oriented guide to understanding and configuring a Cisco IOS Gateway GPRS Support Node (GGSN) in a 2.5G General Packet Radio Service (GPRS) and 3G Universal Mobile Telecommunication System (UMTS) network. The command reference provides detailed information about the commands used in the configuration guide.

Table 5 Cisco IOS Release 12.4T Configuration Guides and Command References (Continued)

Configuration Guide and Command Reference Titles	Description
<p><i>Cisco IOS Mobile Wireless Home Agent Configuration Guide</i>, Release 12.4</p> <p><i>Cisco IOS Mobile Wireless Home Agent Command Reference</i>, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to understanding and configuring the Cisco Mobile Wireless Home Agent, which is an anchor point for mobile terminals for which Mobile IP or Proxy Mobile IP services are provided. The command reference provides detailed information about the commands used in the configuration guide.</p>
<p><i>Cisco IOS Mobile Wireless Packet Data Serving Node Configuration Guide</i>, Release 12.4</p> <p><i>Cisco IOS Mobile Wireless Packet Data Serving Node Command Reference</i>, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to understanding and configuring the Cisco Packet Data Serving Node (PDSN), a wireless gateway between the mobile infrastructure and standard IP networks that enables packet data services in a Code Division Multiple Access (CDMA) environment. The command reference provides detailed information about the commands used in the configuration guide.</p>
<p><i>Cisco IOS Mobile Wireless Radio Access Networking Configuration Guide</i>, Release 12.4</p> <p><i>Cisco IOS Mobile Wireless Radio Access Networking Command Reference</i>, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to understanding and configuring Cisco IOS Radio Access Network products. The command reference provides detailed information about the commands used in the configuration guide.</p>
<p><i>Cisco IOS Wireless LAN Configuration Guide</i>, Release 12.4T</p>	<p>The configuration guide provides the conceptual information, configuration tasks, and examples to help you configure and monitor a "wireless-aware" router using the Cisco IOS CLI, which can be used through a console port or Telnet session.</p>
<p>Long Reach Ethernet (LRE) and Digital Subscriber Line (xDSL)</p>	
<p><i>Cisco IOS Broadband Access Aggregation and DSL Configuration Guide</i>, Release 12.4</p> <p><i>Cisco IOS Broadband Access Aggregation and DSL Command Reference</i>, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring broadband access aggregation and digital subscriber line features. The command reference provides detailed information about the commands used in the configuration guide.</p>
<p><i>Cisco IOS Service Selection Gateway Configuration Guide</i>, Release 12.4</p> <p><i>Cisco IOS Service Selection Gateway Command Reference</i>, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring Service Selection Gateway (SSG) features, including subscriber authentication, service access, and accounting. The command reference provides detailed information about the commands used in the configuration guide.</p>
<p>Dial—Access</p>	
<p><i>Cisco IOS Dial Technologies Configuration Guide</i>, Release 12.4</p> <p><i>Cisco IOS Dial Technologies Command Reference</i>, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring lines, modems, and ISDN services. This guide also contains information about configuring dialup solutions, including solutions for remote sites dialing in to a central office, Internet service providers (ISPs), ISP customers at home offices, enterprise WAN system administrators implementing dial-on-demand routing, and other corporate environments. The command reference provides detailed information about the commands used in the configuration guide.</p>

Table 5 Cisco IOS Release 12.4T Configuration Guides and Command References (Continued)

Configuration Guide and Command Reference Titles	Description
<p><i>Cisco IOS VPDN Configuration Guide</i>, Release 12.4T</p> <p><i>Cisco IOS VPDN Command Reference</i>, Release 12.4T</p>	<p>This book contains the commands used to configure and maintain a Cisco IOS virtual private dialup network (VPDN). The commands are listed alphabetically.</p>
Asynchronous Transfer Mode (ATM)	
<p><i>Cisco IOS Asynchronous Transfer Mode Configuration Guide</i>, Release 12.4</p> <p><i>Cisco IOS Asynchronous Transfer Mode Command Reference</i>, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring Asynchronous Transfer Mode (ATM), including WAN ATM, LAN ATM, and multiprotocol over ATM (MPOA). The command reference provides detailed information about the commands used in the configuration guide.</p>
WAN	
<p><i>Cisco IOS Wide-Area Networking Configuration Guide</i>, Release 12.4</p> <p><i>Cisco IOS Wide-Area Networking Command Reference</i>, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring wide-area network (WAN) features, including: Layer 2 Tunneling Protocol Version 3 (L2TPv3); Frame Relay; Link Access Procedure, Balanced (LAPB); and X.25. The command reference provides detailed information about the commands used in the configuration guide.</p>
System Management	
<p><i>Cisco IOS Configuration Fundamentals Configuration Guide</i>, Release 12.4</p> <p><i>Cisco IOS Configuration Fundamentals Command Reference</i>, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to using Cisco IOS software to configure and maintain Cisco routers and access servers, including information about using the Cisco IOS command-line interface (CLI), loading and maintaining system images, using the Cisco IOS file system, using the Cisco IOS Web browser user interface (UI), and configuring basic file transfer services. The command reference provides detailed information about the commands used in the configuration guide.</p>
<p><i>Cisco IOS Interface and Hardware Component Configuration Guide</i>, Release 12.4</p> <p><i>Cisco IOS Interface and Hardware Component Command Reference</i>, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring and managing interfaces and hardware components, including dial shelves, LAN interfaces, logical interfaces, serial interfaces, and virtual interfaces. The command reference provides detailed information about the commands used in the configuration guide.</p>

Table 5 Cisco IOS Release 12.4T Configuration Guides and Command References (Continued)

Configuration Guide and Command Reference Titles	Description
IBM Technologies	
<p>Cisco IOS Bridging and IBM Networking Configuration Guide, Release 12.4</p> <p>Cisco IOS Bridging Command Reference, Release 12.4T</p> <p>Cisco IOS IBM Networking Command Reference, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring:</p> <ul style="list-style-type: none"> • Bridging features, including: transparent and source-route transparent (SRT) bridging, source-route bridging (SRB), Token Ring Inter-Switch Link (TRISL), and Token Ring Route Switch Module (TRRSM). • IBM network features, including: data-link switching plus (DLSw+), serial tunnel (STUN), and block serial tunnel (BSTUN); Logical Link Control, type 2 (LLC2), and Synchronous Data Link Control (SDLC); IBM Network Media Translation, including SDLC Logical Link Control (SDLLC) and Qualified Logical Link Control (QLLC); downstream physical unit (DSPU), Systems Network Architecture (SNA) service point, SNA Frame Relay Access, Advanced Peer-to-Peer Networking (APPN), native client interface architecture (NCIA) client/server topologies, and IBM Channel Attach. <p>The two command references provide detailed information about the commands used in the configuration guide.</p>
Additional and Legacy Protocols	
<p>Cisco IOS AppleTalk Configuration Guide, Release 12.4</p> <p>Cisco IOS AppleTalk Command Reference, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring the AppleTalk protocol. The command reference provides detailed information about the commands used in the configuration guide.</p>
<p>Cisco IOS DECnet Configuration Guide, Release 12.4</p> <p>Cisco IOS DECnet Command Reference, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring the DECnet protocol. The command reference provides detailed information about the commands used in the configuration guide.</p>
<p>Cisco IOS ISO CLNS Configuration Guide, Release 12.4</p> <p>Cisco IOS ISO CLNS Command Reference, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring International Organization for Standardization (ISO) Connectionless Network Service (CLNS). The command reference provides detailed information about the commands used in the configuration guide.</p>
<p>Cisco IOS Novell IPX Configuration Guide, Release 12.4</p> <p>Cisco IOS Novell IPX Command Reference, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring the Novell Internetwork Packet Exchange (IPX) protocol. The command reference provides detailed information about the commands used in the configuration guide.</p>
<p>Cisco IOS Terminal Services Configuration Guide, Release 12.4</p> <p>Cisco IOS Terminal Services Command Reference, Release 12.4T</p>	<p>The configuration guide is a task-oriented guide to configuring terminal services, including DEC, local-area transport (LAT), and X.25 packet assembler/disassembler (PAD). The command reference provides detailed information about the commands used in the configuration guide.</p>

Table 6 lists the documents and resources that support the Cisco IOS Release 12.4T software configuration guides and command references.

Table 6 Cisco IOS Release 12.4T Supporting Documents and Resources

Document Title	Description
<i>Cisco IOS Master Commands List, Release 12.4T</i>	An alphabetical listing of all the commands documented in the Cisco IOS Release 12.4T command references.
<i>Cisco IOS New, Modified, Replaced, and Removed Commands, Release 12.4T</i>	A listing of all the new, modified, replaced and removed commands for the Cisco IOS Release 12.4T release, grouped by maintenance release and ordered alphabetically within each group.
<i>System Messages for Cisco IOS Release 12.4 T</i>	These publications list and describe Cisco IOS system messages for Cisco IOS Release 12.4T. Not all system messages indicate problems with your system. Some are purely informational, and others may help diagnose problems with communications lines, internal hardware, or the system software.
<i>Cisco IOS Debug Command Reference, Release 12.4T</i>	This publication contains an alphabetical listing of the debug commands and their descriptions. Documentation for each command includes a brief description of its use, command syntax, and usage guidelines.
<i>Cisco IOS Fax and Modem Services over IP Application Guide, Release 12.4T</i>	The application guide includes descriptions and configuration instructions for fax and modem transmission capabilities on Cisco Voice over IP (VoIP) networks.
<i>Cross-Platform Release Notes for Cisco IOS Release 12.4T</i>	This documentation describes general release information, including information about supported platforms, feature sets, platform-specific notes, and Cisco IOS software defects.
<i>Dictionary of Internetworking Terms and Acronyms</i>	This publication compiles and defines the terms and acronyms used in the internetworking industry.
RFCs	RFCs are standards documents maintained by the Internet Engineering Task Force (IETF). Cisco IOS software documentation references supported RFCs when applicable. The full text of referenced RFCs may be obtained at the following URL: http://www.rfc-editor.org/
MIBs	MIBs are used for network monitoring. To locate and download MIBs for selected platforms, Cisco IOS releases, and feature sets, use Cisco MIB Locator found at the following URL: http://www.cisco.com/go/mibs

Obtaining Documentation

Cisco documentation and additional literature are available on Cisco.com. Cisco also provides several ways to obtain technical assistance and other technical resources. These sections explain how to obtain technical information from Cisco Systems.

Cisco.com

You can access the most current Cisco documentation at this URL:

<http://www.cisco.com/techsupport>

You can access the Cisco website at this URL:

<http://www.cisco.com>

You can access international Cisco websites at this URL:

http://www.cisco.com/public/countries_languages.shtml

Product Documentation DVD

Cisco documentation and additional literature are available in the Product Documentation DVD package, which may have shipped with your product. The Product Documentation DVD is updated regularly and may be more current than printed documentation.

The Product Documentation DVD is a comprehensive library of technical product documentation on portable media. The DVD enables you to access multiple versions of hardware and software installation, configuration, and command guides for Cisco products and to view technical documentation in HTML. With the DVD, you have access to the same documentation that is found on the Cisco website without being connected to the Internet. Certain products also have .pdf versions of the documentation available.

The Product Documentation DVD is available as a single unit or as a subscription. Registered Cisco.com users (Cisco direct customers) can order a Product Documentation DVD (product number DOC-DOCDVD=) from Cisco Marketplace at this URL:

<http://www.cisco.com/go/marketplace/>

Ordering Documentation

Beginning June 30, 2005, registered Cisco.com users may order Cisco documentation at the Product Documentation Store in the Cisco Marketplace at this URL:

<http://www.cisco.com/go/marketplace/>

Nonregistered Cisco.com users can order technical documentation from 8:00 a.m. to 5:00 p.m. (0800 to 1700) PDT by calling 1 866 463-3487 in the United States and Canada, or elsewhere by calling 011 408 519-5055. You can also order documentation by e-mail at tech-doc-store-mkpl@external.cisco.com or by fax at 1 408 519-5001 in the United States and Canada, or elsewhere at 011 408 519-5001.

Documentation Feedback

You can rate and provide feedback about Cisco technical documents by completing the online feedback form that appears with the technical documents on Cisco.com.

You can send comments about Cisco documentation to bug-doc@cisco.com.

You can submit comments by using the response card (if present) behind the front cover of your document or by writing to the following address:

Cisco Systems
Attn: Customer Document Ordering
170 West Tasman Drive
San Jose, CA 95134-9883

We appreciate your comments.

Cisco Product Security Overview

Cisco provides a free online Security Vulnerability Policy portal at this URL:

http://www.cisco.com/en/US/products/products_security_vulnerability_policy.html

From this site, you can perform these tasks:

- Report security vulnerabilities in Cisco products.
- Obtain assistance with security incidents that involve Cisco products.
- Register to receive security information from Cisco.

A current list of security advisories and notices for Cisco products is available at this URL:

<http://www.cisco.com/go/psirt>

If you prefer to see advisories and notices as they are updated in real time, you can access a Product Security Incident Response Team Really Simple Syndication (PSIRT RSS) feed from this URL:

http://www.cisco.com/en/US/products/products_psirt_rss_feed.html

Reporting Security Problems in Cisco Products

Cisco is committed to delivering secure products. We test our products internally before we release them, and we strive to correct all vulnerabilities quickly. If you think that you might have identified a vulnerability in a Cisco product, contact PSIRT:

- Emergencies—security-alert@cisco.com

An emergency is either a condition in which a system is under active attack or a condition for which a severe and urgent security vulnerability should be reported. All other conditions are considered nonemergencies.

- Nonemergencies — psirt@cisco.com

In an emergency, you can also reach PSIRT by telephone:

- 1 877 228-7302
- 1 408 525-6532



Tip

We encourage you to use Pretty Good Privacy (PGP) or a compatible product to encrypt any sensitive information that you send to Cisco. PSIRT can work from encrypted information that is compatible with PGP versions 2.x through 8.x.

Never use a revoked or an expired encryption key. The correct public key to use in your correspondence with PSIRT is the one linked in the Contact Summary section of the Security Vulnerability Policy page at this URL:

http://www.cisco.com/en/US/products/products_security_vulnerability_policy.html

The link on this page has the current PGP key ID in use.

Obtaining Technical Assistance

Cisco Technical Support provides 24-hour-a-day award-winning technical assistance. The Cisco Technical Support & Documentation website on Cisco.com features extensive online support resources. In addition, if you have a valid Cisco service contract, Cisco Technical Assistance Center (TAC) engineers provide telephone support. If you do not have a valid Cisco service contract, contact your reseller.

Cisco Technical Support & Documentation Website

The Cisco Technical Support & Documentation website provides online documents and tools for troubleshooting and resolving technical issues with Cisco products and technologies. The website is available 24 hours a day, at this URL:

<http://www.cisco.com/techsupport>

Access to all tools on the Cisco Technical Support & Documentation website requires a Cisco.com user ID and password. If you have a valid service contract but do not have a user ID or password, you can register at this URL:

<http://tools.cisco.com/RPF/register/register.do>



Note

Use the Cisco Product Identification (CPI) tool to locate your product serial number before submitting a web or phone request for service. You can access the CPI tool from the Cisco Technical Support & Documentation website by clicking the **Tools & Resources** link under Documentation & Tools. Choose **Cisco Product Identification Tool** from the Alphabetical Index drop-down list, or click the **Cisco Product Identification Tool** link under Alerts & RMAs. The CPI tool offers three search options: by product ID or model name; by tree view; or for certain products, by copying and pasting **show** command output. Search results show an illustration of your product with the serial number label location highlighted. Locate the serial number label on your product and record the information before placing a service call.

Submitting a Service Request

Using the online TAC Service Request Tool is the fastest way to open S3 and S4 service requests. (S3 and S4 service requests are those in which your network is minimally impaired or for which you require product information.) After you describe your situation, the TAC Service Request Tool provides recommended solutions. If your issue is not resolved using the recommended resources, your service request is assigned to a Cisco engineer. The TAC Service Request Tool is located at this URL:

<http://www.cisco.com/techsupport/servicerequest>

For S1 or S2 service requests or if you do not have Internet access, contact the Cisco TAC by telephone. (S1 or S2 service requests are those in which your production network is down or severely degraded.) Cisco engineers are assigned immediately to S1 and S2 service requests to help keep your business operations running smoothly.

To open a service request by telephone, use one of the following numbers:

Asia-Pacific: +61 2 8446 7411 (Australia: 1 800 805 227)

EMEA: +32 2 704 55 55

USA: 1 800 553-2447

For a complete list of Cisco TAC contacts, go to this URL:

<http://www.cisco.com/techsupport/contacts>

Definitions of Service Request Severity

To ensure that all service requests are reported in a standard format, Cisco has established severity definitions.

Severity 1 (S1)—Your network is “down,” or there is a critical impact to your business operations. You and Cisco will commit all necessary resources around the clock to resolve the situation.

Severity 2 (S2)—Operation of an existing network is severely degraded, or significant aspects of your business operation are negatively affected by inadequate performance of Cisco products. You and Cisco will commit full-time resources during normal business hours to resolve the situation.

Severity 3 (S3)—Operational performance of your network is impaired, but most business operations remain functional. You and Cisco will commit resources during normal business hours to restore service to satisfactory levels.

Severity 4 (S4)—You require information or assistance with Cisco product capabilities, installation, or configuration. There is little or no effect on your business operations.

Obtaining Additional Publications and Information

Information about Cisco products, technologies, and network solutions is available from various online and printed sources.

- Cisco Marketplace provides a variety of Cisco books, reference guides, documentation, and logo merchandise. Visit Cisco Marketplace, the company store, at this URL:

<http://www.cisco.com/go/marketplace/>

- *Cisco Press* publishes a wide range of general networking, training and certification titles. Both new and experienced users will benefit from these publications. For current Cisco Press titles and other information, go to Cisco Press at this URL:

<http://www.ciscopress.com>

- *Packet* magazine is the Cisco Systems technical user magazine for maximizing Internet and networking investments. Each quarter, Packet delivers coverage of the latest industry trends, technology breakthroughs, and Cisco products and solutions, as well as network deployment and troubleshooting tips, configuration examples, customer case studies, certification and training information, and links to scores of in-depth online resources. You can access Packet magazine at this URL:

<http://www.cisco.com/packet>

- *iQ Magazine* is the quarterly publication from Cisco Systems designed to help growing companies learn how they can use technology to increase revenue, streamline their business, and expand services. The publication identifies the challenges facing these companies and the technologies to help solve them, using real-world case studies and business strategies to help readers make sound technology investment decisions. You can access iQ Magazine at this URL:

<http://www.cisco.com/go/iqmagazine>

or view the digital edition at this URL:

<http://ciscoiq.texterity.com/ciscoiq/sample/>

- *Internet Protocol Journal* is a quarterly journal published by Cisco Systems for engineering professionals involved in designing, developing, and operating public and private internets and intranets. You can access the Internet Protocol Journal at this URL:

<http://www.cisco.com/ipj>

- Networking products offered by Cisco Systems, as well as customer support services, can be obtained at this URL:

<http://www.cisco.com/en/US/products/index.html>

- Networking Professionals Connection is an interactive website for networking professionals to share questions, suggestions, and information about networking products and technologies with Cisco experts and other networking professionals. Join a discussion at this URL:

<http://www.cisco.com/discuss/networking>

- World-class networking training is available from Cisco. You can view current offerings at this URL:

<http://www.cisco.com/en/US/learning/index.html>

This document is to be used in conjunction with the documents listed in the [“Related Documentation”](#) section on page 13.

CCSP, CCVP, the Cisco Square Bridge logo, Follow Me Browsing, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Access Registrar, Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, the Networkers logo, Networking Academy, Network Registrar, *Packet*, PIX, Post-Routing, Pre-Routing, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, StrataView Plus, TeleRouter, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0502R)

Copyright © 2007
Cisco Systems, Inc.
All rights reserved.

