

---

## Numerics

- 802.11a policy name [10-47](#)
- 802.11b/g RRM interval template [10-56](#)
- 802.11b/g RRM threshold templates
- 802.11b/g voice templates [10-52](#)
- 802.11 counters report [13-9, 13-10](#)
  - configuring [10-57](#)
- 802.11 security trap [10-63](#)
- 802.1X
- 802.3 bridging
  - configuring

---

## A

- AAA override
- AAA servers
- AAA traps
- access control list template
- accessing the schedule panel
- access point
  - configuring for hybrid REAP
- access point/radio templates [10-68](#)
- access point authentication and MFP templates
- access point authorization template
- access point inventory report
- access point load
  - avoiding
- access point placement
- access point reports
  - modifying
  - viewing
- access points
  - adding
    - adding to maps [5-18 to 5-20](#)
    - [9-10](#)
  - converting to LWAPP [B-2](#)
  - searching [9-14](#)
- access point security statistics
  - for mesh [6-30](#)
- access point templates
  - adding [10-67](#)
- access point traps [10-63](#)
- ACL template
  - configuring
- active sessions
  - monitoring
- adaptive scan threshold
- add config groups
- adding access points
- adding access point templates
- adding a license [A-5](#)
- adding chokepoints
- adding controllers
  - adding controllers from config group
- adding guest user accounts
- adding templates from config group
- add known rogue
- adjusted link metric
- administration menu
- advanced debug
- advanced options
  - definition
- Advanced tab
  - on WLAN template
- Aironet IE
- alarm
- alarm dashboard
- alarm emails
- alarm monitor
- alarms
  - search filters
- alarm severity
  - configuring
- alarm trigger threshold
- alternate parent
  - for mesh

---

- analyzing element location accuracy
- anonymous provisioning
- AP list by location
- AP list by location report
- AP list by SSID
- applying calibration models
- applying config groups
- applying controller templates
- AP policies
- AP policies template
- AP profile status report
- audience of document [ii](#)
- auditing config groups [8-18](#)
- audit reports
  - configuring [9-5](#)
- authentication order
  - managing [9-4](#)
- authentication priority [9-5](#)
- authentication process
  - Hybrid REAP
- automatic backups, scheduling
- automatic client exclusion
- auto-synchronizing location appliances
- avoid access point load
- avoid Cisco AP load
- avoid foreign AP interference
- avoid non-802.11 noise

---

## B

- background tasks
  - running
- backing up location appliance data
- backing up the WCS database
  - on Linux
  - on Windows
- backup and restore license
- bandwidth
  - making expedited

- bridging link information
- bronze
- buildings
  - adding to a campus map
  - adding to WCS database
- busiest APs report
- busiest clients report

---

## C

- calculating access point requirements
- calibration models
  - applying
  - monitoring
- call admission control
- campus map, adding to WCS database
- cascade reboot
- caution, defined
- CCA sensitivity
- channels
  - monitoring on a floor map
- checking the status of WCS
  - on Linux
  - on Windows
- chokepoints
  - adding
  - removing
- Cisco AP load
  - avoiding
- Cisco Discovery Protocol
- Cisco UDI
- Cisco Unified Wireless Network Solution
- Cisco WCS base
- Cisco WCS location
- Cisco Wireless LAN Solution
  - overview

- security solutions
- CKIP
- clear config
- client association report
- client authentication provision
- client count report
- client devices
  - connecting to WLANs
- client exclusion
  - happening automatically
- client exclusion policies template
- client properties
- client related traps
- client report
  - creating new
  - modifying
  - viewing
- clients
  - finding
  - map
  - monitoring on a floor map
  - parameters
- clients, monitoring on floor map
- client statistics
- client troubleshooting
- combined inventory report
- command buttons
- config group
  - adding controllers
  - adding templates
  - applying
  - auditing
  - configuring
  - creating
  - downloading customized webauth
  - downloading IDS signatures
  - downloading sw to controllers
  - rebooting
  - removing controllers
  - removing templates
- configure menu
- configuring 802.3 bridging
- configuring access control lists
- configuring access points
- configuring a client exclusion policy template
- configuring a CPU ACL template
- configuring alarm severity
- configuring audit reports
- configuring config group
- configuring the controller for hybrid REAP
- configuring firewall for WCS
- configuring general templates
- configuring global email parameters
- configuring high density templates
- configuring Hybrid REAP
- Configuring IDS
- Configuring IDS signatures
- configuring IDS signatures
- configuring intrusion detection systems
- configuring a LDAP server template
- configuring a local EAP general template
- configuring a local EAP profile template
- configuring a manually disabled client template
- configuring a mesh template
- configuring an 802.11h template
- configuring an access point for hybrid REAP
- configuring an EAP-FAST template
- configuring multiple country codes
- configuring a network access control template
- configuring RADIUS servers
- configuring an RRM interval template
- configuring an RRM threshold template
- configuring a policy name template
- configuring a roaming parameters template
- configuring a rogue policies template
- configuring the switch
  - for hybrid REAP
- configuring a TACACS+ server template

configuring a trusted AP policies template  
configuring a user authentication priority template  
configuring a user login policies template  
configuring a video parameter template  
configuring a voice parameter template  
configuring templates  
    802.11a policy name  
    802.11b/g RRM interval  
    802.11b/g RRM threshold  
    802.11b/g voice  
    access point/radio  
    access point authentication and MFP  
    access point authorization  
    ACL  
    file encryption  
    guest users  
    known rogue access point  
    local management user  
    local net users  
    MAC filter  
    QoS  
    RADIUS accounting  
    RADIUS authentication  
    syslog  
    Telnet SSH  
    traffic stream metrics QoS  
    trap control  
    trap receiver  
    web authentication  
    WLAN  
connecting client devices  
    to WLANs  
connecting to the Guest WLAN  
controller inventory report  
controllers  
    adding  
    adding to WCS database  
    configuring for hybrid REAP  
    pinging network devices

    searching  
    specified  
    viewing status and configurations  
controller templates  
    applying  
controller utilization report  
conventions of document  
converting WLSE autonomous to WCS controller  
counters report  
    for 802.11  
country codes  
    multiple  
    setting  
coverage holes  
    finding  
    monitoring on a floor map  
coverage hole summary report  
cranite  
creating guest user accounts  
creating a lobby ambassador account  
creating a network design  
creating a new access point report  
creating a new client report  
creating a new inventory report  
creating a new mesh report  
creating a new performance report  
creating a new security report  
creating calibration models  
CSV file format  
customized webauth  
    downloading  
Customized Web authentication  
customized web authentication  
    downloading  
Custom signature

---

## **D**

data management tasks

| \_\_\_\_\_ ■

\_\_\_\_\_ **F**

\_\_\_\_\_ **E**

| \_\_\_\_\_ ■ **IN-5**

■ \_\_\_\_\_ |

**G** \_\_\_\_\_

\_\_\_\_\_ |

\_\_\_\_\_ **H**

**IN-6** ■ \_\_\_\_\_ |

---

**K**

---

**L**

link aggregation (LAG)

A-2  
A-2  
7-13  
10-5  
A-6 to ??  
A-4  
A-5  
B-4

guidelines  
link metric  
    adjusted  
    unadjusted  
link SNR  
link stats  
    for mesh  
link test  
    running  
link test result  
load-based CAC  
    enabling  
lobby ambassador  
    creating  
    logging activities  
Local EAP check box  
local EAP general template  
local EAP profile template  
local management user template  
local net users template  
local password policy  
local switching  
    Hybrid REAP  
location accuracy  
    analyzing  
    using testpoints  
location appliance  
    importing  
location appliance data  
    backing up  
location appliance functionality  
location appliances  
    adding to WCS database  
    auto-synchronizing  
    relationship with WCS Location  
location menu  
location server inventory report  
location server utilization  
location tab

---

location upgrade

log analysis

logging

logging in

to the WCS user interface

logging into the WCS user interface

logging options

logging the lobby ambassador activities

login.html

long preambles, enabling for SpectraLink NetLink  
phones

---

## **M**

---

## **N**

---

## **O**

Outdoor areas

- adding to a campus map

- monitoring

overview

- Cisco Wireless LAN Solution

- WCS

■ \_\_\_\_\_ |

\_\_\_\_\_

**P**

\_\_\_\_\_

**R**

\_\_\_\_\_

**Q**

\_\_\_\_\_ |

**IN-10** ■

---

10-55r

6-36

15-2

13-1

10-51

---

**S**

---

T

traps added in 4.0  
traps added in 4.0.96.0  
traps added in 4.1  
trend report type  
troubleshooting a client  
trusted AP policies  
    template for  
tunneling  
turning password rules on or off  
Tx channel report  
Tx power level report

---

## U

UDI  
    retrieving on controllers and access points  
unadjusted link metric  
uninstalling WCS  
    on Linux  
    on Windows  
unique client report  
unique device identifier  
unsupported traps  
update map view  
updating system software  
upgrading to Linux 4  
    during WLSE conversion  
upgrading WCS  
    on Linux  
    on Windows  
uploading IDS signatures  
upstream delay  
upstream packet loss rate  
user accounts  
    for guest  
user authentication order  
    managing  
user authentication priority template  
    configuring  
user credential retrieval priority  
user details  
    emailing  
    printing  
user groups  
user interface  
user login policies  
    configuring a template  
user preferences  
using chokepoints  
using filtering  
using maps  
    to monitor mesh access points  
    to monitor mesh AP neighbors  
    to monitor mesh link statistics  
using maps to monitor mesh networks  
using planning mode  
using template  
    ACL  
using templates  
    802.11a policy name  
    802.11b/g RRM interval  
    802.11b/g RRM threshold  
    802.11b/g voice  
    access point/radio  
    access point authentication & MFP  
    access point authorization  
    file encryption  
    guest users  
    known rogue access point  
    local management user  
    local net users  
    MAC filter  
    NTP server  
    QoS  
    RADIUS accounting  
    RADIUS authentication

■

---

syslog

Telnet SSH

traffic stream metrics QoS

trap control

trap receiver

web authentication

WLAN

using testpoints

to analyze element location accuracy

utilization report

for controllers

---

## W

---

## V

WCS Base, described

WCS controller deployment

from WLSE autonomous

WCS database

adding chokepoints

adding controllers

adding location appliances

backing up

on Linux

on Windows

removing chokepoints

restoring

on Linux

on Windows

scheduling automatic backups

WCS licenses

---

■

---

- WCS Location
  - described
  - relationship with Cisco location appliances
- WCS Navigator
- WCS user accounts
  - adding
  - changing passwords
  - deleting
- WCS user interface
  - described
  - logging into
- web authentication template
- web authentication types
- web login
  - enabling
- Wireless Control System (WCS)
  - See WCS
- wireless LAN event correlation
- WLAN client troubleshooting
- WLAN templates
- WLSE autonomous deployment conversion
- WLSE management stations
- WLSE map data
  - exporting
  - importing
- WLSE upgrade
- WMM policy
- worst node hops
  - for mesh
- worst SNR links
  - for mesh
- WPA1 + WPA2
- WPA1+WPA2
- WPS traps