



Supported Devices Table for the CiscoWorks Wireless LAN Solution Engine 2.9

Revised: 11/18/2005

The following sections show the Cisco devices supported when the CiscoWorks Wireless LAN Solution Engine 2.9 was released:

- [Network Management—Supported Access Points and Bridges, page 2](#)
- [Radio Management—Supported Access Points and Radios, page 3](#)
- [Radio Management—Supported Client Adaptor Cards, page 4](#)
- [Radio Management—Supported Directional Antennas, page 4](#)
- [Supported Switches, page 5](#)
- [Supported Routers, page 8](#)
- [Supported Access Servers, page 10](#)

To see a list of supported firmware versions, select **Administration > System > Firmware Supported Versions**.

To see a list of devices discovered by the Wireless LAN Solution Engine, select **Devices > Discover > Managed Devices**.

Non-IOS to IOS Conversions

For information on conversions from non-IOS to IOS, refer to the Conversion to IOS guide on Cisco.com:

http://www.cisco.com/univercd/cc/td/doc/product/rtrmgmt/cwparent/cw_1105/wlse/2_9/index.htm.



Corporate Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

Copyright © 2004 Cisco Systems, Inc. All rights reserved.

Network Management—Supported Access Points and Bridges

Table 1 Supported Access Points and Bridges

Series	SysObjectID	Supported Firmware Versions		
		Discovery, Inventory, Faults, Reporting	Configuration	Firmware
Cisco Aironet 1100 series access points	1.3.6.1.4.1.9.1.507	12.2(4)JA, 12.2(4)JA1, 12.2(8)JA, 12.2(11)JA, 12.2(13)JA, 12.2(13)JA1, 12.2(13)JA2, 12.2(13)JA3, 12.2(15)JA*, 12.2(15)XR*, 12.3(2)JA	12.2(4)JA, 12.2(4)JA1, 12.2(8)JA, 12.2(11)JA, 12.2(11)JA1, 12.2(13)JA, 12.2(13)JA1, 12.2(13)JA2, 12.2(13)JA3, 12.2(15)JA*, 12.2(15)XR*, 12.3(2)JA	12.2(8)JA*, 12.2(11)JA*, 12.2(13)JA*, 12.2(15)JA*, 12.2(15)XR*, 12.3(2)JA*
Cisco 1130 series access points	1.3.6.1.4.1.9.1.618	12.3(2)JA	12.3(2)JA	12.3(2)JA*
Cisco Aironet 1210 and 1230 series (Cisco IOS) access points	1.3.6.1.4.1.9.1.525	12.2(8)JA, 12.2(11)JA, 12.2(11)JA1, 12.2(13)JA, 12.2(13)JA1, 12.2(13)JA2, 12.2(13)JA3, 12.2(15)JA*, 12.2(15)XR, 12.3(2)XT,, 12.3(2)JA	12.2(8)JA, 12.2(11)JA, 12.2(11)JA1, 12.2(13)JA, 12.2(13)JA1, 12.2(13)JA2, 12.2(13)JA3, 12.2(15)JA*, 12.2(15)XR, 12.3(2)XT, 12.3(2)JA	12.2(8)JA*, 12.2(11)JA*, 12.2(13)JA*, 12.2(15)JA*, 12.2(15)XR*, 12.3(2)JA*
Cisco Aironet 1200 and 1220 series access points ¹	1.3.6.1.4.1.9.1.474	11.54T, 11.56, 12.01T1, 12.02T1, 12.03T, 12.04	12.01T1, 12.02T1, 12.03T, 12.04	11.54T, 11.56, 12.01T1, 12.02T1, 12.03T, 12.04
Cisco Aironet 350 series access points	1.3.6.1.4.1.9.1.380	11.21, 11.23T, 12.01T1, 12.02T1, 12.03T, 12.04	12.01T1, 12.02T1, 12.03T, 12.04	11.21, 11.23T, 12.x
Cisco Aironet 350 IOS series access points ²	1.3.6.1.4.1.9.1.552	12.2(13)JA, 12.2(13)JA1, 12.2(13)JA2, 12.2(13)JA3, 12.2(15)JA, 12.3(2)JA	12.2(13)JA, 12.2(13)JA1, 12.2(13)JA2, 12.2(13)JA3, 12.2(15)JA, 12.3(2)JA	12.2(11)JA*, 12.2(13)JA*, 12.2(15)JA*, 12.3(2)JA*, 12.2(15)XR*
Cisco Aironet 340 series access points	1.3.6.1.4.1.9.1.379	11.21, 11.23T, 12.01T, 12.02T1, 12.03T, 12.04	12.01T1, 12.02T1, 12.03T, 12.04	11.21, 11.23T, 12.x

Table 1 Supported Access Points and Bridges (Continued)

Series	SysObjectID	Supported Firmware Versions		
		Discovery, Inventory, Faults, Reporting	Configuration	Firmware
Cisco Aironet 350 series bridges	1.3.6.1.4.1.9.1.380	11.21, 11.23T, 12.01T, 12.02T1, 12.03T, 12.04	12.01T1, 12.02T1, 12.03T, 12.04	11.21, 11.23T, 12.x
Cisco Aironet 350 series workgroup bridges ³	N/A	Not supported.	Not supported.	Not supported.
Cisco Aironet 1310 Wireless Bridges	1.3.6.1.4.1.9.1.565	12.2(15)JA, 12.3(2)JA	12.2(15)JA, 12.3(2)JA	12.2(15)JA*, 12.3(2)JA*
Cisco Aironet 1410 Wireless Bridges	1.3.6.1.4.1.9.1.533	12.2(15)JA, 12.3(2)JA	12.2(15)JA, 12.3(2)JA	12.2(15)JA*, 12.3(2)JA*

* 802.11g radios for Series 1100 and 1200 access points are supported only with 12.2(15)JA or later.

1. When a 1200 access point is converted to IOS, its SysObjectID and supported images correspond with the IOS 1210 and 1230 models.
2. Cannot be used as a WDS.
3. Workgroup bridges are discovered as clients.

Radio Management—Supported Access Points and Radios

Table 2 Radio Management Supported Access Points and Radios

Radio Management Feature	Supported AP Models	Supported Radios	Minimum IOS Version Required
Radio Monitoring, AP Radio Scan, Client Walkabout, RM Assisted Configuration, Self Healing, Auto Re-Site Survey, Location Manager	Cisco Aironet 1100 series access points	.11b	12.3(2)JA or later.
		.11g	12.3(2)JA or later.
	Cisco 1130 (Cisco IOS) series access points	.11a, .11g	12.3(2)JA or later.
	Cisco Aironet 1210 and 1230 series (Cisco IOS) access points	.11a	12.3(2)JA or later.
		.11b	12.3(2)JA or later.
		.11g	12.3(2)JA or later.
	Cisco Aironet 350 IOS series access points ¹	.11b	12.3(2)JA or later.
	BR1310 (AP-only mode)	.11g	12.3(2)JA or later.

Table 2 Radio Management Supported Access Points and Radios (Continued)

Radio Management Feature	Supported AP Models	Supported Radios	Minimum IOS Version Required
Scanning-Only AP	Cisco Aironet 1100 series access points	.11b, .11g	12.3(2)JA or later.
	Cisco 1130 (Cisco IOS) series access points	.11a, .11g	12.3(2)JA or later.
	Cisco Aironet 1210 and 1230 series (Cisco IOS) access points	.11a, .11b, .11g	12.3(2)JA or later.

1. Cannot be used as a WDS or Scanning-Only AP

Radio Management—Supported Client Adaptor Cards

Table 3 Radio Management Supported Client Adaptor Cards

Radio Management Feature	Supported Client Adaptors
All Radio Manager and Location Manager features ¹	AIR-PCI351x (Air350 based client card, B-radio) ² AIR-CB20A ³ , AIR-CB21AG ^{4 5}

1. Require CCX-V2 or later compliant clients. To check the status of partner client cards, see the CCX partner website at http://www.cisco.com/en/US/partners/pr46/pr147/partners_pgm_concept_home.html
2. To allow the client adaptor to participate in the Radio Management feature, the Enable Radio Management Support parameter must be checked. This parameter, which is accessible from the Advanced (Infrastructure) Parameters screen in ACU, is available in:
 - Windows ACU version 6.2 or later for 350 series client adaptors using firmware version 5.30.17 or later
 - Windows ACU version 6.3 or later for CB20A client adaptors using firmware version 5.40.10 or later
3. See Footnote 2.
4. Requires ADU software version 1.1 or later.
5. Includes both 802.11a and 802.11g radios. The 802.11g radio can act like a 802.11b radio (g is a superset of b), so effectively the AG client can operate in A, B, and G modes.

Radio Management—Supported Directional Antennas

Following are the supported directional antennas:

- AIR-ANT1729 2.4 GHz, 6 dBi Patch Ant w/RP-TNC Connector
- AIR-ANT2410 2.4 GHz, 10dBi Yagi Mast Mount Ant. with RP-TNC Connector
- AIR-ANT2012 2.4 GHz, 6.5 dBi Diversity Patch Ant with RP-TNC Connector
- AIR-ANT3549 2.4 GHz, 9 dBi Patch Antenna with RP-TNC Connector
- AIR-ANT570-R 5 GHz, 7 dBi Diversity AIR-ANT1729 2.4 GHz, 6 dBi Patch Ant with RP-TNC Connector
- AIR-ANT2410 2.4 GHz, 10dBi Yagi Mast Mount Ant. with RP-TNC Connector
- AIR-ANT2012 2.4 GHz, 6.5 dBi Diversity Patch Ant with RP-TNC Connector
- AIR-ANT3549 2.4 GHz, 9 dBi Patch Antenna with RP-TNC Connector
- AIR-ANT570-R 5 GHz, 7 dBi Diversity Directional Antenna for Connectors on Release 12.3(2)XT

Supported Switches



Note

The WLSE monitors basic MIB-II attributes that are available on all switches. In general, different software versions of these devices will be supported because those attributes are not expected to change.

Table 4 *Supported Switches*

Series	Devices Supported	SysObjectID
Cisco Catalyst 1200	1200	1.3.6.1.4.1.9.5.5
Cisco Catalyst 1900	1924	1.3.6.1.4.1.9.5.18
		1.3.6.1.4.1.9.5.28
	1912	1.3.6.1.4.1.9.5.175
		1.3.6.1.4.1.9.5.31
Cisco PGW 2200 Softswitch	2200	1.3.6.1.4.1.9.5.13
Cisco Catalyst 2820	2820	1.3.6.1.4.1.9.5.20
Cisco Catalyst 2900 ¹	2980G-A	1.3.6.1.4.1.9.5.51
	2980G	1.3.6.1.4.1.9.5.49
	2948GL3Dc	1.3.6.1.4.1.9.1.386
	2948G	1.3.6.1.4.1.9.5.42
	2926	1.3.6.1.4.1.9.5.35
	2900	1.3.6.1.4.1.9.5.12
Cisco Catalyst 2900XL ²	2908XL	1.3.6.1.4.1.9.1.170
	2912XL	1.3.6.1.4.1.9.1.219
	2912MFXL	1.3.6.1.4.1.9.1.221
	2916MXL	1.3.6.1.4.1.9.1.171
	2924XL	1.3.6.1.4.1.9.1.183
	2924CXL	1.3.6.1.4.1.9.1.184
	2924XLV	1.3.6.1.4.1.9.1.217
	2924CXLV	1.3.6.1.4.1.9.1.218
2924MXL	1.3.6.1.4.1.9.1.220	

Table 4 Supported Switches (Continued)

Series	Devices Supported	SysObjectID
Cisco Catalyst 2950 ³	2950-12	1.3.6.1.4.1.9.1.323
	2950-24	1.3.6.1.4.1.9.1.324
	2950-24C	1.3.6.1.4.1.9.1.325
	2950T	1.3.6.1.4.1.9.1.359
	2950-12G	1.3.6.1.4.1.9.1.427
	2950-24G	1.3.6.1.4.1.9.1.428
	2950-48G	1.3.6.1.4.1.9.1.429
	2950-24S	1.3.6.1.4.1.9.1.430
	2950-24GDC	1.3.6.1.4.1.9.1.472
Cisco Catalyst 2970	C2970G-24T	1.3.6.1.4.1.9.1.527
	C2970G-24TS	1.3.6.1.4.1.9.1.561
Cisco Catalyst 3000 series switches	C3000	1.3.6.1.4.1.9.5.10
		1.3.6.1.4.1.9.5.26
	C3100	1.3.6.1.4.1.9.5.23
	C3200	1.3.6.1.4.1.9.5.15
	CPW16	1.3.6.1.4.1.9.5.9
1.3.6.1.4.1.9.5.25		
Cisco Catalyst 3500 XL series switches ⁴	3508GXL	1.3.6.1.4.1.9.1.246
	3512XL	1.3.6.1.4.1.9.1.247
	3524XL,	1.3.6.1.4.1.9.1.248
	3548XL	1.3.6.1.4.1.9.1.278
	3524PWRXL,	1.3.6.1.4.1.9.1.287
	3524PWRXLEn	1.3.6.1.4.1.9.1.515
Cisco Catalyst 3550 series switches ⁵	3550-24	1.3.6.1.4.1.9.1.366
	3550-48	1.3.6.1.4.1.9.1.367
	3550-12T	1.3.6.1.4.1.9.1.368
	3550-12G	1.3.6.1.4.1.9.1.431
	3550-24DC	1.3.6.1.4.1.9.1.452
	3550-24-MMF	1.3.6.1.4.1.9.1.453
	3550-24PWR	1.3.6.1.4.1.9.1.485
	3550-24-PWR	1.3.6.1.4.1.9.1.485
Cisco Catalyst 3750 series switches	3750	1.3.6.1.4.1.9.1.516
	3750-24TS	1.3.6.1.4.1.9.1.511
	3750-248TS	1.3.6.1.4.1.9.1.512
	3750G-24S	1.3.6.1.4.1.9.1.513
	3750G-24T	1.3.6.1.4.1.9.1.514

Table 4 Supported Switches (Continued)

Series	Devices Supported	SysObjectID
Cisco Catalyst 3900 series switches	3900	1.3.6.1.4.1.9.5.33
	3920	1.3.6.1.4.1.9.5.37
Cisco Catalyst 4000 series switches ⁶	4003	1.3.6.1.4.1.9.5.40
	4912G,	1.3.6.1.4.1.9.5.41
	4006	1.3.6.1.4.1.9.5.46
	4006-SW	1.3.6.1.4.1.9.1.448
	4908gL3Dc	1.3.6.1.4.1.9.1.387
	4503	1.3.6.1.4.1.9.1.501
Cisco Catalyst 4000 IOS series switches ⁷	4006-SW	1.3.6.1.4.1.9.1.448
	4503	1.3.6.1.4.1.9.1.501
	4503-SUP	1.3.6.1.4.1.9.5.58
	4506	1.3.6.1.4.1.9.1.502
	4506-SUP	1.3.6.1.4.1.9.5.59
	4507R	1.3.6.1.4.1.9.1.503
Cisco Catalyst 5000 series switches ⁸	5000	1.3.6.1.4.1.9.5.7
	5002	1.3.6.1.4.1.9.5.29
Cisco Catalyst 5500 series switches ⁹	5500	1.3.6.1.4.1.9.5.17
	5505	1.3.6.1.4.1.9.5.34
	5509	1.3.6.1.4.1.9.5.36
Cisco Catalyst 6000* series switches ¹⁰	6006	1.3.6.1.4.1.9.5.38
	6009	1.3.6.1.4.1.9.5.39
	6503	1.3.6.1.4.1.9.5.56
	6506	1.3.6.1.4.1.9.5.45
	6509	1.3.6.1.4.1.9.5.44
	6509SP	1.3.6.1.4.1.9.5.47
	6513	1.3.6.1.4.1.9.5.50
Cisco Catalyst 7600 Series	7603*	1.3.6.1.4.1.9.1.401
	7606*	1.3.6.1.4.1.9.1.402

*The Wireless LAN Services Module (WLSM) can be implemented in these switches to provides WDS to the wireless network.

1. Tested with Software Release 12.0(7)WX5(15a)
2. Tested with Software Release 11.2 (8.5)SA6
3. Tested with Software Release 12.0(5.3)WC(1) and 12.1(9)EA1
4. Tested with Software Release 12.0(5.3)WC(1), 12.0(5.2)XU
5. Tested with Software Release 12.1(6)EA1
6. Tested with Software Release 6.3 (3) and 7.2(2)
7. Tested with Software Release 12.1(12c)EW
8. Tested with Software Release 4.5(3)

- 9. Tested with Software Release 5.4(1)
- 10. Tested with Software Releases 6.2(2) and 6.3(1)

Supported Routers



Note

The WLSE monitors basic MIB-II attributes that are available on all switches. In general, different software versions of these devices will be supported because those attributes are not expected to change.

Table 5 Supported Routers

Series	Devices Supported	SysObjectID
Cisco 800 series routers	801	1.3.6.1.4.1.9.1.212
	802	1.3.6.1.4.1.9.1.213
	803	1.3.6.1.4.1.9.1.214
	804	1.3.6.1.4.1.9.1.215
	804J	1.3.6.1.4.1.9.1.296
	805	1.3.6.1.4.1.9.1.245
	806	1.3.6.1.4.1.9.1.384
	811	1.3.6.1.4.1.9.1.295
	813	1.3.6.1.4.1.9.1.396
	826	1.3.6.1.4.1.9.1.322
	826 QuadV	1.3.6.1.4.1.9.1.321
	827	1.3.6.1.4.1.9.1.284
	827-H	1.3.6.1.4.1.9.1.446
	827 QuadV	1.3.6.1.4.1.9.1.270
	828	1.3.6.1.4.1.9.1.382
	831	1.3.6.1.4.1.9.1.497
837	1.3.6.1.4.1.9.1.495	
Cisco 1700 series routers	1710	1.3.6.1.4.1.9.1.200
	1721	1.3.6.1.4.1.9.1.444
	1760	1.3.6.1.4.1.9.1.416

Table 5 Supported Routers

Series	Devices Supported	SysObjectID
Cisco 2600 series routers ¹	2610	1.3.6.1.4.1.9.1.185
	2611	1.3.6.1.4.1.9.1.186
	2612	1.3.6.1.4.1.9.1.187
	2613	1.3.6.1.4.1.9.1.195
	2620	1.3.6.1.4.1.9.1.208
	2621	1.3.6.1.4.1.9.1.209
	2650	1.3.6.1.4.1.9.1.319
	2651	1.3.6.1.4.1.9.1.320
	2691	1.3.6.1.4.1.9.1.413
	2610XM	1.3.6.1.4.1.9.1.466
	2611XM	1.3.6.1.4.1.9.1.467
	2620XM	1.3.6.1.4.1.9.1.468
	2621XM	1.3.6.1.4.1.9.1.469
	2650XM	1.3.6.1.4.1.9.1.470
	2651XM	1.3.6.1.4.1.9.1.471
Cisco 3600 series routers ²	3620	1.3.6.1.4.1.9.1.122
	3640	1.3.6.1.4.1.9.1.110
	3660	1.3.6.1.4.1.9.1.205
	3661-AC	1.3.6.1.4.1.9.1.338
	3661-DC	1.3.6.1.4.1.9.1.339
	3662-AC	1.3.6.1.4.1.9.1.340
	3662-AC-CO	1.3.6.1.4.1.9.1.342
	3662-DC	1.3.6.1.4.1.9.1.341
	3662-DC-CO	1.3.6.1.4.1.9.1.343

1. Tested with Cisco IOS Software Release 12.2(1)

2. Tested with Cisco IOS Software Release 12.0(5)XK

Supported Access Servers

Table 6 Supported Access Servers

Devices	Supported Versions	
	Discovery, Inventory, Faults, Reporting	Configuration and Firmware
LEAP, PEAP, RADIUS, EAP-FAST, and EAP-MD5 servers	Cisco Secure Access Control Server (ACS) ¹ , Version 3.2.3	Not supported.
RADIUS, LEAP, and EAP-MD5 servers	Cisco Access Registrar (CAR), Version 3.0 ²	Not Supported.

1. The WLSE cannot perform Microsoft PEAP (EAP-MSCHAPv2) transactions with ACS.
2. Because CAR 3.0 supports only RADIUS, LEAP, and EAP-MD5 protocols, the WLSE 2.9 supports monitoring of CAR 3.0 configured as RADIUS, LEAP, and EAP-MD5 type AAA servers only.