



DATA SHEET

CISCO IOS XR SOFTWARE RELEASE 3.0

The Cisco® CRS-1 Carrier Routing System is the industry's first carrier router that offers continuous system operation, unprecedented service flexibility, and system longevity. The Cisco CRS-1 is powered by Cisco IOS® XR Software—a unique self-healing, distributed operating system designed for always-on operation while scaling system capacity up to 92 Tbps. The innovative system architecture combines the Cisco Silicon Packet Processor, the first programmable 40-Gbps application-specific integrated circuit (ASIC), with the Cisco Service Separation Architecture for unprecedented service flexibility and speed to service. The Cisco CRS-1 marks a new era in carrier IP Communications by powering the foundation for network and service convergence today while protecting investments for decades to come.

This data sheet provides detailed product specifications for the Cisco IOS XR Software Release 3.0. For more information about the Cisco CRS-1 or about other interfaces available for the Cisco CRS-1, visit: <http://www.cisco.com/go/crs>.

PRODUCT SPECIFICATIONS

Table 1. Product Specifications of Cisco IOS XR Software Release 3.0

Software compatibility	<ul style="list-style-type: none">• Release 3.0 interoperates with Cisco CRS-1 products running Cisco IOS XR Software Release 2.0 in the network and with other Cisco products running Cisco IOS operating systems.
Modular software design	<ul style="list-style-type: none">• Cisco IOS XR Software is a continuation of the Cisco networking leadership in helping customers realize the power of their networks and the Internet. Cisco IOS XR Software provides unprecedented routing-system scalability, high availability, service isolation, and manageability to meet the mission-critical requirements of next-generation networks.
Features and benefits	<ul style="list-style-type: none">• Ethernet support New features in this release include support for the 10-Gigabit Ethernet interface and Ethernet features including IEEE 802.1Q VLAN encapsulation and Layer 2 MAC accounting.• IP and routing Cisco IOS XR Software supports a wide range of IPv4 and IPv6 services and routing protocols, including Border Gateway Protocol (BGP), Intermediate System-to-Intermediate System (IS-IS), Open Shortest Path First (OSPF), static, IPv4 Multicast, Routing Policy Language (RPL), and Hot Standby Router Protocol (HSRP)/Virtual Router Redundancy Protocol (VRRP) features. New features in this release include support for BGP attributes-based policy accounting.• Multiprotocol Label Switching (MPLS) Cisco IOS XR Software supports MPLS protocols such as Traffic Engineering/Fast Reroute (TE-FRR), Resource Reservation Protocol (RSVP), and Label Distribution Protocol (LDP). These features interoperate with Cisco IOS Software. In Release 3.0, the FRR performance is independent of the number of tunnels or prefixes that are rerouted.• Multicast Cisco IOS XR Software provides comprehensive IP Multicast software, including Source Specific Multicast

	<p>(SSM) and Bidirectional Protocol Independent Multicast-Protocol Independent Multicast (BIDIR-PIM) support. The multicast protocols interoperate with Cisco IOS Software.</p> <ul style="list-style-type: none"> • Quality of service (QoS) <p>Cisco IOS XR Software supports a rich variety of QoS mechanisms, including policing, marking, queuing, dropping, and shaping. Additionally, the operating systems support Modular QoS CLI (MQC). Modular CLI is used to configure various QoS features on various Cisco Systems® platforms.</p> • Manageability <p>Cisco IOS XR Software manageability provides industry-standard management interfaces, including modular command-line interface (CLI), Simple Network Management Protocol (SNMP), and native Extensible Markup Language (XML) interfaces.</p> • Security <p>Cisco IOS XR Software provides comprehensive network security features, including access control lists (ACLs), routing authentications, authentication, authorization, and accounting (AAA)/TACACS+, IP Security (IPSec), Secure Shell (SSH) Protocol, SNMPv3, and leading Routing Policy Language (RPL) support. Control-plane protection continues to be distributed into line-card ASICs such as the generalized TTL security mechanism (GTSM), RFC 3682, and dynamic control-plane protection.</p> • Availability <p>Cisco IOS XR Software supports rich availability features such as fault containment, fault tolerance, fast switchover, and nonstop forwarding (NSF).</p> • Scalability <p>Cisco IOS XR Software provides complete distributed processing of routing protocols, data forwarding plane, management plane, and infrastructure services to support 90-Tbps multishelf carrier-class router systems.</p> • Cisco In Service Software Upgrade (ISSU) <p>Cisco IOS XR Software supports a modular packaging-based release model in order to minimize the impact of upgrades and also support Cisco ISSU with NSF where possible.</p>
<p>Supported hardware components</p>	<ul style="list-style-type: none"> • Cisco CRS-1 16-Slot Single-Shelf System and Cisco CRS-1 16-Slot Line-Card Chassis Route Processor • Cisco CRS-1 8-Slot Single-Shelf System and Cisco CRS-1 8-Slot Line-Card Chassis Route Processor • Cisco CRS-1 1-Port OC-768c/STMc-256 Packet over SONET (POS) Interface Module, short reach (SR) • Cisco CRS-1 4-Port OC-192c/STM-64c POS/Dynamic Packet Transport (DPT) Interface Module, very short (VS), short reach (SR), intermediate reach (IR), and long reach (LR) • Cisco CRS-1 16-Port OC-48c/STM-16c POS/DPT Interface Module <ul style="list-style-type: none"> – Pluggable optic module, 1310 nm SM-SR-LC – Pluggable optic module, 1550 nm SM-LR2-LC • Cisco CRS-1 8-Port 10-Gigabit Ethernet Interface Module, LR • Cisco CRS-1 Modular Services Card • Fan trays

ORDERING INFORMATION

To place an order, visit:

Cisco Ordering Home Page at http://www.cisco.com/en/US/ordering/or13/or8/order_customer_help_how_to_order_listing.html or refer to Table 2.

Table 2. Ordering Information

Product Name	Product Part Number
Cisco IOS XR Control Plane Software	XC-RP-03.00
Cisco IOS XR Control Plane Software with encryption	XC-RPK9-03.00
Cisco IOS XR Data Plane Software Base	XC-LCBase-03.00

TO DOWNLOAD THE SOFTWARE

Visit the Cisco Software Center at <http://www.cisco.com/en/US/partner/products/ps5763/index.html> to download Cisco IOS XR Software.

SERVICE AND SUPPORT

Cisco offers a wide range of services programs to accelerate customer success. These innovative services programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you protect your network investment, optimize network operations, and prepare your network for new applications to extend network intelligence and the power of your business. For more information about Cisco services, refer to Cisco Technical Support Services at http://www.cisco.com/en/US/products/svcs/ps3034/serv_category_home.html and Cisco Advanced Services at <http://www.cisco.com/en/US/partner/products/ps5763/index.html>.

FOR MORE INFORMATION

For more information about the single-shelf configuration of the Cisco CRS-1 and Cisco IOS XR Software, visit Cisco at <http://www.cisco.com/go/crs> or contact your local Cisco account representative.



Corporate Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

European Headquarters

Cisco Systems International
BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: 31 0 20 357 1000
Fax: 31 0 20 357 1100

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-7660
Fax: 408 527-0883

Asia Pacific Headquarters

Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on **the Cisco Web site at www.cisco.com/go/offices.**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland
Israel • Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland
Portugal • Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden
Switzerland • Taiwan • Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2004 Cisco Systems, Inc. All rights reserved. CCIP, CCSP, the Cisco *Powered* Network mark, Cisco Unity, Follow Me Browsing, FormShare, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, the Cisco IOS logo, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherSwitch, Fast Step, GigaStack, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MGX, MICA, the Networkers logo, Networking Academy, Network Registrar, *Packet*, PIX, Post-Routing, Pre-Routing, RateMUX, Registrar, ScriptShare, SlideCast, SMARTnet, StrataView Plus, Stratm, SwitchProbe, TeleRouter, The Fastest Way to Increase Your Internet Quotient, TransPath, and VCO are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Web site are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0411R) 204132.32_ETMG_MC_11.04

