

Cisco CRS-1 8-Port 10 Gigabit Ethernet Interface Module

The Cisco® CRS-1 Carrier Routing System is the industry's first carrier router offering continuous system operation, unprecedented service flexibility, and system longevity. The Cisco CRS-1 is powered by Cisco IOS® XR Software – a unique self-healing, distributed operating system designed for always-on operation while scaling system capacity up to 92 Tbps. The innovative system architecture combines the Cisco Silicon Packet Processor, the first programmable 40-Gbps application-specific integrated circuit (ASIC), with the Cisco Service Separation Architecture for unprecedented service flexibility and speed to service. The Cisco CRS-1 marks a new era in carrier IP Communications by powering the foundation for network and service convergence today while protecting investments for decades to come.

This data sheet provides detailed product specifications for the Cisco CRS-1 8-Port 10 Gigabit Ethernet Interface Module. For more information about the Cisco CRS-1 or about other interfaces available for the Cisco CRS-1, visit: <http://www.cisco.com/go/crs>.

Figure 1. Cisco CRS-1 8-Port 10 Gigabit Ethernet Interface Module



Product Specifications

Table 1. Product Specifications

| Feature | Description |
|-------------------------------------|---|
| Chassis Compatibility | Compatible with all current Cisco CRS-1 line-card chassis Requires Cisco CRS-1 Modular Services Card for operation |
| Software Compatibility | Cisco IOS XR Software Release 3.0 or later |
| Port Density | Eight ports of 10 Gigabit Ethernet per PLIM slot |
| Ethernet | Encapsulations: ARPA, IEEE 802.2/SAP, IEEE 802.3/SNAP IEEE 802.x flow control 802.1q VLAN support, jumbo frames IEEE 802.1p tagging Source/destination MAC accounting and VLAN accounting |
| Reliability and Availability | Online insertion and removal (OIR) without affecting system traffic |

| Feature | Description |
|---------------------------------|---|
| Network Management | Cisco IOS XR Software command-line interface (CLI) Simple Network Management Protocol (SNMP) Extensible Markup Language (XML) interface CraftWorks Interface (CWI) |
| Physical Dimensions | Occupies one PLIM slot Weight: 8.4 lb (3.8 kg) Height: 20.6 in. (52.2 cm) Depth: 11.2 in. (28.4 cm) Width: 1.8 in. (4.49 cm) |
| Power | 150W |
| Environmental Conditions | Storage Temperature: –40 to 70°C (–40 to 158°F) Operating Temperature: Normal: 5 to 40°C (41 to 104°F) Short-term: –5 to 50°C (23 to 122°F) short-term Relative Humidity: Normal: 5% to 85% Short-term: 5% to 90% but not to exceed 0.024 kg water/kg of dry air Short-term refers to a period of not more than 96 consecutive hours and a total of not more than 15 days in 1 year. (This refers to a total of 360 hours in any given year, but no more than 15 occurrences during that 1-year period.) |

Approvals and Compliance

Table 2. Compliance and Agency Approvals

| Feature | Description |
|--|---|
| Safety Standards | UL/CSA/IEC/EN 60950-1 IEC/EN 60825 Laser Safety ACA TS001 AS/NZS 60950 FDA – Code of Federal Regulations Laser Safety |
| EMI | FCC Class A ICES 003 Class A AS/NZS 3548 Class A CISPR 22 (EN55022) Class A VCCI Class A BSMI Class A IEC/EN 61000-3-2: Power Line Harmonics IEC/EN 61000-3-3: Voltage Fluctuations and Flicker |
| Immunity (Basic Standards) | IEC/EN-61000-4-2: Electrostatic Discharge Immunity (8 kV Contact, 15 kV Air) IEC/EN-61000-4-3: Radiated Immunity (10 V/m) IEC/EN-61000-4-4: Electrical Fast Transient Immunity (2 kV Power, 1 kV Signal) IEC/EN-61000-4-5: Surge AC Port (4 kV CM, 2 kV DM) IEC/EN-61000-4-5: Signal Ports (1 kV) IEC/EN-61000-4-5: Surge DC Port (1 kV) IEC/EN-61000-4-6: Immunity to Conducted Disturbances (10 Vrms) IEC/EN-61000-4-8: Power Frequency Magnetic Field Immunity (30 A/m) IEC/EN-61000-4-11: Voltage DIPS, Short Interruptions, and Voltage Variations |
| ETSI and EN | EN300 386: Telecommunications Network Equipment (EMC) EN55022: Information Technology Equipment (Emissions) EN55024: Information Technology Equipment (Immunity) EN50082-1/EN-61000-6-1: Generic Immunity Standard |
| Network Equipment Building Systems (NEBS) | This product is designed to meet the following requirements (qualification in progress): SR-3580: NEBS Criteria Levels (Level 3) GR-1089-CORE: NEBS EMC and Safety GR-63-CORE: NEBS Physical Protection |

Additional Specifications

Table 3. Additional Specifications

| Parameter | Long Reach 1310 nm (LR/LR+) | Extended Reach 1550 nm (ER+) | DWDM 1530.33-1560.61 nm |
|------------------------|---------------------------------|------------------------------|-------------------------|
| Connector Type | SC | SC | SC |
| Target Distance | 10 km | 40 km | 80 km |
| Transmitter | | | |
| Power out (maximum) | 0.5 dBm | 4 dBm | 3 dBm |
| Power out (minimum) | -8.2 dBm | -4.7 dBm | -1.0 dBm |
| Receiver | | | |
| P (RMax) (overload) | 0.5 dBm | -1.0 dBm | -7.0 dBm |
| P (RMin) (sensitivity) | -14.4 dBm | -15.8 dBm | -24.0 dBm |
| Optical Link | | | |
| Fiber type | G.652 (single-mode fiber [SMF]) | G.652 (SMF) | G.652 (SMF) |
| Optical path penalty | 3.2 dB | 4.1 dB | 3.0 dB |
| Compliance | IEEE 802.3ae 10GBASE-LR | IEEE 802.3ae 10GBASE-ER | IEEE 802.3ae 10GBASE |

Ordering Information

To place an order, visit: [Cisco Ordering Home Page](#).

Table 4. Ordering Information

| Product Part Number | Product Name |
|--|--|
| 8-10GBE(=) | Cisco CRS-1 Carrier Routing System 8-port 10 Gigabit Ethernet Interface Card |
| CRS-XENPAK-10GB-LR(=) | XENPAK 10GBASE-LR Optics Module |
| XENPAK-10GB-LR+(=) | XENPAK 10GBASE-LR+ Optics Module |
| XENPAK-10GB-ER+(=) | XENPAK 10GBASE-ER+ Optics Module |
| DWDM-XENPAK-60.61= to DWDM-XENPAK-30.33= | XENPAK 10GBASE DWDM Modules (32 ITU 100-GHz wavelengths) |

Service and Support

Cisco offers numerous innovative services programs to accelerate customer success. These programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you to protect your network investment, optimize network operations, and prepare the network for new applications to extend network intelligence and the power of your business. For more information about Cisco services, see [Cisco Technical Support Services](#) or [Cisco Advanced Services](#).

For More Information

For more information about the Cisco CRS-1 8-Port 10 Gigabit Ethernet Interface Module, contact your local account representative or visit: <http://www.cisco.com/go/crs>.

**Americas Headquarters**

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 527-0883

Asia Pacific Headquarters

Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Europe Headquarters

Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: +31 0 800 020 0791
Fax: +31 0 20 357 1100

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

©2007 Cisco Systems, Inc. All rights reserved. CCVP, the Cisco logo, and the Cisco Square Bridge logo are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, IQ Expertise, the IQ logo, IQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networking Academy, Network Registrar, Packet, PIX, ProConnect, ScriptShare, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0705R)