

Cisco MGX 8800/8900 Series 16-Port OC-3c/STM-1 ATM Switch Service Module

Product Overview

The Cisco MGX[®] 8800/8900 Series Switches provide the industry's most scalable family of multiservice switches, scaling from 1.2 Gbps to 180 Gbps redundant switching capacity and from DS0 to OC-192/STM-64 interface capacity. This scalability provides exceptional savings and efficiency for network operations and services growth. The Cisco[®] MGX 8800/8900 Series includes the Cisco MGX 8830/B, MGX 8850, MGX 8850/B, and MGX 8950 Multiservice Switches.

The Cisco 16-Port OC-3c/STM-1 ATM Switch Service Module is a line card for use in the Cisco MGX 8800/8900 Series multiservice Cisco MGX Switches in combination with the Cisco MGX 8800/8900 Series PXM-45 Processor Switch Module and the Cisco MGX 8950 XM-60 Switching Module (the latter for use on the Cisco MGX 8950 only). This ATM switch service module has 16 physical 155-Mbps interfaces that can be used to deliver high-density OC-3c or STM-1 trunking and User-Network Interface (UNI).

Up to 12 Cisco 16-port OC-3c/STM-1 ATM Switch Service Modules can reside in the Cisco MGX 8850, MGX 8850/B, or MGX 8950 to provide support for up to 192 OC-3c/STM-1 interfaces for service providers that require both high bandwidth and high network availability.

The Cisco 16-Port OC-3c/STM-1 ATM Switch Service Module meets service providers' demand for carrier-class availability by offering hot-standby 1+1 card redundancy as well as port redundancy with SONET/SDH automatic protection switching (APS). (See Figure 1.)

Figure 1. Cisco MGX 8800/8900 Series 16-Port OC-3c/STM-1 ATM Switch Service Module



Key Features

The main features of the Cisco MGX 8800/8900 16-Port OC-3c/STM-1 ATM Switch Service Module are listed here.

- Full nonblocking, full-duplex line-rate throughput on all 16 ports
- High reliability with hot-standby 1+1 16-port ATM switch service module card redundancy
- Per-virtual-path and per-virtual-circuit traffic shaping and available bit rate (ABR) with virtual source and virtual destination
- Y-cable and APS (1:1 and 1+1) port redundancy, plus APS 1+1 card redundancy
- Up to 4 million cell buffers
- Up to 16 classes of service (CoS) that can be used to support IP or ATM services
- Support for standards-based Private Network-to-Network Interface (PNNI), switched virtual circuit (SVC) and switched virtual path (SVP), soft permanent virtual connection (SPVC) and soft permanent virtual path (SPVP), and Multiprotocol Label Switching (MPLS) services

Technical Specifications

Table 1 lists the specifications for the Cisco 16-Port OC-3c/STM-1 ATM Switch Service Module.

Table 1. Product Specifications

Description	Specification
Chassis Compatibility	Cisco MGX 8830/B, MGX 8850, MGX 8850/B, and MGX 8950
Software Compatibility	Cisco MGX 8800/8900 SW Release 5.0.20 and above
Protocols	ATM and SONET/SDH
Port Density	16 ports
Layer 1 (Physical Layer) Feature Summary	<ul style="list-style-type: none"> • Support for ports and trunks on the same Cisco 155-Mbps 16-port ATM switch service module • UNI 3.0, 3.1, and 4.0 physical layer specifications • Compliance with the following SONET standards: <ul style="list-style-type: none"> ◦ Bellcore GR-253-CORE ◦ ANSI T1.105 • Compliance with the following SDH standards: <ul style="list-style-type: none"> ◦ ITU-T G.707, G.708, G.709, and G.783 ◦ ITU-T G.957 and G.958

Description	Specification			
Layer 1 (Physical Layer) Feature Summary (continued)	Additional Physical Layer Specifications for Ports and Optics			
	Connection Options	MMF¹	SMF-IR²	SMF-LR³
	Port speed	155 Mbps	155 Mbps	155 Mbps
	Number of ports per Cisco MGX 8800/8900 Series 16-Port OC-3c/STM-1 ATM Switch Service Module	16	16	16
	Port media	MMF	SMF	SMF
	Port connector	LC	LC	LC
	Optics (nanometers- [nm])	Laser 1310 nm	Laser 1310 nm	Laser 1310 nm
	Transmit power level (decibels per milliwatt [dBm])	-15 minimum and -8 maximum	-15 minimum and -8 maximum	-5 minimum and -0 maximum
	Receive power level (dBm)	-23 minimum and -8 maximum	-28 minimum and -8 maximum	-34 minimum and -8 maximum
	Typical reach	200 meters [218 yards] with 62.5 micrometer core) and 500 meters [545 yards] with 50 micrometer core	15 km [9.3 mi]	40 km [24.85 mi]
	Redundancy	1+1 and 1:1 APS line	1+1 and 1:1 APS line	1+1 and 1:1 APS line
	¹ Multimode fiber ² Single-mode fiber, short reach ³ Single-mode fiber, long reach			
Layer 2 (ATM) Feature Summary	<ul style="list-style-type: none"> Configurable for trunk, Network-to-Network Interface (NNI), or UNI application Conformant to ATM Forum UNI 3.0, 3.1, and 4.0 and ITU-T I.361 and I.432 specifications Supports up to 16 CoS queues for IP and ATM traffic and includes all ATM Forum traffic-type services: ABR, unspecified bit rate (UBR), non-real-time variable bit rate (VBR-nrt), real-time variable bit rate (VBR-rt), constant bit rate (CBR); ABR supported with explicit forward congestion indicator (EFCI), RM marking, and explicit-rate stamping; supports ABR virtual source and destination Supports Integrated Local Management Interface (ILMI) 4.0 Complies with standard usage parameter control (UPC) as specified by ATM Forum UNI 3.0 and 4.0, TM 4.1, and ITU-T I.371 Supports early packet discard (EPD), Weighted Random Early Detection (WRED), and partial packet discard (PPD) Supports virtual circuit connections (VCCs) and virtual path connections (VPCs) Supports up to 128,000 connections per 16-port ATM switch service module controlled by PNNI Supports virtual path identifier (VPI) and virtual circuit identifier (VCI) range for VCCs and VPCs per UNI 3.1 Supports virtual circuit merge, per-virtual-circuit and per-virtual-path shaping, and multipoint connections <p>Virtual trunks</p> <ul style="list-style-type: none"> Supports a maximum of 128 virtual interfaces per module; the interfaces can be ports, trunks, or virtual trunks, and each virtual interface supports 16 CoS queues <p>Cell buffering</p> <ul style="list-style-type: none"> Supports 4 million cells of buffering to accommodate large traffic bursts and avoid network congestion and cell discard; suitable for TCP/IP traffic <p>Support for dynamic routing using PNNI 1.0</p> <ul style="list-style-type: none"> Offers an automatic end-to-end connection management mechanism Deterministically allocates bandwidth and reroutes connections autonomously over optimum network paths Preserves service integrity during network failure Offers E.164 and network-service-access-point (NSAP) addressing Offers support for SVC and SVP and for SPVC and SPVP Offers quality-of-service (QoS) based routing <p>Enhanced call admission control</p> <ul style="list-style-type: none"> A user-programmable Enhanced Call Admission Control (E-CAC) feature determines whether to admit or deny connections based on the requested QoS. 			

Description	Specification
Layer 2 (ATM) Feature Summary (continued)	<p>Statistics</p> <ul style="list-style-type: none"> • Statistics supported per connection • Diagnostic statistics available per interface and CoS queues <p>Operation, administration, and management</p> <ul style="list-style-type: none"> • F4 to F5 fault propagation • In-band diagnostics support using loopback cells • In-band continuity check and automatic fault reporting for PVCs • Loopback facility support for diagnostics and self-test purposes
Network Management	<ul style="list-style-type: none"> • Managed by Cisco WAN Manager software suite • Based on Simple Network Management Protocol (SNMP)
Power	<ul style="list-style-type: none"> • Input power required: -48 VDC • Power consumption: 114W
Physical Dimensions	H x D: 15.83 x 15.65 in. (40.20 x 39.75 cm)
Weight	6.5 lb (2.95 kg)
Environmental Conditions	<ul style="list-style-type: none"> • Storage temperature: -40 to 158F (-40 to 70°C) • Operating temperature: <ul style="list-style-type: none"> ◦ Normal: 41 to 104F (5 to 40°C) ◦ Short term: 23 to 122F (-5 to 50°C) • Relative humidity: <ul style="list-style-type: none"> ◦ Normal: 5 to 85% ◦ Short term: 5 to 90% but not to exceed 0.024 kg (0.048 lb) of water per kg (lb) of dry air <p>Short term refers to a period of not more than 96 consecutive hours and a total of not more than 15 days in 1 year</p>

Approvals and Compliance

Table 2 lists regulatory information.

Table 2. Compliance and Agency Approvals

Compliance Type	Description
Safety standards	<ul style="list-style-type: none"> • UL/CSA/IEC/EN 60950-1 • IEC/EN 60825 Laser Safety • ACA TS001 • AS/NZS 60950 • FDA-Code of Federal Regulations Laser Safety
EMI	<ul style="list-style-type: none"> • FCC Class A • ICES 003 Class A • AS/NZS 3548 Class A • CISPR 22 (EN55022) Class A • VCCI Class A • BSMI Class A • IEC/EN 61000-3-2: Power Line Harmonics • IEC/EN 61000-3-3: Voltage Fluctuations and Flicker
Immunity (basic standards)	<ul style="list-style-type: none"> • IEC/EN-61000-4-2: Electrostatic Discharge Immunity (8 kV Contact and 15 kV Air) • IEC/EN-61000-4-3: Radiated Immunity (10 V/m) • IEC/EN-61000-4-4: Electrical Fast Transient Immunity (2 kV AC Power and 1 kV DC Power) • IEC/EN-61000-4-5: Surge AC Port (2 kV CM and 2 kV DM) • IEC/EN-61000-4-5: Signal Ports (1 kV) • IEC/EN-61000-4-5: Surge DC Port (1 kV) • IEC/EN-61000-4-6: Immunity to Conducted Disturbances (10 Vrms) • IEC/EN-61000-4-8: Power Frequency Magnetic Field Immunity (30 A/m) • IEC/EN-61000-4-11: Voltage DIPS, Short Interruptions, and Voltage Variations

Compliance Type	Description
Network Equipment Building Systems (NEBS)	This product is designed to meet the following requirements (qualification in progress): <ul style="list-style-type: none"> • SR-3580: NEBS Criteria Levels (Level 3) • GR-1089-CORE: NEBS EMC and Safety • GR-63-CORE: NEBS Physical Protection
Telcordia CLEI	<ul style="list-style-type: none"> • GR-485-CORE: CLEI coding • GR-383-CORE: CLEI code product label • GR-209-CORE: PCN process

Ordering Information

Table 3 lists ordering information for the Cisco MGX 8800/8900 Series 16-Port OC-3c/STM-1 ATM Switch Service Module.

Table 3. Ordering Information

Part Number	Product Name
AXSM-16-155-XG	Double-height ATM VS/VD service module, 16 OC-3c/STM-1
SFP-8-155	8-port SFP back card for OC-3/STM-1
MMF-1-155-SFP	Multi Mode Fiber FRU
SMFIR-1-155-SFP	Single Mode Fiber FRU, Intermediate Range
SMFLR-1-155-SFP	Single Mode Fiber FRU, Long Range
MGX8950-EXTDR-CON	AXSM-XG Extender Connector for MGX 8950
CAB-SMF-LC	SM Fiber Cable, IR or LR, with LC connector
CAB-SMF-LC-Y	Single Mode Fiber Y-Cable, LC connector, IR or LR
ADPT-LC/SC-SM+MM=	LC-To-SC Adapter Cable, SM and MM
MGX-8850-APS-CON	APS connector for PXM1E, SRME and AXSM product family
MGX-APS-CON-8950	APS connector for MGX 8950

Note: An MGX8950-EXTDR-CON is required with each AXSM-16-155-XG when this front card is configured on the Cisco MGX 8950.

For More Information

For more information about Cisco service and support programs and benefits, go to:

<http://www.cisco.com/>.



Americas Headquarters
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 527-0883

Asia Pacific Headquarters
Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Europe Headquarters
Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: +31 0 800 020 0791
Fax: +31 0 20 357 1100

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

©2007 Cisco Systems, Inc. All rights reserved. CCVP, the Cisco logo, and the Cisco Square Bridge logo are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, IQ Expertise, the IQ logo, IQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networking Academy, Network Registrar, Packet, PIX, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0704R)