



Data Sheet

Cisco MCS 7825-I2-UC1 Media Convergence Server

PRODUCT OVERVIEW

The Cisco[®] MCS 7825-I2-UC1 Media Convergence Server is a powerful platform for Cisco Unity[®] Connection and is preinstalled with an operating system optimized for the application. It occupies only 1 rack unit (1RU) while providing the features most requested in a server platform at a very economical price point.

- Intel Pentium D dual-core 2.8-GHz processor, an 800-MHz front side bus (FSB), and 4 MB of Layer 2 cache
- PC2-4200 Double Data Rate 1 (DDR1) memory
- Two onboard Gigabit Ethernet network interface cards (NICs)
- Two 80-GB serial-advanced-technology-attachment (SATA) hard disk drives configured in Redundant Array of Independent Disks (RAID) 1
- Quick-deployment third-party rail kit
- 350W Power Factor Correction (PFC) power supply
- 1RU (1.75-in.) form factor, 22-in. deep

SUPPORTED APPLICATIONS

The Cisco MCS 7825-I2-UC1 supports Cisco Unity Connection.

PRIMARY FEATURES AND BENEFITS

Performance

The Cisco MCS 7825-I2-UC1 is a robust, highly available server platform designed to support today's IP Communications applications. It uses a single Intel Pentium D dual-core 2.8-GHz processor with an 800-MHz FSB.

Memory

The Cisco MCS 7825-I2-UC1 supports up to 8 GB of DDR memory. The increased processor performance coupled with DDR memory allows customers to retrieve and process information faster and more efficiently. DDR memory executes twice the number of operations per cycle than traditional synchronous dynamic RAM (SDRAM) memory, effectively doubling the data exchange rate between memory and processors.

Variable-Speed Fan Support

The Cisco MCS 7825-I2-UC1 includes variable-speed fans to reduce operating noise. Through the use of temperature sensors within the server, the speed of the fans is adjusted to maintain the proper cooling, reducing the noise generated by the fans by operating them only when required and at a speed based upon the cooling requirements.

SATA and Integrated RAID

The Cisco MCS 7825-I2-UC1 server supports enhanced serviceability through integrated RAID level 1 and front-accessible, simple-swap SATA hard disk drives. If a hard drive fails, user data is preserved on the mirrored drive, and system administrators can easily replace the failing drive without removing the server from the rack, reducing downtime and providing data reliability in a compact, highly cost-effective server.

System Error LEDs

The Cisco MCS 7825-I2-UC1 provides a system error LED and system locator LED on the front of the server to make pinpointing system problems easier than ever. When a system error occurs, this indication is made on the front panel of the Cisco MCS 7825-I2-UC1. If no failures have occurred, the system error LED is not lit.

DAT Tape Drive Support

The Cisco MCS 7825-I2 can support an optional 36-/72-GB universal-serial-bus (USB) external Digital Audio Tape (DAT) drive. This tape drive connects through the USB 2.0 port on the server. The 36/72-GB DAT drive is available as either an external tape drive (part number DAT-USB-EXT-72=) or as a rack-mounted drive (part number DAT-USB-RM-72=).

PRODUCT SPECIFICATIONS

Table 1 gives product specifications of the Cisco MCS 7825-I2-UC1.

Table 1. Product Specifications

Processor at Product Introduction	
Processor (CPU)	Intel Pentium D dual core
Processor internal clock speed	2.8 GHz
Level 2 cache	4 MB
Maximum processors	1
Processors installed	1
Basic input/output system (BIOS) type	Flash memory
Memory	
Memory maximum	8 GB
Memory bus clock	533 MHz
Memory technology	PC2-4200 DDR SDRAM
Bit-error mitigation	Error correction code (ECC)
Total RAM slots	4
Memory installed	2 GB (2 x 1 GB)
RAID Controller	
Controller model	IBM mezzanine ServeRAID-8e Controller
Interface	Embedded to planar
Cache	No
Battery-backed write caching	No
RAID levels supported	1
Hard Disk	
Hard disk installed	2 x 80 GB
Hard disk rotate processor module (RPM)	7200
Hard disk interface type	SATA

Network Connectivity	
Ethernet NIC	2 onboard 10/100/1000
Connector	2 RJ-45 connectors on back of server
10BASE-T cable support	EIA Category 3, 4, or 5 unshielded twisted-pair (UTP) (2 or 4 pair) up to 328 ft (100m)
100BASE-TX cable support	EIA Category 5 UTP (2 pair) up to 328 ft (100m)
1000BASE-T cable support	EIA Category 6 UTP (recommended), 5E UTP, or 5 UTP (2 pair) up to 328 ft (100m)
Expansion Options	
PCI-X non-hot plug 66-MHz and 64-bit slots	1 (full height, three-fourths length)
PCI-X non-hot plug 66-MHz and 64-bit slots	1 (half height, half length)
Interfaces	
Serial ports	1 RS-232D
Parallel ports	0
USB 2.0 ports	4
Keyboard port	1 PS/2
Mouse port	1 PS/2
Audio ports	None
External Small Computer System Interface (SCSI) port	None
Security	
<ul style="list-style-type: none"> Power-on and privileged access password functions that control who has access to the data and server setup program on the server Selectable boot sequence that can prevent unauthorized installation of software or removal of data from the diskette drive 	
Power	
Maximum input power	350W
Autoranging AC input	Yes
PFC	Yes
Input low range	100 to 127 (nominal) VAC; 50–60Hz; 6A
Input high range	200 to 240 (nominal) VAC; 50–60Hz; 3A
Input kVA approximately	Maximum configuration 0.290 kVA
Environmental	
Air temperature—server on	50 to 95°F (10 to 35°C)
Air temperature—server off	–104 to 140°F (–40 to 60°C)
Humidity—server on	8 to 80% (noncondensing)
Maximum altitude	7000 ft (2133m)
BTU rating full configuration	989 Btu/hr (290W)
Sound emissions, idle	6.5 bel (operating)
Cooling system	7 fans installed (two are in power supply)
Dimensions	
Form factor	Rack-mount 1RU
Rack-mounting	Included for standard third-party rack

Weight—maximum	30.0 lb (12.7 kg)
Height	1.75 in. (43mm)
Width	17.32 in. (440mm)
Depth	22.0 in. (559mm)
Equipment Approvals and Safety	
<ul style="list-style-type: none"> • FCC—Verified to comply with Part 15 of the FCC Rules, Class A • Canada ICES-003, issue 4, Class A • UL/IEC 60950-1 • CAN C22.2 No. 60950-1-03 • NOM-019 	

ORDERING INFORMATION

To place an order, visit the [Cisco Ordering Home Page](#). Table 2 gives the part number for ordering based on product.

Table 2. Ordering Information

Product Name	Part Number
Cisco Unity Connection	UNITYCN-BUNDLE

SERVER SPARES

Table 3 gives information about ordering spare servers.

Table 3. Ordering Information for Spare Servers

Application	Spare Part Number
Cisco Unity Connection	MCS-7825-I2-UC1

FIELD-REPLACEABLE SPARES

Table 4 gives ordering information for server spare parts.

Table 4. Ordering Information for Server Spare Parts

Spare-Part Number	Description
MEM-7825-I2-2GB=	Spare pair 1-GB SDRAM dual in-line memory module (DIMM) for Cisco MCS 7825-I2 server
HDD-7825-I2-80=	Spare 80-GB SATA hard disk drive, cold pluggable

IDENTIFYING SERVER CPU SPEED

As the Cisco MCS 7825-I2 matures, the processor speeds will be changed as Intel retires slower processors and replaces them with faster processors. Table 5 provides the Cisco manufacturing part number shown on the chassis to help identify the processor speed of any individual server.

Table 5. Manufacturing Part Numbers by Processor Speed

Processor	Manufacturing Part Number Located on Server	Introduction
Intel Pentium 4 3.4-GHz processor	74-4521-01	Initial production of server

SERVICE AND SUPPORT

Cisco Systems® offers a wide range of services programs to accelerate customer success. These innovative services programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you protect your network investment, optimize network operations, and prepare your network for new applications to extend network intelligence and the power of your business. For more information about Cisco services, refer to [Cisco Technical Support Services](#) or [Cisco Advanced Services](#).

WARRANTY INFORMATION

Cisco offers a one-year limited hardware warranty on Cisco media convergence servers. For terms and conditions of this warranty, refer to http://www.cisco.com/univercd/cc/td/doc/es_inpk/1y1cen_.htm.

**Corporate Headquarters**

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

European Headquarters

Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: 31 0 20 357 1000
Fax: 31 0 20 357 1100

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-7660
Fax: 408 527-0883

Asia Pacific Headquarters

Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on **the Cisco Website at www.cisco.com/go/offices.**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel
Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal
Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan
Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2006 Cisco Systems, Inc. All rights reserved. CCSP, CCVP, the Cisco Square Bridge logo, Follow Me Browsing, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, the Networkers logo, Networking Academy, Network Registrar, Packet, PIX, Post-Routing, Pre-Routing, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0601R)

