

End-of-Sale and End-of-Life Announcement for the Cisco PIX 525 Security Appliance

EOL6266

Cisco® announces the end-of-sale and end-of life dates for the Cisco PIX 525 Security Appliance. The last day to order the affected product(s) is July 28, 2008. Customers with active service contracts will continue to receive support from the Cisco Technical Assistance Center (TAC) as shown in Table 1 of the EoL bulletin. Table 1 describes the end-of-life milestones, definitions, and dates for the affected product(s). Table 2 lists the product part numbers affected by this announcement. For customers with active and paid service and support contracts, support will be available until the termination date of the contract, even if this date exceeds the Last Date of Support shown in Table 1.

Cisco PIX Security Appliance customers are encouraged to migrate to Cisco ASA 5500 Series Adaptive Security Appliances. Built on the same software foundation as Cisco PIX Security Appliances, the Cisco ASA 5500 Series offers more robust firewall and IPsec VPN capabilities, as well as many additional benefits, including:

- Significantly better performance and scalability
- Secure Sockets Layer (SSL) VPN support (including clientless, portal-based remote access)
- Advanced Unified Communications (voice/video) security
- A modular design that allows you to add features such as intrusion prevention (IPS), anti-virus, anti-spam, anti-phishing, and URL filtering.

Migration to the Cisco ASA 5500 Series is straightforward. Customers can take advantage of their knowledge and investment in Cisco PIX Security Appliances, because there are essentially no changes in user interface, operations, or training.

Table 1. End-of-Life Milestones and Dates for the Cisco PIX 525 Security Appliance

Milestone	Definition	Date
End-of-Life Announcement Date	The date the document that announces the end of sale and end of life of a product is distributed to the general public.	January 28, 2008
End-of-Sale Date	The last date to order the product through Cisco point-of-sale mechanisms. The product is no longer for sale after this date.	July 28, 2008
Last Ship Date: HW	The last-possible ship date that can be requested of Cisco and/or its contract manufacturers. Actual ship date is dependent on lead time.	October 26, 2008
End of Routine Failure Analysis Date: HW	The last-possible date a routine failure analysis may be performed to determine the cause of product failure or defect.	July 28, 2009
End of New Service Attachment Date: HW	For equipment and software that is not covered by a service-and-support contract, this is the last date to order a new service-and-support contract or add the equipment and/or software to an existing service-and-support contract.	July 28, 2009
End of Service Contract Renewal Date: HW	The last date to extend or renew a service contract for the product.	October 23, 2012

Last Date of Support: HW	The last date to receive service and support for the product. After this date, all support services for the product are unavailable, and the product becomes obsolete.	July 27, 2013
--------------------------	--	---------------

HW = Hardware

OS SW = Operating System Software

App. SW = Application Software

Table 2. Product Part Numbers Affected by This Announcement

End-of-Sale Product Part Number	Product Description	Replacement Product Part Number	Replacement Product Description
PIX-525	PIX 525 Chassis (Chassis, Software, 2 FE Ports)	ASA5520-BUN-K9	ASA 5520 Appliance with SW, HA, 4GE+1FE, 3DES/AES
PIX-525	PIX 525 Chassis (Chassis, Software, 2 FE Ports)	ASA5520-K8	ASA 5520 Appliance with SW, HA, 4GE+1FE, DES
PIX-525-AA-GE-BUN	PIX 525 FO-AA Bundle (SW, Act/Act FO Lic, VAC+, 2 GE+2FE)	ASA5520-BUN-K9	ASA 5520 Appliance with SW, HA, 4GE+1FE, 3DES/AES
PIX-525-AA-GE-BUN	PIX 525 FO-AA Bundle (SW, Act/Act FO Lic, VAC+, 2 GE+2FE)	ASA5520-K8	ASA 5520 Appliance with SW, HA, 4GE+1FE, DES
PIX-525-FO-BUN	PIX 525-FO Bundle (Chassis, Failover SW, 2 FE Ports, VAC+)	ASA5520-BUN-K9	ASA 5520 Appliance with SW, HA, 4GE+1FE, 3DES/AES
PIX-525-FO-BUN	PIX 525-FO Bundle (Chassis, Failover SW, 2 FE Ports, VAC+)	ASA5520-K8	ASA 5520 Appliance with SW, HA, 4GE+1FE, DES
PIX-525-FO-GE-BUN	PIX 525-FO-GE Bundle (Chassis,Failover SW,2 GE+2 FE,VAC+)	ASA5520-BUN-K9	ASA 5520 Appliance with SW, HA, 4GE+1FE, 3DES/AES
PIX-525-FO-GE-BUN	PIX 525-FO-GE Bundle (Chassis,Failover SW,2 GE+2 FE,VAC+)	ASA5520-K8	ASA 5520 Appliance with SW, HA, 4GE+1FE, DES
PIX-525-R-BUN	PIX 525-R Bundle (Chassis, Restricted SW, 2 FE Ports)	ASA5520-BUN-K9	ASA 5520 Appliance with SW, HA, 4GE+1FE, 3DES/AES
PIX-525-R-BUN	PIX 525-R Bundle (Chassis, Restricted SW, 2 FE Ports)	ASA5520-K8	ASA 5520 Appliance with SW, HA, 4GE+1FE, DES
PIX-525-UR-BUN	PIX 525-UR Bundle (Chassis,Unrestricted SW,2 FE Ports,VAC+)	ASA5520-BUN-K9	ASA 5520 Appliance with SW, HA, 4GE+1FE, 3DES/AES
PIX-525-UR-BUN	PIX 525-UR Bundle (Chassis,Unrestricted SW,2 FE Ports,VAC+)	ASA5520-K8	ASA 5520 Appliance with SW, HA, 4GE+1FE, DES
PIX-525-UR-GE-BUN	PIX 525-UR-GE Bundle (Chassis,Unrestr. SW,2 GE+2 FE,VAC+)	ASA5520-BUN-K9	ASA 5520 Appliance with SW, HA, 4GE+1FE, 3DES/AES
PIX-525-UR-GE-BUN	PIX 525-UR-GE Bundle (Chassis,Unrestr. SW,2 GE+2 FE,VAC+)	ASA5520-K8	ASA 5520 Appliance with SW, HA, 4GE+1FE, DES

Product Migration Options

Customers are encouraged to migrate to the Cisco ASA 5520 Adaptive Security Appliance, which provides significantly higher firewall and VPN performance, advanced security features for greater network protection, SSL VPN support, and a modular design that allows customers to add features such as intrusion prevention (IPS),antivirus, antispam, antiphishing, URL filtering, and more. For customers requiring even higher firewall and VPN performance, firewall connection capacity, SSL/IPsec connection capacity, or small packet performance, Cisco recommends the Cisco ASA 5540 Adaptive Security Appliance.

Table 3. Product Comparisons

Feature	Cisco PIX 525 Security Appliance	Cisco ASA 5520 Adaptive Security Appliance
Maximum Firewall Throughput	330 Mbps	450 Mbps

Feature	Cisco PIX 525 Security Appliance	Cisco ASA 5520 Adaptive Security Appliance
Maximum 3DES/AES VPN Throughput	30 Mbps (R)/135 Mbps (UR/FO)	225 Mbps
Maximum Connections	140,000 (R)/280,000 (UR/FO)	280,000
Connections per Second	9500	12,000
Packets per Second (64-byte)	190,000	320,000
Maximum IPsec VPN Sessions	2000	750
Maximum SSL VPN Sessions	Not Supported	750
Integrated Network Ports	2 Fast Ethernet (R/UR/FO), 2 Gigabit Ethernet + 2 Fast Ethernet (UR-GE/FO-GE/AA-GE)	4 Gigabit Ethernet + 1 Fast Ethernet
Maximum Network Ports	10 Fast Ethernet, or 3 Gigabit Ethernet and 2 Fast Ethernet	8 Gigabit Ethernet + 1 Fast Ethernet
VLANs	25 (R)/100 (UR/FO)	150
High Availability/Scalability	Not Supported (R)/Active/Standby (FO)/Active/Active and Active/Standby (UR/FO-AA)	Active/Active, Active/Standby, and VPN Clustering/Load Balancing
Expandability	1 Fast Ethernet (1FE), 4 Fast Ethernet (4FE-66), 1 Gigabit Ethernet (1GE-66), VPN Accelerator Plus (VAC PLUS)	4 Gigabit Ethernet (4GE SSM), IPS (AIP SSM), Content Security (CSC SSM)

Customers can use the Cisco Technology Migration Plan (TMP) to trade in products and receive credit toward the purchase of new Cisco equipment. For more information about Cisco TMP, go to <http://www.cisco.com/go/tradein/>. The Cisco TMP application requires all users to have a Cisco.com user ID.

Customers may be able to continue to purchase the Cisco PIX 525 Security Appliance through the Cisco Certified Refurbished Equipment program. Refurbished units may be available in limited supply for sale in certain countries on a first-come, first-served basis until the Last Date of Support has been reached. For information about the Cisco Certified Refurbished Equipment program, go to <http://www.cisco.com/go/eos>.

For More Information

For more information about the Cisco ASA 5520 Adaptive Security Appliance, visit <http://www.cisco.com/go/asa>, or contact your local account representative.

For more information about the Cisco End-of-Life Policy, go to http://www.cisco.com/en/US/products/prod_end_of_life.html.

To subscribe to receive end-of-life/end-of-sale information, go to <http://www.cisco.com/cgi-bin/Support/FieldNoticeTool/field-notice>.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDF, CCENT, Cisco Eos, Cisco StadiumVision, the Cisco logo, DCE, and Welcome to the Human Network are trademarks. Changing the Way We Work, Live, Play, and Learn is a service mark and Access Registrar, Altnet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSR, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IQ Experience, the IQ logo, IQ Net, Readiness Scorecard, iQuickStudy, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MEX, Newscenter, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SNA First, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (080239)