



---

## A

additional information xvii  
addresses 2-21, 2-26  
admission control 3-15, 3-18, 6-3  
    for centralized call processing 7-3  
    for QoS 8-11  
    gatekeeper 3-15, 6-8, 6-15  
    locations 3-18, 7-4  
alarms 11-19  
ANI 11-8  
assistance with Cisco products xix

---

## B

bandwidth  
    in distributed systems 6-28  
    per call 3-15  
    provisioning for WAN 8-4  
best practices for QoS 8-10

---

## C

call admission control 3-15, 3-18, 6-3  
    for centralized call processing 7-3

    for QoS 8-11  
    gatekeeper 3-15, 6-8, 6-15  
    locations 3-18, 7-4

Call Detail Record (CDR) 11-1  
called party transformation 5-9  
calling party transformation 5-9  
calling search space 5-14, 5-15  
campus infrastructure 2-1  
Campus Manager 11-11  
Catalyst switches 9-1  
    4000 family 9-13  
    6000 family 2-34, 9-15  
    conferencing services 9-4  
    transcoding services 9-7  
CDP 2-22, 11-1  
CDR 11-1  
centralized call processing 1-10, 3-18, 7-1  
Cisco.com xix  
Cisco CallManager clusters 3-1  
Cisco Discovery Protocol (CDP) 2-22, 11-1  
CiscoWorks2000 11-1, 11-8, 11-13  
    Asynchronous Network Interface (ANI) 11-8  
    Campus Manager 11-11  
    Common Management Framework  
        (CMF) 11-8

- Resource Manager Essentials (RME) 11-15
  - User Tracking (UT) 11-12
  - class of service (CoS) 2-28
  - clusters 3-1
    - communication between 3-14
    - communication within 3-5
    - for centralized systems 7-8
    - guidelines 3-12
    - in distributed systems 6-30
    - provisioning 3-14
    - size of 3-1
    - with centralized call processing 3-18
    - with distributed call processing 3-15
  - CMF 11-8
  - comments on this guide xix
  - Common Object Request Broker Architecture (CORBA) 11-4
  - communication
    - between clusters 3-14
    - within a cluster 3-5
  - composite model 1-1
  - compression of voice stream 9-7
  - conferencing 9-4
  - connections
    - IP phone 2-9
    - PC 2-9
    - to the network 2-25
  - consumption of resources 3-3
  - conventions used in this guide xv
  - CORBA 11-4
  - CoS 2-28
- 
- D
- database
    - publisher 3-1, 3-5
    - subscriber 3-5
  - default power allocation 2-14
  - design goals 1-1
  - device pools 3-9
  - devices
    - in route group 5-8
    - pools 3-9
    - sessions 3-3
    - weight of 3-1, 3-3
  - device weights 3-1, 3-3
  - DHCP 2-21
  - dial plan 5-1
    - calling search space 5-14
    - for centralized systems 7-5
    - for distributed systems 6-15
    - guidelines 5-18
    - individual site 5-19
    - multiple sites 5-21
    - partitions 5-14
    - restrictions 6-28
  - dial string 5-10
  - Digital PBX Adapter (DPA) 10-20

digital signal processor (DSP) 9-1  
digit translation 5-9  
distributed call processing 1-7, 3-15, 6-1  
documentation  
    CD-ROM xviii  
    obtaining xviii  
    ordering from Cisco xviii  
    World Wide Web xviii  
    your feedback xix  
DPA 7630 10-20  
    described 10-20  
    integration modes 10-22  
DSP 9-1  
    for centralized systems 7-10  
    for distributed systems 6-30  
DTMF Relay  
    gateway support 4-3  
    supported in IOS H.323 gateways 4-4  
    supported in MGCP gateways 4-4  
    supported in Skinny gateways 4-4  
dual supervisors 2-16  
Dynamic Host Configuration Protocol  
    (DHCP) 2-21

---

## E

error messages for inline power 2-16  
Ethernet 2-5  
external patch panel 2-17

---

## F

features required for gateway selection 4-1  
feature transparency 3-21

---

## G

gatekeeper 3-15, 6-8, 6-15, 6-19  
gateways 4-1  
    list of 4-2  
    required features 4-1  
    site requirements 4-9  
    supported protocols 4-2  
    supported site requirements 4-11  
goals 1-1  
groups for redundancy 3-6

---

## H

H.323 used in VoIP gateways 4-2  
help with Cisco products xix  
high availability 2-7

---

## I

independent call processing 1-5  
infrastructure 2-1  
inline power 2-10  
integration modes 10-22

intercluster communication 3-14  
 interface queuing 8-2  
 intracluster communication 3-5  
 IP addresses 2-21, 2-26  
 IP phones 2-25  
   addresses 2-21, 2-26  
   external power supply 2-17  
   internals 2-5  
   power consumption 2-15  
   power to 2-10  
   wall power 2-20  
 IP telephony  
   design goals 1-1  
   network models 1-3

---

L

LAN infrastructure 2-1  
 legacy systems 10-1  
 link efficiency techniques 8-7  
 locations 3-18, 7-4

---

M

Management Information Base (MIB) 11-2  
 mask for digit translation 5-9  
 Media Gateway Control Protocol (MGCP) 4-2  
 media termination point (MTP) 9-7  
 MGCP 4-2

MIB 11-2  
 migration to IP telephony network 10-1  
 MTP 9-7  
 multisite 1-5  
   with centralized call processing 1-10, 7-1  
   with distributed call processing 1-7, 6-1  
   with independent call processing 1-5

---

N

network design 1-1  
   composite model 1-1  
   infrastructure 2-5  
   models 1-1  
   multiple sites with centralized call processing 1-10  
   multiple sites with distributed call processing 1-7  
   multiple sites with independent call processing 1-5  
   single site 1-3  
   topology 1-1  
 network management 11-1  
 notational conventions xv

---

O

off-net route pattern 5-12  
 on-net route pattern 5-11

---

**P**

partitions 5-14, 5-15  
PBX migration 10-1  
physical connections 2-9  
power  
    consumption 2-15  
    default allocation 2-14  
    error messages 2-16  
    external patch panel 2-17  
    for IP phones 2-10  
    from Catalyst module 2-10  
    inline 2-10  
    ports 2-17  
    protection 2-4, 2-16  
    recommendations 2-20  
    status 2-14  
    uninterruptible supply 2-4  
    wall outlet 2-20  
protection for power 2-4  
protocols  
    CDP 2-22  
    DHCP 2-21  
    for PBX and voice messaging 10-2  
    H.323 4-2  
    Media Gateway Control Protocol 4-2  
    Skinny Gateway Protocol 4-2  
    supported in VoIP gateways 4-2

PSTN 5-12  
publisher of the database 3-1

---

**Q**

QoS 2-28, 2-33, 8-1  
quality of service (QoS) 2-28  
queuing 8-2

---

**R**

redundancy 2-7, 3-6  
    supported in IOS H.323 gateways 4-5  
    supported in MGCP gateway 4-6  
    supported in Skinny gateways 4-5  
    support for gateways 4-5  
Remote Serviceability 11-1  
reports for network management 11-16  
resource consumption 3-3  
restrictions on dialing 6-28  
revision history xiv  
RME 11-15  
route group 5-1, 5-7  
route list 5-1, 5-7  
route pattern 5-1, 5-6  
    off-net 5-12  
    on-net 5-11  
routing calls through a gatekeeper 6-19

## S

SAC 11-4

SAenvProperties.ini file 11-4

servers

- per cluster 1-5
- TFTP 3-1

service

- class 2-28
- quality 2-28
- type 2-28

sessions 3-3

Simple Network Management Protocol (SNMP) 11-2

Simplified Message Desk Interface (SMDI) 10-21

single site 1-3

site requirements for gateway selection 4-9

Skinny Gateway Protocol 4-2

SMDI 10-21

SNMP 11-2

subscriber of the database 3-5

supplementary services 4-7

- supported in IOS H.323 gateways 4-8
- supported in MGCP gateways 4-9
- supported in Skinny gateways 4-7
- support for in gateways 4-7

Syslog

- administrative interface 11-6
- alarms 11-19

Analyzer Collector (SAC) 11-4

Collector 11-1, 11-4

components 11-3

log management 11-16

message filtering 11-18

Receiver 11-3

reports 11-16

## T

TAC xix, xx

technical assistance xix

TFTP server 3-1

tools for QoS 8-5

ToS 2-28

trace path analysis 11-13

traffic

- classification 2-28, 2-30, 2-34, 8-2
- prioritization 8-5
- shaping 8-9

transcoding 9-7

transformation of digits 5-9

translation of digits 5-9

transparency of features 3-21

trust boundaries 2-29

type of service (ToS) 2-28

---

## U

UDP 11-4

uninterruptible power supply (UPS) 2-4

UPS 2-4

User Datagram Protocol (UDP) 11-4

User Tracking (UT) 11-12

UT 11-12

---

## V

VLAN 2-22, 2-23, 2-24

voice compression 9-7

voice messaging

    for centralized systems 7-12

    for distributed systems 6-32

    migration to IP network 10-1

Voice VLAN ID (VVID) 2-22

VVID 2-22

---

## W

wall power 2-20

WAN

    bandwidth provisioning 8-4

    multisite with centralized call processing 7-1

    multisite with distributed call processing 6-1

    QoS 8-1

