

## Cisco IP Phone 7912G

As the market leader in IP telephony, Cisco continues to deliver unsurpassed end-to-end data and true voice-over-IP (VoIP) solutions, offering the most complete, stylish, and fully featured IP phone portfolio to enterprise and small to medium-size customers. Cisco IP phones provide unmatched levels of integrated business functionality and converged communications features beyond today's conventional voice systems.

Cisco IP phone products include pixel-based displays to bring productivity-enhancing applications to the phone, customization options that can be modified as needs change, and inline power support over Ethernet.

The Cisco IP Phone 7912G (Figure 1) provides core business features and addresses the communication needs of a cubicle worker who conducts low to medium telephone traffic. The Cisco IP Phone 7912G offers four dynamic soft keys that guide a user through call features and functions. The graphic capability of the display provides a rich user experience by providing calling information and intuitive access to features.

The Cisco IP Phone 7912G supports an integrated Ethernet switch, providing LAN connectivity to a collocated PC. In addition, the Cisco IP Phone 7912G supports inline power, which allows the phone to receive power over the LAN. This capability gives the network administrator centralized power control, translating into greater network availability. The combination of inline power and Ethernet switch support reduces cabling needs to a single wire to the desktop.

### Cisco IP Phone 7912G Features

The Cisco IP Phone 7912G is designed to be easy to use with conveniently placed features.

- Pixel-based display—A pixel-based display provides intuitive access to calling features.
- Four soft keys dynamically present calling options to the user. The scroll toggle bar allows easy movement through the displayed information.



Figure 1  
Cisco IP Phone 7912G



- “Menu” key—This key allows users to quickly access information such as call logs and phone settings.
  - The user can retrieve voice-mail messages.
  - The user can display missed calls, outgoing calls that have been placed, and incoming calls that have been received.
  - The user can set various preferences such as ring types and display contrast.
- “Hold” key—This lighted key provides users a red visual indication that they have placed a call on hold.
- A volume-control toggle provides easy decibel-level adjustments of the handset and ringer.
- The handset is hearing-aid compatible (meets American Disabilities Act [ADA] requirements).
- A single-position foot stand provides optimum display viewing and comfortable use of buttons and keys. The foot stand can be removed to allow wall mounting via mounting holes located on the base of the phone.

### Calling Features

The Cisco IP Phone 7912G is designed to grow with system capabilities. Features will keep pace with new changes via software updates to the phone Flash memory. Examples of currently available features include:

- Support of a single line or directory number
- Calling name and number display
- Call waiting
- Call forward
- Call transfer
- Three-way calling (conference)
- On-hook dialing, predialing, and off-hook dialing
- Redial
- Call hold
- Call monitor (speaker only, no microphone)
- “Messages” soft key that allows access to voicemail messages
- Four speed dials configurable at the Cisco CallManager

### Network Features

- Cisco Discovery Protocol
- Automatic IEEE 802.1q (virtual LAN [VLAN]) configuration
- G.711a, G.711u, and G.729ab audiocompression coders-decoders (codecs)
- Integrated Ethernet switch
- 10/100BASE-T Ethernet connection through an RJ-45 interface for LAN connectivity
- Software upgrade supported using a Trivial File Transfer Protocol (TFTP) server
- Provisioning of network parameters through Dynamic Host Configuration Protocol (DHCP)
- Voice activity detection, silence suppression, comfort-noise generation, and error concealment



### Protocols Supported

- Compatible with Cisco CallManager Version 3.3(2) and later, using the Skinny Client Control Protocol (SCCP) protocol

### Physical Specifications

- Dimensions (H x W x D): 6.5 x 7 x 6 in. (20.3 x 17.67 x 15.2 cm)
- Weight: 1.9 lb (0.9 kg)

### Power Supply

- Inline power
- Power can also be supplied locally using an optional AC to 48-VDC power adapter (CP-PWR-CUBE), which requires one of the following country-specific cords:
  - CP-PWR-CORD-NA (North America)
  - CP-PWR-CORD-CE (Central Europe)
  - CP-PWR-CORD-UK (United Kingdom)
  - CP-PWR-CORD-AU (Australia)
  - CP-PWR-CORD-JP (Japan)
  - CP-PWR-CORD-AP (Asia Pacific)

### Temperature

- Operating temperature: 32 to 104 F (0 to 40 C)
- Relative humidity: 10 to 95% (noncondensing)
- Storage temperature: 14 to 140 F (-10 to 60 C)

### Certification

#### **Regulatory Compliance**

- CE Marking

#### **Safety**

- UL 60950
- CSA-C22.2 No. 60950
- EN 60950
- IEC 60950
- AS/NZS 3260
- TS 001



## EMC

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B
- AS/NZS 3548 Class B
- VCCI Class B
- EN55024
- EN50082-1
- EN 61000-3-2
- EN 61000-3-3
- EN 61000-6-1

## Telecom

- FCC Part 68 (CFR 47) (HAC)

## Service and Support

Cisco IP Communications services and support reduce the cost, time, and complexity associated with implementing a converged network. Cisco and its partners have designed and deployed some of today's largest and most complex IP communications

networks—meaning that they understand how to integrate an IP communications solution into your network. Cisco design tools and best practices ensure that the solution best fits your business needs from the start, eliminating costly redesigns and downtime. Cisco proven methods ensure a sound implementation that will deliver the functions and features you expect—on time. Support services include remote network operations, network management tools to administer the converged application and network infrastructure, and technical support services.

Through these services, your organization benefits from the experience gained by Cisco and its partners. Taking advantage of this valuable experience, you can create and maintain a resilient, converged network that will meet your business needs today—and in the future.

## Ordering Information

Table 1 lists part numbers for the Cisco IP Phone 7912G and Cisco CallManager.

Table 1 Part Numbers

Part Number	Description
CP-7912G	Cisco IP Phone 7912 hardware
SW-CCM-UL-7912	Station user license for Cisco CallManager

Cisco offers a standard one-year warranty. A Cisco SMARTnet<sup>®</sup> optional service agreement is available.

## For More Information

For more information about Cisco products, call or visit:

- United States and Canada: (toll free) 800 553-NETS (6387)
- Europe: 32 2 778 4242
- Australia: 612 9935 4107
- Other: 408 526-7209
- <http://www.cisco.com>



Corporate Headquarters  
Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
[www.cisco.com](http://www.cisco.com)  
Tel: 408 526-4000  
800 553-NETS (6387)  
Fax: 408 526-4100

European Headquarters  
Cisco Systems International BV  
Haarlerbergpark  
Haarlerbergweg 13-19  
1101 CH Amsterdam  
The Netherlands  
[www-europe.cisco.com](http://www-europe.cisco.com)  
Tel: 31 0 20 357 1000  
Fax: 31 0 20 357 1100

Americas Headquarters  
Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
[www.cisco.com](http://www.cisco.com)  
Tel: 408 526-7660  
Fax: 408 527-0883

Asia Pacific Headquarters  
Cisco Systems, Inc.  
Capital Tower  
168 Robinson Road  
#22-01 to #29-01  
Singapore 068912  
[www.cisco.com](http://www.cisco.com)  
Tel: +65 6317 7777  
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on the  
**Cisco Web site at [www.cisco.com/go/offices](http://www.cisco.com/go/offices)**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia  
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland  
Israel • Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland  
Portugal • Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden  
Switzerland • Taiwan • Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

All contents are Copyright © 1992-2003 Cisco Systems, Inc. All rights reserved. Cisco, Cisco Systems, the Cisco Systems logo, and SMARTnet are registered trademarks or trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries.

All other trademarks mentioned in this document or Web site are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company.  
(0303R) 203057/ETMG\_04/03