

# Configuring Cisco Secure UNIX for Large Scale Dialout Using RADIUS

Document ID: 4185

## Contents

### Introduction

#### Prerequisites

- Requirements
- Components Used
- Conventions

#### Cisco Secure UNIX RADIUS Configuration

- Route Download Profile
- Dialout Profile
- Callee Authentication Profile

#### Configure

- Network Diagram
- Configurations

#### Verify

#### Troubleshoot

- Troubleshooting Commands

#### Related Information

## Introduction

This document provides step-by-step instructions for configuring Cisco Secure UNIX for Large Scale Dialout (LSDO) using the RADIUS protocol. The configuration described here assumes that the ISDN connection works prior to attempting LSDO.

In this example, Bacteria is a router that acts as the caller, and Ohio is a router that acts as the receiver (or "callee"). Bacteria downloads information from Cisco Secure UNIX on the routes to remote sites (this includes Ohio) so that traffic hitting Bacteria with an Ohio network destination is properly routed. In addition, Bacteria dynamically composes the dialer-map to Ohio and authenticates Ohio through Cisco Secure UNIX.

## Prerequisites

### Requirements

There are no specific requirements for this document.

### Components Used

The information in this document is based on these software and hardware versions:

- Cisco Secure UNIX Version 2.3.5.2
- Cisco IOS® Software Release 12.1(6)

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, make sure that you understand the potential impact of any command.

## Conventions

For more information on document conventions, refer to the Cisco Technical Tips Conventions.

# Cisco Secure UNIX RADIUS Configuration

## Route Download Profile

This downloads routes from Cisco Secure UNIX to Bacteria (the caller) and indicates routes to Ohio (the callee).

**Note:** The password must be **cisco**.

```
root@kilimanjaro(/opt/csecure/CLI)./ViewProfile -p 9900 -u bacteria-1
User Profile Information
user = bacteria-1{
profile_id = 232
set server current-failed-logins = 0
profile_cycle = 45
radius=Cisco {
check_items= {
2=cisco
}
reply_attributes= {
9,1="ip:route=2.2.2.2 255.255.255.255 Dialer1 200 name ohio"
9,1="ip:route=10.8.8.5 255.255.255.255 2.2.2.2"
}
}
}
```

## Dialout Profile

When there is traffic for Ohio, Bacteria fetches the "Ohio-out" profile from Cisco Secure UNIX in order to compose the dialer map dynamically. The password for this profile is hardcoded as **cisco** until Cisco IOS Software Release 12.1.5T, when the password is configurable with the **dialer aaa** command.

These are the required parameters:

- User service type is outbound user.
- Dial number is required.
- "send-secret" is sent to Ohio when it sends a Challenge Handshake Authentication Protocol (CHAP) request.
- "send-auth=2" represents CHAP.

```
root@kilimanjaro(/opt/csecure/CLI)./ViewProfile -p 9900 -u ohio-out
User Profile Information
user = ohio-out{
profile_id = 36
profile_cycle = 5
radius=Cisco {
check_items= {
2=cisco
}
reply_attributes= {
6=5
9,1="outbound:send-auth=2"
9,1="outbound:dial-number=244"
}
}
```

```
9,1="outbound:send-secret=cisco1"  
}  
}  
  
}  
;
```

## Callee Authentication Profile

This profile should also contain the authentication, authorization, and accounting (AAA) parameters in case AAA authorization is configured. The only parameters required are:

- Framed-Protocol=PPP
- User-Service-Type (Framed user)

```
root@kilimanjaro(/opt/csecure/CLI)./ViewProfile -p 9900 -u ohio  
User Profile Information  
user = ohio{  
  profile_id = 47  
  profile_cycle = 3  
  password = chap "*****"  
  radius=Cisco {  
    reply_attributes= {  
      6=2  
      7=1  
    }  
  }  
}
```


## Configure

In this section, you are presented with the information to configure the features described in this document.

**Note:** To find additional information on the commands used in this document, use the Command Lookup Tool (registered customers only) .

## Network Diagram

This document uses the network setup shown in this diagram.



## Configurations

This document uses the configurations shown here.

- Bacteria Router
- Ohio Router

### Bacteria Router

```
bacteria#show run
Building configuration...

Current configuration : 1358 bytes
!
version 12.1
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname bacteria
!
aaa new-model
aaa authentication login default none
aaa authentication ppp default group radius
aaa authentication ppp pppauthen group radius
aaa authorization network pppauthor group radius
aaa authorization configuration default group radius
aaa route download 15
enable password ww
!
ip subnet-zero
ip wccp web-cache
no ip finger
!
```

```

isdn switch-type basic-net3
!
interface Loopback1
no ip address
!
interface Ethernet0
ip address 172.17.241.2 255.255.255.0
!
interface Ethernet1
no ip address
shutdown
!
interface BRI0
no ip address
encapsulation ppp
dialer rotary-group 1
isdn switch-type basic-net3
no cdp enable
!
interface Dialer1
ip unnumbered Ethernet0
encapsulation ppp
load-interval 30
dialer in-band
dialer aaa
dialer-group 1
no cdp enable
ppp authentication chap pppauthen
ppp authorization pppauthor
!
ip classless
no ip http server
!
dialer-list 1 protocol ip permit
radius-server host 172.17.241.20 auth-port 1645 acct-port 1646
radius-server retransmit 3
radius-server key cisco
!
line con 0
exec-timeout 0 0
transport input none
line vty 0 4
exec-timeout 0 0
!
end

```

### Ohio Router

```

ohio#show run
Building configuration...

Current configuration : 1172 bytes
!
! Last configuration change at 11:15:05 UTC Tue Mar 20 2001
!
version 12.1
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname ohio
!
aaa new-model
aaa authentication login default none
aaa authentication ppp default local

```

```
enable password ww
!
username bacteria password 0 cisco1
!
ip subnet-zero
no ip finger
!
isdn switch-type basic-net3
!
interface Loopback0
ip address 10.8.8.5 255.255.255.255
!
interface Ethernet0
!
interface Ethernet1
no ip address
shutdown
!
interface BRI0
no ip address
encapsulation ppp
dialer pool-member 1
isdn switch-type basic-net3
!
interface Dialer1
ip address 2.2.2.2 255.255.255.0
encapsulation ppp
dialer pool 1
dialer remote-name bacteria
dialer string 245
dialer-group 1
no peer default ip address
pulse-time 0
no cdp enable
ppp authentication chap callin
ppp chap hostname ohio
!
ip classless
no ip http server
!
dialer-list 1 protocol ip permit
!
line con 0
exec-timeout 0 0
transport input none
line vty 0 4
!
end

ohio#
```

## Verify

There is currently no verification procedure available for this configuration.

## Troubleshoot

This section provides information you can use to troubleshoot your configuration.

## Troubleshooting Commands

Certain **show** commands are supported by the Output Interpreter Tool (registered customers only) , which allows you to view an analysis of **show** command output.

**Note:** Before issuing **debug** commands, please see Important Information on Debug Commands.

- **debug aaa authentication** Displays information on AAA authentication.
- **debug aaa authorization** Displays information on AAA authorization.
- **debug radius** Displays information associated with the RADIUS protocol.
- **debug ppp authentication** Displays authentication protocol messages, including CHAP packet exchanges and Password Authentication Protocol (PAP) exchanges.
- **debug ppp negotiation** Displays PPP packets transmitted during PPP startup, where PPP options are negotiated.

**Note:** Some of this "good" **debug** output has been wrapped to multiple lines because of spacing considerations.

### Bacteria Debug

```
bacteria#show debug
General OS:
  AAA Authentication debugging is on
  AAA Authorization debugging is on
PPP:
  PPP authentication debugging is on
  PPP protocol negotiation debugging is on
Radius protocol debugging is on
bacteria#debug dial
Dial on demand events debugging is on

!--- Clear and download routes manually.

bacteria#clear ip route download reload
Mar 20 12:14:06.030: AAA: parse name=<no string idb type=-1 tty=-1
Mar 20 12:14:06.030: AAA/MEMORY: create_user (0x2F71D94) user='' ruser=''
  port='' rem_addr='' authn_type=NONE service=LOGIN priv=0
Mar 20 12:14:06.038: unknown AAA/AUTHOR/CONFIG (4084759268): Port=''
  list='default' service=unknown
Mar 20 12:14:06.042: AAA/AUTHOR/CONFIG: unknown (4084759268) user='bacteria- 1'
Mar 20 12:14:06.042: unknown AAA/AUTHOR/CONFIG (4084759268): send AV service=ppp
Mar 20 12:14:06.046: unknown AAA/AUTHOR/CONFIG (4084759268): send AV protocol=ip
Mar 20 12:14:06.046: unknown AAA/AUTHOR/CONFIG (4084759268): found list "default"
Mar 20 12:14:06.050: unknown AAA/AUTHOR/CONFIG (4084759268): Method=radius (radius)
Mar 20 12:14:06.050: RADIUS: authenticating to get author data
Mar 20 12:14:06.054: RADIUS: ustruct sharecount=2
Mar 20 12:14:06.058: RADIUS: Initial Transmit id 154 172.17.241.20:164 5,
  Access-Request, len 68
Mar 20 12:14:06.062: Attribute 4 6 AC11F102
Mar 20 12:14:06.062: Attribute 61 6 00000000
Mar 20 12:14:06.062: Attribute 1 12 62616374
Mar 20 12:14:06.066: Attribute 2 18 D1F7B4AC
Mar 20 12:14:06.066: Attribute 6 6 00000005
Mar 20 12:14:06.189: RADIUS: Received from id 154 172.17.241.20:1645,
  Access-Accept, len 131
Mar 20 12:14:06.189: Attribute 26 62 0000000901386970
Mar 20 12:14:06.193: Attribute 26 49 00000009012B6970
Mar 20 12:14:06.197: RADIUS: saved authorization data for
  user 2F71D94 at 2F77564
Mar 20 12:14:06.201: RADIUS: cisco AVPair
  "ip:route=2.2.2.2 255.255.255.255 Dialer1 200 name ohio"
Mar 20 12:14:06.205: RADIUS: cisco AVPair
```

```
"ip:route=10.8.8.5 255.255.255.255 2.2.2.2"
Mar 20 12:14:06.209: AAA/AUTHOR (4084759268): Post authorization
status = PASS_REPL
Mar 20 12:14:06.209: AAA/AUTHOR/CONFIG: Processing AV route=2.2.2.2 255.255.255.255
Dialer1 200 name ohio
Mar 20 12:14:06.213: AAA/AUTHOR/CONFIG: Parse 'ip route 2.2.2.2 255.255.255. 255
Dialer1 200 name ohio'
Mar 20 12:14:06.364: AAA/AUTHOR/CONFIG: Parse returned ok (0)
Mar 20 12:14:06.364: AAA/AUTHOR/CONFIG: Processing
AV route=10.8.8.5 255.255.255.255 2.2.2.2
Mar 20 12:14:06.368: AAA/AUTHOR/CONFIG: Parse
'ip route 10.8.8.5 255.255.255 .255 2.2.2.2'
Mar 20 12:14:06.395: AAA/AUTHOR/CONFIG: Parse returned ok (0)
Mar 20 12:14:06.395: unknown AAA/AUTHOR/CONFIG (1200529675):
Port='' list='default' service=unknown
Mar 20 12:14:06.399: AAA/AUTHOR/CONFIG: unknown (1200529675) user='bacteria- 2'
Mar 20 12:14:06.399: unknown AAA/AUTHOR/CONFIG (1200529675): send AV service=ppp
Mar 20 12:14:06.403: unknown AAA/AUTHOR/CONFIG (1200529675): send AV protocol=ip
Mar 20 12:14:06.403: AAA/AUTHOR/CONFIG: unknown (1200529675)
Processing AV route=2.2.2.2 255.255.255.255 Dialer1 200 name ohio
Mar 20 12:14:06.407: AAA/AUTHOR/CONFIG: unknown (1200529675)
Processing AV route=10.8.8.5 255.255.255.255 2.2.2.2
Mar 20 12:14:06.411: unknown AAA/AUTHOR/CONFIG (1200529675): found list "default"
Mar 20 12:14:06.411: unknown AAA/AUTHOR/CONFIG (1200529675): Method=radius (radius)
Mar 20 12:14:06.415: RADIUS: authenticating to get author data
Mar 20 12:14:06.415: RADIUS: ustruct sharecount=2
Mar 20 12:14:06.419: RADIUS: Initial Transmit id 155 172.17.241.20:164 5,
Access-Request, len 68
Mar 20 12:14:06.423: Attribute 4 6 AC11F102
Mar 20 12:14:06.423: Attribute 61 6 00000000
Mar 20 12:14:06.427: Attribute 1 12 62616374
Mar 20 12:14:06.427: Attribute 2 18 B7819303
Mar 20 12:14:06.427: Attribute 6 6 00000005
Mar 20 12:14:07.490: RADIUS: Received from id 155 172.17.241.20:1645,
Access-Reject, len 20
Mar 20 12:14:07.506: RADIUS: saved authorization data for user 2F71D94 at 0
Mar 20 12:14:07.506: RADIUS: failed to get authorization data: authen status = 2
Mar 20 12:14:07.506: AAA/AUTHOR (1200529675): Post authorization status = ERROR
Mar 20 12:14:07.510: unknown AAA/AUTHOR/CONFIG (1200529675): Method=NOT_SET
Mar 20 12:14:07.510: unknown AAA/AUTHOR/CONFIG (1200529675): no methods left to try
Mar 20 12:14:07.514: AAA/AUTHOR (1200529675): Post authorization status = ERROR
Mar 20 12:14:07.514: AAA/AUTHOR/CONFIG: route downloading completed
Mar 20 12:14:07.518: AAA/MEMORY: free_user (0x2F71D94) user='bacteria-2' ruser=''
port='' rem_addr='' authen_type=NONE service=LOGIN priv=0
```

*!--- Show the downloaded route to the remote network.*

*!--- If everything goes well up to this step, you see the following.*

```
bacteria#show ip route static download
Connectivity: A - Active, I - Inactive
2.2.2.2 255.255.255.255 Dialer1 200 name ohio
10.8.8.5 255.255.255.255 2.2.2.2
```

*!--- Initiate traffic from the caller router to the*

*!--- callee router's loopback to bring up the link.*

```
bacteria#ping 10.8.8.5
```

*!--- Bacteria initiates call to Ohio.*

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 10.8.8.5, timeout is 2 seconds:

```
Mar 20 12:00:24.015: 6018: Same state, 0
Mar 20 12:00:24.015: DSES 6018: Session create
Mar 20 12:00:24.019: DSES 0x6018: Building dialer map
Mar 20 12:00:24.023: DSES 0x6018: Next hop name is ohio
```

```
Mar 20 12:00:24.023: AAA: parse name=Dialer1 idb type=-1 tty=-1
Mar 20 12:00:24.027: AAA: name=Dialer1 flags=0x11 type=6 shelf=0 slot=0
adapter=0 port=1 channel=0
Mar 20 12:00:24.027: AAA: parse name=<no string idb type=-1 tty=-1
Mar 20 12:00:24.031: AAA/MEMORY: create_user (0x2F6ED60) user='ohio-out' ruser=''
port='Dialer1' rem_addr='Dial out' authen_type=NONE service=LOGIN priv=0
Mar 20 12:00:24.035: Di1 AAA/AUTHOR/DIALOUT (324326219): Port='Dialer1'
list='default' service=unknown
Mar 20 12:00:24.039: AAA/AUTHOR/DIALOUT: Di1 (324326219) user='ohio-out'
Mar 20 12:00:24.039: Di1 AAA/AUTHOR/DIALOUT (324326219): send AV service=out bound
Mar 20 12:00:24.039: Di1 AAA/AUTHOR/DIALOUT (324326219): send AV protocol=ip
Mar 20 12:00:24.043: Di1 AAA/AUTHOR/DIALOUT (324326219): found list "default"
Mar 20 12:00:24.043: Di1 AAA/AUTHOR/DIALOUT (324326219): Method=radius (radius)
Mar 20 12:00:24.047: RADIUS: authenticating to get author data
Mar 20 12:00:24.047: RADIUS: ustruct sharecount=2
Mar 20 12:00:24.055: RADIUS: Initial Transmit Dialer1 id 150 172.17.241.20:1 645,
Access-Request, len 76
Mar 20 12:00:24.055: Attribute 4 6 AC11F102
Mar 20 12:00:24.059: Attribute 61 6 00000000
Mar 20 12:00:24.059: Attribute 1 10 6F68696F
Mar 20 12:00:24.059: Attribute 31 10 4469616C
Mar 20 12:00:24.063: Attribute 2 18 B8255AF6
Mar 20 12:00:24.063: Attribute 6 6 00000005
Mar 20 12:00:24.123: RADIUS: Received from id 150 172.17.241.20:1645,
Access-Accept, len 121
Mar 20 12:00:24.127: Attribute 6 6 00000005
Mar 20 12:00:24.127: Attribute 26 28 0000000901166F75
Mar 20 12:00:24.130: Attribute 26 32 00000009011A6F75
Mar 20 12:00:24.130: Attribute 26 35 00000009011D6F75
Mar 20 12:00:24.134: RADIUS: saved authorization data for user
2F6ED60 at 2F79CBC
Mar 20 12:00:24.138: RADIUS: cisco AVPair "outbound:send-auth=2"
Mar 20 12:00:24.142: RADIUS: cisco AVPair "outbound:dial-number=244"
Mar 20 12:00:24.142: RADIUS: cisco AVPair "outbound:send-secret=ciscol"
Mar 20 12:00:24.146: Di1 AAA/AUTHOR (324326219): Post authorization
status = PASS_REPL
Mar 20 12:00:24.146: Di1 AAA/AUTHOR/DIALOUT: Processing AV send-auth=2
Mar 20 12:00:24.150: Di1 AAA/AUTHOR/DIALOUT: Processing AV dial-number=244
Mar 20 12:00:24.150: Di1 AAA/AUTHOR/DIALOUT: Processing AV send-secret=cisco 1
Mar 20 12:00:24.154: Di1 AAA/AUTHOR/DIALOUT: Authorization succeeded
Mar 20 12:00:24.158: Di1 AAA/AU.THOR/DIALOUT: truncating '-out' suffix,
user now is 'ohio'
Mar 20 12:00:24.158: %LSDialout: temporary debug to verify the data integrity
Mar 20 12:00:24.158: dial number = 244
Mar 20 12:00:24.162: dialnum_count = 1
Mar 20 12:00:24.162: force_56 = 0
Mar 20 12:00:24.162: routing = 0
Mar 20 12:00:24.166: data_svc = -1
Mar 20 12:00:24.166: port_type = -1
Mar 20 12:00:24.166: map_class =
Mar 20 12:00:24.166: ip_address = 0.0.0.0
Mar 20 12:00:24.170: send_secret = ciscol
Mar 20 12:00:24.170: send_auth = 2
Mar 20 12:00:24.174: BR0 DDR: rotor dialout [priority]
Mar 20 12:00:24.174: BR0 DDR: Dialing cause dialer session 0x6018
Mar 20 12:00:24.178: BR0 DDR: Attempting to dial 244
Mar 20 12:00:24.210: %ISDN-6-LAYER2UP: Layer 2 for Interface BR0,
TEI 66 changed to up
Mar 20 12:00:25.785: %LINK-3-UPDOWN: Interface BRI0:1, changed state to up
Mar 20 12:00:25.805: BR0:1 PPP: Treating connection as a callout
Mar 20 12:00:25.809: BR0:1 PPP: Phase is ESTABLISHING, Active Open
Mar 20 12:00:25.813: BR0:1 AAA/AUTHOR/FSM: (0): LCP succeeds trivially
Mar 20 12:00:25.813: BR0:1 LCP: O CONFREQ [Closed] id 101 len 15
Mar 20 12:00:25.817: BR0:1 LCP: AuthProto CHAP (0x0305C223 05)
Mar 20 12:00:25.817: BR0:1 LCP: MagicNumber 0x258B27C2 (0x0506258B27C2)
Mar 20 12:00:25.861: BR0:1 LCP: I CONFREQ [REQsent] id 102 len 15
```

```

Mar 20 12:00:25.861: BR0:1 LCP: AuthProto CHAP (0x0305C223 05)
Mar 20 12:00:25.865: BR0:1 LCP: MagicNumber 0x488AD858 (0x0506488AD858)
Mar 20 12:00:25.868: BR0:1 LCP: O CONFACK [REQsent] id 102 len 15
Mar 20 12:00:25.868: BR0:1 LCP: AuthProto CHAP (0x0305C223 05)
Mar 20 12:00:25.872: BR0:1 LCP: MagicNumber 0x488AD858 (0x0506488AD858)
Mar 20 12:00:25.876: BR0:1 LCP: I CONFACK [ACKsent] id 101 len 15
Mar 20 12:00:25.876: BR0:1 LCP: AuthProto CHAP (0x0305C223 05)
Mar 20 12:00:25.880: BR0:1 LCP: MagicNumber 0x258B27C2 (0x0506258B27C2)
Mar 20 12:00:25.884: BR0:1 LCP: State is Open
Mar 20 12:00:25.884: BR0:1 PPP: Phase is AUTHENTICATING, by both
Mar 20 12:00:25.888: BR0:1 CHAP: O CHALLENGE id 73 len 29 from "bacteria"
Mar 20 12:00:25.904: BR0:1 CHAP: I CHALLENGE id 66 len 25 from "ohio"
Mar 20 12:00:25.908: AAA: parse name=BRI0:1 idb type=14 tty=-1
Mar 20 12:00:25.912: AAA: name=BRI0:1 flags=0x51 type=2 shelf=0 slot=0
    adapter=0 port=0 channel=1
Mar 20 12:00:25.912: AAA: parse name=<no string idb type=-1 tty=-1
Mar 20 12:00:25.916: AAA/MEMORY: create_user (0x2F7C4AC) user='ohio' ruser=''
    port='BRI0:1' rem_addr='244' authen_type=CHAP service=PPP priv=1
Mar 20 12:00:25.916: AAA/AUTHEN/START (2058338926): port='BRI0:1'
    list='pppa uthen' action=SENDAUTH service=PPP
Mar 20 12:00:25.920: AAA/AUTHEN/START (2058338926): found list pppauthen
    .!!!
Success rate is 60 percent (3/5), round-trip min/avg/max = 36/36/36 ms
bacteria#
Mar 20 12:00:25.920: AAA/AUTHEN/START (2058338926): Method=radius (radius)

!--- Bacteria uses the send-secret from the ohio-out profile,
!--- which was cached in response to the CHAP challenge from Ohio.

Mar 20 12:00:25.924: AAA/AUTHEN/SENDAUTH (2058338926): found cached secret for ohio
Mar 20 12:00:25.928: AAA/AUTHEN (2058338926): status = PASS
Mar 20 12:00:25.928: AAA/MEMORY: free_user (0x2F7C4AC) user='ohio' ruser=''
    port='BRI0:1' rem_addr='244' authen_type=CHAP service=PPP priv=1
Mar 20 12:00:25.932: BR0:1 CHAP: O RESPONSE id 66 len 29 from "bacteria"
Mar 20 12:00:25.956: BR0:1 CHAP: I SUCCESS id 66 len 4

!--- The above shows a successful authentication to Ohio.
!--- Now it is Ohio's turn to authenticate Bacteria.
!--- Bacteria receives the CHAP response from Ohio now.

Mar 20 12:00:25.972: BR0:1 CHAP: I RESPONSE id 73 len 25 from "ohio"
Mar 20 12:00:25.976: AAA: parse name=BRI0:1 idb type=14 tty=-1
Mar 20 12:00:25.980: AAA: name=BRI0:1 flags=0x51 type=2 shelf=0 slot=0
    adapter=0 port=0 channel=1
Mar 20 12:00:25.980: AAA: parse name=<no string idb type=-1 tty=-1
Mar 20 12:00:25.984: AAA/MEMORY: create_user (0x2F7C4AC) user='ohio' ruser=''
    port='BRI0:1' rem_addr='244' authen_type=CHAP service=PPP priv=1
Mar 20 12:00:25.984: AAA/AUTHEN/START (2332678419): port='BRI0:1'
    list='pppa uthen' action=LOGIN service=PPP
Mar 20 12:00:25.988: AAA/AUTHEN/START (2332678419): found list pppauthen
Mar 20 12:00:25.988: AAA/AUTHEN/START (2332678419): Method=radius (radius)
Mar 20 12:00:25.991: RADIUS: ustruct sharecount=1
Mar 20 12:00:25.999: RADIUS: Initial Transmit BRI0:1 id 151 172.17.241.20:16 45,
    Access-Request, len 80
Mar 20 12:00:25.999: Attribute 4 6 AC11F102
Mar 20 12:00:26.003: Attribute 5 6 00007531
Mar 20 12:00:26.003: Attribute 61 6 00000002
Mar 20 12:00:26.003: Attribute 1 6 6F68696F
Mar 20 12:00:26.007: Attribute 31 5 32343403
Mar 20 12:00:26.007: Attribute 3 19 495D0BB6

!--- Bacteria computes whether the expected CHAP response from Ohio matches
!--- Bacteria's password. Bacteria looks for this password in the AAA server and verify
!--- that Ohio passes CHAP authentication.

Mar 20 12:00:26.011: Attribute 6 6 00000002

```

```

Mar 20 12:00:26.011: Attribute 7 6 00000001
Mar 20 12:00:26.118: RADIUS: Received from id 151 172.17.241.20:1645,
  Access-Accept, len 32
Mar 20 12:00:26.118: Attribute 6 6 00000002
Mar 20 12:00:26.122: Attribute 7 6 00000001
Mar 20 12:00:26.126: AAA/AUTHEN (2332678419): status = PASS
Mar 20 12:00:26.126: BR0:1 AAA/AUTHOR/LCP: Authorize LCP
Mar 20 12:00:26.130: BR0:1 AAA/AUTHOR/LCP (2058167235): Port='BRI0:1'
  list='pppauthor' service=NET
Mar 20 12:00:26.130: AAA/AUTHOR/LCP: BR0:1 (2058167235) user='ohio'
Mar 20 12:00:26.134: BR0:1 AAA/AUTHOR/LCP (2058167235): send AV service=ppp
Mar 20 12:00:26.134: BR0:1 AAA/AUTHOR/LCP (2058167235): send AV protocol=lcp
Mar 20 12:00:26.138: BR0:1 AAA/AUTHOR/LCP (2058167235): found list "pppauthor"
Mar 20 12:00:26.138: BR0:1 AAA/AUTHOR/LCP (2058167235): Method=radius (radius)
Mar 20 12:00:26.142: BR0:1 AAA/AUTHOR (2058167235):
  Post authorization status = PASS_REPL
Mar 20 12:00:26.142: BR0:1 AAA/AUTHOR/LCP: Processing AV service=ppp
Mar 20 12:00:26.146: BR0:1 CHAP: O SUCCESS id 73 len 4
Mar 20 12:00:26.150: BR0:1 PPP: Phase is UP
Mar 20 12:00:26.154: BR0:1 AAA/AUTHOR/FSM: (0): Can we start IPCP?
Mar 20 12:00:26.158: BR0:1 AAA/AUTHOR/FSM (3151880806): Port='BRI0:1'
  list='pppauthor' service=NET
Mar 20 12:00:26.158: AAA/AUTHOR/FSM: BR0:1 (3151880806) user='ohio'
Mar 20 12:00:26.162: BR0:1 AAA/AUTHOR/FSM (3151880806): send AV service=ppp
Mar 20 12:00:26.162: BR0:1 AAA/AUTHOR/FSM (3151880806): send AV protocol=ip
Mar 20 12:00:26.166: BR0:1 AAA/AUTHOR/FSM (3151880806): found list "pppauthor"
Mar 20 12:00:26.166: BR0:1 AAA/AUTHOR/FSM (3151880806): Method=radius (radius)
Mar 20 12:00:26.170: BR0:1 AAA/AUTHOR (3151880806):
  Post authorization status = PASS_REPL
Mar 20 12:00:26.170: BR0:1 AAA/AUTHOR/FSM: We can start IPCP
Mar 20 12:00:26.174: BR0:1 IPCP: O CONFREQ [Closed] id 23 len 10
Mar 20 12:00:26.178: BR0:1 IPCP: Address 172.17.241.2 (0x0306AC11F102)
Mar 20 12:00:26.182: BR0:1 IPCP: I CONFREQ [REQsent] id 27 len 10
Mar 20 12:00:26.186: BR0:1 IPCP: Address 2.2.2.2 (0x030602020202)
Mar 20 12:00:26.190: BR0:1 AAA/AUTHOR/IPCP: Start. Her address 2.2.2.2,
  we want 2.2.2.2
Mar 20 12:00:26.194: BR0:1 AAA/AUTHOR/IPCP (2349819948): Port='BRI0:1'
  list='pppauthor' service=NET
Mar 20 12:00:26.194: AAA/AUTHOR/IPCP: BR0:1 (2349819948) user='ohio'
Mar 20 12:00:26.198: BR0:1 AAA/AUTHOR/IPCP (2349819948): send AV service=ppp
Mar 20 12:00:26.198: BR0:1 AAA/AUTHOR/IPCP (2349819948): send AV protocol=ip
Mar 20 12:00:26.202: BR0:1 AAA/AUTHOR/IPCP (2349819948): send AV addr*2.2.2. 2
Mar 20 12:00:26.202: BR0:1 AAA/AUTHOR/IPCP (2349819948): found list "pppauthor"
Mar 20 12:00:26.206: BR0:1 AAA/AUTHOR/IPCP (2349819948): Method=radius (radius)
Mar 20 12:00:26.210: BR0:1 AAA/AUTHOR (2349819948): Post authorization
  status = PASS_REPL
Mar 20 12:00:26.210: BR0:1 AAA/AUTHOR/IPCP: Reject 2.2.2.2, using 2.2.2.2
Mar 20 12:00:26.214: BR0:1 AAA/AUTHOR/IPCP: Processing AV service=ppp
Mar 20 12:00:26.218: BR0:1 AAA/AUTHOR/IPCP: Processing AV addr*2.2.2.2
Mar 20 12:00:26.218: BR0:1 AAA/AUTHOR/IPCP: Authorization succeeded
Mar 20 12:00:26.222: BR0:1 AAA/AUTHOR/IPCP: Done. Her address 2.2.2.2,
  we want 2.2.2.2
Mar 20 12:00:26.226: BR0:1 IPCP: O CONFACK [REQsent] id 27 len 10
Mar 20 12:00:26.226: BR0:1 IPCP: Address 2.2.2.2 (0x030602020202)
Mar 20 12:00:26.230: BR0:1 IPCP: I CONFACK [ACKsent] id 23 len 10
Mar 20 12:00:26.234: BR0:1 IPCP: Address 172.17.241.2 (0x0306AC11F102)
Mar 20 12:00:26.234: BR0:1 IPCP: State is Open
Mar 20 12:00:26.241: BR0:1 DDR: dialer protocol up
Mar 20 12:00:26.245: BR0:1: Call connected, 1 packets unqueued,
  0 transmitte d, 1 discarded
Mar 20 12:00:26.249: Di1 IPCP: Install route to 2.2.2.2
Mar 20 12:00:27.662: %LINEPROTO-5-UPDOWN: Line protocol on Interface BRI0:1,
  changed state to up

```

## Ohio Debug

```
ohio#show debug
PPP:
  PPP authentication debugging is on
  PPP protocol negotiation debugging is on
Mar 20 12:00:26.293: %DIALER-6-BIND: Interface BR0:1 bound to profile Dil
Mar 20 12:00:26.309: %LINK-3-UPDOWN: Interface BRI0:1, changed state to up
Mar 20 12:00:26.329: BR0:1 PPP: Treating connection as a callin
Mar 20 12:00:26.329: BR0:1 PPP: Phase is ESTABLISHING, Passive Open
Mar 20 12:00:26.333: BR0:1 LCP: State is Listen
Mar 20 12:00:26.337: %ISDN-6-LAYER2UP: Layer 2 for Interface BR0,
  TEI 75 changed to up
Mar 20 12:00:27.448: BR0:1 LCP: I CONFREQ [Listen] id 101 len 15
Mar 20 12:00:27.452: BR0:1 LCP: AuthProto CHAP (0x0305C223 05)
Mar 20 12:00:27.456: BR0:1 LCP: MagicNumber 0x258B27C2 (0x0506258B27C2)
Mar 20 12:00:27.460: BR0:1 LCP: O CONFREQ [Listen] id 102 len 15
Mar 20 12:00:27.460: BR0:1 LCP: AuthProto CHAP (0x0305C223 05)
Mar 20 12:00:27.464: BR0:1 LCP: MagicNumber 0x488AD858 (0x0506488AD858)
Mar 20 12:00:27.468: BR0:1 LCP: O CONFACK [Listen] id 101 len 15
Mar 20 12:00:27.468: BR0:1 LCP: AuthProto CHAP (0x0305C223 05)
Mar 20 12:00:27.472: BR0:1 LCP: MagicNumber 0x258B27C2 (0x0506258B27C2)
Mar 20 12:00:27.495: BR0:1 LCP: I CONFACK [ACKsent] id 102 len 15
Mar 20 12:00:27.495: BR0:1 LCP: AuthProto CHAP (0x0305C223 05)
Mar 20 12:00:27.499: BR0:1 LCP: MagicNumber 0x488AD858 (0x0506488AD858)
Mar 20 12:00:27.503: BR0:1 LCP: State is Open
Mar 20 12:00:27.503: BR0:1 PPP: Phase is AUTHENTICATING, by both
Mar 20 12:00:27.503: BR0:1 CHAP: Using alternate hostname ohio
Mar 20 12:00:27.507: BR0:1 CHAP: O CHALLENGE id 66 len 25 from "ohio"
Mar 20 12:00:27.511: BR0:1 CHAP: I CHALLENGE id 73 len 29 from "bacteria"
Mar 20 12:00:27.515: BR0:1 CHAP: Waiting for peer to authenticate first
Mar 20 12:00:27.555: BR0:1 CHAP: I RESPONSE id 66 len 29 from "bacteria"
Mar 20 12:00:27.563: BR0:1 CHAP: O SUCCESS id 66 len 4
Mar 20 12:00:27.567: BR0:1 CHAP: Processing saved Challenge, id 73
Mar 20 12:00:27.571: BR0:1 CHAP: Using alternate hostname ohio
Mar 20 12:00:27.575: BR0:1 CHAP: O RESPONSE id 73 len 25 from "ohio"
Mar 20 12:00:27.777: BR0:1 CHAP: I SUCCESS id 73 len 4
Mar 20 12:00:27.781: BR0:1 PPP: Phase is UP
Mar 20 12:00:27.785: BR0:1 IPCP: O CONFREQ [Not negotiated] id 27 len 10
Mar 20 12:00:27.789: BR0:1 IPCP: Address 2.2.2.2 (0x030602020202)
Mar 20 12:00:27.801: BR0:1 IPCP: I CONFREQ [REQsent] id 23 len 10
Mar 20 12:00:27.805: BR0:1 IPCP: Address 172.17.241.2 (0x0306AC11F102)
Mar 20 12:00:27.805: BR0:1 IPCP: O CONFACK [REQsent] id 23 len 10
Mar 20 12:00:27.809: BR0:1 IPCP: Address 172.17.241.2 (0x0306AC11F102)
Mar 20 12:00:27.856: BR0:1 IPCP: I CONFACK [ACKsent] id 27 len 10
Mar 20 12:00:27.860: BR0:1 IPCP: Address 2.2.2.2 (0x030602020202)
Mar 20 12:00:27.864: BR0:1 IPCP: State is Open
Mar 20 12:00:28.039: Dil IPCP: Install route to 172.17.241.2
Mar 20 12:00:28.777: %LINEPROTO-5-UPDOWN: Line protocol on Interface BRI0:1,
  changed state to up
ohio#
```

## Related Information

- [Cisco Secure Access Control Server for Unix](#)
- [Technical Support – Cisco Systems](#)

---

[Contacts & Feedback](#) | [Help](#) | [Site Map](#)

© 2010 – 2011 Cisco Systems, Inc. All rights reserved. [Terms & Conditions](#) | [Privacy Statement](#) | [Cookie Policy](#) | [Trademarks of Cisco Systems, Inc.](#)