



```
:Choose the operation you want to perform
.NEW - Create a new listener -
.EDIT - Modify a listener -
.DELETE - Remove a listener -
.SETUP - Change global settings -
edit <[]
```

```
.Enter the name or number of the listener you wish to edit
2 <[]
```

```
Name: OutboundMail
Type: Private
Interface: Privatenet (172.20.0.142/24) TCP Port 25
Protocol: SMTP
:Default Domain
(Max Concurrency: 600 (TCP Queue: 50
Domain Map: Disabled
TLS: No
SMTP Authentication: Disabled
Bounce Profile: Default
Footer: None
LDAP: Off
```

```
:Choose the operation you want to perform
.NAME - Change the name of the listener -
.INTERFACE - Change the interface -
.LIMITS - Change the injection limits -
.SETUP - Configure general options -
.HOSTACCESS - Modify the Host Access Table -
BOUNCECONFIG - Choose the bounce profile to use for messages injected on this -
.listener
.MASQUERADE - Configure the Domain Masquerading Table -
.DOMAINMAP - Configure domain mappings -
LDAPACCEPT - Configure an LDAP query to determine whether a recipient address -
.should be accepted or bounced/dropped
setup <[]
```

```
Enter the default domain for email addresses without a fully qualified domain
.name
```

```
Enter the word "DELETE" to clear the setting and disable the addition of a
.default domain
<[]
```

```
Would you like the system to add a received header to each message received on
<[this listener? [Y
```

```
Would you like to enable SenderBase Reputation Filters and IP Profiling
<[support? [N
```

```
Would you like to attach a footer to all mail on this listener? [N]> y
```

```
Disclaimer .1
<[1]
```

```
Name: OutboundMail
Type: Private
Interface: Privatenet (172.20.0.142/24) TCP Port 25
Protocol: SMTP
:Default Domain
(Max Concurrency: 600 (TCP Queue: 50
Domain Map: Disabled
TLS: No
SMTP Authentication: Disabled
```

Bounce Profile: Default

Footer: Disclaimer

LDAP: Off

```
:Choose the operation you want to perform
.NAME - Change the name of the listener -
.INTERFACE - Change the interface -
.LIMITS - Change the injection limits -
.SETUP - Configure general options -
.HOSTACCESS - Modify the Host Access Table -
BOUNCECONFIG - Choose the bounce profile to use for messages injected on this -
.listener
.MASQUERADE - Configure the Domain Masquerading Table -
.DOMAINMAP - Configure domain mappings -
LDAPACCEPT - Configure an LDAP query to determine whether a recipient address -
.should be accepted or bounced/dropped
<[]
```

:Currently configured listeners

```
InboundMail (on PublicNet, 192.168.195.42) SMTP TCP Port 25 Public .1
OutboundMail (on Privatenet, 172.20.0.142) SMTP TCP Port 25 Private .2
```

```
:Choose the operation you want to perform
```

```
.NEW - Create a new listener -
.EDIT - Modify a listener -
.DELETE - Remove a listener -
.SETUP - Change global settings -
<[]
```

```
smtp.scu.com>commit
```

```
:Please enter some comments describing your changes
add outgoing Disclaimer on OutboundMail listener <[]
```

```
Changes committed: Tue Nov 23 19:48:47 2004 MST
```

**تلميح:** في الإصدارات الأحدث من AsyncOS، يمكنك أيضا إضافة إخلاء مسؤولية أعلى الرسالة

ةمچرتل هذه لوح

ةللأل تاي نقتل نمة ومة م ادخت ساب دن تسمل اذة Cisco ت مچرت  
ملاعلاء انء مچ م ف ن م دخت سمل معد و ت م م دقت ل ة يرش بل او  
امك ة قق د نوك ت نل ةللأل مچرت ل ضف أن ة ظحال م چرئ. ة صاأل م هت بل ب  
Cisco يلخت. فرت م مچرت م ا م دق ي ت ل ة فارت حال ة مچرت ل عم ل األ و ه  
ل إأمئ اد عوچر ل اب ي صؤت و ت ا مچرت ل هذه ة قق د ن ع اهت ي ل وئ س م  
Systems (رفو تم ط بارل ا) ي ل صأل ا ي زل ل چ ن إل ا دن تسمل ا