



Collaboration Endpoint Product Matrix

Cisco Spark Board



MX200 G2



MX300 G2



MX700



MX800



Feature/Functionality	Cisco Spark Board	MX200 G2	MX300 G2	MX700	MX800
Form Factor	Single 55-inch and 70-inch integrated system	Single 42-inch screen integrated system	Single 55-inch screen integrated system	Dual 55-inch screen integrated system	Single 70-inch screen integrated system
Category	Collaboration Endpoints - Room System	Collaboration Endpoints - Room System	Collaboration Endpoints - Room System	Collaboration Endpoints - Room System	Collaboration Endpoints - Room System
Key Features	<p>All-in-one system for rich team collaboration: it's a wireless presentation screen, a digital whiteboard, and a video conferencing device. Designed for rich collaboration, connecting physical and virtual meeting rooms to facilitate continuous workflow – before, during, and even after everyone has left the physical room.</p> <p>Supports:</p> <ul style="list-style-type: none"> • Cisco Spark Proximity • Cisco Spark cloud registration • Continuous workflow through any Cisco Spark app-enabled device and associated to a Cisco Spark space 	<p>42-inch screen endpoint offers high-quality, easy-to-use video collaboration experience with sleek, new design in second generation product; transforms any meeting space into a video-enabled team room; premium resolution and dual-display support included; embedded four-way multisite conferencing option; installs in minutes for easy deployment; simple to use with Touch 10 UI</p> <p>Supports:</p> <ul style="list-style-type: none"> • Cisco Intelligent Proximity for content sharing to mobile devices and wireless sharing from Macs and PCs • Multistreaming (switched conferencing) for enhanced layouts • In-room control of peripherals from Touch 10 • New cloud registration through Cisco Spark for even faster and cost-effective deployment 	<p>55-inch endpoint offers high-quality, easy-to-use video collaboration experience with sleek, new design in second generation product; transforms any meeting space into a video-enabled team room; premium resolution and dual-display support included; embedded four-way multisite conferencing option; installs in minutes for easy deployment; simple to use with Touch 10 UI</p> <p>Supports:</p> <ul style="list-style-type: none"> • Cisco Intelligent Proximity for content sharing to mobile devices and wireless sharing from Macs and PCs • Multistreaming (switched conferencing) for enhanced layouts • In-room control of peripherals from Touch 10 • New cloud registration through Cisco Spark for even faster and cost-effective deployment 	<p>Dual 55-inch LED screen system turns any medium-to-large meeting room into a video collaboration hub; dual screens offer a people-and-content experience, supporting up to 3 screens; comes standard with a built-in amplifier and speaker system for the ultimate high fidelity sound; true 1080p60 resolution with option for single camera or intelligent dual-camera speaker-tracking solution; premium resolution and additional display are standard features; simple to use with Touch 10 UI; supports H.264 and H.265</p> <p>Supports:</p> <ul style="list-style-type: none"> • Cisco Intelligent Proximity for content sharing to mobile devices and wireless sharing from Macs and PCs • Multistreaming (switched conferencing) for enhanced layouts and video enablement on both screens of dual-screen endpoints • In-room control of peripherals from Touch 10 • New cloud registration through Cisco Spark for even faster and cost-effective deployment 	<p>70 inch LED screen system turns any medium-to-large meeting room into a video collaboration hub; large, single screen offers a people-centric experience, supporting up to 3 screens; comes standard with a built-in amplifier and speaker system for the ultimate high fidelity sound; true 1080p60 resolution with option for single camera or intelligent dual-camera speaker-tracking solution; premium resolution and additional display are standard features; simple to use with Touch 10 UI; supports H.264 and H.265</p> <p>Supports:</p> <ul style="list-style-type: none"> • Cisco Intelligent Proximity for content sharing to mobile devices and wireless sharing from Macs and PCs • Multistreaming (switched conferencing) for enhanced layouts • In-room control of peripherals from Touch 10 • New cloud registration through Cisco Spark for even faster and cost-effective deployment
Screens	<p>Cisco Spark Board 55:</p> <ul style="list-style-type: none"> • Edge LED LCD – 55-inch 4K, 350 nits, 16:9 • Resolution: Up to 1920 x 1080@30 (HD1080p) • Contrast ratio: Typical 4000:1 • Viewing angle: +/- 89 degrees (all directions) • Response time: 5.5 ms <p>Cisco Spark Board 70:</p> <ul style="list-style-type: none"> • Edge LED LCD – 70-inch 4K, 300 nits, 16:9 • Resolution: Up to 1920 x 1080@30 (HD1080p) • Contrast ratio: Typical 4000:1 • Viewing angle: +/- 88 degrees (all directions) • Response time: Typical 6 ms 	<p>Cisco TelePresence MX200 G2:</p> <p>42-inch LCD monitor</p> <ul style="list-style-type: none"> • Resolution: 1920 x 1080 (16:9) • Contrast ratio: Typical 1300:1 • Viewing angle: +/- 178 deg • Response time: Typical 8 ms • Brightness: 450 cd/m2 	<p>Cisco TelePresence MX300 G2:</p> <p>55-in. (1.4m) LCD monitor</p> <ul style="list-style-type: none"> • Resolution: 1920 x 1080 (16:9) • Contrast ratio: Typical 4000:1 • Viewing angle: +/- 178 deg • Response time: Typical 8 ms • Brightness: Typical 450cd/m2 	<p>Cisco TelePresence MX700: 2x 55-in. (1.4m) TFT-LCD monitor, edge-lit LED</p> <ul style="list-style-type: none"> • Resolution: 1920 x 1080 (16:9) • Contrast ratio: Typical 4000:1 • Viewing angle: +/- 178 deg • Response time: Typical 8 ms • Brightness: Typical 450cd/m2 	<p>Cisco TelePresence MX800:</p> <p>70-inch TFT-LCD monitor, edge-lit LED</p> <ul style="list-style-type: none"> • Resolution: 1920 x 1080 (16:9) • Contrast ratio: Typical 4000:1 • Viewing angle: +/- 176 deg • Response time: Typical 8 ms • Brightness: 350 cd/m2
Camera	<p>Fixed lens, infinite focus</p> <p>Resolution: 4Kp60</p> <p>83° horizontal field of view</p> <p>55° vertical field of view</p> <p>Resolutions: 1080p60 and 720p60</p> <p>F 2.8</p>	<p>Cisco TelePresence MX200 G2:</p> <p>2.5x optical zoom (5x with digital)</p> <p>Motorized +5°/-25° tilt, +/- 30° pan</p> <p>83° horizontal field of view</p> <p>51.5° vertical field of view</p> <p>Resolutions: 1080p60 and 720p60</p> <p>F 2.0</p> <p>Automatic or manual focus, brightness, and white balance</p> <p>Far-end camera control</p> <p>Focus distance 0.98 ft (0.3m) to infinity</p>	<p>Cisco TelePresence MX300 G2:</p> <p>4x optical zoom (8x with digital)</p> <p>Motorized +15°/-25° tilt, +/- 90° pan</p> <p>72° horizontal field of view</p> <p>43.5° vertical field of view</p> <p>Resolutions: 1080p60 and 720p60</p> <p>F 1.7</p> <p>Automatic or manual focus, brightness, and white balance</p> <p>Far-end camera control</p> <p>Focus distance 0.98 ft (0.3m) to infinity</p>	<p>20x total zoom (10x optical, 2x digital zoom)</p> <p>Motorized +20°/-20° tilt, +/- 90° pan</p> <p>80° horizontal field of view</p> <p>48.8° vertical field of view</p> <p>F 1.5</p> <p>Resolutions: 1080p60 and 720p60</p> <p>Automatic or manual focus, brightness, and white balance</p> <p>Far-end camera control</p> <p>Camera control over Ethernet</p> <p>Focus distance 3.28 ft (1m) to infinity</p>	<p>20x total zoom (10x optical, 2x digital zoom)</p> <p>Motorized +20°/-20° tilt, +/- 90° pan</p> <p>80° horizontal field of view</p> <p>48.8° vertical field of view</p> <p>F 1.5</p> <p>Resolutions: 1080p60 and 720p60</p> <p>Automatic or manual focus, brightness, and white balance</p> <p>Far-end camera control</p> <p>Camera control over Ethernet</p> <p>Focus distance 3.28 ft (1m) to infinity</p>
Recommended Number of Participants	Cisco Spark Board 55: up to 5 people Cisco Spark Board 70: up to 7 people	2 to 4 people	4 to 6 people	6 to 10 people	6 to 10 people
Video Quality	Up to 1080p30	Up to 1080p60	Up to 1080p60	Up to 1080p60	Up to 1080p60
Resolution	Up to 1920 x 1080@30 (HD1080p)	1920 x 1080 (16:9)	1920 x 1080 (16:9)	1920 x 1080 (16:9)	1920 x 1080 (16:9)
Video Standards	H.263 H.263+ H.264	H.263 H.263+ H.264	H.263 H.263+ H.264	H.261 H.263 H.263+ H.264 H.265 (SIP only for H.265)	H.261 H.263 H.263+ H.264 H.265 (SIP only for H.265)

Cisco Spark Board

MX200 G2

MX300 G2

MX700

MX800



Video Frame Rate	Up to 30 fps	Up to 60 fps	Up to 60 fps	Up to 60 fps	Up to 60 fps
Supported PC Resolutions (Content Sharing)	Up to 1920 x 1080@30 (HD1080p)	SVGA (800 x 600) to 1080p (1920 x 1080) at 30fps	SVGA (800 x 600) to 1080p (1920 x 1080) at 30fps	SVGA (800 x 600) up to 1080p (1920 x 1080) at 30fps	SVGA (800 x 600) up to 1080p (1920 x 1080) at 30fps
Software Supported	Cisco Spark Board OS, provisioned by the Cisco Collaboration Cloud	Cisco TelePresence Software Version TC 7.1.2 or later, Collaboration Endpoint Software 8.0 or later and Spark Room OS	Cisco TelePresence Software Version TC 7.0 or later, Collaboration Endpoint Software 8.0 or later and Spark Room OS	Cisco TelePresence Software Version TC 7.1.2 or later, Collaboration Endpoint Software 8.0 or later and Spark Room OS	Cisco TelePresence Software Version TC 7.1.2 or later, Collaboration Endpoint Software 8.0 or later and Spark Room OS
Signaling Protocol	Cisco Spark: HTTP, REST APIs	VCS: H.323 and SIP CUCM: SIP Cisco Spark: HTTP, REST APIs	VCS: H.323 and SIP CUCM: SIP Cisco Spark: HTTP, REST APIs	VCS: H.323 and SIP CUCM: SIP Cisco Spark: HTTP, REST APIs	VCS: H.323 and SIP CUCM: SIP Cisco Spark: HTTP, REST APIs
Peripherals Supported	Cisco Spark Pen	Cisco TelePresence Touch 10 & ISDN Link	Cisco TelePresence Touch 10 & ISDN Link	Cisco TelePresence Touch 10 & ISDN Link	Cisco TelePresence Touch 10 & ISDN Link
Bandwidth Consumption	From 768 Kbps to 10 Mbps	H.323 and SIP up to 6 Mbps point-to-point MultiSite: Up to 6 Mbps total	H.323 and SIP up to 6 Mbps point-to-point MultiSite: Up to 6 Mbps total	H.323/SIP up to 10 Mbps point-to-point MultiSite: Up to 6 Mbps total	H.323/SIP up to 10 Mbps point-to-point MultiSite: Up to 6 Mbps total
Audio Standards	64- and 128-kbps AAC-LD OPUS G.722 G.722.1 G.711 G.728 G.729 AB	64- and 128-kbps AAC-LD OPUS G.722 G.722.1 G.711 G.728 G.729 AB	64- and 128-kbps AAC-LD OPUS G.722 G.722.1 G.711 G.728 G.729 AB	OPUS G.711 G.722 G.722.1 G.729AB 64 kbps and 128 kbps MPEG4 AAC-LD mono and stereo	OPUS G.711 G.722 G.722.1 G.729AB 64 kbps and 128 kbps MPEG4 AAC-LD mono and stereo
Audio Features	High-quality 20-kHz audio Acoustic echo cancellation Automatic Gain Control (AGC) Automatic noise reduction Active lip synchronization Microphone array with intelligent voice tracking capabilities	High quality 20 kHz audio Three acoustic echo cancellers Automatic Gain Control (AGC) Automatic noise reduction Active lip synchronization	High quality 20 kHz audio Three acoustic echo cancellers Automatic Gain Control (AGC) Automatic noise reduction Active lip synchronization	CD-quality 20 kHz mono and stereo Eight separate acoustic echo cancellers Eight-port audio mixer Automatic Gain Control (AGC) Automatic noise reduction Active lip synchronization	CD-quality 20 kHz mono and stereo Eight separate acoustic echo cancellers Eight-port audio mixer Automatic Gain Control (AGC) Automatic noise reduction Active lip synchronization
Suggested Use Cases	Create Flexible Work Areas/Office Spaces	Create Flexible Workspaces	Incorporate Video into Meetings	Video Centric Meeting Space	Collaborate with External Organizations
Physical Dimensions	Cisco Spark Board 55: • Main unit: 36.2 x 55.7 x 7.5 in (919 x 1416 x 191 mm) • Wall stand kit: 30.2 x 48.5 x 4.2 in (768 x 1231 x 106 mm) • Wall mount kit: 10 x 54.5 x 2 in (253 x 1386 x 51 mm) • Floor stand kit Consolidated package size: 41.9 x 77.7 x 5.2 in (1064 x 1974 x 132 mm) Cisco Spark Board 70: • Main unit: 47.5 x 73.8 x 9.6 in (1207 x 1875 x 245 mm) • Wall mount kit: 10.1 x 66 x 3.6 in (256 x 1675 x 92 mm) • Floor stand kit: 60 x 47 x 6.7 in (1524 x 1186 x 172 mm) Cisco Spark Board and the selected mounting option will be shipped in a consolidation pack on a pallet. The dimensions above describe each of the individual boxes within the consolidation packaging.	Cisco TelePresence MX200 G2 main unit with: • Floor stand: 55 x 39.2 x 23.7 in. (1397 x 995 x 602 mm) • Table stand: 30.7 x 39.2 x 10.2 in. (781 x 995 x 259 mm) • Wall-mount: 26.4 x 39.2 x 5.7 in. (671 x 995 x 146 mm) • Wheel base: 58.3 x 995 x 711 in. (1480 x 39.2 x 28 mm)	Cisco TelePresence MX300 G2 main unit with: • Floor stand: 59.8 x 50.3 x 26.4 in. (1518 x 1278 x 671 mm) • Wall mount: 37.3 x 50.3 x 7.9 in. (948 x 1278 x 200 mm) • Wheel base: 63.2 x 50.3 x 29.7 in. (1605 x 1278 x 755 mm)	MX700 Dimensions & Weight: • Width: 99.09" in. (251.7 cm) • Height Freestand: 64.33" in (163.4 cm) • Height Wallmount: 42.17" in (107.1 cm) • Depth Freestand: 4.76" in, 36.22" incl. ski (12.1 cm system, 92.0 cm incl. ski) • Depth Wallmount: 5.83" in (14.8 cm) • Weight Single Camera: Freestand: 339.51 lbs (154.0 kg) • Weight Dual Camera: Freestand: 352.73 lbs (160.0 kg) • Weight Single Camera: Wallmount: 357.15 lbs (162.0 kg) • Weight Dual Camera: Wallmount: 370.38 lbs (168.0 kg)	MX800 Dimensions & Weight: • Width: 62.83" in. (159.6 cm) • Height Freestand: 71.69" in (182.1 cm) • Height Wallmount: 49.52" in (125.8 cm) • Depth Freestand: 4.76" in, 36.22" incl. ski (12.1 cm system, 92.0 cm incl. Ski) • Depth Wallmount: 5.87" in (14.9 cm) • Weight Single Camera: Freestand: 244.71 lbs (111.0 kg) • Weight Dual Camera: Freestand: 257.94 lbs (117.0 kg) • Weight Single Camera: Wallmount: 240.30 lbs (109.0 kg) • Weight Dual Camera: Wallmount: 253.53 lbs (115.0 kg)
PID	Cisco Spark Board 55: SPARK-BOARD55-K9 Cisco Spark Board 70: SPARK-BOARD70-K9	For Cisco cloud registration: CS-MX200-K9 For registration to VCS, UCM and 3rd party call control: CTS-MX200-K9	For Cisco cloud registration: CS-MX300-K9 For registration to VCS, UCM and 3rd party call control: CTS-MX300-K9	For Cisco cloud registration: CS-MX700D-2CAM-K9 (dual camera only) For registration to VCS, UCM and 3rd party call control: * CTS-MX700D-1CAM-K9 (single camera) * CTS-MX700D-2CAM-K9 (dual camera)	For Cisco cloud registration: CS-MX800S-2CAM-K9 (dual camera only) For registration to VCS, UCM and 3rd party call control: * CTS-MX800S-1CAM-K9 (single camera) * CTS-MX800S-2CAM-K9 (dual camera)
Datasheet URL	Cisco Spark Board 55: https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/spark-board/datasheet-c78-738316.html Cisco Spark Board 70: https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/spark-board/datasheet-c78-738851.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/telepresence-mx-series/data-sheet-c78-729734.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/telepresence-mx-series/data-sheet-c78-729734.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/telepresence-mx-series/datasheet-c78-731263.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/telepresence-mx-series/datasheet-c78-731263.html

Collaboration Room Systems

Desk

Immersive

IP Phones

Peripherals

MX800 Dual



Cisco Spark Room Kit



Cisco Spark Room Kit Plus



SX10 Quick Set



SX20 Quick Set



SX80



Feature/Functionality	MX800 Dual	Cisco Spark Room Kit	Cisco Spark Room Kit Plus	SX10 Quick Set	SX20 Quick Set	SX80
Form Factor	Dual 70-inch screen integrated system	Integrated camera, codec, speaker, microphone; Cisco TelePresence Touch 10 UI; monitor not included	Quad Camera and Codec Plus with Touch 10 UI; monitor not included	Camera-in-codec unit with microphone and remote control; monitor not included	Camera and codec with microphone and remote control; monitor not included	Codec only, or integrator packages available with Touch control and camera options Integrator packages: <ul style="list-style-type: none"> • Cisco SX80 Codec, PHD 1080p 4x Camera, and Touch 10 • Cisco SX80 Codec, Precision 60 Camera, and Touch 10 • Cisco SX80 Codec, SpeakerTrack60 Microphone Array, and Touch10
Category	Collaboration Endpoints - Room System	Collaboration Endpoints - Room System	Collaboration Endpoints - Room System	Collaboration Endpoints - Room-based Solution	Collaboration Endpoints - Room-based Solution	Collaboration Endpoints - Room-based Solution
Key Features	<p>Dual 70 inch LED screen system turns any medium-to-large meeting room into a video collaboration hub; large, dual screens offer a people-and-content experience, supporting up to 3 screens; comes standard with a built-in amplifier and speaker system for the ultimate high fidelity sound; true 1080p60 resolution with intelligent dual-camera speaker-tracking solution; premium resolution and dual-display support included are standard features; simple to use with Touch 10 UI; supports H.264 and H.265</p> <p>Supports:</p> <ul style="list-style-type: none"> • Cisco Intelligent Proximity for content sharing to mobile devices and wireless sharing from Macs and PCs • Multistreaming (switched conferencing) for enhanced layouts and video enablement on both screens of dual-screen endpoints • In-room control of peripherals from Touch 10 • New cloud registration through Cisco Spark for even faster and cost-effective deployment 	<p>Cisco Spark Room Kit is video innovation in a box, bringing more intelligence and usability to small to medium team collaboration rooms of up to 7 people. Room Kit enables smarter meetings, smarter presentations, and smarter room and device integrations. These features were previously the domain of higher-end video conferencing rooms, but can now be brought to every room and every team.</p> <ul style="list-style-type: none"> • Smart meetings: Powerful, integrated cameras deliver intelligent view capabilities, such as automatic framing and speaker tracking • Smart presentations: Dual screens, dual content sources, wireless sharing, and 4K content make for great presentations • Smart integrations: People count for usage metrics and resource allocation; tight integrations with screens for enhanced functionalities • Registration flexibility: Built for both cloud and on-premises deployment, protecting your investment 	<p>Cisco Spark Room Kit Plus is video innovation in a box, bringing more intelligence and usability to medium to large team collaboration rooms of up to 14 people. Room Kit Plus enables smarter meetings, smarter presentations, and smarter room and device integrations. These features were previously the domain of higher-end video conferencing rooms, but can now be brought to every room and every team.</p> <ul style="list-style-type: none"> • Smart meetings: Powerful, integrated cameras deliver intelligent view capabilities, such as automatic framing and speaker tracking • Smart presentations: Dual screens, dual content sources, wireless sharing, and 4K content make for great presentations • Smart integrations: People count for usage metrics and resource allocation; tight integrations with screens for enhanced functionalities • Registration flexibility: Built for both cloud and on-premises deployment, protecting your investment 	<p>SX10 Quick Set is an all-in-one unit designed to video-enable your smaller collaboration spaces; low-cost, high-quality unit combines camera and codec into a single, compact device that is mounted over your standard flat-panel display and connects through a discreet single-cable system for Power over Ethernet (PoE)</p> <p>Supports:</p> <ul style="list-style-type: none"> • Cisco Intelligent Proximity for content sharing to mobile devices and wireless sharing from Macs and PCs • In-room control of peripherals from Touch 10 • New cloud registration through Cisco Spark for even faster and cost-effective deployment 	<p>SX20 Quick Set is designed to deliver high definition video and multiparty conferencing with the flexibility to accommodate various room sizes and configurations - all at a value price; combines a powerful codec, resolution of up to 1080p, two camera choices, and a dual-display in an easy-to-deploy and easy-to-use solution</p> <p>Supports:</p> <ul style="list-style-type: none"> • Cisco Intelligent Proximity for content sharing to mobile devices and wireless sharing from Macs and PCs • Multistreaming (switched conferencing) for enhanced layouts and video enablement on both screens of dual-screen endpoints • In-room control of peripherals from Touch 10 • New cloud registration through Cisco Spark for even faster and cost-effective deployment 	<p>SX80 is a powerful codec platform to build large, custom video-collaboration environments; delivers up to a 1080p60 end-to-end HD video and offers industry-first support for H.265 for future bandwidth efficiencies; flexible media engine with rich input and output set; support for three screens enable a variety of use cases; integrator packages provide option for single camera or intelligent dual-camera speaker-tracking solution and Touch 10 UI; supports H.264 and H.265</p> <p>Supports:</p> <ul style="list-style-type: none"> • Cisco Intelligent Proximity for content sharing to mobile devices and wireless sharing from Macs and PCs • Multistreaming (switched conferencing) for enhanced layouts and video enablement on both screens of dual-screen endpoints • In-room control of peripherals from Touch 10 • New cloud registration through Cisco Spark for even faster and cost-effective deployment
Screens	<p>Cisco TelePresence MX800 Dual</p> <ul style="list-style-type: none"> • 2x 70-inch TFT-LCD monitor, edge-lit LED • Resolution: 1920 x 1080 (16:9) • Contrast ratio: Typical 4000:1 • Viewing angle: +/- 176 deg • Response time: Typical 8 ms • Brightness: 350 cd/m2 	Screen not included	Screen not included	Screen not included	Screen not included	Screen not included
Camera	<p>20x total zoom (10x optical, 2x digital zoom) Motorized +20°/-20° tilt, +/-90° pan 80° horizontal field of view 48.8° vertical field of view F 1.5 Resolutions: 1080p60 and 720p60</p> <p>Automatic or manual focus, brightness, and white balance Far-end camera control Camera control over Ethernet Focus distance 3.28 ft (1m) to infinity</p>	<p>5K UltraHD camera 3x digital zoom 83° horizontal field of view 51.5° vertical field of view Resolution: up to 1080p60 F 2.0</p> <p>Auto-framing (audio + face detect) Auto focus, brightness, and white balance Focus distance 1 m to infinity</p>	<p>5K Ultra HD camera 5x digital zoom (3 tele-lenses each with 50° horizontal field of view) 83° horizontal field of view 51.5° vertical field of view Resolution: up to 1080p60 F 2.0</p> <p>Auto-framing (audio + face detect) Auto focus, brightness, and white balance Focus distance 1 m to infinity</p>	<p>5x zoom (2.65 optical and digital zoom) +5°/-25° tilt, +/-30° pan 51.5° vertical field of view 83° horizontal field of view F-value from 2.1 1920 x 1080 pixels progressive @ 30 fps Automatic or manual focus, brightness, and white balance Far-end camera control** Automatic flipping of picture when upside down</p>	<p>Two camera options: 4x optical zoom (8x with digital) 12x optical zoom</p> <p>Both have: 1920 x 1080 pixels progressive @ 60 fps Far-end camera control Automatic or manual focus, brightness, and white balance</p>	<p>Cisco offers three camera options in the SX80 Integrator Packages: SX80 Codec and PrecisionHD 1080p 4x camera for smaller room scenarios SX80 Codec and Precision 60 Camera, for larger room scenarios with the best image quality in the market SX80 and the SpeakerTrack 60 dual camera system, which features a unique direct, fast switching approach for active speaker tracking</p>
Recommended Number of Participants	6 to 10 people	Up to 7 people	Up to 14 people	1 to 4 people	2 to 12 people	12 to 16+ people
Video Quality	Up to 1080p60	Up to 1080p60	Up to 1080p60	1080p30	Up to 1080p60	Up to 1080p60

Collaboration Room Systems

Desk

Immersive

IP Phones

Peripherals

MX800 Dual

Cisco Spark Room Kit

Cisco Spark Room Kit Plus

SX10 Quick Set

SX20 Quick Set

SX80



Resolution	1920 x 1080 (16:9)	3840 x 2160 (16:9)	3840 x 2160 (16:9)	1920 x 1080 (16:9)	1920 x 1080 (16:9)	1920 x 1080 (16:9)
Video Standards	H.261 H.263 H.263+ H.264 H.265 (SIP only for H.265)	H.264, H.265	H.264, H.265	H.263 H.263+ H.264	H.263 H.263+ H.264	H.261 H.263 H.263+ H.264 H.265
Video Frame Rate	Up to 60 fps	Up to 60 fps	Up to 60 fps	Up to 30 fps	Up to 60 fps	Up to 60 fps
Supported PC Resolutions (Content Sharing)	SVGA (800 x 600) up to 1080p (1920 x 1080) at 30fps	1080p30 4kp5	1080p30 4kp5	SVGA (800 x 600) up to 1080p (1920 x 1080) at 5fps	SVGA (800 x 600) up to 1080p (1920 x 1080) at 30fps	SVGA (800 x 600) up to 1080p (1920 x 1080) at 30fps
Software Supported	Cisco TelePresence Software Version TC 7.2 or later, Collaboration Endpoint Software 8.0 or later and Spark Room OS	Cisco Collaboration Endpoint Software Version 9.0 or later, or Cisco Spark Room OS	Cisco Collaboration Endpoint Software Version 9.1 or later, or Cisco Spark Room OS	Cisco TelePresence Software Version TC 7.1 or later, Collaboration Endpoint Software 8.0 or later and Spark Room OS	TC 6.0 and higher, Collaboration Endpoint Software 8.0 or later and Spark Room OS	Cisco TelePresence Software Version TC 7.1 or later, Collaboration Endpoint Software 8.0 or later and Spark Room OS
Signaling Protocol	VCS: H.323 and SIP CUCM: SIP Cisco Spark: HTTP, REST APIs	VCS: H.323 and SIP CUCM: SIP Cisco Spark: HTTP, REST APIs	VCS: H.323 and SIP CUCM: SIP Cisco Spark: HTTP, REST APIs	H.323 and SIP (CE8.2 or later) CUCM: SIP Cisco Spark: HTTP, REST APIs	VCS: H.323 and SIP CUCM: SIP Cisco Spark: HTTP, REST APIs	VCS: H.323 and SIP CUCM: SIP Cisco Spark: HTTP, REST APIs
Peripherals supported	Cisco TelePresence Touch 10 & ISDN Link	Cisco TelePresence Touch 10 For cloud registration: Any Cisco Spark-app enabled device	Cisco TelePresence Touch 10 For cloud registration: Any Cisco Spark-app enabled device	Cisco TelePresence Remote Control 6, Touch 10	Cisco TelePresence Remote Control, Touch 8/10 and ISDN Link PrecisionHD 4x and 12x cameras	Cisco TelePresence Touch 10, ISDN Link, Precision 60 Camera, SpeakerTrack 60 Camera
Bandwidth Consumption	H.323/SIP up to 10 Mbps point-to-point MultiSite: Up to 6 Mbps total	H.264: from 768 kbps to 6000 kbps	H.264: from 768 kbps to 6000 kbps	Up to 3 Mbps	H.323/SIP up to 6 Mbps point-to-point MultiSite: Up to 6 Mbps total	H.323/SIP up to 6 Mbps point-to-point MultiSite: Up to 6 Mbps total
Audio Standards	OPUS G.711 G.722 G.722.1 G.729 G.729AB 64 kbps and 128 kbps MPEG4 AAC-LD mono and stereo	G.711 G.722 G.722.1 G.729 AAC-LD Opus	G.711 G.722 G.722.1 G.729 AAC-LD Opus	64 kbps MPEG4 AAC-LD OPUS G.722 G.722.1 G.729 G.711 G.729ab G.729	G.711 G.722 G.722.1 G.728 G.729ab 64 kbps and 128 kbps AAC-LD mono and stereo OPUS	G.711 G.722 G.722.1 G.729AB 64 kbps and 128 kbps MPEG4 AAC-LD mono and stereo
Audio Features	CD-quality 20 kHz mono and stereo Eight separate acoustic echo cancellers Eight-port audio mixer Automatic Gain Control (AGC) Automatic noise reduction Active lip synchronization	High quality 20 kHz audio Subwoofer line out for Quad Camera Automatic Gain Control (AGC) Automatic noise reduction Active lip synchronization	High quality 20 kHz audio Subwoofer line out for Quad Camera Automatic Gain Control (AGC) Automatic noise reduction Active lip synchronization	High-quality 20-kHz mono Two acoustic echo cancellers Automatic Gain Control (AGC) Automatic noise reduction Active lip synchronization	CD-quality 20 KHz mono and stereo Two acoustic echo cancellers Automatic Gain Control (AGC) Automatic noise reduction Active lip synchronization	CD-quality 20 kHz mono and stereo Eight separate acoustic echo cancellers Eight-port audio mixer Eight assignable equalizers Automatic Gain Control (AGC) Automatic noise reduction Active lip synchronization
Suggested Use Cases	Extended Collaboration	Create Flexible Work Areas / Office Spaces Incorporate Video Into Meetings	Briefing or Training Rooms	Collaborative Meeting Spaces	Support Teleworkers and Branch Offices	Briefing or Training Rooms
Physical Dimensions	MX800 Dual Dimensions & Weight: • Width: 124.77" in. (316.9 cm) • Height Freestand: 71.69" in (182.1 cm) • Height Wallmount: 49.52" in (125.8 cm) • Depth Freestand: 4.76" in, 36.22" incl. ski (12.1 cm system, 92.0 cm incl. ski) • Depth Wallmount: 5.87" in (14.9 cm) • Weight Dual Camera: Freestand: 467.38 lbs (212.0 kg) • Weight Dual Camera: Wallmount: 493.84 lbs (224.0 kg)	• Width: 27.5 in. (70.0 cm) • Height: 3.5 in. (10.6 cm) • Depth: 2.9 in. (8.8 cm) • Weight: 7 lb. (3.2 kg)	Quad Camera: • Width: 37.4 in. (95.0 cm) • Height: 4.7 in. (12.0 cm) • Depth: 4.0 in. (10.3 cm) • Weight: 10.6 lb. (4.8 kg) Codec Plus: • Width: 14.1 in. (35.9 cm) • Height: 1.7 in. (4.3 cm) • Depth: 5.6 in. (14.3 cm) • Weight: 3.9 lb. (1.77 kg)	SX10 Codec Dimensions: • Width: 10.8 inches (27.5 cm) • Height: 4.6 inches (11.7 cm) • Depth: 3.6 inches (9.1 cm) (with max tilt downward on camera) • Weight: 2.0 pounds (0.9 kg)	SX20 Codec Dimensions: • Width: 11.8 inches (30.0 cm) • Height: 1.4 inches (3.4 cm) • Depth: 7.1 inches (18.0 cm) • Weight: 3.1 pounds (1.4 kg)	• Length: 17.4 in. (44.2 cm) • Height: 1.7 in (4.4 cm) • Depth: 12.2 in. (30.98 cm) • Weight: 8.05 lbs. (3.65 kg)
PID	For Cisco cloud registration: CS-MX800D-2CAM-K9 (dual camera only) For registration to VCS, UCM and 3rd party call control: CTS-MX800D-2CAM-K9 (dual camera only)	For Cisco cloud registration: CS-KIT-MSRP-K9 For registration to VCS, UCM and 3rd party call control: CS-KIT-K9	For Cisco cloud registration: CS-KITPLUS-MSRP-K9 For on-premises registration to VCS, UCM and 3rd party call control: CS-KITPLUS-K9	For Cisco cloud registration: CS-SX10N-MSRP-K9 For on-premises registration to VCS, UCM and 3rd party call control: CTS-SX10N-K9	CTS-SX20N-P40-K9 (SX20 Quick Set 4x); CTS-SX20N-12X-K9 (SX20 Quick Set 12x)	CTS-SX80-K9 (SX80 Codec); CTS-SX80-IP40-K9 (SX80 with 4x camera & Touch10); CTS-SX80-IP60-K9 (SX80 with P60 & Touch10); CTS-SX80-IPST60-K9 (SX80 with SpeakerTrack 60 & Touch10)
Datasheet URL	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/telepresence-mx-series/datasheet-c78-731263.html?cachemode=refresh	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/spark-room-kit-series/datasheet-c78-738729.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/spark-room-kit-series/datasheet-c78-738752.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/telepresence-quick-set-series/datasheet-c78-731274.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/telepresence-sx20-quick-set/data_sheet_c78-688342.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/telepresence-quick-set-series/datasheet-c78-731242.html

DX70

DX80



Feature/Functionality		
Form Factor		
Category	Collaboration Endpoints - Desk	Collaboration Endpoints - Desk
Key Features	<p>Midsize 14 inch 16:9 display with intuitive touchscreen</p> <p>HD voice and video</p> <p>Ability to share PC/Mac content while in meetings or use as an external monitor</p> <p>WiFi and Bluetooth</p> <p>New cloud registration through Cisco Spark for even faster and cost-effective deployment</p>	<p>Large 23 inch 16:9 display with intuitive touchscreen</p> <p>HD voice and video</p> <p>Ability to share PC/Mac content while in meetings or use as an external monitor</p> <p>WiFi and Bluetooth</p> <p>New cloud registration through Cisco Spark for even faster and cost-effective deployment</p>
Screens	<p>Display:</p> <p>14-inch LCD monitor</p> <p>Resolution: 1920 x 1080 (16:9)</p> <p>AHVA display technology</p> <p>Contrast ratio: 700:1 (typ.)</p> <p>Viewing cone: 89/89/89/89</p> <p>Response time: 25ms</p> <p>Brightness: 300 cd/m2 (5 points avg.)</p> <p>10-point multi-touch surface with capacitive sensing</p>	<p>Display:</p> <p>23-inch (0.58m) LCD monitor</p> <p>Resolution: 1920 x 1080 (16:9)</p> <p>High contrast IPS LED panel</p> <p>Contrast ratio: 1000:1 (typ.)</p> <p>Viewing angle: +/- 178 deg (typ.)</p> <p>Response time: 5ms (typ.)</p> <p>Brightness: 215 cd/m2 (typ.)</p> <p>Color depth: 16.7 million colors</p> <p>Color gamut 72% (of NTSC)</p> <p>10 point multi-touch surface</p>
Camera	<p>Front camera:</p> <p>63° horizontal field of view</p> <p>38° vertical field of view</p> <p>Resolution: 1080p30</p> <p>F 2.2</p> <p>Instant Focus based on face detection</p> <p>Privacy shutter</p>	<p>Front Camera:</p> <p>63° horizontal field of view</p> <p>38° vertical field of view</p> <p>Resolution: 1080p30</p> <p>F 2.2</p> <p>Instant Focus based on face detection</p> <p>Privacy shutter</p>
Recommended Number of Participants	1	1-2
Video Quality	HD video with H.264 and AVC video calling up to 1080p at 30 fps	HD video with H.264 and AVC video calling up to 1080p at 30 fps
Resolution	1920 x 1080 (16:9)	1920 x 1080 (16:9)
Video Standards	H.263 H.263+ H.264	H.263 H.263+ H.264
Video Frame Rate	30 fps	30 fps
Supported PC Resolutions	SVGA (800 x 600) up to 1080p (1920 x 1080) at 60fps	SVGA (800 x 600) up to 1080p (1920 x 1080) at 60fps
Software Supported	Collaboration Endpoint Software 8.2 or later and Spark Room OS	Collaboration Endpoint Software 8.2 or later and Spark Room OS
Signaling Protocol	VCS: H.323 and SIP CUCM: SIP Cisco Spark: HTTP, REST APIs	VCS: H.323 and SIP CUCM: SIP Cisco Spark: HTTP, REST APIs
Peripherals Supported	Analog headset Bluetooth and USB headset	Analog headset Bluetooth and USB headset
Bandwidth Consumption	1 Mbps for 720p30 2 Mbps for 1080p30	1 Mbps for 720p30 2 Mbps for 1080p30
Audio Standards	64 kbps MPEG4 AAC-LD OPUS G.722 G.722.1 G.711mu G.711a G.729ab G.729	64 kbps MPEG4 AAC-LD OPUS G.722 G.722.1 G.711mu G.711a G.729ab G.729



DX70



DX80



Audio Features	<p>In-call audio features:</p> <ul style="list-style-type: none"> Up to 16kHz sampling rate 100 Hz - 15 kHz loudspeaker frequency response Automatic static noise reduction Acoustic echo cancellers Automatic Gain Control (AGC) Active lip synchronization 	<p>Loudspeaker frequency range:</p> <ul style="list-style-type: none"> 70Hz - 20kHz <p>Microphones frequency range: 100z - 20kHz Up to 48kHz sampling rate</p> <ul style="list-style-type: none"> Automatic static noise reduction Acoustic echo cancellers Automatic Gain Control (AGC) Active lip synchronization
Suggested Use Cases	Incorporate Video into Meetings	Support Teleworkers and Branch Offices
Physical Dimensions	14.84 x 13.91 x 2.45 in. (377.1mm x 353.1mm x 62.3mm)	20.2 x 22.2 x 3.5 in. (51.2 x 56.5 x 8.9 cm)
PID	<p>For Cisco cloud registration: CS-DX70-K9=</p> <p>For registration to VCS, UCM and 3rd party call control: CP-DX70-W-K9=</p>	<p>For Cisco cloud registration: CS-DX80-K9=</p> <p>For registration to VCS, UCM and 3rd party call control: CP-DX80-K9=</p>
Datasheet URL	https://www.cisco.com/c/en/us/products/collaboration-endpoints/desktop-collaboration-experience-dx600-series/datasheet-listing.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/desktop-collaboration-experience-dx600-series/datasheet-listing.html

IX5000

IX5200



Feature/Functionality		
Form Factor		
Category	Collaboration Endpoints - TelePresence	Collaboration Endpoints - TelePresence
Key Features	Cisco IX5000 is the state-of-the-art triple-screen system combining high fidelity audio/video and rich collaboration functionality for the most vivid immersive collaboration experience possible. As the first single-codec, H.265 triple-screen product, the IX5000 is both powerful and efficient. The system is designed for high value and flexibility for deployment beyond the boardroom. The IX5000 features a single row of seats up to 6 people and supports Intelligent Proximity for content sharing to iOS and Android mobile devices (requires IX 8.1 software).	Cisco IX5200 is the state-of-the-art triple-screen system combining high fidelity audio/video and rich collaboration functionality for the most vivid immersive collaboration experience possible. As the first single-codec, H.265 triple-screen product, the IX5200 is both powerful and efficient. The system is designed for high value and flexibility for deployment beyond the boardroom. The IX5200 features a dual row of seats up to 18 people and supports Intelligent Proximity for content sharing to iOS and Android mobile devices (requires IX 8.1 software).
Screens	Three 70-inch HD screens	Three 70-inch HD screens
Camera	Cisco TelePresence UHD Camera: <ul style="list-style-type: none"> • CMOS 1/2.3-inch sensor • M12 mount lens • 2160p, 60 fps • Minimum vertical illumination 200 lux • Fixed focus 	Cisco TelePresence UHD Camera: <ul style="list-style-type: none"> • CMOS 1/2.3-inch sensor • M12 mount lens • 2160p, 60 fps • Minimum vertical illumination 200 lux • Fixed focus
Recommended Number of Participants	6 people	Up to 18 people
Video Quality	Up to 1080p	Up to 1080p
Resolution	Video resolution: native support up to 1920 x 1080p, 60 fps	Video resolution: native support up to 1920 x 1080p, 60 fps
Video Standards	SIP, H.264, H.265, TIP, BFCP	SIP, H.264, H.265, TIP, BFCP
Video Frame Rate	Up to 60 fps using H.264 and H.265	Up to 60 fps using H.264 and H.265
Supported PC Resolutions (Content Sharing)	Content sharing up to 1920 x 1080p resolution, 30 fps	Content sharing up to 1920 x 1080p resolution, 30 fps
Software Supported	Cisco TelePresence System Software IX8.0.1 or later	Cisco TelePresence System Software IX8.0.1 or later
Signaling Protocol	Cisco Discovery Protocol, Session Initiation Protocol (SIP), IP, Dynamic Host Configuration Protocol (DHCP), Secure Shell (SSH) Protocol, 802.1p/q, Real-Time Transport Protocol (RTP) and Secure RTP (SRTP), Telepresence Interoperability Protocol (TIP), H.264, H.265 and Binary Floor Control Protocol (BFCP)	Cisco Discovery Protocol, Session Initiation Protocol (SIP), IP, Dynamic Host Configuration Protocol (DHCP), Secure Shell (SSH) Protocol, 802.1p/q, Real-Time Transport Protocol (RTP) and Secure RTP (SRTP), Telepresence Interoperability Protocol (TIP), H.264, H.265 and Binary Floor Control Protocol (BFCP)
Peripherals Supported	Touch 10	Touch 10
Bandwidth Consumption	Minimum requirement - 720p, 30 fps at 1.8 Mbps (H.265) or 3 Mbps (H.264) Maximum requirement - 1080p, 60 fps at 10.8 Mbps (H.265) or 18 Mbps (H.264)	Minimum requirement - 720p, 30 fps at 1.8 Mbps (H.265) or 3 Mbps (H.264) Maximum requirement - 1080p, 60 fps at 10.8 Mbps (H.265) or 18 Mbps (H.264)
Audio Standards	G.711/G722 and AAC-LD (22 kHz)	G.711/G722 and AAC-LD (22 kHz)
Audio Features	Cisco Dynamic Echo Cancellation for spatial audio 18 discrete microphones	Cisco Dynamic Echo Cancellation for spatial audio 54 discrete microphones
Suggested Use Cases	Immersive Rooms	Immersive Rooms
Physical Dimensions	IX5000, 6-seat: 6' x 15' x 9'6" (1.8 x 4.6 x 2.9m)	IX5200, 18-seat: 6' x 25'11" x 17' (1.8 x 7.9 x 5.2m)
PID	<ul style="list-style-type: none"> • 6 seat system: CTS-IX5000 • Hickory (default): CTS-5K-TBL-H-6S • Walnut: CTS-5K-TBL-W-6S 	<ul style="list-style-type: none"> • 18 seat system: CTS-IX5200 • Hickory (default): CTS-5K-TBL-H-18S • Walnut: CTS-5K-TBL-W-18S
Datasheet URL	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/ix5000-series/datasheet-c78-733257.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/ix5000-series/datasheet-c78-733257.html



Collaboration Room Systems	Desk	Immersive	IP Phones	Peripherals
----------------------------	------	-----------	-----------	-------------

	3900 Series	3900 Series	6900 Series	6900 Series	7800 Series	7800 Series
						
Feature/Functionality						
Integral Switch		10/100		No		10/100
Display		128 x 32 pixel-based, graphical monochrome LCD without backlit		No		384 x 106 pixel-based, anti-glare graphical monochrome display
Integrated Video		No		No		No
Touch Screen		No		No		No
Speakerphone		Yes		No		Yes (Narrowband)
Number of Line keys		1		1		0
Programmable (Soft) keys		0		No		4
Fixed Feature Keys		8		4		11 (No headset audio key)
Advanced Features						Wideband audio available with purchase of wideband handset; Mobile Remote Access without a VPN client through Cisco Expressway; New cloud registration through Cisco Spark for even faster and cost-effective deployment
Handsfree		Yes		No		Yes
Message Waiting Indication		Yes		Yes		Yes
Third Party XML Support		No		No		Yes
Headset Port		No		No		No
Signaling Protocol		SIP		SCCP and SIP		SIP
802-3AF		Yes		Yes		Yes
Cisco Power		N/A		No		No
PoE Classification		Class 1		Class 1		Class 1
DHCP		Yes		Yes		Yes
802-1p/q		Yes		Yes		Yes
Codecs		G.711a, G.711μ, G.729, G.729a, and G.729b		G.711a, G.711u, G.729a, G.729b, and G.729ab. and Internet Low Bitrate Codec (iLBC)		G.711a/μ, G.722, G.729a, iLBC and OPUS
Supported Cisco Call Control Platform(s)		CUCM 7.1(5) or later CUCMBE3000 - 8.6 CUCMBE5000 - 8.5 CUCMBE6000 - 8.5		CUCM 7.1(3) and later		CUCM: 8.5.1, 8.6.2, 9.1.2, 10x and later Bus. Edition: 8.6.2 HCS: 9.1.2 Cisco Spark: Requires Spark Phone OS 11.0 or later
UC Manager Encryption Support (TLS/SRTP)		No		Yes		Yes
Notes						FIPS 140-2 Level 1: Requires Phone OS 11.5 or later
PID		CP-3905=		CP-6901-C-K9=, CP-6901-CL-K9= CP-6901-W-K9=, CP-6901-WL-K9=		CP-7811-K9= CP-7811-3PCC-K9= Multiplatform Phone: (Cisco approved Service Providers)
Datasheet URL	https://www.cisco.com/c/en/us/products/collaboration-endpoints/unified-sip-phone-3900-series/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/unified-sip-phone-3905/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/unified-ip-phone-6900-series/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/unified-ip-phone-6901/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/unified-ip-phone-7800-series/index.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/unified-ip-phone-7800-series/data-sheet-c78-729488.html

7800 Series

7800 Series

7800 Series

7800 Series

7900 Series

7821



7841








7861








7832 Conference Phone



Feature/Functionality	7821	7841	7861	7832 Conference Phone	7900 Series
Intergral Switch	10/100	10/100/1000	10/100	N/A	
Display	396 x 162 pixel-based, anti-glare graphical monochrome display with white backlight	396 x 162 pixel-based, anti-glare graphical monochrome display with white backlight	396 x 162 pixel-based, anti-glare graphical monochrome display with white backlight	384 x 128 pixel, monochrome display with white LED backlight	
Integrated Video	No	No	No	No	
Touch Screen	No	No	No	No	
Speakerphone	Yes	Yes	Yes	Yes	
Number of Line keys	2	4	16	1	
Programmable (Soft) keys	4	4	4	4	
Fixed Feature Keys	11	11	11	4 (navigation up/down, select key, mute key and volume toggle)	
Advanced Features	Multi-call per-line appearance Full Wideband Audio Electronic Hookswitch Support (Through AUX Port); Mobile Remote Access without a VPN client through Cisco Expressway; New cloud registration through Cisco Spark for even faster and cost-effective deployment	Multi-call per-line appearance Full Wideband Audio Electronic Hookswitch Support (Through AUX Port); Mobile Remote Access without a VPN client through Cisco Expressway; New cloud registration through Cisco Spark for even faster and cost-effective deployment	Multi-call per-line appearance Full Wideband Audio Electronic Hookswitch Support (Through AUX Port); Mobile Remote Access without a VPN client through Cisco Expressway; New cloud registration through Cisco Spark for even faster and cost-effective deployment	360-degree Full Wideband Audio Expanded mute key eases participant access Raised edges enhances portability	
Handsfree	Yes	Yes	Yes	Yes	
Message Waiting Indication	Yes	Yes	Yes	Yes	
Third Party XML Support	Yes	Yes	Yes	Yes	
Headset Port	Yes	Yes	Yes	No	
Signaling Protocol	SIP	SIP	SIP	SIP	
802-3AF	Yes	Yes	Yes	Yes	
Cisco Power	No	No	No	No	
PoE Classification	Class 1	Class 1	Class 1	Class 2	
DHCP	Yes	Yes	Yes	Yes	
802-1p/q	Yes	Yes	Yes	Yes	
Codecs	G.711a, G.711u, G.729a, G.729b, G.729ab, G.722, Internet Low Bitrate Codec (iLBC) and OPUS	G.711a, G.711u, G.729a, G.729b, G.729ab, G.722, Internet Low Bitrate Codec (iLBC) and OPUS	G.711a, G.711u, G.729a, G.729b, G.729ab, G.722, Internet Low Bitrate Codec (iLBC) and OPUS	G.711(u/A), G.729a, G.729ab, iLBC, iSAC, G.722, G.722.2, OPUS	
Supported Cisco Call Control Platform(s)	CUCM: 8.5.1, 8.6.2, 9.1.2, 10x and later Bus. Edition: 8.6.2 HCS: 9.1.2 Cisco Spark: Requires Spark Phone OS 11.0 or later	CUCM: 8.5.1, 8.6.2, 9.1.2, 10x and later Bus. Edition: 8.6.2 HCS: 9.1.2 Cisco Spark: Requires Spark Phone OS 11.0 or later	CUCM: 8.5.1, 8.6.2, 9.1.2, 10x and later Bus. Edition: 8.6.2 HCS: 9.1.2 Cisco Spark: Requires Spark Phone OS 11.0 or later	Cisco Spark (requires Phone OS 12.0 or later); CUCM and Business Edition 6000/7000 10.5(2), 11.0, 11.5, 12.0 and later"	
UC Manager Encryption Support (TLS/SRTP)	Yes	Yes	Yes	Yes	
Notes	FIPS 140-2 Level 1: Requires Phone OS 11.5 or later	FIPS 140-2 Level 1: Requires Phone OS 11.5 or later	FIPS 140-2 Level 1: Requires Phone OS 11.5 or later		
PID	CP-7821-K9= (Charcoal); CP-7821-W-K9= (White); CP-7821-3PCC-K9= Multiplatform Phone: (Cisco approved Service Providers)	CP-7841-K9= (Charcoal); CP-7841-W-K9= (White); CP-7841-3PCC-K9= Multiplatform Phone: (Cisco approved Service Providers)	CP-7861-K9= (Charcoal); CP-7861-W-K9= (White); CP-7861-3PCC-K9= Multiplatform Phone: (Cisco approved Service Providers)	CP-7832-K9= (Charcoal) CP-7832-W-K9= (White) CP-7832-3PCC-K9= Multiplatform Phone (Cisco approved Service Providers)	
Datasheet URL	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/unified-ip-phone-7800-series/data-sheet-c78-729488.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/unified-ip-phone-7800-series/data-sheet-c78-729488.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/unified-ip-phone-7800-series/data-sheet-c78-729488.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/unified-ip-phone-7800-series/data-sheet-c78-738318.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/unified-ip-phone-7900-series/index.html

	7900 Series	7900 Series	7900 Series	7900 Series	8800 Series
	7916 Expansion Module	7945G	7965G	7975G	
					
Feature/Functionality					
Integral Switch	N/A	10/100/1000	10/100/1000	10/100/1000	
Display	4.3" graphical (TFT) backlit (480 x 272) 16-bit color	5.0" (12.7 cm), graphical, 320 x 240, backlit, 16-bit, color	5.0" (12.7 cm), graphical, 320 x 240, backlit, 16-bit, color	5.6" (14.2 cm), graphical, 320 x 240, backlit, 16-bit, color with touch screen	
Integrated Video	N/A	No	No	No	
Touch Screen		No	No	Yes	
Speakerphone		Yes	Yes	Yes	
Number of Line keys	24 (12 buttons, 2 display pages)	2 - lighted	6 - lighted	8 - lighted	
Programmable (Soft) keys		4 soft keys, 2 line keys for use as lines, or as a line plus a speed dial or PLK	4 soft keys, 6 line keys for use as lines, speed dials or PLKs	5 soft keys, 8 line keys for use as lines, speed dials or PLKs	
Fixed Feature Keys		10	10	10	
Advanced Features		High-resolution and many infrastructure integration options; support of Headset Hookswitch Control	High-resolution and many infrastructure integration options; support of Headset Hookswitch Control; key Expansion Module support with up to 2 7914s, 7915s or 7916s	High-resolution and many infrastructure integration options; key Expansion Module support with up to 2 7914s, 7915s or 7916s; Support of Headset Hookswitch Control	
Handsfree		Yes, Wideband support	Yes, Wideband support	Yes, Wideband support	
Message Waiting Indication		Yes	Yes	Yes	
Third Party XML Support		Yes	Yes	Yes	
Headset Port		Yes, Wideband support	Yes, Wideband support	Yes, Wideband support	
Signaling Protocol	SCCP/SIP (with appropriate UCM firmware release)	SCCP/SIP	SCCP/SIP	SCCP/SIP	
802-3AF		Yes	Yes	Yes	
Cisco Power		No	No	No	
PoE Classification		Class 3	Class 3	Class 3	
DHCP		Yes	Yes	Yes	
802-1p/q		Yes	Yes	Yes	
Codecs					
Supported Cisco Call Control Platform(s)		CUCM 4.1 and later	CUCM 4.1 and later	CUCM 4.1 and later	
UC Manager Encryption Support (TLS/SRTP)	N/A	Yes	Yes	Yes	
Notes					
PID	CP-7916=	CP-7945G	CP-7965G	CP-7975G	
Datasheet URL	https://www.cisco.com/c/en/us/products/collaboration-endpoints/unified-ip-phone-expansion-module-7916/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/unified-ip-phone-7945g/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/unified-ip-phone-7965g/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/unified-ip-phone-7975g/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/unified-ip-phone-8800-series/index.html

	8800 Series	8800 Series	8800 Series	8800 Series	8800 Series
	8811	8841	8845	8851	8861
					
Feature/Functionality					
Integral Switch	10/100/1000	10/100/1000	10/100/1000	10/100/1000	10/100/1000
Display	5" (800 x 480) monochrome display with white backlight	5" high-resolution (800 x 480) WVGA color display	5" high-resolution (800 x 480) WVGA color display	5" high-resolution (800 x 480) WVGA color display	5" high-resolution (800 x 480) WVGA color display
Integrated Video	No	No	Yes - 720p HD, H.264 AVC Camera: 80 degree FOV, 25 degree tilt up/down; manual shutter (privacy)	No	No
Touch Screen	No	No	No	No	No
Speakerphone	Yes	Yes	Yes	Yes	Yes
Number of Line keys	5	5	5	5	5
Programmable (Soft) keys	4	4	4	4	4
Fixed Feature Keys	12	12	12	12	12
Advanced Features	Gig Ethernet, Wideband Audio; Mobile Remote Access without a VPN client through Cisco Expressway; New cloud registration through Cisco Spark for even faster and cost-effective deployment	Gig Ethernet, Wideband Audio; Mobile Remote Access without a VPN client through Cisco Expressway; New cloud registration through Cisco Spark for even faster and cost-effective deployment	Gigabit Ethernet, Wideband Audio, Cisco Intelligent Proximity for Mobile Voice; Mobile Remote Access without a VPN client through Cisco Expressway; New cloud registration through Cisco Spark for even faster and cost-effective deployment; A non-Bluetooth radio version is also available	Gigabit Ethernet, Wideband Audio, Cisco Intelligent Proximity for Mobile Voice, USB Charging of Smartphone and Tablets, IP Phone 8800 Key Expansion Module - Up to 2; Mobile Remote Access without a VPN client through Cisco Expressway; New cloud registration through Cisco Spark for even faster and cost-effective deployment	Gigabit Ethernet, Wideband Audio, Cisco Intelligent Proximity for Mobile Voice, USB Charging of Smartphone, IP Phone 8800 Key Expansion Module - Up to 3, 802.11a/b/g/n/ac Wi-Fi; Mobile Remote Access without a VPN client through Cisco Expressway; New cloud registration through Cisco Spark for even faster and cost-effective deployment
Handsfree	Yes	Yes	Yes	Yes	Yes
Message Waiting Indication	Yes	Yes	Yes	Yes	Yes
Third Party XML Support	Yes	Yes	Yes	Yes	Yes
Headset Port	Yes, Wideband Support	Yes - Wideband Support	Yes - Wideband Support	Yes - Wideband Support	Yes - Wideband Support
Signaling Protocol	SIP	SIP	SIP Other Protocols Supported: Bluetooth	SIP Other Protocols Supported: USB (1 port) Bluetooth and Non-Bluetooth versions available	SIP Other Protocols Supported: USB (2 ports) Bluetooth
802-3AF	Yes	Yes	Yes	Yes	Yes
Cisco Power	No	No	No	No	No
PoE Classification	Class 2	Class 2	Class 2	Class 4	Class 4
DHCP	Yes	Yes	Yes	Yes	Yes
802-1p/q	Yes	Yes	Yes	Yes	Yes
Codecs	G.711a, G.711u, G.729a, G.729b, G.729ab, iSAC, Internet Low Bitrate Codec (iLBC) and OPUS	G.711a, G.711u, G.729a, G.729b, G.729ab, iSAC, Internet Low Bitrate Codec (iLBC) and OPUS	G.711a, G.711u, G.729a, G.729b, G.729ab, iSAC, Internet Low Bitrate Codec (iLBC) and OPUS	G.711a, G.711u, G.729a, G.729b, G.729ab, iSAC, Internet Low Bitrate Codec (iLBC) and OPUS	G.711a, G.711u, G.729a, G.729b, G.729ab, iSAC, Internet Low Bitrate Codec (iLBC) and OPUS
Supported Cisco Call Control Platform(s)	CUCM: 8.5.1 (non-secured mode), 8.6.2, 9.1.2, 10.0 and later Bus. Edition: 8.6.2, 9.1.2, 10.0 and later HCS: 8.6.2 and later Cisco Spark: Requires Spark Phone OS 11.0 or later	CUCM: 8.5.1 (non-secured mode), 8.6.2, 9.1.2, 10.0 and later Bus. Edition: 8.6.2, 9.1.2, 10.0 and later HCS: 8.6.2 and later Cisco Spark: Requires Spark Phone OS 11.0 or later	CUCM: 8.5.1 (non-secured mode), 8.6.2, 9.1.2, 10.0 and later Bus. Edition: 8.6.2, 9.1.2, 10.0 and later HCS: 8.6.2 and later Cisco Spark: Requires Spark Phone OS 11.0 or later	CUCM: 8.5.1 (non-secured mode), 8.6.2, 9.1.2, 10.0 and later Bus. Edition: 8.6.2, 9.1.2, 10.0 and later HCS: 8.6.2 and later Cisco Spark: Requires Spark Phone OS 11.0 or later	CUCM: 8.5.1 (non-secured mode), 8.6.2, 9.1.2, 10.0 and later Bus. Edition: 8.6.2, 9.1.2, 10.0 and later HCS: 8.6.2 and later Cisco Spark: Requires Spark Phone OS 11.0 or later
UC Manager Encryption Support (TLS/SRTP)	Yes	Yes	Yes	Yes	Yes
Notes	FIPS 140-2 Level 1: Requires Phone OS 11.5 or later	FIPS 140-2 Level 1: Requires Phone OS 11.5 or later	FIPS 140-2 Level 1: Requires Phone OS 11.5 or later	FIPS 140-2 Level 1: Requires Phone OS 11.5 or later	FIPS 140-2 Level 1: Requires Phone OS 11.5 or later
PID	CP-8811-K9= (Charcoal); CP-8811-W-K9= (White); CP-8811-3PCC-K9= Multiplatform Phone: (Cisco approved Service Providers)	CP-8841-K9= (Charcoal); CP-8841-W-K9= (White); CP-8841-3PCC-K9= Multiplatform Phone: (Cisco approved Service Providers)	CP-8845-K9= (Charcoal); CP-8845-W-K9= (White)	CP-8851-K9= (Charcoal); CP-8851-W-K9= (White); CP-8851-3PCC-K9= Multiplatform Phone: (Cisco approved Service Providers)	CP-8861-K9= (Charcoal); CP-8861-W-K9= (White); CP-8861-3PCC-K9= Multiplatform Phone: (Cisco approved Service Providers)
Datasheet URL	https://www.cisco.com/c/en/us/products/collaboration-endpoints/ip-phone-8811/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/ip-phone-8841/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/ip-phone-8845/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/ip-phone-8851/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/ip-phone-8861/index.html



Collaboration Room Systems

Desk

Immersive

IP Phones

Peripherals

8800 Series

8800 Series

8800 Series

8800 Series

8865

8821

8821-EX

8831 Conference Phone







Feature/Functionality	8865	8821	8821-EX	8831 Conference Phone
Intergral Switch	10/100/1000	No	No	No
Display	5" high-resolution (800 x 480) WVGA color display	2.4" (6 cm) high-resolution color, graphical 240 x 320 pixel display	2.4" (6 cm) high-resolution color, graphical 240 x 320 pixel display	396 x 162 pixel-based, anti-glare graphical monochrome display with white backlight
Integrated Video	Yes - 720p HD, H.264 AVC Camera: 80 degree FOV, 25 degree tilt up/down; manual shutter (privacy)	No	No	No
Touch Screen	No	No	No	No
Speakerphone	Yes	Yes	Yes	Yes (full-duplex, 360-degree room coverage)
Number of Line keys	5	6	6	1 line
Programmable (Soft) keys	4	2	2	4
Fixed Feature Keys	12	6	6	9
Advanced Features	Gigabit Ethernet, Wideband Audio, Cisco Intelligent Proximity for Mobile Voice, USB Charging of Smartphone, IP Phone 8800 Key Expansion Module - Up to 3, 802.11a/b/g/n/ac Wi-Fi; Mobile Remote Access without a VPN client through Cisco Expressway; New cloud registration through Cisco Spark for even faster and cost-effective deployment; A non-Bluetooth radio version is also available	Wideband Audio Rechargeable Batteries - Talk Time 13 hours; 240 Standby Ingress Protection Rating: IP67 MIL-STD 810G Fast Transition (802.11r) Simple Certificate Enrollment Protocol (SCEP)	Wideband Audio Rechargeable Batteries - Talk Time 13 hours; 240 Standby Ingress Protection Rating: IP67 MIL-STD 810G Fast Transition (802.11r) Simple Certificate Enrollment Protocol (SCEP) Atmospheres Explosibles (ATEX) Class 1, Zone 2 CSA Division 1, Class 22	Optional wired or wireless Digital Equipment Cordless Telephony (DECT) microphone kit Daisy-Chain Configuration
Handsfree	Yes	Yes	Yes	Yes Speakerphone
Message Waiting Indication	Yes	Yes	Yes	Yes: Red button on dial control unit (DCU), message status via display
Third Party XML Support	Yes	Yes	Yes	Yes
Headset Port	Yes - Wideband Support	Yes (3.5mm headset jack)	Yes (3.5mm headset jack)	No
Signaling Protocol	SIP Other Protocols Supported: USB (2 ports) Bluetooth	SIP Other Protocols Supported: USB (1 port) Bluetooth	SIP Other Protocols Supported: USB (1 port) Bluetooth	SIP
802-3AF	Yes	N/A	N/A	Yes
Cisco Power	No	N/A	N/A	No
PoE Classification	Class 4	N/A	N/A	Class 3
DHCP	Yes	Yes	Yes	Yes
802-1p/q	Yes	N/A	N/A	Yes
Codecs	G.711a, G.711u, G.729a, G.729b, G.729ab, iSAC, Internet Low Bitrate Codec (iLBC) and OPUS	G.711a, G.711u, G.729a, G.729ab, G.722, Internet Low Bitrate Codec (iLBC), WAV and iSAC	G.711a, G.711u, G.729a, G.729ab, G.722, Internet Low Bitrate Codec (iLBC), WAV and iSAC	G.711a, G.711u, G.722, G.729a, G.729b, G.729ab, iLBC
Supported Cisco Call Control Platform(s)	CUCM: 8.5.1 (non-secured mode), 8.6.2, 9.1.2, 10.0 and later Bus. Edition: 8.6.2, 9.1.2, 10.0 and later HCS: 8.6.2 and later Cisco Spark: Requires Spark Phone OS 11.0 or later	CUCM: 9.1(2), 10.5(2), 11.0(1), and later • Cisco Unified Survivable Remote Site Telephony (SRST): 10.x, 11.x, and later • CME: 10.x, 11.x, and later • Cisco Hosted Collaboration Solution (HCS): 9.x, 10.x, 11.x, and later	CUCM: 9.1(2), 10.5(2), 11.0(1), and later • Cisco Unified Survivable Remote Site Telephony (SRST): 10.x, 11.x, and later • CME: 10.x, 11.x, and later • Cisco Hosted Collaboration Solution (HCS): 9.x, 10.x, 11.x, and later	CUCM: 7.1(5), 8.5(1), 8.6(2), 9.0 and later Bus. Edition: 8.6(5) and later HCS: 8.6(2) and later CME: 10.0 and above. On IOS 15.4(1)T with fast track support. Third Party Call Control
UC Manager Encryption Support (TLS/SRTP)	Yes	Yes	Yes	Yes
Notes	FIPS 140-2 Level 1: Requires Phone OS 11.5 or later		Available CY Q3 2017	
PID	CP-8865-K9= (Charcoal); CP-8865-W-K9= (White)	CP-8821-K9-BUN: (includes phone in world mode, battery, power cord, power adapter and country clip); CP-8821-K9= 8821 handset world mode only	Available CY Q3 2017	CP-8831-K9=
Datasheet URL	https://www.cisco.com/c/en/us/products/collaboration-endpoints/ip-phone-8865/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/wireless-ip-phone-8821/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/wireless-ip-phone-8821-ex/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/unified-ip-conference-phone-8831/index.html









Collaboration Room Systems	Desk	Immersive	IP Phones	Peripherals
----------------------------	------	-----------	-----------	-------------

8800 Series	8800 Series	8800 Series	8800 Series	SPA300 Series	SPA300 Series
-------------	-------------	-------------	-------------	---------------	---------------

	8832 Conference Phone	IP Phone 8800 Key Expansion Module for 8851, 8861, 8865	IP Phone 8851/8861 Key Expansion Module	IP Phone 8865 Key Expansion Module	SPA300 Series	SPA300 Series
						
Feature/Functionality						
Intergral Switch	No		N/A	N/A		No
Display	3.9-inch (99 mm), 480 x 120 pixelbased, anti-glare graphical color display with white backlight	4.3-inch graphical (TFT) color display provides 16-bit color depth and 480 x 272 effective pixel resolution, with backlight	Twp 3.5-inch (89mm) 18-bit 320x480 pixel, backlit, anti-glare color display	Twp 3.5-inch (89mm) 18-bit 320x480 pixel, backlit, anti-glare color display		N/A
Integrated Video	No	N/A	N/A	N/A		
Touch Screen	No	N/A	N/A	N/A		
Speakerphone	Yes (full duplex; 360-degree coverage)	N/A	N/A	N/A		
Number of Line keys	1 line	18 physical keys per module; Second "page" of 18 keys via software = total of 36 keys per module	Per Module: 14; 28 with "page 2" via software	Per Module: 14 physical keys; 28 with "page 2" via software		N/A
Programmable (Soft) keys	4	N/A	N/A	N/A		0
Fixed Feature Keys	8	2 - Page 1 and Page 2 keys	2: (Page 1 and Page 2 keys)	2: (Page 1 and Page 2 keys)		4
Advanced Features	Optional wired microphones DECT wireless microphones (CYQ4 2017) Daisy-chain option (CYQ4 2017)	Supports third-party USB headsets via USB port; Cisco Session Line Mode (SLM) support.	USB port for headsets and smartphone charging; Supports Session Line Mode (SLM) and Enhanced Line Mode (ELM)"	USB port for headsets and smartphone charging; Supports Session Line Mode (SLM) and Enhanced Line Mode (ELM)"		TFTP, HTTP, HTTPS, provisioning
Handsfree	Yes - Speakerphone	N/A	N/A	N/A		No
Message Waiting Indication	Yes	Message count	N/A	N/A		Yes
Third Party XML Support	?		N/A	N/A		N/A
Headset Port	No	USB	One side port (USB)	One side port (USB)		No
Signaling Protocol	SIP	SIP	SIP	SIP		SIP/SPCP Other Protocols Supported: SIP, TCPIP, UDP, RTP, HTTP/HTTPS, ARP/RARP , ICMP , DNS (A record, SRV, NAPTR), DHCP, TFTP, NTP
802-3AF	Yes	Limited: 8851 + 1 KEM	802.3at PoE	802.3at PoE		No
Cisco Power	No	No	No	No		No
PoE Classification	Class 4	Class 4 with 8851/61/65 phones; Power Cube 4 also supported	Power drawn from IP phone	Power drawn from IP phone		No
DHCP	Yes	N/A	N/A	N/A		Yes: 66, 150, 159, 160
802-1p/q	Yes	N/A	N/A	N/A		Yes
Codecs	G.711a, G.711u, G.722, G.729a, G.729b, G.729ab, iLBC, OPUS	N/A	N/A	N/A		G.711u/a, G.722, G.726- 16, 24, 32, 40, G.729a
Supported Cisco Call Control Platform(s)	CUCM, Business Edition 6000/7000: 10.5(2), 11.0(2), 11.5, 12.0 and later	CUCM 8.5(1) and later; and Cisco Unified Survivable Remote Site Telephony (SRST) 8.0 (with Cisco IOS® Software Release 15.1(1)T) and later; Cisco Spark	CUCM, Business Edition 6000/7000: 10.5(2), 11.0(2), 11.5, 12.0 and later	CUCM, Business Edition 6000/7000: 10.5(2), 11.0(2), 11.5, 12.0 and later		
UC Manager Encryption Support (TLS/SRTP)	Yes		Supported by IP Phone	Supported by IP Phone		Yes
Notes	Available Sept 2017: US and Canada; CYQ4 2017 - select countries (EMEA); DECT microphones and Daisy-chain option available CYQ4 2017		Available Sept 2017	Available Sept 2017		
PID	CP-8832-K9= (charcoal) CP-8832-W9= (white)	CP-BEKEM= (Charcoal); CP-BEKEM-W= (White)	CP-8800-A-K9= (charcoal)	CP-8800-V-K9= (charcoal)		SPA301-G1 (North America power adapter); SPA301-G2 (Europe power adapter); SPA301-G3 (UK power adapter); SPA301-G4 (Australia power adapter)
Datasheet URL	https://www.cisco.com/c/en/us/products/collaboration-endpoints/ip-conference-phone-8832/index.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/ip-phone-8800-series-key-expansion-module/datasheet-c78-732356.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/ip-phone-8851-8861-key-expansion-module/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/ip-phone-8865-key-expansion-module/index.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/small-business-spa300-series-ip-phones/index.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/small-business-spa300-series-ip-phones/datasheet_c78-601647.html

Collaboration Room Systems Desk Immersive IP Phones Peripherals

	SPA300 Series	SPA500	SPA500 Series	SPA500 Series	SPA500 Series	SPA500 Series
	SPA303		SPA500S	SPA500DS	SPA501G	SPA502G
						
Feature/Functionality						
Integral Switch	Yes: 10/100		N/A	N/A	Yes: 10/100	Yes: 10/100
Display	128 x 64 pixel		N/A	128 x 320 pixel (backlit)	N/A	128 x 64 pixel (backlit)
Integrated Video						
Touch Screen						
Speakerphone						
Number of Line keys	3		0	0 (coming in future release)	8	N/A
Programmable (Soft) keys	4		32	15 (second page to make 30 keys)	0	4
Fixed Feature Keys	7		0	0	11	7
Advanced Features	TFTP, HTTP, HTTPS, provisioning		Provides call pickup (CP), speed dial (SD), and busy lamp field (BLF) support via XML configuration	Provides call pickup (CP), speed dial (SD), and busy lamp field (BLF) support via XML configuration	TFTP, HTTP, HTTPS, provisioning	TFTP, HTTP, HTTPS, provisioning
Handsfree	Yes: Speakerphone		N/A	N/A	Yes: Speakerphone	Yes: Speakerphone
Message Waiting Indication	Yes		N/A	N/A	Yes	Yes
Third Party XML Support	Yes		N/A	Yes	N/A	Yes
Headset Port	Yes: 2.5mm		N/A	N/A	Yes: 2.5mm	Yes: 2.5mm
Signaling Protocol	SIP/SPCP Other Protocols Supported: SIP, TCPIP, UDP, RTP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, TFTP, NTP		N/A	N/A	SIP/SPCP Other Protocols Supported: SIP, TCPIP, UDP, RTP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, TFTP, NTP	SIP/SPCP Other Protocols Supported: SIP, TCPIP, UDP, RTP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, TFTP, NTP
802-3AF	No		N/A powered by phone	N/A powered by phone	Yes	Yes
Cisco Power	No		No	No	No	No
PoE Classification	N/A		N/A	N/A	Class 2	Class 2
DHCP	Yes: 66, 150, 159, 160		N/A	N/A	Yes: 66, 150, 159, 160	Yes: 66, 150, 159, 160
802-1p/q	Yes		N/A	N/A	Yes	Yes
Codecs	G.711u/a, G.722, G.726- 16, 24, 32, 40, G.729a		N/A	N/A	G.711u/a, G.722, G.726- 16, 24, 32, 40, G.729a	G.711u/a, G.722, G.726- 16, 24, 32, 40, G.729a
Supported Cisco Call Control Platform(s)						
UC Manager Encryption Support (TLS/SRTP)	Yes		N/A	N/A	Yes	Yes
Notes			Add up to two per SPA5xx IP phone	Add up to two per SPA5xx IP phone		
PID	SPA303-G1 (North America power adapter); SPA303-G2 (Europe power adapter); SPA303-G3 (UK power adapter); SPA303-G4 (Australia power adapter)		SPA500S	SPA500DS	SPA501G	SPA502G
Datasheet URL	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/small-business-spa300-series-ip-phones/data_sheet_c78-601648.html	https://www.cisco.com/c/en/us/products/collaboration-endpoints/small-business-spa500-series-ip-phones/index.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/small-business-spa500-series-ip-phones/data_sheet_c78-548281.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/spa500ds-digital-expansion-module/data_sheet_c78-711964.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/small-business-spa500-series-ip-phones/data_sheet_c78-548558.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/small-business-spa500-series-ip-phones/data_sheet_c78-548561.html







Collaboration Room Systems




Desk

Immersive

IP Phones


Peripherals

	SPA500 Series SPA504G	SPA500 Series SPA508G	SPA500 Series SPA509G	SPA500 Series SPA512	SPA500 Series SPA514	SPA500 Series SPA525G2
						
Feature/Functionality						
Integral Switch	Yes: 10/100	Yes: 10/100	Yes: 10/100	Yes: 10/100/1000	Yes: 10/100/1000	Yes: 10/100
Display	128 x 64 pixel (backlit)	128 x 64 pixel (backlit)	128 x 64 pixel (backlit)	128 x 64 pixel (backlit)	128 x 64 pixel (backlit)	320 x 240 pixel (backlit color)
Integrated Video						
Touch Screen						
Speakerphone						
Number of Line keys	4	8	12	N/A	4	5
Programmable (Soft) keys	4	4	4	4	4	4
Fixed Feature Keys	7	7	7	7	7	7
Advanced Features	TFTP, HTTP, HTTPS, provisioning	TFTP, HTTP, HTTPS, provisioning	TFTP, HTTP, HTTPS, provisioning	TFTP, HTTP, HTTPS, TR-069/TR-104/TR-111 provisioning, port mirroring for easy network tracing	TFTP, HTTP, HTTPS, TR-069/TR-104/TR-111 provisioning, port mirroring for easy network tracing	TFTP, HTTP, HTTPS, TR-069, TR-104, TR-111 provisioning, 802.11G client, MP3 player, picture frame, USB port for charging of mobile phone or USB stick, call recording direct to USB stick
Handsfree	Yes: Speakerphone	Yes: Speakerphone	Yes: Speakerphone	Yes: Speakerphone	Yes: Speakerphone	Yes: Speakerphone, Bluetooth headset
Message Waiting Indication	Yes	Yes	Yes	Yes	Yes	Yes
Third Party XML Support	Yes	Yes	Yes	Yes	Yes	Yes
Headset Port	Yes: 2.5mm	Yes: 2.5mm	Yes: 2.5mm	Yes: 2.5mm	Yes: 2.5mm	Yes: 2.5mm
Signaling Protocol	SIP/SPCP Other Protocols Supported: SIP, TCPIP, UDP, RTP, HTTP/HTTPS, ARP/ RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, TFTP, NTP	SIP/SPCP Other Protocols Supported: SIP, TCPIP, UDP, RTP, HTTP/HTTPS, ARP/ RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, TFTP, NTP	SIP/SPCP Other Protocols Supported: SIP, TCPIP, UDP, RTP, HTTP/HTTPS, ARP/ RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, TFTP, NTP	SIP/SPCP Other Protocols Supported: SIP, TCPIP, UDP, RTP, HTTP/HTTPS, ARP/ RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, TFTP, NTP, TR-069, TR-104, TR-111	SIP/SPCP Other Protocols Supported: SIP, TCPIP, UDP, RTP, HTTP/HTTPS, ARP/ RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, TFTP, NTP, TR-069, TR-104, TR-111	SIP/SPCP Other Protocols Supported: SIP, TCPIP, UDP, RTP, HTTP/HTTPS, ARP/ RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, TFTP, NTP, TR-069, TR-104, TR-111
802-3AF	Yes	Yes	Yes	Yes	Yes	Yes
Cisco Power	No	No	No	No	No	No
PoE Classification	Class 2	Class 2	Class 2	Class 2	Class 2	Class 2
DHCP	Yes: 66, 150, 159, 160	Yes: 66, 150, 159, 160	Yes: 66, 150, 159, 160	Yes: 66, 150, 159, 160	Yes: 66, 150, 159, 160	Yes: 66, 150, 159, 160
802-1p/q	Yes	Yes	Yes	Yes	Yes	Yes
Codecs	G.711u/a, G.722, G.726- 16, 24, 32, 40, G.729a	G.711u/a, G.722, G.726- 16, 24, 32, 40, G.729a	G.711u/a, G.722, G.726- 16, 24, 32, 40, G.729a	G.711u/a, G.722, G.726- 16, 24, 32, 40, G.729a	G.711u/a, G.722, G.726- 16, 24, 32, 40, G.729a	G.711u/a, G.722, G.726- 16, 24, 32, 40, G.729a
Supported Cisco Call Control Platform(s)						
UC Manager Encryption Support (TLS/SRTP)	Yes	Yes	Yes	Yes	Yes	Yes
Notes				EHS	EHS	EHS
PID	SPA504G	SPA508G	SPA509G	SPA512G	SPA514G	SPA525G2
Datasheet URL	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/small-business-spa500-series-ip-phones/data_sheet_c78-548564.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/small-business-spa500-series-ip-phones/data_sheet_c78-548569.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/small-business-spa500-series-ip-phones/data_sheet_c78-548571.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/spa512g-1-line-gige-ip-phone/c78-698950_data_sheet.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/spa514g-4-line-gige-ip-phone/c78-698951_data_sheet.html	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/spa525g2-5-line-ip-phone/data_sheet_c78-603725.html

	Collaboration Room Systems	Desk	Immersive	IP Phones	Peripherals
	ISDN Link		SpeakerTrack 60		Precision 60 Camera
					
Feature/Functionality					
Category	Telepresence Peripherals		Telepresence Peripherals		Telepresence Peripherals
Key Features	Compact appliance for in-room ISDN and external network connectivity supporting Cisco TelePresence EX, MX, SX, and C Series endpoints. Provides direct connectivity to ISDN or external networks (V.35) for individual telepresence endpoints without the need for additional gateways or other infrastructure.		Cisco TelePresence SpeakerTrack 60 Camera (SpeakerTrack 60) is an unparalleled dual-camera system that lets participants in a video meeting see the active speaker on the other end of a conference - in full view		Precision 60 provides a powerful integrator imaging solution for large meeting room scenarios. The camera offers large zoom range to cover large and advanced scenarios, great adaptability to light conditions; low noise interference for better image, and wide angle view
Screens	None		None		None
Camera	None		Dual Camera System Zoom: 10x optical zoom 2x digital zoom 20x zoom combined Pan and Tilt: Pan range: +/- 100 degrees Tilt range: +/- 20 degrees Field of View (FoV): Horizontal FoV: 80 degrees Vertical FoV: 48.8 degrees Tracking horizontal FoV: 80 degrees Focus Distance 1.0m to infinity (wide)		Precision 60 Camera Zoom: 10x optical zoom 2x digital zoom 20x total zoom combined Pan and Tilt: Pan range: +/- 100 degrees Tilt range: +/- 20 degrees Field of View (FoV): Horizontal FoV: 80 degrees Vertical FoV: 48.8 degrees Focus Distance: 1.0m to infinity (wide) F1.5 Camera control over Ethernet
Video Quality	N/A		True 1080p60 HD resolution delivers rich, vivid image quality002E		1920 x 1080 at 60 frames per second (fps)
Resolution	N/A		1920 x 1080 (16:9)		1920 x 1080 (16:9)
Video Standards	H.261 H.263 H.263++ H.264 depending upon codec support		N/A		N/A
Video Frame Rate	N/A		1920 x 1080 at 60 fps		1920 x 1080 at 60 fps
Software Supported	N/A		N/A		N/A
Signaling Protocol	IP-to-ISDN or IP-to-V.35 4 Basic Rate Interface (BRI) or 1 Primary Rate Interface (PRI) ISDN ports and external networks (cable standards V.35, RS530, RS449, and RS366)		N/A		N/A
Bandwidth Consumption	4 BRI up to 512 kbps; 1 PRI up to 1920 kbps; external networks up to 1920 kbps		N/A		N/A
Audio Standards	AAC-LD G.711 G.722 G.722.1		N/A		N/A
Physical Dimensions	• 1.18 x 11.02 x 6.69 in. (28 x 3 x 17 cm)		• Length: 31.5 in. (80.0 cm) • Height: 11.5 in. (29.2 cm) • Depth: 8.3 in. (21.0 cm) • Weight: 25.4 lb (11.5 kg)		• Length: 10.6 in. (26.8 cm) • Height: 6 in. (15.2 cm) • Depth: 6.4 in. (16.3 cm) • Weight: 5.5 lbs (2.5 kg)
PID	CTS-ISDNLINK-K9		CTS-SPKER-TRACK60		CTS-CAM-P60=
Datasheet URL	https://www.cisco.com/c/dam/en/us/products/collateral/collaboration-endpoints/telepresence-isdn-link/telepresence_isdn_link.pdf		https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/telepresence-speaker-track-60/datasheet-c78-729836.html		https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/telepresence-precision-cameras/datasheet-c78-669051.html?cachemode=refresh



Collaboration Room Systems	Desk	Immersive	IP Phones	Peripherals
----------------------------	------	-----------	-----------	-------------

	Precision 40 Camera	Precision 12X Camera	Touch 10
			
Feature/Functionality			
Category	Telepresence Peripherals	Telepresence Peripherals	Telepresence Peripherals
Key Features	<p>Cisco TelePresence Precision 40 Camera enables users to fully realize the high-definition experience and provides superior video quality at any bandwidth with the following features:</p> <ul style="list-style-type: none"> • Full 1080 HD • Mount upside down-(select option through VISCA™) • Automatic or manual focus, brightness, and white balance • High-definition multimedia interface (HDMI) • In-call LED indicator and power indicator 	<p>Cisco TelePresence Precision Camera enables users to fully realize the high-definition experience and provides superior video quality at any bandwidth with the following features:</p> <ul style="list-style-type: none"> • Ultimate high-definition camera designed by Cisco • Full 1080 HD • Upside-down mounting with automatic flipping of picture • Dual high-definition multimedia interface (HDMI) and high-definition serial digital interface (HD-SDI) output • Improved autofocus with multifocus points • Improved white balance with ambient light sensor • Automatic or manual focus, brightness, and white balance • In-call LED indicator and power indicator 	<p>Cisco TelePresence Touch devices take ease-of-use and user interaction benefits to the next level by adding touch interfaces to Cisco TelePresence endpoints</p> <p>Touch 10-inch devices support the second-generation MX300 and future generations of SX and MX Series</p>
Screens	None	None	Capacitive touch LCD 10.1-inch diagonal
Camera	<p>PrecisionHD 1080p 4x Camera</p> <p>Delivers 1080p30 (30 frames per second) or 720p60 (60 fps) true HD video with the following features:</p> <p>Excellent autofocus and white balance 4x optical zoom with smooth, quiet handling Dual HDMI/Camera control output Upside down mount, with manual flipping of image Pan range: -90 to +90°; tilt range: -25 to +15°</p>	<p>Precision 12X Camera</p> <p>Delivers 1080p60 (60 frames per second) true HD video with the following features:</p> <p>Excellent autofocus and white balance 12x optical zoom with smooth, quiet handling HDMI and HD-SDI outputs: the picture can be shared through both simultaneously Upside down mount; the picture is flipped automatically Pan range: -90 to +90°; tilt range: -25 to +15° 70° horizontal field of view F1.7</p>	N/A
Video Quality	1280 x 720 at 60 frames per second (fps) 1920 x 1080 at 30 frames per second (fps)	1920 x 1080 at 60 frames per second (fps)	N/A
Resolution	1280 x 720 (16:9) 1920 x 1080 (16:9)	1920 x 1080 (16:9)	1280 x 800
Video Standards	N/A	N/A	N/A
Video Frame Rate	1080p X 60 FPS	1920 x 1080 at 60 and 50 fps (HDMI only) 1920 x 1080 at 30 and 25fps 1280 x 720 at 60, 50, 30, and 25fps	N/A
Software Supported	N/A	N/A	TC7.0 or later and Collaboration Endpoint Software 8.0
Signaling Protocol	N/A	N/A	TCP/IP
Bandwidth Consumption	N/A	N/A	N/A
Audio Standards	N/A	N/A	N/A
Physical Dimensions	<ul style="list-style-type: none"> • Height (at max tilt): 151 mm/5.94 in • Width: 212 mm/8.35 in • Depth: 138 mm/5.43 in • Weight: 1.44 kg/3.17 lbs 	<ul style="list-style-type: none"> • Height (at maximum tilt): 6.8 inches (17.2 cm) • Width: 8.7 inches (22 cm) • Depth: 5.8 inches (14.7 cm) • Weight: 3.95 lb (1.8kg) 	3.3 x 10 x 7.4 in. (8.6 x 25.5 x 18.8 cm) Maximum height in vertical position 6.4 in (16.3 cm). Minimal height in lower position on the table: 2.9 in (7.35 cm)
PID	CTS-P40-K9=	CTS-PHD-1080P12XS=	CTS-CTRL-DV10=
Datasheet URL	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/telepresence-precision-cameras/datasheet-c78-669051.html?cachemode=refresh	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/telepresence-precision-cameras/datasheet-c78-669051.html?cachemode=refresh	https://www.cisco.com/c/en/us/products/collateral/collaboration-endpoints/telepresence-touch/data_sheet_c78-646041.html