

SPEC® OMPG2012 Result

Copyright 2012-2016 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS C460 M4 (Intel Xeon E7-8890 v4, 2.20 GHz)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 26.0

OMP2012 license:9019


Test sponsor: Cisco Systems

Tested by: Cisco Systems

Test date: May-2016

Hardware Availability: Jul-2016

Software Availability: Aug-2015



Hardware

CPU Name: Intel Xeon E7-8890 v4
 CPU Characteristics: Intel Turbo Boost Technology up to 3.40 GHz
 CPU MHz: 2200
 CPU MHz Maximum: 3400
 FPU: Integrated
 CPU(s) enabled: 96 cores, 4 chips, 24 cores/chip, 2 threads/core
 CPU(s) orderable: 2,4 Chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 60 MB I+D on chip per chip
 Other Cache: None
 Memory: 512 GB (32 x 16 GB 2Rx4 PC4-2400T-R, running at 1600 MHz)
 Disk Subsystem: 1 X 300 GB SAS, 15K RPM
 Other Hardware: None
 Base Threads Run: 192

Continued on next page

Software

Operating System: Red Hat Enterprise Linux 6.7 (Santiago),
 Kernel 2.6.32-573.el6.x86_64
 Compiler: C/C++/Fortran: Version 16.0.0.109 of Intel Composer for Linux Build 20150815
 Auto Parallel: No
 File System: Linux ext3
 System State: Default
 Base Pointers: 64-bit
 Peak Pointers: 64-bit
 Other Software: None

SPEC OMPG2012 Result

Copyright 2012-2016 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS C460 M4 (Intel Xeon E7-8890 v4, 2.20 GHz)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 26.0

OMP2012 license:9019
Test sponsor: Cisco Systems
Tested by: Cisco Systems

Test date: May-2016
Hardware Availability: Jul-2016
Software Availability: Aug-2015

Minimum Peak Threads: --
Maximum Peak Threads: --

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
350.md	192	124	37.2	130	35.6	<u>125</u>	<u>37.2</u>							
351.bwaves	192	179	25.4	<u>179</u>	<u>25.3</u>	179	25.3							
352.nab	192	<u>176</u>	<u>22.1</u>	176	22.1	176	22.1							
357.bt331	192	159	29.8	159	29.8	<u>159</u>	<u>29.8</u>							
358.botsalgn	192	177	24.5	<u>177</u>	<u>24.5</u>	177	24.5							
359.botsspar	192	<u>346</u>	<u>15.2</u>	345	15.2	348	15.1							
360.ilbdc	192	223	15.9	<u>223</u>	<u>15.9</u>	223	15.9							
362.fma3d	192	171	22.2	172	22.1	<u>171</u>	<u>22.2</u>							
363.swim	192	<u>222</u>	<u>20.4</u>	224	20.2	222	20.4							
367.imagick	192	<u>253</u>	<u>27.8</u>	252	27.9	253	27.8							
370.mgrid331	192	<u>249</u>	<u>17.7</u>	249	17.7	249	17.7							
371.applu331	192	104	58.0	<u>104</u>	<u>58.0</u>	104	58.1							
372.smithwa	192	93.6	57.2	<u>93.8</u>	<u>57.1</u>	94.5	56.7							
376.kdtree	192	<u>190</u>	<u>23.7</u>	190	23.7	190	23.7							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
sysinfo program /opt/omp2012/Docs/sysinfo
$Rev: 395 $ $Date:: 2012-07-25 #$ 8f8c0fe9e19c658963ale67685e50647
running on rhel67 Sat May 7 17:19:06 2016
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/omp2012/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E7-8890 v4 @ 2.20GHz
 4 "physical id"s (chips)
192 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
cpu cores : 24
siblings : 48
physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 1: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
physical 2: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
```

Continued on next page

SPEC OMPG2012 Result

Copyright 2012-2016 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS C460 M4 (Intel Xeon E7-8890 v4, 2.20 GHz)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 26.0

OMP2012 license:9019

Test sponsor: Cisco Systems

Tested by: Cisco Systems

Test date: May-2016

Hardware Availability: Jul-2016

Software Availability: Aug-2015

Platform Notes (Continued)

```
27 28 29
physical 3: cores 0 1 2 3 4 5 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26
27 28 29
cache size : 61440 KB

From /proc/meminfo
MemTotal:          529124784 kB
HugePages_Total:   0
Hugepagesize:      2048 kB

/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.7 (Santiago)

From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.7 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.7 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server

uname -a:
Linux rhel67 2.6.32-573.el6.x86_64 #1 SMP Wed Jul 1 18:23:37 EDT 2015 x86_64
x86_64 x86_64 GNU/Linux

run-level 3 May 7 11:54

SPEC is set to: /opt/omp2012
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sdb2        ext4  225G   64G  150G  30% /

Additional information from dmidecode:
BIOS Cisco Systems, Inc. C460M4.2.0.11.30.032820161452 03/28/2016
Memory:
32x 16 GB
32x 0xCE00 M393A2G40EB1-CRC 16 GB 1600 MHz 2 rank
64x NO DIMM NO DIMM

(End of data from sysinfo program)
```

General Notes

```
=====
Transparent Huge Pages enabled with:
echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
BIOS settings notes:
Intel Turbo Boost Technology (Turbo) : Enabled
CPU performance set to Enterprise
Processor Power State set to C0/C1
Power Technology set to Performance
Memory RAS configuration set to Maximum Performance
Energy Performance BIAS setting set to OS
Memory Power Saving Mode set to Disabled
QPI Snooper Mode set to Cluster-on-Die
```

Continued on next page

SPEC OMPG2012 Result

Copyright 2012-2016 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS C460 M4 (Intel Xeon E7-8890 v4, 2.20 GHz)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 26.0

OMP2012 license:9019

Test sponsor: Cisco Systems

Tested by: Cisco Systems

Test date: May-2016

Hardware Availability: Jul-2016

Software Availability: Aug-2015

General Notes (Continued)

General OMP Library Settings

ENV_KMP_LIBRARY=turnaround

ENV_OMP_SCHEDULE=static

ENV_KMP_BLOCKTIME=200

ENV_KMP_STACKSIZE=702M

ENV_OMP_DYNAMIC=FALSE

ENV_OMP_NESTED=FALSE

=====
General base OMP Library Settings

ENV_KMP_AFFINITY=compact,1

Submitted_by: "Rajendra Yogendra (ryogendr)" <ryogendr@cisco.com>

Submitted: Wed May 18 17:07:51 EDT 2016

Submission: omp2012-20160511-00074.sub

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Base Portability Flags

350.md: -FR
351.bwaves: No flags used
352.nab: No flags used
357.bt331: -mmodel=medium
358.botsalgn: No flags used
359.botsspar: No flags used
360.ilbdc: No flags used
362.fma3d: No flags used
363.swim: -mmodel=medium
367.imagick: -std=c99
370.mgrid331: No flags used
371.applu331: No flags used
372.smithwa: No flags used
376.kdtree: No flags used

SPEC OMPG2012 Result

Copyright 2012-2016 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS C460 M4 (Intel Xeon E7-8890 v4, 2.20 GHz)

SPECompG_peak2012 = Not Run

SPECompG_base2012 = 26.0

OMP2012 license:9019

Test sponsor: Cisco Systems

Tested by: Cisco Systems

Test date: May-2016

Hardware Availability: Jul-2016

Software Availability: Aug-2015

Base Optimization Flags

C benchmarks:

-O2 -openmp -ipo -xCORE-AVX2 -ansi-alias

C++ benchmarks:

-O2 -openmp -ipo -xCORE-AVX2 -ansi-alias

Fortran benchmarks:

-O2 -openmp -ipo -xCORE-AVX2 -align array64byte

The flags file that was used to format this result can be browsed at

<https://pro.spec.org/private/hpg/submit/omp2012/flags/Intel-ic13.0-linux64.20140219.00.html>

You can also download the XML flags source by saving the following link:

<https://pro.spec.org/private/hpg/submit/omp2012/flags/Intel-ic13.0-linux64.20140219.00.xml>

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.0.
Report generated on Wed May 18 17:07:59 2016 by SPEC OMP2012 PS/PDF formatter v541.