



Cisco TrustSec Software-Defined Segmentation Platform and Capability Matrix Release 6.3

Cisco TrustSec uniquely builds upon your existing identity-aware infrastructure by enforcing segmentation and access control policies in a scalable manner using the capabilities detailed below. This document summarizes the platforms and features that are validated in the Cisco TrustSec testing. It is in current with the TrustSec 6.3 validation program.

Table 1 provides cross-platform group-based policy exchange interoperability testing results. Application Centric Infrastructure (ACI) and TrustSec integration enables customers to apply consistent security policy across the enterprise- leveraging user roles and device type together with application context. The validated Open Source Open Daylight SDN use case included Nexus 7k SXPv3, ASA SXPv3, and OpenDaylight SXPv4 (Lithium, Beryllium, or Carbon release) working together in the Data Center.

Table 1. TrustSec Group-Based Policy (GBP) Interoperability

System Component	Platform	Solution-Level Validated Version	Group Information Exchange	Interoperability Platform & Propagation method
Cisco Nexus 9000 Series Switches	Cisco 9000 Series: Spine & Leaf	NX-OS 11.3(2f)	EndPoint Group – Security Group Mappings via TrustSec-ACI policy and data plane exchange	Cisco ISE 2.1, 2.2- ACI API
Cisco Application Policy Infrastructure Controller – Data Center	Cisco APIC-DC	APIC-DC 2.3 Data Plane APIC-DC 1.3(1g) Policy plane;		
Open Daylight SDN controller	ODL SDN	Lithium, Beryllium, or Carbon	SGT via SXP v4	Cisco ISE 2.1- SXP v4 Nexus 7000 7.3- SXP v3 ASA 9.6.1- SXP v3

In Table 2 Cisco Platform Support Matrix, Dynamic classification includes IEEE 802.1X, MAC Authentication Bypass (MAB), Web Authentication (Web Auth), and Easy Connect. IP to SGT, VLAN to SGT, subnet to SGT, port profile to SGT, L2IF to SGT, and L3IF to SGT use the static classification method.

Solution-level validated versions listed in Table 2 may not always represent the latest available platform version and feature set. Releases may encounter issues in other subsystems and be deferred. For latest platform firmware version and feature set, refer to product release notes.

Cisco ONE for Access is a simple and economical solution for deploying branch and campus switches and wireless access points. It offers an uncompromised user experience in a highly secure and feature-rich access infrastructure and simplifies the licensing requirements for TrustSec deployment.

Table 2. Cisco TrustSec Platform Support Matrix

System Component	Platform	License	Solution-Level Validated Version	Minimum version for all features	Security Group Tag (SGT) Classification	SGT Exchange Protocol (SXP) Support and Version	Inline SGT Tagging	SGT Enforcement
Cisco Identity Services Engine	ISE 3515, 3595, 3415, and 3495 Appliance & VMware	Base Plus for pxGrid	Cisco ISE 2.2, 2.1, 2.0, 1.4	Cisco ISE 2.2	Dynamic, IP to SGT, Subnet to SGT	Speaker, Listener V4 pxGrid	–	–
Cisco Catalyst® 2000 Series	Catalyst 2960-Plus Series Switches	LAN Base K9	-	Cisco IOS 15.2(2)E3	Dynamic, IP to SGT, VLAN to SGT, Subnet to SGT	Speaker V4	No	No
	Catalyst 2960-C Series	LAN Base K9	-	Cisco IOS 15.2(2)E3	Dynamic, IP to SGT, VLAN to SGT, Subnet to SGT	Speaker V4	No	No
	Catalyst 2960-CX Series	LAN Base K9	-	Cisco IOS 15.2(3)E	Dynamic, IP to SGT, VLAN to SGT, Subnet to SGT	Speaker V4	No	No
	Catalyst 2960-S and 2960-SF Series	LAN Base K9	Cisco IOS 15.0(2)SE ^{Note1} 15.2(2)E	Cisco IOS 15.2(2)E3	Dynamic, IP to SGT, VLAN to SGT, Subnet to SGT	Speaker V4 ^{Note1}	No	No
	Catalyst 2960-X Series	LAN Base K9	Cisco IOS 15.2(2)E	Cisco IOS 15.2(2)E3	Dynamic, IP to SGT, VLAN to SGT, Subnet to SGT	Speaker V4	No	No
	Catalyst 2960-XR Series	IP Lite K9	Cisco IOS 15.2(2)E	Cisco IOS 15.2(2)E3	Dynamic, IP to SGT, VLAN to SGT, Subnet to SGT	Speaker V4	No	No
	Cisco Catalyst 3000 Series	Catalyst 3560-E and 3750-E Series	IP Base K9	Cisco IOS 15.0(2)SE5	Cisco IOS 15.0(2)SE5	Dynamic, IP to SGT, VLAN to SGT	Speaker, Listener V2	No
Catalyst 3560-C/CG Series		IP Base K9	Cisco IOS 15.0(1)SE2	Cisco IOS 15.2(2)E	Dynamic, IP to SGT, VLAN to SGT, Subnet to SGT	Speaker, Listener V4	No	No
Catalyst 3560-CX Series		IP Base K9	Cisco IOS 15.2(3)E	Cisco IOS 15.2(4)E	Dynamic, IP to SGT (v4, v6), VLAN to SGT, Subnet to SGT	Speaker, Listener V4	No	SGACL
Catalyst 3560-X and 3750-X Series		IP Base K9	Cisco IOS 15.2(2)E3	Cisco IOS 15.2(2)E1	Dynamic, IP to SGT (prefix must be 32), VLAN to SGT, Port to SGT (only on switch to switch links)	Speaker V4	SGT over Ethernet; SGT over MACsec (with C3KX-SM-10G uplink)	SGACL (maximum of 8 VLANs on a VLAN-trunk link)
Catalyst 3650 and 3850 Series		IP Base K9 & above Cisco ONE Foundation & above	Cisco IOS XE 3.6.4	Cisco IOS XE 3.6.0SE	Dynamic, IP to SGT (v4,v6), VLAN to SGT, Port to SGT, Subnet to SGT, L3IF to SGT	Speaker, Listener V4	SGT over Ethernet; SGT over MACsec (3650 requires 3.7.1)	SGACL
Catalyst 3650 and 3850 Series		IP Base K9 & above Cisco ONE Foundation & above	Cisco IOS XE Denali 16.3.1	Cisco IOS XE Denali 16.3.1	Dynamic, IP to SGT (v4,v6), VLAN to SGT, Port to SGT, Subnet to SGT, L3IF to SGT	Speaker, Listener V4	SGT over Ethernet; SGT over MACsec; SGT over VXLAN	SGACL
Catalyst 3850-XS Series		IP Base K9 & above Cisco ONE Foundation & above	Cisco IOS XE 3.7.4	Cisco IOS XE 3.7.4	Dynamic, IP to SGT, VLAN to SGT, Port to SGT, Subnet to SGT, L3IF to SGT	Speaker, Listener V4	SGT over Ethernet ^{Note5} ; SGT over MACsec	SGACL

System Component	Platform	License	Solution-Level Validated Version	Minimum version for all features	Security Group Tag (SGT) Classification	SGT Exchange Protocol (SXP) Support and Version	Inline SGT Tagging	SGT Enforcement Services
Cisco Catalyst 4500 Series	Catalyst 4500 E-Series Supervisor Engine 6-E and 6L-E ; Cisco Catalyst 4948 Series	IP Base K9	Cisco IOS 15.1(1)SG	Cisco IOS 15.1(1)SG	Dynamic, IP to SGT	Speaker, Listener V4	No	No
	Catalyst 4500 E-Series Supervisor Engine 7-E and 7L-E	IP Base K9 & above Cisco ONE Foundation & above	Cisco IOS XE 3.5.1E	Cisco IOS XE 3.5.1E	Dynamic, IP to SGT, VLAN to SGT, Subnet to SGT, L3IF to SGT, Port to SGT	Speaker, Listener V4	SGT over Ethernet; SGT over MACsec (See note 2 for supported line cards)	SGACL
	Catalyst 4500 E-Series Supervisor Engine 8-E and 8L-E	IP Base K9 & above Cisco ONE Foundation & above	Cisco IOS XE 3.6.6E	Cisco IOS XE 3.6.0E	Dynamic, IP to SGT (v4, v6), VLAN to SGT, Port to SGT, Subnet to SGT (Src & Dst), L3IF to SGT	Speaker, Listener V4	SGT over Ethernet; SGT over MACsec (See note 2 for supported line cards)	SGACL
	Catalyst 4500-X Series	IP Base K9 & above Cisco ONE Foundation & above	Cisco IOS XE 3.6.6	Cisco IOS XE 3.5.1E	Dynamic, IP to SGT (v4,v6), VLAN to SGT, Port to SGT, Subnet to SGT (Src & Dst), L3IF to SGT	Speaker, Listener V4	SGT over Ethernet; SGT over MACsec	SGACL
Cisco Catalyst 6500 Series	Catalyst 6500 Series Supervisor Engine 32 and 720	IP Base K9	Cisco IOS 12.2(33)SXJ2	Cisco IOS 15.1(2)SY1	Dynamic, IP to SGT	Speaker, Listener V4	No	No
	Catalyst 6500 Series Supervisor Engine 2T & 6T Catalyst 6807-XL	2T: IP Base K9 6T: IP Services K9	Cisco IOS 15.2(1)SY0a Sup 6T Cisco IOS 15.4(1)SY1	Cisco IOS 15.2(1)SY0a Sup 6T Cisco IOS 15.4(1)SY1	Dynamic, IP to SGT (v4, v6), VLAN to SGT, Port to SGT, Subnet to SGT (v4,v6), L3IF-to- SGT (v4,v6)	Speaker, Listener V4 (IPv4, IPv6)	SGT over Ethernet & SGT over MACsec supported on: WS-X69xx modules, C6800 32P10G/G-XL, C6800-16P10G/G-XL, C6800-8P10G/G-XL	SGACL (IPv4, IPv6) SGT Caching
	Catalyst 6880-X, 6840-X, and 6800ia	IP Base K9 & above Cisco ONE Foundation & above	Cisco IOS 15.2(1)SY0a, 15.2(3a)E	Cisco IOS 15.2(1)SY0a	Dynamic, IP to SGT (v4, v6), VLAN to SGT, Port to SGT, Subnet to SGT (v4,v6), L3IF-to- SGT (v4,v6)	Speaker, Listener V4 (IPv4, IPv6)	SGT over Ethernet; SGT over MACsec	SGACL (IPv4, IPv6) SGT Caching
Cisco Catalyst 9300 Series	Catalyst 9300 Series	DNA Advantage	Cisco IOS XE Everest 16.6.2	Cisco IOS XE Everest 16.6.2 (Note 10)	Dynamic, IP to SGT, VLAN to SGT, Port to SGT, Subnet to SGT, L3IF to SGT	Speaker, Listener V4	SGT over Ethernet SGT over VXLAN	SGACL
Cisco Connected Grid Routers and Switches	CGR 2010 Series	-	Cisco IOS 15.5(2)T	Cisco IOS 15.4(1)T	Dynamic, IP to SGT, VLAN to SGT	Speaker, Listener V4	SGT over GETVPN, SGT over IPsec VPN	SG Firewall
	CGS 2500 Series	-	Cisco IOS 15.2(3)EA	Cisco IOS 15.0(2)EK1	Dynamic, IP to SGT, VLAN to SGT, Port to SGT, Subnet to SGT	Speaker, Listener V3	No	No
Cisco Industrial Ethernet Switches	IE 2000 & 2000U Series IE 3000 Series	LAN Base	Cisco IOS 15.2(3)EA	Cisco IOS 15.2(1)EY	Dynamic, IP to SGT, VLAN to SGT, Subnet to SGT	Speaker, Listener V4	No	No
			IE2000U: IOS 15.2(3)E3	IE2000U: IOS 15.2(3)E3				

System Component	Platform	License	Solution-Level Validated Version	Minimum version for all features	Security Group Tag (SGT) Classification	SGT Exchange Protocol (SXP) Support and Version	Inline SGT Tagging	SGT Enforcement
Cisco Industrial Ethernet Switches	IE 4000 Series	LAN Base; IP Services for SGTtoE & SGACL	Cisco IOS 15.2(4)EA, 15.2(5)E	Cisco IOS 15.2(5)E	Dynamic, IP to SGT, VLAN to SGT, Subnet to SGT	Speaker, Listener V4	SGT over Ethernet	SGACL
Cisco Industrial Ethernet Switches	IE 5000 Series	LAN Base; IP Services for SGTtoE & SGACL	Cisco IOS 15.2(2)EB1, 15.2(5)E	Cisco IOS 15.2(5)E	Dynamic, IP to SGT, VLAN to SGT, Subnet to SGT	Speaker, Listener V4	SGT over Ethernet on 1G interfaces only	SGACL
Cisco Access Points	1700, 2700, 2800, 3700, AP Series (Wave 1)	-	Cisco AireOS 8.4	Cisco AireOS 8.4	Dynamic	Speaker, Listener V4 <small>Note6</small>	SGT over Ethernet <small>Note6</small>	SGACL
	1815, 1830, 1850, 2800, 3800 AP Series (Wave 2)	-	Cisco AireOS 8.4	Cisco AireOS 8.4	Dynamic	Speaker, Listener V4 <small>Note6</small>	SGT over Ethernet <small>Note6</small>	SGACL
Cisco Wireless Controllers	5500 Series (5508,5520)	-	Cisco AireOS 8.3.102.0, 7.6.130.0	Cisco AireOS 7.6.130.0	Dynamic	Speaker V2	No	No
	2500 Series (2504)	-	Cisco AireOS 8.3.102.0, 7.6.130.0	Cisco AireOS 7.6.130.0	Dynamic	Speaker V2	No	No
	Wireless Services Module 2 (WiSM2)	-	Cisco AireOS 8.3.102.0, 7.6.130.0	Cisco AireOS 7.6.130.0	Dynamic	Speaker V2	No	No
	5760 Wireless Controller Series	IP Base K9	Cisco IOS XE 3.7.1E	Cisco IOS XE 3.3.1SE	Dynamic, IP to SGT, VLAN to SGT, Port to SGT, Subnet to SGT	Speaker, Listener V4	SGT over Ethernet	SGACL
	Flex 7500 Series Wireless Controller	-	Cisco AireOS 8.3.102.0, 7.6.130.0	Cisco AireOS 8.3	Dynamic	Speaker V2	No	No
	8500 Series Wireless Controller (8540,8510)	-	Cisco AireOS 8.3.102.0	Cisco AireOS 8.1	Dynamic	Speaker V2	No	No
	8540 Series Wireless Controller 5520 Series Wireless Controller		Cisco AireOS 8.4	Cisco AireOS 8.4	Dynamic	Speaker v2	SGT over Ethernet	No
Cisco Nexus® 7000 Series	Nexus 7000 M-Series and F-Series ^{Note4} modules Nexus 7700 F-Series ^{Note4} modules	Base License NX-OS 6.1 and later	Cisco NX-OS 7.3(0)D1(1), 7.2(0)D1(1)	Cisco NX-OS 8.0(1)	IP to SGT ¹ , Port Profile to SGT, VLAN to SGT ² , Port to SGT ² Subnet to SGT ⁵ ¹ :FabricPath support requires 6.2(10) or later ² VPC/VPC+ support requires 7.2(0)D1(1) or later ⁵ Subnet to SGT requires 7.3(0)D1(1) or later	Speaker, Listener V4	SGT over Ethernet ³ ; SGT over MACsec ⁴ ³ : F3 interfaces (L2 or L3) require 802.1Q or FabricPath ⁴ : M & F2e (Copper) all ports; F2e (SFP) & F3 (10G)- last 8 ports; All others- no support	SGACL

System Component	Platform	License	Solution-Level Validated Version	Minimum version for all features	Security Group Tag (SGT) Classification	SGT Exchange Protocol (SXP) Support and Version	Inline SGT Tagging	SGT Enforcement	
Cisco Nexus 1000 Series	Nexus 1000V for VMware vSphere	Advanced license for SGTtoE/SGACL support	Cisco NX-OS 5.2(1)SV3(1.3)	Cisco NX-OS 5.2(1)SV3 (1.1)	IP to SGT, Port Profile to SGT	Speaker, Listener v1	SGT over Ethernet ^{Note9}	SGACL	
Cisco Nexus 5000, 6000 Series	Nexus 6000/5600 Series	-	Cisco NX-OS 7.1(0)N1(1a)	Cisco NX-OS 7.0(1)N1(1)	Port to SGT	Speaker V1	SGT over Ethernet	SGACL	
	Nexus 5548P, 5548UP, and 5596UP (Note: No support for 5010 or 5020)	-	Cisco NX-OS 7.0(5)N1(1)	Cisco NX-OS 6.0(2)N2(6)	Port to SGT	Speaker V1 ¹ ¹ : FabricPath	SGT over Ethernet	SGACL	
Cisco Integrated Services Router (ISR)	890, 1900, 2900, 3900 Series	IPbase/K9 for classify/propagate; Security/K9 for SG FW enforcement	890: Cisco IOS <u>15.4(1)T1</u> <i>IOS 15.4(3)M</i> 1900/2900/3900: Cisco IOS <u>15.5(1)20T</u> <i>IOS 15.4(3)M</i>	890: Cisco IOS 15.4(3)M 1900/2900/3900: Cisco IOS 15.6(1)T	IP to SGT, Subnet to SGT, L3IF to SGT	Speaker, Listener V4	SGT over Ethernet (no support on ISR G2-Cisco 800 Series), SGT over GETVPN, DMVPN, or IPsec VPN	SG Firewall (890:No services) <i>SGT based PBR</i> <i>SGT Caching</i> <i>SGT based QoS</i>	
	4000 Series (ISR 4451-X validated)	IPbase /K9 for classify/propagate; Security/K9 for SG FW enforcement	Cisco IOS XE 3.15.01S	Cisco IOS XE 3.17.0S	IP to SGT, Subnet to SGT, L3IF to SGT	Speaker, Listener V4	SGT over Ethernet, SGT over GETVPN, DMVPN, or IPsec VPN	SG Firewall <i>SGT based PBR</i> <i>SGT Caching</i> <i>SGT based QoS</i>	
	4000 Series ISR 4431, 4451-X, 4321, 4331, 4351	IP Services/K9 for classify/propagate, SGACL; Security/K9 for SG FW enforcement	Cisco IOS XE Denali 16.3.2, Everest 16.4.1	Cisco IOS XE Denali 16.3.2	IP to SGT, Subnet to SGT, L3IF to SGT	Speaker, Listener V4	SGT over Ethernet, SGT over GETVPN, DMVPN, or IPsec VPN	SGACL SG Firewall <i>SGT based PBR</i> <i>SGT Caching</i> <i>SGT based QoS</i>	
	ISRv	IPbase/K9 for classify/propagate, SGACL	Cisco IOS XE Denali 16.3.2	Cisco IOS XE Denali 16.3.2	IP to SGT, Subnet to SGT, L3IF to SGT	Speaker, Listener V4	SGT over Ethernet, SGT over IPsec VPN, DMVPN	SGACL	
	SM-X Layer 2/3 EtherSwitch Module	IP Services/K9	Cisco IOS 15.5.2T	Cisco IOS 15.2(2)E	Dynamic, IP to SGT, VLAN to SGT	Speaker, Listener V4	SGT over Ethernet; SGT over MACsec	SGACL	
	Cisco Cloud Services Router	Cloud Services Router 1000V Series (CSR)	IPbase/K9 for classify/propagate; Security/K9 for enforcement	Cisco IOS XE 3.15.01S	Cisco IOS XE 3.11.0S	IP to SGT, Subnet to SGT, L3IF to SGT	Speaker, Listener V4	SGT over Ethernet, SGT over IPsec VPN, DMVPN	SG Firewall <i>SGT based PBR</i> <i>SGT Caching</i>
		Cloud Services Router 1000V Series (CSR)	IPbase/K9 for classify/propagate, SGACL;	Cisco IOS XE Denali 16.3.2, Everest 16.4.1	Cisco IOS XE Denali 16.3.2	IP to SGT, Subnet to SGT, L3IF to SGT	Speaker, Listener V4	SGT over Ethernet, SGT over IPsec VPN, DMVPN	SGACL

System Component	Platform	License	Solution-Level Validated Version	Minimum version for all features	Security Group Tag (SGT) Classification	SGT Exchange Protocol (SXP) Support and Version	Inline SGT Tagging	SGT Enforcement Services
Cisco Aggregation Services Router (ASR)	ASR 1000 Series Router Processor 1 or 2 (RP1, RP2); ASR 1001, 1002, 1004, 1006 and 1013 with ESP (10,20, 40, 100, 200) and SIP (10/40)	IP Services/K9 for classify/propagate; Security/K9 for enforcement	Cisco IOS XE 3.15.0S	Cisco IOS 3.17.0S	IP to SGT, Subnet to SGT, L3IF to SGT	Speaker, Listener V4	SGT over Ethernet, SGT over GETVPN, IPsec VPN, or DMVPN	SG Firewall SGT based PBR (1000 RP2) SGT based QoS SGT Caching
	ASR 1001-X and 1002-X	IPbase/K9 for classify/propagate; Security/K9 for enforcement	Cisco IOS XE 3.13.0S	Cisco IOS XE 3.17.0S	IP to SGT, Subnet to SGT, L3IF to SGT	Speaker, Listener V4	SGT over Ethernet, SGT over GETVPN, IPsec VPN, DMVPN	SG Firewall SGT based PBR SGT based QoS SGT Caching
	ASR 1004, 1006, 1013, 1001-X, 1002-X, 1002-HX, 1006-X, and 1009-X	IPbase/K9 for classify/propagate, SGACL; Security/K9 for SGFW enforcement	Cisco IOS XE Denali 16.3.2, Everest 16.4.1	Cisco IOS XE Denali 16.3.2	IP to SGT, Subnet to SGT, L3IF to SGT	Speaker, Listener V4	SGT over Ethernet, SGT over GETVPN, DMVPN, or IPsec VPN	SGACL SG Firewall SGT based PBR SGT Caching SGT based QoS
Cisco Adaptive Security Appliance (ASA)	ASA 5510, 5520, 5540, 5550, 5580	-	Cisco ASA 9.0.1, ASDM 7.1.6	Cisco ASA 9.0.1, ASDM 7.1.6		Speaker, Listener v2		SG Firewall
	ASA 5505 ^{Note3} , 5512, 5515, 5525, 5545, 5555, 5585	-	ASA 9.3.1, ASDM 7.3.1, CSM 4.8	Cisco ASA 9.3.1, ASDM 7.3.1, CSM 4.8	Remote Access VPN (IPsec, SSL-VPN)	Speaker, Listener V2 (IPv4, IPv6)	SGT over Ethernet	SG Firewall (IPv4, IPv6) SGT based PBR
	ASA 5506-X, 5506H-X, 5506W-X, 5508-X, 5516-X	-	Cisco ASA 9.6.1, ASDM 7.6.1	Cisco ASA 9.6.1, ASDM 7.6.1	Remote Access VPN (IPsec, SSL-VPN)	Speaker, Listener V3	SGT over Ethernet	SG Firewall (IPv4, IPv6) SGT based PBR
	ASA 5512-X, 5515-X, 5525-X, 5545-X, 5555-X, 5585-X with FirePower Services	-	Cisco ASA 9.6.1, ASDM 7.6.1	Cisco ASA 9.6.1, ASDM 7.6.1	Remote Access VPN (IPsec, SSL-VPN)	Speaker, Listener V3	SGT over Ethernet	SG Firewall (IPv4, IPv6) SGT based PBR
	ASAv	-	Cisco ASA 9.3.1 ASDM 7.1.6	Cisco ASA 9.6.1 ASDM 7.6.1	Remote Access VPN (IPsec, SSL-VPN)	Speaker, Listener V3	SGT over Ethernet	SG Firewall SGT based PBR

System Component	Platform	License	Solution-Level Validated Version	Minimum version for all features	Security Group Tag (SGT) Classification	SGT Exchange Protocol (SXP) Support and Version	Inline SGT Tagging	SGT Enforcement
Cisco Firepower (FP)	FP 4100	-	Cisco FXOS 2.0.1.37	Cisco FXOS 2.0.1.37	Remote Access VPN (IPsec, SSL-VPN)	Speaker, Listener V3	SGT over Ethernet	SG Firewall
	FP 9300	-	Cisco ASA 9.6.1	Cisco ASA 9.6.1	-	pxGrid	SGT over Ethernet	SG Firewall
	Cisco Firepower Threat Defense Firepower 4100 & 9300	Firepower Threat Defense Base	Cisco Firepower System 6.1.0	Cisco Firepower System 6.1.0	-	-	SGT over Ethernet	-
	FirePOWER 7000 and 8000 Series	-	Cisco FireSIGHT 5.4.0.6, 5.4.1.5, 6.0.1.1, 6.2	Cisco FireSIGHT 5.4.0.6, 5.4.1.5, 6.0.1.1	-	-	SGT over Ethernet	-
Cisco Industrial Security Appliance 3000	ISA 3000 Series	-	Cisco ASA 9.6.1	Cisco ASA 9.6.1	Remote Access VPN (IPsec, SSL-VPN)	Speaker, Listener V3	SGT over Ethernet	SG Firewall (IPv4, IPv6) <i>SGT based PBR</i>

Notes

- 1: Catalyst 2960 S/SF Product management recommends 15.0(2)SE which supports SXP v2.
- 2: Product part numbers of supported line cards for SGT over Ethernet and SGT over MACsec on the Cisco Catalyst 4500 Supervisor Engine 7-E, 7L-E, 8-E, and 8L-E include the following: WS-X4712-SFP+E, WS-X4712-SFP-E, WS-X4748-UPOE+E, WS-X4748-RJ45V+E, WS-X4748-RJ45-E, WS-X4724-SFP-E, WS-X4748-SFP-E, and WS-X4748-12X48U+E.
- 3: Cisco ASA 5505 does not support releases after 9.2.
- 4: Cisco Nexus 7000 F1-Series modules do not support Cisco TrustSec.
- 5: Use of inline tagging with LACP requires future IOS XE Denali or IOS 3.7 release (CSCva22545)
- 6: For SXP support, AP must run in FlexConnect Mode
- 7: With IPv6 support, DGT can be IPv4.
- 8: Prior versions of this document listed Cisco Catalyst 3750-X validated version, IOS 12.2(3)E1, and WLC AireOS 8.1. These releases have been deferred.
- 9: When TrustSec inline tagging (SGToE) is enabled with the VIC 12xx and VIC 13xx, packet processing is handled at the processor level which will attribute to lower network I/O performance. An alternative solution is to use Intel adaptors.
- 10: IOS XE 16.6.2-ES1 (Engineering Special) is required for ISE BYOD, Guest, and Posture features. See ISE Compatibility Matrix: <https://www.cisco.com/c/en/us/support/security/identity-services-engine/products-device-support-tables-list.html>



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)