

Release Notes for Cisco RV110W Firmware Version 1.2.0.9

March 19, 2012

Contents

This document includes the following topics:

- [Changes Since Firmware Release 1.0.1.9](#)
- [Related Information](#)

Changes Since Firmware Release 1.0.1.9

Table 1 Resolved Issues in Firmware Version 1.2.0.9

Ref Number	Description
none	Site-to-Site VPN for a single gateway-to-gateway VPN tunnel is supported. See the <i>Cisco RV110W Administration Guide</i> for more information.
none	Capability for separate “guest” wireless network is supported. See the <i>Cisco RV110W Administration Guide</i> for more information.
none	Security for Access Point PIN mode in Wi-Fi Protected Setup is supported. After the wrong PIN is entered 10 consecutive times, the AP PIN mode is disabled. AP PIN mode remains disabled for 24 hours, until the device is rebooted, or until the system administrator logs in to the management interface and re-enables AP PIN mode.
none	WPS push-button configuration mode is disabled by default.

Release Notes

Table 1 Resolved Issues in Firmware Version 1.2.0.9

Ref Number	Description
none	Context-sensitive online help is enabled.
CSCtw90662	When the XML command is sent with the <i>PrivMethod</i> of <i>privDES</i> , the <i>PrivMethod</i> is set as <i>AES</i> instead.
CSCtw90666	When the <i>Password Complexity Setting of the new password must be different than the current one</i> setting is enabled, it is not enforced when modifying the configuration using the XML API.
CSCtw91393	When performing a backup of a configuration file using SNMP, the user cannot use the MIB object <i>ciscosbAdminTransferFileName</i> to specify a filename. The default filename is used instead.
CSCtw91400	Dependency checking for SNMP authentication/privacy fields is not thorough.
CSCtw99076	Changing the method of remote access to the management interface between HTTP and HTTPS redirects the user to an error screen.
CSCtx03835	Guest wireless network issues: the time limit is always 30 minutes despite configured time, and <i>time left</i> and <i>hostname</i> fields are not displayed on the observation page.
CSCtx08187	After changing the LAN IP, an “X” option is presented that performs no action when clicked.
CSCtx01372	The Save button on the Networking > LAN > DMZ Host page does not work.
none	Port forwarding issue has been resolved.
none	SNMP supports <i>dot1dBasePortTable</i> for OnPlus.
none	IPv6 rapid deployment is supported.
none	IPv6 4in6 (RFC2473) is supported.
none	IPv6 over PPPoE is supported.
none	IPv6 prefix delegation through DHCPv6 is supported.
none	The option for advertising the router address through DHCPv6 as DNS (DNS proxy), or advertising the DNS addresses received from the SP is supported.
none	The Connected Devices page supports the IPv6 NDP table.
none	Port forwarding supports IPv6 addresses.
none	SNMP traps support IPv6 addresses.

Table 1 Resolved Issues in Firmware Version 1.2.0.9

Ref Number	Description
none	The WAN status page displays information learned through DHCP from the SP, such as DNS addresses, NTP servers, and prefixes.
none	IPv6 fragmentation issue.
none	IPv6 shows full format.
CSCtt19783	The Connected Devices status page only shows devices connected to the default VLAN and does not show devices connected to other VLANs.
CSCtt19776	The Quick VPN connection shows as connected after client disconnects. In some cases, the client must manually be disconnected from the VPN before the client can reconnect.
CSCts62309	The refresh rate on the logging page cannot be configured.
CSCto40444	No log or connection status for Wireless Distribution System (WDS) is displayed.
CSCtt19795	Clicking the Reload button on the web browser requires the user to log in again to the management interface.

Known Issues in Release 1.2.0.6

Issue—The RV110W cannot block previously-installed ActiveX applications when *Block ActiveX* is enabled.

Workaround—Clear the cache on the browser before beginning configuration.

Issue—When adding a new VLAN, the user loses connection to the GUI.

Workaround—None; the management interface should become available in approximately 15 seconds.

Issue—If DHCP server is turned off on the RV110W, the status page still displays the DHCP server as “on,” even if there is only one VLAN.

Workaround—None.

Release Notes

Issue—In the Logging page, the email Settings Test button is unavailable when the *authentication with SMTP server* parameter is set to *none*.

Workaround—Do not use the *none* option; use one of the other authentication methods.

Issue—When the SNMPv3 traps are set with the *Authentication and No Privacy* or *Authentication and Privacy* security levels, no SNMPv3 traps are seen.

Workaround—Set SNMPv3 traps with the security level of *No Authentication and No Privacy*.

Issue—Minor online help navigation bar display issue in Google Chrome browser.

Workaround—Open Chrome browser using the command-line interface:

- Windows: `chrome.exe --allow-file-access-from-files`
 - Mac: `open /Applications/Google\ Chrome.app --args --allow-file-access-from-files`
-

Issue—Text-based configuration files cannot be modified by the user and then uploaded to the router.

Workaround—None

Issue—Degraded performance with certain wireless client adapters.

Workaround—Upgrade to the latest drivers. Enable Wireless Multimedia (WMM) and disable the power save mode in the wireless client driver properties.

Related Information

Support	
Cisco Small Business Support Community	www.cisco.com/go/smallbizsupport
Cisco Small Business Support and Resources	www.cisco.com/go/smallbizhelp
Phone Support Contacts	www.cisco.com/en/US/support/tsd_cisco_small_business_support_center_contacts.html
Cisco Small Business Firmware Downloads	www.cisco.com/go/software Select a link to download firmware for Cisco Small Business Products. No login is required.
Product Documentation	
Cisco Small Business RV Series Routers	www.cisco.com/go/smallbizrouters
Cisco Small Business	
Cisco Partner Central for Small Business (Partner Login Required)	www.cisco.com/web/partners/sell/smb
Cisco Small Business Home	www.cisco.com/smb

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)

© 2012 Cisco Systems, Inc. All rights reserved.

OL-26914-01