



QUICK START GUIDE



Cisco Video Surveillance 253x Series IP Dome, Models CIVS-IPC-2530V and CIVS-IPC-2531V

- 1 Overview
- 2 Package Contents
- 3 Optional Accessories
- 4 About Installing the IP Dome
- 5 Technical Support

Americas Headquarters
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
<http://www.cisco.com>
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 527-0883



Cisco, Cisco Systems, the Cisco logo, and the Cisco Systems logo are registered trademarks or trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries. All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0705R)

© 2009 Cisco Systems, Inc. All rights reserved.

♻️ Printed in China PRC

1 Overview

The Cisco Video Surveillance 253x Series IP Dome models CIVS-IPC-2530V and CIVS-IPC-2531V are high-resolution, feature-rich IP cameras. They offer wide dynamic ranges, dual streaming, motion detection, event notification, day/night operation, 24 VAC power, flexible mounting options, and many other features. They also support external devices that trigger alarms and respond to alarms, and provide audio input and output.

The IP domes are vandal-resistant and include an integrated heater and fan. They are designed to be mounted outdoors. Model CIVS-IPC-2530V includes a clear dome cover and model CIVS-IPC-2531V includes a smoked dome cover.

2 Package Contents

The Cisco Video Surveillance IP Dome package includes these items:

- This *Quick Start Guide*
- Regulatory Compliance and Safety Information
- Template for mounting
- Camera
- Conduit case
- Mini cable with BNC adapter
- Y cable for audio input and output
- 0.9 mm Allen wrench for adjusting back focus
- TORX security screwdriver for tamper resistant TORX head screws
- 8-32 x 5/16 inch screws (qty. 4)
- Rubber sheet
- Spare gasket (qty. 1)

3 Optional Accessories

The following accessories are available for the 253x Series IP Dome. You can order these accessories from Cisco or a Cisco partner.

- Bubble, clear, 2500 Series—Cisco part number CIVS-IPCA-1004=
- Bubble, smoked, 2500 Series—Cisco part number CIVS-IPCA-1005=
- Conduit base spare with extra gaskets, 2500 Dome series—CIVS-IPCA-1006=

4 About Installing the IP Dome

Installing the IP dome involves mounting it by using a conduit case or a pendant. Mounting options include the following:

- Conduit case mounting—Use this method with the provided conduit case in situations where you cannot cut a hole through a surface for cables or where cables run through a small hole in a surface
- Pendant mounting—You can mount the IP dome 253x series to a wall with an optional pendant and wall mount assembly

The IP dome requires a connection to a network via a shielded twisted pair (STP) category 5 or higher network cable. The IP dome also requires power from a customer-supplied table-top or rack-mounted 24 VAC power supply. The 24 VAC source must be isolated from the ground (floating output).

In addition, you can use the following optional devices with the IP dome:

- External speaker
- External microphone
- Up to two external input devices and up to two external output devices

For detailed information about installing, configuring, operating, administering, and troubleshooting the IP dome, see *Cisco Video Surveillance IP Camera User Guide, Cisco Video Surveillance 253x Series IP Dome, Models CIVS-IPC-2530V and CIVS-IPC-2531V*. This document is available at www.cisco.com/go/ipcamera.

5 Technical Support

To request technical assistance, contact the Cisco Technical Assistance Center (TAC) in one of the following ways:

- Online—<http://www.cisco.com/tac/>
- E-mail—tac@cisco.com
- Phone—In North America: 800 553-2447
Outside North America: 408 526-7209