



Release Notes for the StarOS™ Software Version 2024.04.gah1

First Published: December 18, 2024

Introduction

This Release Notes identifies changes and issues related to the Control and User Plane Separation (CUPS) software releases.

Products Qualified and Released in this Release

Products	Qualified Yes/No
cups-cp	Yes
cups-up	Yes
mme	No
ePDG	No
pdn-gw	No
saegw	No
sgsn	No
Platforms	
ASR 5500	No
VPC-DI	Yes
VPC-SI	Yes

Release Lifecycle Milestones

Release Lifecycle Milestone	Milestone	Date
First Customer Ship	FCS	30-Oct-2024
End of Life	EoL	30-Oct-2024
End of Software Maintenance	EoSM	30-Apr-2026
End of Vulnerability and Security Support	EoVSS	30-Apr-2026
Last Date of Support	LDoS	30-Apr-2027

Release Package Version Information

Software Packages	Version	Build Number
StarOS Package	2024.04.gah1	21.28.h11.96242

Descriptions for the various packages provided with this release are available in the [Release](#) Package Descriptions section.

Verified Compatibility

Products	Version
ADC P2P Plugin	2.74.h2.2489
RCM	20241016-104205Z
CVIM	5.0.1
ESC	6.0.0.50
Host OS	RHEL 9.2
RedHat OpenStack	RHOSP 17.1
XL710 NIC Version	Driver: 5.14.0-284.30.1.el9_2.x86_64 Firmware: 7.00 0x80005119 0.385.115
CIMC Version (UCS C220-M5)	4.1(2a)

Note: Use only these compatible software versions for the products qualified in this release.

What's New in this Release

This version of Release Notes includes a new section titled **What's New in this Release** comprising all new features, enhancements, and behavior changes applicable for the release.

Features and Enhancements

There are no specific features and enhancements introduced in this release.

Related Documentation

For a complete list of documentation available for this release, go to:

<http://www.cisco.com/c/en/us/support/wireless/asr-5000-series/products-installation-and-configuration-guides-list.html>

Installation and Upgrade Notes

This Release Note does not contain general installation and upgrade instructions. Refer to the existing installation documentation for specific installation and upgrade considerations.

Synchronizing Boot File for Service Function Cards

To synchronize the boot file for all the Service Function (SF) VPC-DI non-management cards, use the following:

CLI executable command:

```
[local] host_name# system synchronize boot
```

This assures that the changes in boot file are identically maintained across the SF cards.

Ensure that you execute this command before reload for version upgrade from any version less than mh14 to mh14 or later.

Firmware Updates

There are no firmware upgrades required for this release.

Software Integrity Verification

To verify the integrity of the software image you have from Cisco, you can validate the SHA512 checksum information against the checksum identified by Cisco for the software.

Image checksum information is available through [Cisco.com Software Download Details](#). Click **Linux**, and then choose the Software Image Release Version.

To find the checksum, hover the mouse pointer over the software image you have downloaded.

At the bottom you find the SHA512 checksum, if you do not see the whole checksum you can expand it by pressing the "... " at the end.

Open Bugs for this Release

To validate the information, calculate a SHA512 checksum using the information in Table 1 and verify that it matches either the one provided on the software download page.

To calculate a SHA512 checksum on your local desktop see Table 1

Table 1 - Checksum Calculations per Operating System

Operating System	SHA512 checksum calculation command examples
Microsoft Windows	Open a command line window and type the following command <code>> certutil.exe -hashfile <filename>.<extension> SHA512</code>
Apple MAC	Open a terminal window and type the following command <code>\$ shasum -a 512 <filename>.<extension></code>
Linux	Open a terminal window and type the following command <code>\$ sha512sum <filename>.<extension></code> Or <code>\$ shasum -a 512 <filename>.<extension></code>
NOTES: <filename> is the name of the file. <extension> is the file extension (e.g. .zip or .tgz).	

If the SHA512 checksum matches, you can be sure that no one has tampered with the software image or the image has not been corrupted during download.

If the SHA512 checksum does not match, we advise you to not attempt upgrading any systems with the corrupted software image. Download the software again and verify the SHA512 checksum again. If there is a constant mismatch, please open a case with the Cisco Technical Assistance Center.

Certificate Validation

In 2024.01 and later releases, software images for StarOS, VPC-DI, and VPC-SI, and the companion software packages for StarOS and VPC are signed via x509 certificates.

USP ISO images are signed with a GPG key.

For more information and instructions on how to validate the certificates, refer to the README file available with the respective software packages.

Open Bugs for this Release

The following table lists the open bugs in this specific software release.

NOTE: This software release may contain open bugs first identified in other releases. Additional information for all open bugs for this release are available in the [Cisco Bug Search Tool](#).

Resolved Bugs for this Release

Table 2 - Open Bugs in this Release

Bug ID	Headline	Product Found
CSCwn06583	While performing SGW Relocation getting error as EGTP_CAUSE_PEER_NOT_RESPONDING	cups-cp
CSCwm74110	[CUPS 21.28] Reboot SF Demux leads to BFD sessions DOWN on Standby Card	cups-cp
CSCwk67137	[CUPS / LIVE / CP / 21.28.h7] Di-Net Heartbeat drop > 1% - Health status = Bad	cups-cp
CSCwk79042	[CUPS-UP] SX path failure is not leading to SRP switchover with sx monitor enabled	cups-up
CSCwm51816	sessmgr task restarted on UP, when LI and S8hr interception call is getting cleared	cups-up

Resolved Bugs for this Release

The following table lists the resolved bugs in this specific software release.

NOTE: This software release may contain bug fixes first introduced in other releases. Additional information for all resolved bugs for this release are available in the [Cisco Bug Search Tool](#).

Table 3 - Resolved Bugs in this Release

Bug ID	Headline	Product Found
CSCwn12434	SAEGW is ignoring GTPC messages	cups-cp
CSCwm38684	vpnmgr task restarts in dns-client are of code due to DNS huge amount Timeouts/ServFail	mme
CSCwn11056	DNS-MME is not handling DNS response with CNAME format properlye	mme
CSCwm82278	[CP-MME] Observing Heartbeat loss in VPC-DI setup(DI-NET)	staros
CSCwn19439	CVIM5.0.1 - VPCDI deployment fails to bring up SF	staros
CSCwn41761	flash, hard drive and service interfaces not getting loaded in 21.28.hx	staros

Operator Notes

StarOS Version Numbering System


The output of the **show version** command displays detailed information about the version of StarOS currently running on the ASR 5500 or Cisco Virtualized Packet Core platform.

NOTE: Starting 2024.01.0 release (January 2024), Cisco is transitioning to a new release versioning scheme. The release version is based on the current year and product. Refer to [Figure 1](#) for more details.

During the transition phase, some file names will reflect the new versioning whereas others will refer to the 21.28.x-based naming convention. With the next release, StarOS-related packages will be completely migrated to the new versioning scheme.

Version Numbering for FCS, Emergency, and Maintenance Releases

Figure 1 – Version Numbering



Note: For any clarification, contact your Cisco account representative.

StarOS Configuration Recommendations for VPC-DI

Configure the following StarOS-level settings in the **staros_param.cfg** file to set up the day-0 cloud configuration for the VNF.

Enable the boot parameter to move KNI packets over MCDMA threads by setting
`KNI_ON_MCDMA_THREAD_ENABLE=1.`

Troubleshooting Information

Issue: VIP accessibility for VPC-DI instances deployed via ESC on Openstack using the ML2/OVN mechanism driver may be problematic.

Workaround:

1. Identify the CF1 and CF2 ports on the management network within Openstack
2. Configure **allowed_address_pairs** for these ports to match the virtual port IP address (use /32 notation)
3. Avoid using CIDR format IP addresses for **allowed_address_pairs** on these ports
4. Execute the following command to set the allowed address **pairs:openstack port set <CF-mgmt-port-ID> -- allowed-address ip-address=<VIP-address>,mac-address=<CF-mgmt-port-MAC-address>**

Release Package Descriptions

Table 4 provides examples of packages according to the release. For more information about the release packages up to 21.28.x releases, refer to the corresponding releases of the release note.

Table 4 - Release Package Information

Software Package	Description
ASR 5500	
asr5500-<release>.zip	Contains the signed ASR 5500 software image, the signature file, a verification script, the x509 certificate, and a README file containing information on how to use the script to validate the certificate.
asr5500_T-<release>.zip	Contains the signed, trusted ASR 5500 software image, the signature file, a verification script, the x509 certificate, and a README file containing information on how to use the script to validate the certificate.
VPC Companion Package	
companion-vpc-<release>.zip For example, companion-vpc-2024.02.gh2.i4.zip	Contains numerous files pertaining to this version of the VPC including SNMP MIBs, RADIUS dictionaries, ORBEM clients. These files pertain to both VPC-DI and VPC-SI, and for trusted and non-trusted build variants.
VPC-DI	
qvpc-di-<release>.bin.zip	Contains the VPC-DI binary software image that is used to replace a previously deployed image on the flash disk in existing installations.
qvpc-di_T-<release>.bin.zip	Contains the trusted VPC-DI binary software image that is used to replace a previously deployed image on the flash disk in existing installations.
qvpc-di-<release>.iso.zip	Contains the VPC-DI ISO used for new deployments, a new virtual machine is manually created and configured to boot from a CD image.
qvpc-di_T-<release>.iso.zip	Contains the trusted VPC-DI ISO used for new deployments, a new virtual machine is manually created and configured to boot from a CD image.
qvpc-di-template-vmware-<release>.zip	Contains the VPC-DI binary software image that is used to on-board the software directly into VMware.
qvpc-di-template-vmware_T-<release>.zip	Contains the trusted VPC-DI binary software image that is used to on-board the software directly into VMware.
qvpc-di-template-libvirt-kvm-<release>.zip	Contains the same VPC-DI ISO identified above and additional installation files for using it on KVM.
qvpc-di-template-libvirt-kvm_T-<release>.zip	Contains the same trusted VPC-DI ISO identified above and additional installation files for using it on KVM.
qvpc-di-<release>.qcow2.zip	Contains the VPC-DI binary software image in a format that can be loaded directly with KVM using an XML definition file, or with OpenStack.
qvpc-di_T-<release>.qcow2.zip	Contains the trusted VPC-DI binary software image in a format that can be loaded directly with KVM using an XML definition file, or with OpenStack.
VPC-SI	

intelligent_onboarding-<release>.zip	Contains the VPC-SI onboarding signature package that is used to replace a previously deployed image on the flash disk in existing installations.
qvpc-si-<release>.bin.zip	Contains the VPC-SI binary software image that is used to replace a previously deployed image on the flash disk in existing installations.
qvpc-si_T-<release>.bin.zip	Contains the trusted VPC-SI binary software image that is used to replace a previously deployed image on the flash disk in existing installations.
qvpc-si-<release>.iso.zip	Contains the VPC-SI ISO used for new deployments, a new virtual machine is manually created and configured to boot from a CD image.
qvpc-si_T-<release>.iso.zip	Contains the trusted VPC-SI ISO used for new deployments a new virtual machine is manually created and configured to boot from a CD image.
qvpc-si-template-vmware-<release>.zip	Contains the VPC-SI binary software image that is used to on-board the software directly into VMware.
qvpc-si-template-vmware_T-<release>.zip	Contains the trusted VPC-SI binary software image that is used to on-board the software directly into VMware.
qvpc-si-template-libvirt-kvm-<release>.zip	Contains the same VPC-SI ISO identified above and additional installation files for using it on KVM.
qvpc-si-template-libvirt-kvm_T-<release>.zip	Contains the same trusted VPC-SI ISO identified above and additional installation files for using it on KVM.
qvpc-si-<release>.qcow2.zip	Contains the VPC-SI binary software image in a format that can be loaded directly with KVM using an XML definition file, or with OpenStack.
qvpc-si_T-<release>.qcow2.zip	Contains the trusted VPC-SI binary software image in a format that can be loaded directly with KVM using an XML definition file, or with OpenStack.
RCM	
rcm-vm-airgap-<release>.ova.zip	Contains the RCM software image that is used to on-board the software directly into VMware.
rcm-vm-airgap-<release>.qcow2.zip	Contains the RCM software image in a format that can be loaded directly with KVM using an XML definition file, or with OpenStack.
rcm-vm-airgap-<release>.vmdk.zip	Contains the RCM virtual machine disk image software for use with VMware deployments.
Ultra Services Platform	
usp-<version>.iso	The USP software package containing component RPMs (bundles). Refer to the Table 5 for descriptions of the specific bundles.
usp_T-<version>.iso	The USP software package containing component RPMs (bundles). This bundle contains trusted images. Refer to the Table 5 for descriptions of the specific bundles.
usp_rpm_verify_utils-<version>.tar	Contains information and utilities for verifying USP RPM integrity.

Obtaining Documentation and Submitting a Service Request

For information on obtaining documentation, using the Cisco Bug Search Tool (BST), submitting a service request, and gathering additional information, refer to <https://www.cisco.com/c/en/us/support/index.html>.

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright ©1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

All printed copies and duplicate soft copies of this document are considered uncontrolled. See the current online version for the latest version.

Cisco has more than 200 offices worldwide. Addresses and phone numbers are listed on the Cisco website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <http://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

© 2024 Cisco Systems, Inc. All rights reserved.