

Report generated: June 2026, PAIA Version 1.5.2
UCSC-C240-M8L
Cisco UCS C240 M8 Rack Server w/ 1x CPU, 1,024 GB Memory and 12x HDDs

PAIA Environmental Impact Analysis


About this Analysis

Cisco uses PAIA (Product Attribute to Impact Algorithm) to conduct streamlined LCA exercises. PAIA was developed by MIT's Material Systems Laboratory to provide a streamlined approach to analyze the GWP of a product throughout its lifecycle. It focuses on key component attributes that are known to have a high environmental impact and is intended to estimate the range of carbon impact of a product class. The intended uses of these tools are to pinpoint the impact of hotspots and to understand the impact of certain reduction strategies on those hotspots.

Results

The following chart provide the numerical results from the PAIA tool reported as the mean. All estimates of environmental impact and/or carbon footprint are uncertain. The unit for global warming potential is in kg CO₂-equivalent. The impact analysis results are quantified by running 10,000 trials in the model populated with key component attribute data. The model's system boundary was from cradle-to-grave. Please refer to the key product attributes in table 1 for more information on data inputs for this analysis.

Mean Product Life
Cycle Emissions =
9,237 +/- 1,414
kg CO₂e



Note: The Product Attribute to Impact Algorithm model, Version 1.4.7, copyright by the ICT Benchmarking collaboration including the Massachusetts Institute of Technology's Materials Systems Laboratory and partners.

Key Product Attributes

Product Attribute	Input
Server Type	Rack
Server Weight	33.37 kg
PSU Rating and Quantity	2,300 W x2
Fan Quantity	6
Number of CPUs	1
Number of HDDs	12
Number of SSDs	2
DRAM Total Capacity	1,024 GB
Location of Server Use	United States
Lifetime of Server	4 years
Annual Typical Energy Consumption	3,993.51 kWh

Additional Information

The PAIA tools were not developed to support comparisons. It is difficult to draw meaningful conclusions when comparing two life cycle assessment results for two fundamental reasons. First, LCA results are strongly influenced by the assumptions made by the analyst; if those assumptions are inconsistent, comparisons are not likely meaningful. Secondly, LCA results have a high degree of inherent uncertainty, and that uncertainty would not be expected to be statistically independent across a set of alternatives being compared.

Disclaimer: Data and other information in this report are estimates and indicative only, based on assumptions and approximations, for particular products and points in time. They are neither predictions, commitments or guarantees of actual outcomes nor intended for purposes other than identifying opportunities to improve the environmental performance of products at various points in their lifecycle. Cisco continues to refine the methodology, modelling, and assumptions. Data and other information are therefore subject to change and uncertainties that are difficult to predict.

Cisco is not responsible for any errors or omissions in connection with the data and other information in this report. They are generated and provided "as is", with no guarantee of completeness, accuracy, or timeliness. They are made available without warranty of any kind, express or implied. In no event will Cisco, its affiliates, partners, agents, or employees be liable for any decision made or action taken in reliance on the Data and other information in this report, or for any consequential, special, or similar damages, even if advised of the possibility of such damages.

Further information on Cisco's approach to Life Cycle Assessments (LCAs) is available at Cisco's Purpose Reporting Hub, at https://www.cisco.com/c/m/en_us/about/csr/esg-hub.html.