

TELETRON INC.

Sep. 2003

cisco@teletron.co.kr
Tel : 02-6245-7600

Teletron Solutions

www.teletron.co.kr



1.

- 1)
- 2)

2.

- 1)
- 2) **Access Point Series**
- 3) **Bridge Series**
- 4)

3.

- 1) ' '
- 2) ,
- 3)
- 4)

4. Q & A

1.

- 가.



1993 6 1

10

73

www.teletron.co.kr

/

1459-2

TELETRON USA
221 Corporate Terrance Corona, California 91719 USA

1.

1993. 6	INC
1994. 10	Efficient Network Inc. (USA) Distributor
1999. 1	, Cable Modem Up-converter
1999. 2	CMTS Solution (,)
1999. 10	ADSL Modem
2000. 4	Powercom Cable Modem Up-converter
2000. 4	Dreamline ADSL Modem
2000. 8	LG ADSL Modem (FLC-D)
2001.06	KT Ntopia Gigabit Switch (BATM)
2001.09	
2001.10	KT NESLOT() (CISCO)
2001.10	(BATM)
2002.01	Hiban Service() (BATM)
2002.01	CISCO Wireless LAN Solution Partner
2002.02	ANYWAY()
2002.02	
2002.06	(ADSL+Wireless LAN)
2002.10	



▪ AP's

- ✓ 1200 Series (802.11b, 802.11a, & Dual-Band)
- ✓ 1100 Series (802.11b, upgradeable to 802.11g)
- ✓ 350 Series (802.11b only)

▪ Bridge's

- ✓ BR350 (802.11b, P2P & P2MP)
- ✓ WGB352 (802.11b, Workgroup Bridge)
- ✓ BR1400 (802.11a, P2P & P2MP)

▪ Wireless Clients

- ✓ 7920 (802.11, Phone)
- ✓ CB20A (802.11a, Card-bus)
- ✓ PCM352 (802.11b, PCMCIA)
- ✓ LMC352 (802.11b, PCMCIA, no antenna)
- ✓ PCI352 (802.11b, PCI Adapter)

- _____
- ✓ IP-700II (MPEG 1/2/4 Supported)

▪ Etc.

- ✓ ACS RADIUS Software, Cisco Works WLSE



2.

- . Access Point Series (AP1100, AP1200)

■ Interface

- ✓ **AP1100 : 802.11b Single Mode (802.11g Module 가)**
- ✓ **AP1200 : 802.11b + 802.11a Simultaneous Dual Mode or 802.11g + 802.11a Simultaneous Dual Mode ()**
- ✓ Maximum 100mW Transmitter
- ✓ Auto Sense 10/100 Ethernet Port
- ✓ Inline Power
- ✓ PowerPC 200MHz, SDRAM 16M, Flash 8M
- ✓ Cisco IOS

■ Security

- ✓ 40, 128bit WEP Key
- ✓ 802.1X, EAP-TLS, EAP-TTLS, PEAP, LEAP Protocol
- ✓ 802.11i TKIP, MIC
- ✓ Rapid Keying, Broadcast Key Rotation
- ✓ **Mini LEAP RADIUS**

■ Management & Function

- ✓ WEB Management, SNMP I, II , Syslog
- ✓ SNTP-Simple Network Time Protocol
- ✓
- ✓ 16 Multiple-SSID, VLAN
- ✓
- ✓ (1, 5, 20, 30, 50, 100mW)



()

2.

Bridge Series (BR350, BR1400)

Interface

- ✓ **BR350 : 802.11b Single Mode (11M)**
BR1400 : 802.11a Single Mode (54M)

✓

BR350 (2.4GHz), BR1400 (5GHz)

✓

BR350 (1, 2, 5.5 11 Mbps), BR1400 (6~9, 12~18, 24~36, 48~54 Mbps)

- ✓ CSMA/CA , Auto Sense 10/100 Ethernet Port, Inline Power

- ✓ Cisco IOS



Security

✓

128-bit WEP

- ✓ AP IEEE 802.1x (EAP RADIUS)

- ✓ 802.1X, EAP-TLS, EAP-TTLS, PEAP, LEAP Protocol , 802.11i TKIP, MIC

- ✓ Rapid Keying, Broadcast Key Rotation

Management & Function

✓

Telnet, HTTP, FTP, TFTP, SNMP I, II , Syslog

- ✓ SNTP-Simple Network Time Protocol , BOOTP DHCP

✓

가 ()

BR350 → 18 miles (28.9 km) @ 11 Mbps 25 miles (40.2 km) @ 2 Mbps

BR1400 → 7.5 miles (13 km) @ 54 Mbps 16 miles (26 km) @ 9 Mbps

✓

2.

(IP-700II)

- ---

 - ✓ 24 (-10 ~55) MPEG-1,2,4
 - Transcoder 가 . , ,
- ---

 - ✓ IP-700 MPEG-1,2,4 / 가 가 , VOD 가 가 , IP Scheduling .
- ---



 - ✓ (Mutil-Rate) 가 ,
- ---

 - 가
 - ✓ 가 , (Transcoding) (Multicast→Unicast)
- ---
- ---





3.

- 가.





3.

(,)



3.



Thank You !



- ()
- www.teletron.co.kr
-
- 1459-2
- : 02-6247-7600
- FAX : 02-6247-7699

www.teletron.co.kr