

Schema der Vault-Anmeldeinformationen

Inhalt

```
{
  "type": "object",
  "properties": {
    "targetIp": {
      "type": "string",
      "description": "IP address or hostname of the target device(s). Supports wildcards (e.g., 5.0.*.*)",
    },
    "credentials": {
      "type": "object",
      "description": "Object containing protocol-specific credentials.",
      "properties": {
        "snmpv2c": {
          "type": "object",
          "description": "SNMPv2c credentials.",
          "properties": {
            "read": {
              "type": "string",
              "description": "SNMP Read Community"
            }
          },
          "required": ["read"]
        },
        "snmpv3": {
          "type": "object",
          "description": "SNMPv3 credentials.",
          "properties": {
            "user": {
              "type": "string",
              "description": "SNMPv3 User"
            },
            "authAlgorithm": {
              "type": "string",
              "description": "Authentication Algorithm (optional)"
            },
            "authPassword": {
              "type": "string",
              "description": "Authentication Password (required if authAlgorithm is provided)"
            },
            "privacyAlgorithm": {
              "type": "string",
              "description": "Privacy Algorithm (optional)"
            },
            "privacyPassword": {
              "type": "string",
              "description": "Privacy Password (required if privacyAlgorithm is provided)"
            }
          },
          "engineId": {
            "type": "string",

```

```

        "description": "SNMP Engine ID (optional)"
    },
    "required": ["user"]
},
"sshv1": {
    "type": "object",
    "description": "SSHv1 credentials.",
    "properties": {
        "user": {
            "type": "string",
            "description": "Username"
        },
        "password": {
            "type": "string",
            "description": "Password (optional if enablePassword is provided)"
        },
        "enableUser": {
            "type": "string",
            "description": "Enable Username (optional)"
        },
        "enablePassword": {
            "type": "string",
            "description": "Enable Password (required if password is not provided)"
        },
        "port": {
            "type": "integer",
            "description": "Port (optional, default = 22)"
        }
    },
    "required": ["user"]
},
"sshv2": {
    "type": "object",
    "description": "SSHv2 credentials.",
    "properties": {
        "user": {
            "type": "string",
            "description": "Username"
        },
        "password": {
            "type": "string",
            "description": "Password (optional if enablePassword is provided)"
        },
        "enableUser": {
            "type": "string",
            "description": "Enable Username (optional)"
        },
        "enablePassword": {
            "type": "string",
            "description": "Enable Password (required if password is not provided)"
        },
        "port": {
            "type": "integer",
            "description": "Port (optional, default = 22)"
        }
    },
    "required": ["user"]
},

```

```
"telnet": {
  "type": "object",
  "description": "Telnet credentials.",
  "properties": {
    "user": {
      "type": "string",
      "description": "Username"
    },
    "password": {
      "type": "string",
      "description": "Password (optional if enablePassword is provided)"
    },
    "enableUser": {
      "type": "string",
      "description": "Enable Username (optional)"
    },
    "enablePassword": {
      "type": "string",
      "description": "Enable Password (required if password is not provided)"
    },
    "port": {
      "type": "integer",
      "description": "Port (optional, default = 23)"
    }
  },
  "required": ["user"]
},
"http": {
  "type": "object",
  "description": "HTTP credentials.",
  "properties": {
    "user": {
      "type": "string",
      "description": "Username (optional)"
    },
    "password": {
      "type": "string",
      "description": "Password (optional)"
    },
    "port": {
      "type": "integer",
      "description": "Port (optional, default = 80)"
    }
  }
},
"https": {
  "type": "object",
  "description": "HTTPS credentials.",
  "properties": {
    "user": {
      "type": "string",
      "description": "Username (optional)"
    },
    "password": {
      "type": "string",
      "description": "Password (optional)"
    },
    "port": {
      "type": "integer",

```

```
        "description": "Port (optional, default = 443)"
      }
    }
  },
  "additionalProperties": false
},
"required": ["targetIp", "credentials"],
"additionalProperties": false
}
```

Informationen zu dieser Übersetzung

Cisco hat dieses Dokument maschinell übersetzen und von einem menschlichen Übersetzer editieren und korrigieren lassen, um unseren Benutzern auf der ganzen Welt Support-Inhalte in ihrer eigenen Sprache zu bieten. Bitte beachten Sie, dass selbst die beste maschinelle Übersetzung nicht so genau ist wie eine von einem professionellen Übersetzer angefertigte. Cisco Systems, Inc. übernimmt keine Haftung für die Richtigkeit dieser Übersetzungen und empfiehlt, immer das englische Originaldokument (siehe bereitgestellter Link) heranzuziehen.