

# Umbrella-Roaming-Client - Dateien und Ordner

## Inhalt

---

[Einleitung](#)

[Windows](#)

[Betriebssystem X](#)

---

## Einleitung

In diesem Dokument wird der Zweck jeder Datei und jedes Ordners beschrieben, die vom Umbrella Roaming Client für Windows und Mac OS X installiert werden. Diese Informationen können verwendet werden, um Ihre Kenntnisse über den Umbrella Roaming Client zu erweitern oder um Ihnen bei defekten Installationen zu helfen.

## Windows

<#root>

Service Name: "Umbrella\_RC"

C:\ProgramData\OpenDNS\ERC\

**beacon-logs\**

Folder containing log files kept by the Umbrella roaming client for troubleshooting and diagnostic

**Upgrades\**

Folder containing temp files when automatically updating to the latest version.

**Config.json**

Contains the unique "Device" and "Origin" ID's specific to this Umbrella roaming client. This file

**OpenDNS\_ERC\_Service.log**

Live log of the Umbrella roaming client's running process. Used for Umbrella troubleshooting.

**OpenDNS\_ERC\_UI.log**

Live log of the Umbrella roaming client's tray icon process. Used for Umbrella troubleshooting.

**OrgInfo.json**

Contains information about the install-time parameters specified during installations, and also co

### **PersistedNicDefaults.json**

A file for storing the DNS settings assigned to a computer before the Umbrella roaming client initialization. We keep the information in this file in order to gracefully restore the network-defined DNS servers.

### **proxy\_whitelist.txt**

The "Internal Domains" list downloaded from the dashboard, as well as DNS Suffixes imported from the local DNS servers. Read more at [Roaming Client: Internal Domains](#).

### **\*Network Connection Name\*-resolv.conf**

Each active Network Interface on the computer will have its own .conf file, (ie: Local Area Connection). These files contain the local DNS servers that belong to which networking interface. These files contain the local DNS servers.

### **RoamingProfile.json**

A file to be used as part of a future feature.

### **sync-latest.json**

The latest copy of the profile information specific to each Umbrella roaming client. Used for Umbrella roaming client synchronization.

### **whitelist.txt**

The "Internal Domains" list downloaded from the Umbrella dashboard which is used by the Umbrella roaming client. It is a temporary file, which is used as a temporary file. Read more at [Roaming Client: Internal Domains](#).

### **C:\Program Files (x86)\OpenDNS\Umbrella Roaming Client\**

### **dnscryptproxy.exe**

In Umbrella Roaming client 3.0 and above, this is the executable used for encrypting, authenticating, and managing DNS traffic.

### **dnscrypt-proxy.exe (deprecated in 2.3)**

Used in Umbrella Roaming client versions before 2.3. It has been superseded by dnscryptproxy.exe.

### **ERCInterface.exe**

The executable used for running the tray icon.

### **UmbrellaDiagnostic.exe**

The built-in diagnostic tool which customers or Support can run for troubleshooting purposes.

### **\*.dll**

Dynamic Load Libraries associated with running different facets of the Umbrella roaming client.

### **ERCInterface.exe.config**

.NET framework configuration file for the ERCInterface.exe executable.

### **ERCSERVICE.exe.config**

.NET framework configuration file for the ERCSERVICE.exe executable.

#### **Logging.config**

Configuration file used for instructing the Umbrella roaming client what to log or not log. Controls

#### **UmbrellaDiagnostic.exe.config**

.NET framework configuration file for the UmbrellaDiagnostic.exe executable.

#### **GetNetStats.bat**

A facilitating script to assist with getting information as part of the Umbrella Diagnostic tool.

## Betriebssystem X

<#root>

/Library/Application Support/OpenDNS Roaming Client

#### **beacon-logs/**

Folder containing log files kept by the Umbrella roaming client for troubleshooting and diagnostic

#### **Updater.plist**

Local configuration data unique to the local installation of the Umbrella roaming client.

#### **com.opendns.osx.DNSCryptProxy.plist**

The configuration file used to set runtime parameters for the dns-updater executable.

#### **dns-updater**

The executable used for encrypting, authenticating, and sending DNS queries. This executable is re

#### **localdomains**

The list of domain names that the Umbrella roaming client treats as local resources and queries the

#### **p12.hash**

Hash file to verify integrity of clientCert.p12 file.

#### **sync-latest.plist**

The latest copy of the profile information specific to each Umbrella roaming client. Used for Umb

#### **erc\_state.plist**

Data that is synced with our API to populate the Umbrella dashboard with information about the Umb

#### **resolv\_orig.conf**

We use this list to keep an ordered list of DNS servers used for Internal DNS resolution. The list  
VPN DNS servers first. These are the DNS servers normally found on the NIC settings which are [hid](#)

**/Library/LaunchDaemons/**

#### **com.opendns.osx.RoamingClientConfigUpdater.plist**

The configuration file for running the Umbrella roaming client.

**/Library/LaunchAgents/**

#### **com.opendns.osx.RoamingClientMenubar.plist**

The configuration file for running the menu bar icon of the Umbrella roaming client.

### Informationen zu dieser Übersetzung

Cisco hat dieses Dokument maschinell übersetzen und von einem menschlichen Übersetzer editieren und korrigieren lassen, um unseren Benutzern auf der ganzen Welt Support-Inhalte in ihrer eigenen Sprache zu bieten. Bitte beachten Sie, dass selbst die beste maschinelle Übersetzung nicht so genau ist wie eine von einem professionellen Übersetzer angefertigte. Cisco Systems, Inc. übernimmt keine Haftung für die Richtigkeit dieser Übersetzungen und empfiehlt, immer das englische Originaldokument (siehe bereitgestellter Link) heranzuziehen.