

Ändern des Wireless-Kanals auf einem Cisco Small Business VoIP-Router

Inhalt

[Einführung](#)

[Wie kann ich den Kanal meines Wireless-Netzwerks auf einem Cisco Small Business VoIP-Router ändern?](#)

[Zugehörige Informationen](#)

[Einführung](#)

Dieser Artikel ist nur einer von mehreren Serien, um Sie bei der Einrichtung, Fehlerbehebung und Wartung von Cisco Small Business-Produkten zu unterstützen.

[F. Wie kann ich den Kanal meines Wireless-Netzwerks auf einem Cisco Small Business VoIP-Router ändern?](#) Antwort:

Viele Wireless-Produkte in den USA werden mit einem Standard-Channel von 6 ausgeliefert, z. B. mit dem Cisco Small Business-Router. Wenn Störungen durch andere Geräte auftreten, wechseln Sie die Kanäle, um diese Störungen zu vermeiden. Um den Kanal zu ändern, den Ihr Wireless-Netzwerk verwendet, rufen Sie die webbasierte Setup-Seite des Routers auf.

Ändern des Kanals des Routers

Schritt 1:

Rufen Sie die webbasierte Setup-Seite des Routers auf. Anweisungen hierzu erhalten Sie [hier](#).

Schritt 2:

Wenn die webbasierte Setup-Seite des Routers angezeigt wird, klicken Sie auf **Wireless**.

Schritt 3:

Suchen Sie nach **Wireless Channel**, und ändern Sie diesen in den gewünschten Kanal. Die empfohlenen Kanäle sind **1**, **6** oder **11**, da sie nicht überlappende Kanäle sind.

The screenshot shows the Linksys web interface. At the top left is the Linksys logo with the text "LINKSYS® A Division of Cisco Systems, Inc.". Below the logo is a navigation bar with tabs: "Setup", "Wireless", "Security", "Access Restrictions", "Applications & Gaming", "Administration", "Status", and "Voice". The "Wireless" tab is selected. Below the navigation bar are sub-tabs: "Basic Wireless Settings", "Wireless Security", "Wireless MAC Filter", and "Advanced Wireless Settings". The "Basic Wireless Settings" sub-tab is active. The main content area is titled "Wireless Settings" and contains the following fields:

- Wireless Network Mode: Disabled (dropdown menu)
- Wireless Network Name (SSID): (text input field)
- Wireless Channel: 1 (dropdown menu)
- Wireless SSID Broadcast: Enable Disabled

Annotations include:

- A yellow box with the text "Click Wireless." and an arrow pointing to the "Wireless" tab.
- A yellow box with the text "Select 1, 6 or 11 then click Save Settings." and an arrow pointing to the "Wireless Channel" dropdown menu.

At the bottom of the page are two buttons: "Save Settings" and "Cancel Changes". On the right side, there is a "Basic Wireless Settings" sidebar with a description: "The Wireless screen allows you to customize data transmission settings. In most cases, the advanced settings on this screen should remain at their default values." and a "More..." link. The Cisco Systems logo is in the bottom right corner.

Schritt 4:

Klicken Sie **Save Settings**.

Zugehörige Informationen

- [Technischer Support und Dokumentation für Cisco Systeme](#)