

Cisco Unified Wireless IP Phone 7921G Multi-Charger

Cisco® Unified Communications Solutions unify voice, video, data, and mobile applications on fixed and mobile networks, delivering a media-rich collaboration experience across business, government agency, and institutional workspaces. These applications use the network as the platform to enhance comparative advantage by accelerating decision time and reducing transaction time. The security, resilience, and scalability of the network enable users in any workspace to easily connect anywhere, anytime, and anyplace, using any media, device, or operating system. Cisco Unified Communications is part of a comprehensive solution that includes network infrastructure, security, wireless, management applications, lifecycle services, flexible deployment and outsourced management options, and third-party applications.

Features

The Cisco Unified Wireless IP Phone 7921G Multi-Charger (Figure 1) is ideal for environments where customers have multiple shifts and need to keep their Cisco Unified Wireless IP Phone 7921G charged throughout the day. The multi-charger can charge up to 6 phones and 6 batteries simultaneously. Its flexible design allows the unit to be either placed on a desk or mounted on the wall to save desk space. Table 1 gives features of the multi-charger, Table 2 gives its specifications, and Table 3 gives certification and compliance information.

Figure 1. Cisco Unified Wireless IP Phone 7921G Multi-Charger



Table 1. Features

Feature	Description
Charging capacity	6 phones and 6 batteries (standard or extended)
Mounting options	Desk or wall mount
Material	Lead and latex free

Table 2. Specifications

Item	Description
Dimensions (H x W x D)	4.4 x 20.7 x 6.8 in. (112 x 525 x 173 mm)
Weight	<ul style="list-style-type: none"> • Multi-charger: 3.4 lb (1.5 kg) • Power supply: 1.1 lb (0.5 kg) • Mounting bracket: 2.2 lb (1 kg) • Total weight: 6.7 lb (3 kg)
Power supply	<ul style="list-style-type: none"> • Input: 100–240V, 2A, 50/60 Hz • Output: 19V, 5.26A • AC adapters (by geographical region)
Power consumption	100 watts
Operating temperature	32 to 104°F (0 to 40°C)
Storage temperature	–22 to 140°F (–30 to 60°C)
Relative humidity	10 to 95% (noncondensing)
Drop specification	2.5 ft (75 cm) to concrete
Vibration	1.5 Grms maximum, 0.1" double amplitude @0.887 octaves per minute from 5-500-5 Hz sweep, 10-minute dwell on three major peaks, in each of the three major mutually perpendicular axes
Thermal shock	–22°F (–30°C) 24 hours; 158°F (70°C) 24 hours
Charging time	<ul style="list-style-type: none"> • Standard battery only: 3.5 hours • Extended battery only: 5 hours • Phone with standard battery: 3 hours • Phone with extended battery: 4.5 hours

Table 3. Safety and Compliance

Item	Description
Safety	<ul style="list-style-type: none"> • UL 60950-1 • CSA 22.2 No. 60950-1 • EN 60950 • IEC 60950-1 • AS/NZS 60950-1
Electromagnetic compatibility (EMC) and electromagnetic interference (EMI)	<ul style="list-style-type: none"> • CFR 47 Part 15 Class A • ICES-003 Class A • EN 55022 Class A • CISPR 22 Class A • VCCI Class A • AS/NZS CISPR22 • CSPR 24 • EN 55024 • EN 50082-1 • EN 61000-6-1 • EN 61000-3-2 • EN 61000-3-3 • EN 61000-4-2 • EN 61000-4-3 • EN 61000-4-4 • EN 61000-4-5 • EN 61000-4-6 • EN 61000-4-11

Ordering Information

Table 4 gives ordering information for the Cisco Unified Wireless IP Phone 7921G Multi-Charger.

Table 4. Ordering Information

Part Number	Description
CP-MCHGR-7921G-BUN	Cisco Unified Wireless IP Phone 7921G Multi-Charger bundle (includes multi-charger, power supply, and AC power cord)
CP-MCHGR-7921G=	Cisco Unified Wireless IP Phone 7921G Multi-Charger spare
CP-PWR-MC7921G=	Cisco Unified Wireless IP Phone 7921G Multi-Charger power supply spare
CAB-AC2AUS=	AC power cord for Australia spare
CAB-AC2E=	AC power cord for Europe spare
CAB-AC2J=	AC power cord for Japan spare
CAB-AC2=	AC power cord for North America spare
CAB-AC2UK=	AC power cord for United Kingdom spare
CAB-AC2CHI=	AC power cord for China spare

Warranty

The Cisco Unified Wireless IP Phone 7921G Multi-Charger is covered by a Cisco standard 1-year replacement warranty. A Cisco SMARTnet[®] optional service agreement is available.

Cisco Unified Communications Services and Support

Using the Lifecycle Services approach, Cisco and its partners offer a broad portfolio of end-to-end services to support the Cisco Unified Communications System. These services are based on proven methodologies for deploying, operating, and optimizing IP communications solutions. Upfront planning and design services, for example, can help you meet aggressive deployment schedules and minimize network disruption during implementation. Operate services reduce the risk of communications downtime with expert technical support, and optimize services enhance solution performance for operational excellence. Cisco and its partners offer a system-level service and support approach that can help you create and maintain a resilient, converged network that meets your business needs.



Americas Headquarters
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 527-0883

Asia Pacific Headquarters
Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Europe Headquarters
Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: +31 0 800 020 0791
Fax: +31 0 20 357 1100

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

©2007 Cisco Systems, Inc. All rights reserved. CCVP, the Cisco logo, and the Cisco Square Bridge logo are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networking Academy, Network Registrar, PIX, ProConnect, ScriptShare, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0708R)