

Cisco Virtualization Experience Client 6215

Product Overview

Cisco® Virtualization Experience Client 6215 (VXC 6215) is a secure, reliable thin client designed to easily integrate into your virtualized infrastructure (Figure 1). When delivered with the Cisco Virtualization Experience Media Engine (VXME), it unifies voice, video, and virtual desktop all in one device.

When you implement the Cisco VXC 6215 as part of the Cisco Virtualization Experience Infrastructure (VXI) Smart Solution, you can provide a superior virtual workspace experience that is collaborative, mobile, and secure for all your users.

Cisco VXC 6215 is ideal for many work environments such as contact centers, shared workspaces, and telework environments. When Cisco VXC is delivered with Cisco VXME, users are able to access secure virtual desktops with integrated voice and video.

Figure 1. Cisco Virtualization Experience Client 6215



Features and Benefits

- Offers a secure, reliable thin client validated and supported as part of Cisco VXI Smart Solution
- Offers a platform for voice and video using Jabber® for Windows running in a virtualized desktop when implemented with Cisco VXME
- Uses a SUSE Linux-based platform that supports Citrix High-Definition Experience (HDX), Independent Computing Architecture (ICA), PC over IP (PCoIP), and Microsoft Remote Desktop Protocol (RDP) hosted virtual desktop protocols in basic virtual desktop infrastructure (VDI) mode

Compatibility

Cisco VXC 6215 products are certified as Citrix Ready and HDX Ready.

For additional information, please refer to:

<http://www.citrix.com/ready/en/cisco-systems/cisco-vxc-6215>.

Cisco VXC 6215 products are certified as VMware Ready for VMware View Clients.

For additional information, please refer to:

<http://www.vmware.com/resources/compatibility/search.php?action=base&deviceCategory=vdm>.

Product Specifications

Figure 2 shows front and rear views of the Cisco VXC 6215. Table 1 lists hardware specifications for the Cisco VXC 6215.

Figure 2. Cisco VXC 6215



Table 1. Hardware Specifications

Item	Description
Processor	<ul style="list-style-type: none">• Dual-core AMD G-T56N 1.6-GHz processor with AMD Radeon HD 6310 graphics
Memory	<ul style="list-style-type: none">• 4 GB of flash memory and 2 GB of RAM
I/O peripheral support	<ul style="list-style-type: none">• One DisplayPort port• Optional DisplayPort-to-DVI-I adapter available• One DVI-I port• DVI-I to VGA (DB-15) adapter included<ul style="list-style-type: none">◦ Six USB ports:<ul style="list-style-type: none">◦ Four USB 2.0 ports (2 on front and 2 on rear)◦ Two SuperSpeed USB 3.0[†] ports on rear (backward compatible with USB 2.0)
Networking	<ul style="list-style-type: none">• 10/100/1000 Gigabit Ethernet
Display	<ul style="list-style-type: none">• VESA monitor support with display data control (DDC) for automatic setting of resolution and refresh rate• DisplayPort: 2560 x 1600 at 32 bits per pixel (bpp)• DVI-I: 1920 x 1200 at 32 bpp• Dual display: 1920 x 1200 at 32 bpp

[†] USB 3.0 ports support audio-video devices (such as cameras, headsets, and handsets) in the current release 9.0.

Item	Description
Audio	<ul style="list-style-type: none"> • Output: 1/8-in. mini-jack, full 16-bit stereo, 48-KHz sample rate, audio out, and internal monaural speaker • Input: 1/8-in. mini-jack and 8-bit stereo microphone
Physical characteristics (H x W x D)	<ul style="list-style-type: none"> • 7.87 x 1.85 x 8.85 in. (200 x 47 x 225 mm)
Unit and shipping weight	<ul style="list-style-type: none"> • Unit weight: <ul style="list-style-type: none"> ◦ Cisco VXC 6215: 2.4 lb (1.08 kg) ◦ Stand: 0.2 lb (0.09 kg) ◦ Power adapter: 0.5 lb (0.22 kg) ◦ DVI-I-VGA adapter: 0.1 lb (0.04 kg) ◦ U.S. power cord: 0.3 lb (0.13 kg) • Shipping weight: 6 lb (2.7 kg)
Mountings	<ul style="list-style-type: none"> • Vertical feet standard • Optional VESA mounting bracket (sold separately as Cisco accessory)
Device security	<ul style="list-style-type: none"> • Built-in Kensington security slot (cable sold separately)
Power source	<ul style="list-style-type: none"> • Worldwide autosensing 100 to 240 VAC at 50 to 60 Hz
Power consumption	<ul style="list-style-type: none"> • Under 15W (average)
Temperature range	<ul style="list-style-type: none"> • Operating: 32 to 104°F (10 to 40°C); horizontal and vertical positions • Storage: 14 to 140°F (-10 to 60°C)
Humidity	<ul style="list-style-type: none"> • 20-80% relative humidity (operational) • 20-80% relative humidity (storage)
Safety certifications	<ul style="list-style-type: none"> • German EKI-ITB 2000, ISO 9241-3/-8 cULus 60950, TV-GS, EN 60950 FCC Class B, CE, VCCI, and C-Tick • WEEE, CAN ICES-003 Class B, Korea KN22/KN24, Taiwan BSMI, Russia Gost, and China CCC • RoHS-compliant
Warranty	<ul style="list-style-type: none"> • Three-year limited hardware warranty <p>More details: http://www.cisco-servicefinder.com/warrantyfinder.aspx</p>

Software Specifications

Table 2 lists software specifications for the Cisco VXC 6215.

Table 2. Software Specifications

Item	Description
Operating system	<ul style="list-style-type: none"> • SUSE Linux Enterprise Thin Client 11 SP2
Hosted virtual desktop Protocol support for Basic VDI Mode	<ul style="list-style-type: none"> • Citrix XenDesktop • Citrix XenApp • VMware View • RDP (via VMware View Client) <p>Please refer to the Release Notes for the latest VDI support information</p>
Cisco Unified Communications Manager and soft-client support (Version 8.7)	<ul style="list-style-type: none"> • CUPC 8.5x, 8.6 • CUCIMOC 8.5.x, 8.6.1 • CUCILync 8.5.x, 8.6.1 <p>Please refer to the VXME data sheet for the latest UC support information</p>
Security setup and configuration	<ul style="list-style-type: none"> • SUSE Linux standard security: <ul style="list-style-type: none"> ◦ INI-based configuration ◦ Cisco VXC Manager support ◦ Optional add-ons

Item	Description
Network protocol support	<ul style="list-style-type: none"> • TCP/IP, Domain Name System (DNS), Dynamic Host Configuration Protocol (DHCP), Preboot Execution Environment (PXE), FTP, HTTP, and Secure HTTP (HTTPS)
Management	<ul style="list-style-type: none"> • Remote management, configuration, and upgrades through Cisco VXC Manager • Complete image upgrade • Wake terminal remotely (wake-on LAN) • Terminal configuration (IP information, name, etc.) • INI support

Accessories Specifications

Table 3 lists supported accessories for the Cisco VXC 6215.

Table 3. Accessories Support

Item	Description
Headsets	<ul style="list-style-type: none"> • Refer to VXME: Cisco Approved Audio & Video Accessories Datasheet
Cameras	<ul style="list-style-type: none"> • Refer to VXME: Cisco Approved Audio & Video Accessories Datasheet
I/O devices	<ul style="list-style-type: none"> • Refer to VXME: Cisco Approved Audio & Video Accessories Datasheet
Display adapters	<ul style="list-style-type: none"> • DisplayPort-to-DVI-D adapter (sold separately as Cisco accessory) • DisplayPort-to-VGA adapter (sold separately as Cisco accessory) • DisplayPort-to-HDMI adapter (sold separately as Cisco accessory)

Ordering Information

Table 4 provides ordering information. To place an order, visit the Cisco Ordering homepage and refer to Table 4. To download software, visit the Cisco Software Center.

Table 4. Ordering Information

Product Name	Part Number
CVXC-6215-S-BDL=	Cisco VXC 6215 Tower- Smoke Bundle

Cisco Services

Cisco Services makes networks, applications, and the people who use them work better together.

Today, the network is a strategic platform in a world that demands better integration of people, information, and ideas. The network works better when services and products together create solutions aligned with business needs and opportunities.

The unique Cisco Lifecycle approach to services defines the requisite activities at each phase of the network lifecycle to help ensure service excellence. With a collaborative delivery methodology that joins the forces of Cisco, our skilled network of partners, and our customers, we achieve the best results.

For More Cisco VXC Product Information

- <http://www.cisco.com/go/vxc>
- [Design Zone for Cisco VXI](#)



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

 Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)