

Cisco MDS 9000 Family Multiprotocol Services Module

PRODUCT OVERVIEW

Cisco MDS 9000 Family Multiprotocol Services Module

The Cisco MDS 9000 Family Multiprotocol Services Module delivers the intelligence and advanced features required to make multilayer storage area networks a reality. Supported in the Cisco MDS 9200 Series and Cisco MDS 9500 Series and offering fourteen Fibre Channel ports and two Gigabit Ethernet ports, the Cisco Multiprotocol Services Module enables FCIP for long distance SAN extension and iSCSI for Ethernet attached servers without sacrificing Fibre Channel port density. With its multiprotocol capability, the module also integrates FICON protocol, FICON Control Unit Port (CUP) management and switch cascading to enable mainframe connectivity.

The Cisco Multiprotocol Services Module includes hardware-enabled innovations designed to dramatically improve scalability, availability, network security, and manageability of storage networks, resulting in increased utility and lower total cost of ownership (TCO). Hardware-assisted compression and encryption on the Gigabit Ethernet ports ensure optimal utilization of available IT infrastructure and highly reliable and secure data exchange.

The module is hot-swappable and includes hot-swappable, Small Form-Factor Pluggable (SFP), LC interfaces for both Fibre Channel and Gigabit Ethernet. Individual ports can be configured with short-wave, long-wave, or extended-reach SFPs for connectivity up to 100 kilometers. The Gigabit Ethernet interfaces are configurable for both FCIP and iSCSI operation; the ports designated to work as FCIP can be further configured to support up to three virtual ISL connections.

Figure 1. The Cisco MDS 9000 Family Multiprotocol Services Module



KEY FEATURES AND BENEFITS

The Cisco® MDS 9000 Family Multiprotocol Services Module is designed for mission-critical enterprise storage networks that require robust, cost-effective business continuance services. Leveraging Fibre Channel and Internet Protocol (IP) in a single module, Cisco MDS 9000 Family Multiprotocol Services Module offers the following key features:

- **Integrated Fibre Channel and IP Storage Services in an optimized form factor**—Supports fourteen 2-Gbps Fibre Channel interfaces for high performance SAN and mainframe connectivity and two Gigabit Ethernet ports for Fibre Channel over IP (FCIP) and Small Computer System Interface over IP (iSCSI) storage services.
- **Integrated hardware-based VSANs and Inter-VSAN Routing (IVR)**—Enables deployment of large-scale multisite and heterogeneous SAN topologies. Integration into port-level hardware allows any port within a system or fabric to be partitioned into any VSAN. Integrated hardware-based inter-VSAN routing provides line-rate routing between any ports within a system or fabric without the need for external routing appliances.
- **High performance Inter-Switch Links (ISLs)**—Supports up to sixteen 2-Gbps Fibre Channel links in a single PortChannel-links may span any speed-matched ports on any module within a chassis for added scalability and resilience. Up to 3500 buffer-to-buffer credits can be assigned to a single Fibre Channel port to extend storage networks over unprecedented distances.
- **Intelligent network services**—Uses virtual SAN (VSAN) technology for hardware-enforced, isolated environments within a single physical fabric; access control lists (ACLs) for hardware-based intelligent frame processing; and advanced traffic management features such as Fibre Channel Congestion Control (FCC) and fabric-wide quality of service (QoS) to facilitate migration from SAN islands to enterprise-wide storage networks.
- **Comprehensive network security framework**—Supports RADIUS and TACACS+, Fibre Channel Security Protocol (FC-SP), Secure File Transfer Protocol (SFTP), Secure Shell (SSH), and Simple Network Management Protocol Version 3 (SNMPv3) implementing Advanced Encryption Standard (AES), VSANs, hardware-enforced zoning, ACLs, and per-VSAN role-based access control. Additionally, the Gigabit Ethernet ports offer IP security (IPsec) authentication, data integrity, and hardware-assisted data encryption for FCIP and iSCSI.
- **Sophisticated diagnostics**—Provides intelligent diagnostics, protocol decoding, and network analysis tools as well as integrated Call Home capability for added reliability, faster problem resolution, and reduced service costs.
- **FCIP for remote SAN extension:**
 - Simplifies data protection and business continuance strategies by enabling backup, remote replication, and other disaster recovery services over WAN distances using open-standard FCIP tunneling.
 - Optimizes utilization of WAN resources for backup and replication by tunneling up to three virtual ISLs on a single Gigabit Ethernet port, and enabling hardware-based compression, FCIP Write Acceleration, and FCIP Tape Acceleration.
 - Preserves Cisco MDS 9000 Family enhanced capabilities including VSANs, advanced traffic management, and security across remote connections.
- **iSCSI for extension of SAN to Ethernet attached servers:**
 - Extends the benefits of Fibre Channel SAN-based storage to Ethernet attached servers at a lower cost than possible using Fibre Channel interconnect alone.
 - Increases storage utilization and availability through consolidation of IP and Fibre Channel block storage.
 - Transparent operation preserves the capability of existing management storage applications.

FCIP for Remote SAN Extension

Data distribution, data protection, and business continuance services are significant components of today's information-centric businesses. The ability to efficiently replicate critical data on a global scale not only ensures a higher level of data protection for valuable corporate information, but also increases utilization of backup resources and lowers total cost of storage ownership. The Cisco MDS 9000 Family Multiprotocol Services Module uses the open-standard FCIP protocol to break the distance barrier of current Fibre Channel solutions and enable interconnection of SAN islands over extended distances.

Advanced SAN Extension Features

The Cisco MDS 9000 Family Multiprotocol Services Module supports FCIP compression to maximize the effective WAN bandwidth of SAN extension solutions. The Cisco MDS 9000 Family Multiprotocol Services Module achieves up to a 30:1 compression ratio, with typical ratios of 2:1 over a wide variety of data sources. With the addition of hardware-based compression, the MDS 9000 Family Multiprotocol Services Module is able to provide optimal levels of compressed throughput for implementations across both low-bandwidth and high-bandwidth links.

The Cisco MDS 9000 Family Multiprotocol Services Module supports IPsec encryption for secure transmission of sensitive data over extended distances. Hardware enablement of IPsec ensures high throughput. Used together, hardware-based compression and hardware-based encryption provide high performance, highly secure SAN extension capability.

Additionally, the MDS 9000 Family Multiprotocol Services Module supports FCIP Write Acceleration, a feature that can significantly improve application performance when storage traffic is extended across distance. When FCIP Write Acceleration is enabled, WAN throughput is optimized by reducing the latency of command acknowledgments. Similarly, the Cisco MDS 9000 Family Multiprotocol Services Module supports FCIP Tape Acceleration, which significantly improves throughput over WAN links for remote tape backup operations.

Virtual SANs

Ideal for efficient, secure SAN consolidation, VSANs allow more efficient storage network utilization by creating hardware-based isolated environments with a single physical SAN fabric or switch. Each VSAN can be zoned as a typical SAN and maintains its own fabric services for added scalability and resilience. VSANs allow the cost of SAN infrastructure to be shared among more users, while ensuring absolute segregation of traffic and retaining independent control of configuration on a VSAN-by-VSAN basis.

Integrated SAN Routing

In another step toward deploying efficient, cost-effective, consolidated storage networks, the Cisco MDS 9000 Family Multiprotocol Services Module supports IVR, the industry's first routing functionality for Fibre Channel. IVR allows selective transfer of data between specific initiators and targets on different VSANs while maintaining isolation of control traffic within each VSAN. With IVR, data can transit VSAN boundaries while maintaining control plane isolation, thereby maintaining fabric stability and availability. Integrated IVR eliminates the need for external routing appliances, greatly increasing routing scalability while delivering line-rate routing performance, simplifying management, and eliminating the challenges associated with maintaining separate systems. Integrated IVR means lower total cost of SAN ownership.

Integrated Mainframe Support

The Cisco MDS 9000 Family Multiprotocol Services Module is mainframe-ready with full support for IBM zSeries FICON and Linux environments. Qualified by IBM for attachment to all FICON-enabled devices in an IBM zSeries operating environment, Multiprotocol Services Module supports transport of the FICON protocol in both cascaded and non-cascaded fabrics, as well as an intermix of FICON and open systems Fibre Channel Protocol traffic on the same switch. Virtual SANs simplify intermix of SAN resources between z/OS, mainframe Linux, and open systems environments, allowing for increased SAN utilization and simplified SAN management. VSAN-based intermix mode eliminates the uncertainty and instability often associated with zoning-based intermix techniques. VSANs also greatly reduce the probability of a misconfiguration or a component failure in one VSAN affecting operation in other VSANs. VSAN-based management access control simplifies partitioning of SAN management responsibilities between mainframe and open systems environments, enhancing security. FICON VSANs can be managed using the integrated Cisco Fabric Manager, Cisco CLI, or IBM CUP-enabled management tools including SA/390 Resource Measurement Facility (RMF), or Dynamic Channel Path Management (DCM).

Advanced Traffic Management

The following advanced traffic management capabilities integrated into every Cisco MDS 9000 Family Multiprotocol Services Module simplify deployment and optimization of large-scale fabrics.

- **Virtual Output Queuing**—Helps ensure line-rate performance on each port, independent of traffic pattern, by eliminating head-of-line blocking.
- **255 buffer-to-buffer credits**—Are assigned to each port for optimal bandwidth utilization across distance. When extended distances are required, up to 3500 credits can be allocated to a single port within a group of four Fibre Channel ports.
- **PortChannels**—Allow users to aggregate up to 16 physical ISLs into a single logical bundle, providing optimized bandwidth utilization across all links. The bundle can consist of any speed-matched ports from any module in the chassis, ensuring that the bundle can remain active even in the event of a module failure.
- **Fabric Shortest Path First (FSPF)-based multipathing**—Provides the intelligence to load balance across up to 16 equal cost paths and, in the event of a switch failure, dynamically reroute traffic.
- **QoS**—Can be used to manage bandwidth and control latency, to prioritize critical traffic.
- **Fibre Channel Congestion Control (FCC)**—Is an end-to-end, feedback-based congestion control mechanism that augments the Fibre Channel buffer-to-buffer credit mechanism to provide enhanced traffic management.

Advanced Diagnostics and Troubleshooting Tools

Management of large-scale storage networks requires proactive diagnostics, tools to verify connectivity and route latency, and mechanisms for capturing and analyzing traffic. The Cisco MDS 9000 Family integrates the industry's most advanced analysis and diagnostic tools. Power-on self test (POST) and online diagnostics provide proactive health monitoring. The Cisco MDS 9000 Family Multiprotocol Services Module implements diagnostic capabilities such as Fibre Channel Traceroute for detailing the exact path and timing of flows and Switched Port Analyzer (SPAN) to intelligently capture network traffic. Once traffic has been captured, it can then be analyzed with the Cisco Fabric Analyzer, an embedded Fibre Channel analyzer. Comprehensive port-based and flow-based statistics facilitate sophisticated performance analysis and service-level agreement (SLA) accounting. With the Cisco MDS 9000 Family, Cisco Systems® delivers the most comprehensive toolset for troubleshooting and analysis of storage networks.

Comprehensive Solution for Robust Network Security

Addressing the need for failproof security in storage networks, the Cisco MDS 9000 Family Multiprotocol Services Module offers an extensive security framework to protect highly sensitive data crossing today's enterprise networks. The Cisco Multiprotocol Services Module employs intelligent packet inspection at the port level, including the application of ACLs for hardware enforcement of zones, VSANs, and advanced Port Security features.

Extended zoning capabilities are enabled to ensure that LUNs are accessible only by specific hosts (LUN zoning), to limit SCSI read command for a certain zone (read-only zoning), and to restrict broadcasts to only the selected zones (broadcast zones). VSANs are used to achieve higher security and greater stability by providing complete isolation among devices that are connected to the same physical SAN. In addition, Fibre Channel Security Protocol (FC-SP) provides switch-switch and host-switch Diffie-Hellman Challenge Handshake Authentication Protocol (DH-CHAP) authentication supporting RADIUS or TACACS+, to ensure that only authorized devices access protected storage networks. Finally, for both FCIP and iSCSI deployments, the comprehensive IPsec protocol suite delivers secure authentication, data integrity, and hardware-based encryption.

PRODUCT SPECIFICATIONS

Table 1 lists the product specifications for the Cisco MDS 9000 Family Multiprotocol Services Module.

Table 1. Product Specifications

Feature	Description
Product Compatibility	<ul style="list-style-type: none"> • Cisco MDS 9000 Family
Software Compatibility	<ul style="list-style-type: none"> • Cisco MDS SAN-OS Release 2.0(1) or later
Protocols	<ul style="list-style-type: none"> • Fibre Channel standards <ul style="list-style-type: none"> – FC-PH, Revision 4.3 (ANSI/INCITS 230-1994) – FC-PH, Amendment 1 (ANSI/INCITS 230-1994/AM1 1996) – FC-PH, Amendment 2 (ANSI/INCITS 230-1994/AM2-1999) – FC-PH-2, Revision 7.4 (ANSI/INCITS 297-1997) – FC-PH-3, Revision 9.4 (ANSI/INCITS 303-1998) – FC-PI, Revision 13 (ANSI/INCITS 352-2002) – FC-PI-2, Revision 10 (ANSI/INCITS 404-2006) – FC-FS, Revision 1.9 (ANSI/INCITS 373-2003) – FC-FS-2, Revision 0.92 – FC-LS, Revision 1.2 – FC-AL, Revision 4.5 (ANSI/INCITS 272-1996) – FC-AL-2, Revision 7.0 (ANSI/INCITS 332-1999) – FC-AL-2, Amendment 1 (ANSI/INCITS 332-1999/AM1-2003) – FC-AL-2, Amendment 2 (ANSI/INCITS 332-1999/AM2-2006) – FC-SW-2, Revision 5.3 (ANSI/INCITS 355-2001) – FC-SW-3, Revision 6.6 (ANSI/INCITS 384-2004) – FC-SW-4, Revision 7.5 (ANSI/INCITS 418-2006) – FC-GS-3, Revision 7.01 (ANSI/INCITS 348-2001) – FC-GS-4, Revision 7.91 (ANSI/INCITS 387-2004) – FC-GS-5, Revision 8.2 – FC-BB, Revision 4.7 (ANSI/INCITS 342-2001) – FC-BB-2, Revision 6.0 (ANSI/INCITS 372-2003) – FC-BB-3, Revision 6.8 (ANSI/INCITS 414-2006) – FCP, Revision 12 (ANSI/INCITS 269-1996) – FCP-2, Revision 8 (ANSI/INCITS 350-2003) – FCP-3, Revision 4 (ANSI/INCITS 416-2006) – FC-SB-2, Revision 2.1 (ANSI/INCITS 349-2001) – FC-SB-3, Revision 1.6 (ANSI/INCITS 374-2003) – FC-VI, Revision 1.84 (ANSI/INCITS 357-2002) – FC-FLA, Revision 2.7 (INCITS TR-20-1998)

Feature	Description
	<ul style="list-style-type: none"> - FC-PLDA, Revision 2.1 (INCITS TR-19-1998) - FC-Tape, Revision 1.17 (INCITS TR-24-1999) - FC-MI, Revision 1.92 (INCITS TR-30-2002) - FC-MI-2, Revision 2.6 (INCITS TR-39-2005) - FC-SP, Revision 1.74 - FC-DA, Revision 3.1 (INCITS TR-36-2004) - FAIS, Revision 0.7 • IP over Fibre Channel (RFC 2625) • IPv6, IPv4 and ARP over FC (RFC 4338) • Extensive IETF-standards based TCP/IP, SNMPv3, and remote monitoring (RMON) MIBs • Class of Service: Class 2, Class 3, Class F • Fibre Channel standard port types: E, F, FL, B • Fibre Channel enhanced port types: SD, ST, TE • IP standards <ul style="list-style-type: none"> - RFC 791 IPv4 - RFC 793, 1323 TCP - RFC 894 IP/Ethernet - RFC 1041 IP/802 - RFC 792, 950, 1256 ICMP - RFC 1323 TCP performance enhancements - RFC 2338 VRRP - RFC 2460, 4291 IPv6 - RFC 2463 ICMPv6 - RFC 2461, 2462 IPv6 neighbor discovery and stateless auto-configuration - RFC 2464 IPv6/Ethernet - RFC 3270 iSCSI - RFC 3643, 3821 FCIP • Ethernet standards <ul style="list-style-type: none"> - IEEE 802.3z Gigabit Ethernet - IEEE 802.1Q VLAN • IPsec <ul style="list-style-type: none"> - RFC 2401 Security Architecture for IP - RFC 2403, 2404 HMAC - RFC 2405, 2406, 2451 IP ESP - RFC 2407, 2408 ISAKMP - RFC 2412 OAKLEY Key Determination Protocol - RFC 3566, 3602, 3686 AES • Internet Key Exchange (IKE)

Feature	Description
	<ul style="list-style-type: none"> - RFC 2409 IKEv1 - IKEv2, draft
Cards/Ports/Slots	<ul style="list-style-type: none"> • Fourteen fixed auto-sensing 1/2-Gbps Fibre Channel ports and two fixed 1 Gbps Ethernet ports
Features and Functions	
Fabric Services	<ul style="list-style-type: none"> • Name server <ul style="list-style-type: none"> - Internet Storage Name Server (iSNS) - Registered State Change Notification (RSCN) - Login services - Fabric Configuration Server (FCS) - iSCSI Network Boot (iNBP) - Private loop - Public loop - Translative loop - Broadcast - In-order delivery
Advanced Functionality	<ul style="list-style-type: none"> • VSAN • Inter-VSAN Routing • PortChannel with Multipath Load Balancing • QoS-flow-based, zone-based • Fibre Channel Congestion Control • Extended Buffer-To-Buffer Credits • Hardware-based FCIP compression • Hardware-based Encryption • Hardware-based Data Integrity • FCIP Write Acceleration • FCIP Tape Acceleration
Diagnostics and Troubleshooting Tools	<ul style="list-style-type: none"> • Power-on-self-test (POST) diagnostics • Online diagnostics • Internal port loopbacks • SPAN and Remote SPAN • Fibre Channel Traceroute • Fibre Channel Ping • Fibre Channel Debug • Cisco Fabric Analyzer • Syslog • Online system health • Port-level statistics • Real Time Protocol Debug

Feature	Description
Network Security	<ul style="list-style-type: none"> • VSANs • Access Control Lists • Per-VSAN role-based access control • Fibre Channel Zoning <ul style="list-style-type: none"> – N_Port WWN – N_Port FC-ID – Fx_Port WWN – Fx_Port WWN and interface index – Fx_Port domain ID and interface index – Fx_Port domain ID and port number – LUN – Read-only – Broadcast • iSCSI zoning <ul style="list-style-type: none"> – iSCSI name – IP address • Fibre Channel Security Protocol (FC-SP) <ul style="list-style-type: none"> – DH-CHAP switch-switch authentication – DH-CHAP host-switch authentication • Port Security and Fabric Binding • IPsec for FCIP and iSCSI • IKEv1 and IKEv2 • Management access <ul style="list-style-type: none"> – SSH v2 implementing AES – SNMPv3 implementing AES – SFTP
FICON	<ul style="list-style-type: none"> • FC-SB-3 Compliant • Cascaded FICON fabrics • Intermix of FICON and Fibre Channel FCP traffic • CUP management interface
Serviceability	<ul style="list-style-type: none"> • Configuration file management • Non-disruptive software upgrades for Fibre Channel interfaces • Call Home • Power-management LEDs • Port beaconing • System LED

Feature	Description																																				
	<ul style="list-style-type: none"> • SNMP traps for alerts • Network boot 																																				
Performance	<ul style="list-style-type: none"> • Port speed: 1/2-Gbps auto-sensing, optionally configurable • Buffer credits: Up to 3500 per port • PortChannel: Up to 16 2 Gbps ports • FCIP tunnels: up to 3 per port • Supported optics, media, and transmission distances: <table border="1" data-bbox="483 625 1393 1129"> <thead> <tr> <th data-bbox="488 632 829 659">Optics</th> <th data-bbox="834 632 1214 659">Media</th> <th data-bbox="1219 632 1388 659">Distance</th> </tr> </thead> <tbody> <tr> <td data-bbox="488 665 829 693">1 Gbps—SW, LC SFP</td> <td data-bbox="834 665 1214 693">50/125 micron multimode</td> <td data-bbox="1219 665 1388 693">500 m</td> </tr> <tr> <td data-bbox="488 699 829 726">1 Gbps—SX, LC SFP</td> <td data-bbox="834 699 1214 726">50/125 micron multimode</td> <td data-bbox="1219 699 1388 726">550 m</td> </tr> <tr> <td data-bbox="488 732 829 760">1 Gbps—SW, LC SFP</td> <td data-bbox="834 732 1214 760">62.5/125 micron multimode</td> <td data-bbox="1219 732 1388 760">300 m</td> </tr> <tr> <td data-bbox="488 766 829 793">1-Gbps—SX, LC SFP</td> <td data-bbox="834 766 1214 793">62.5/125 micron multimode</td> <td data-bbox="1219 766 1388 793">275 m</td> </tr> <tr> <td data-bbox="488 800 829 827">1 Gbps—LW, LC SFP</td> <td data-bbox="834 800 1214 827">9/125 micron single-mode</td> <td data-bbox="1219 800 1388 827">10 km</td> </tr> <tr> <td data-bbox="488 833 829 861">1 Gbps—LX/LH, LC SFP</td> <td data-bbox="834 833 1214 861">9/125 or 10/125 micron single-mode</td> <td data-bbox="1219 833 1388 861">10 km</td> </tr> <tr> <td data-bbox="488 867 829 894">1 Gbps—CWDM, LC SFP</td> <td data-bbox="834 867 1214 894">9/125 micron single-mode</td> <td data-bbox="1219 867 1388 894">Up to 100 km</td> </tr> <tr> <td data-bbox="488 900 829 928">2 Gbps—SW, LC SFP</td> <td data-bbox="834 900 1214 928">50/125 micron multimode</td> <td data-bbox="1219 900 1388 928">300 m</td> </tr> <tr> <td data-bbox="488 934 829 961">2 Gbps—SW, LC SFP</td> <td data-bbox="834 934 1214 961">62.5/125 micron multimode</td> <td data-bbox="1219 934 1388 961">10 km</td> </tr> <tr> <td data-bbox="488 968 829 995">2 Gbps—LW, LC SFP</td> <td data-bbox="834 968 1214 995">9/125 micron single-mode</td> <td data-bbox="1219 968 1388 995">150 m</td> </tr> <tr> <td data-bbox="488 1001 829 1029">2 Gbps—CWDM, LC SFP</td> <td data-bbox="834 1001 1214 1029">9/125 micron single-mode</td> <td data-bbox="1219 1001 1388 1029">Up to 100km</td> </tr> </tbody> </table> 	Optics	Media	Distance	1 Gbps—SW, LC SFP	50/125 micron multimode	500 m	1 Gbps—SX, LC SFP	50/125 micron multimode	550 m	1 Gbps—SW, LC SFP	62.5/125 micron multimode	300 m	1-Gbps—SX, LC SFP	62.5/125 micron multimode	275 m	1 Gbps—LW, LC SFP	9/125 micron single-mode	10 km	1 Gbps—LX/LH, LC SFP	9/125 or 10/125 micron single-mode	10 km	1 Gbps—CWDM, LC SFP	9/125 micron single-mode	Up to 100 km	2 Gbps—SW, LC SFP	50/125 micron multimode	300 m	2 Gbps—SW, LC SFP	62.5/125 micron multimode	10 km	2 Gbps—LW, LC SFP	9/125 micron single-mode	150 m	2 Gbps—CWDM, LC SFP	9/125 micron single-mode	Up to 100km
Optics	Media	Distance																																			
1 Gbps—SW, LC SFP	50/125 micron multimode	500 m																																			
1 Gbps—SX, LC SFP	50/125 micron multimode	550 m																																			
1 Gbps—SW, LC SFP	62.5/125 micron multimode	300 m																																			
1-Gbps—SX, LC SFP	62.5/125 micron multimode	275 m																																			
1 Gbps—LW, LC SFP	9/125 micron single-mode	10 km																																			
1 Gbps—LX/LH, LC SFP	9/125 or 10/125 micron single-mode	10 km																																			
1 Gbps—CWDM, LC SFP	9/125 micron single-mode	Up to 100 km																																			
2 Gbps—SW, LC SFP	50/125 micron multimode	300 m																																			
2 Gbps—SW, LC SFP	62.5/125 micron multimode	10 km																																			
2 Gbps—LW, LC SFP	9/125 micron single-mode	150 m																																			
2 Gbps—CWDM, LC SFP	9/125 micron single-mode	Up to 100km																																			
Reliability and Availability	<ul style="list-style-type: none"> • Hot-swappable module • Hot-swappable SFP optics • Online diagnostics • Stateful Process Restart • Non-disruptive Supervisor Failover • Any module, any port configuration for PortChannels • Fabric-based multipathing • Per-VSAN fabric services • Port Tracking • Virtual Routing Redundancy Protocol (VRRP) for management and FCIP or iSCSI connections 																																				
Network Management	<ul style="list-style-type: none"> • Access methods through Cisco MDS 9500 Series Supervisor module <ul style="list-style-type: none"> – Out-of-band 10/100 Ethernet port (Supervisor-1 Module) – Out-of-band 10/100/1000 Ethernet port (Supervisor-2 Module) – RS-232 serial console port – In-band IP-over-Fibre Channel – DB-9 COM port • Access protocols <ul style="list-style-type: none"> – CLI-via console and Ethernet ports 																																				

Feature	Description
	<ul style="list-style-type: none"> – SNMPv3-via Ethernet port and in-band IP-over-Fibre Channel access – Storage Networking Industry Association (SNIA) Storage Management Initiative Specification (SMI-S) • Distributed Device Alias service • Network security <ul style="list-style-type: none"> – Per-VSAN role-based access control using RADIUS and TACACS+ based authentication, authorization, and accounting (AAA) functions – SFTP – SSH v2 implementing AES – SNMPv3 implementing AES • Management applications <ul style="list-style-type: none"> – Cisco MDS 9000 Family CLI – Cisco Fabric Manager – Cisco Device Manager – CiscoWorks Resource Manager Essentials (RME) and Device Fault Manager (DFM)
Programming Interfaces	<ul style="list-style-type: none"> • Scriptable CLI • Fabric Manager GUI • Device Manager GUI
Environmental	<ul style="list-style-type: none"> • Temperature, ambient operating: –32 to 104°F (0 to 40°C) • Temperature, ambient non-operating and storage: –40 to 167°F (–40 to 75°C) • Relative humidity, ambient (non-condensing) operating: 10 to 90 percent • Relative humidity, ambient (non-condensing) non-operating and storage: 10 to 95 percent • Altitude, operating: –197 to 6500 feet (-60 to 2000 meter)
Physical Dimensions	<ul style="list-style-type: none"> • Dimensions (H x W x D): 1.75 x 14.4 x 16 inches (3.0 x 35.6 x 40.6 centimeter) <ul style="list-style-type: none"> – Occupies one slot in a Cisco MDS 9200 Series or MDS 9500 Series chassis • Weight: Multiprotocol Services Module only: 10 pound (4.5 kilogram)
Approvals and Compliance	<ul style="list-style-type: none"> • Safety compliance <ul style="list-style-type: none"> – CE Marking – UL 60950 – CAN/CSA-C22.2 No. 60950 – EN 60950 – IEC 60950 – TS 001 – AS/NZS 3260 – IEC60825 – EN60825 – 21 CFR 1040 • EMC compliance <ul style="list-style-type: none"> – FCC Part 15 (CFR 47) Class A

Feature	Description
	<ul style="list-style-type: none"> – ICES-003 Class A – EN 55022 Class A – CISPR 22 Class A – AS/NZS 3548 Class A – VCCI Class A – EN 55024 – EN 50082-1 – EN 61000-6-1 – EN 61000-3-2 – EN 61000-3-3

ORDERING INFORMATION

Table 2 provides ordering information for the Cisco MDS 9000 Family Multiprotocol Services Module.

Table 2. Ordering Information

Part Number	Product Description
DS-X9302-14K9	Cisco MDS 9000 Family 14/2-port Multiprotocol Services Module
DS-SFP-FC-2G-SW	Cisco MDS 9000 Family 1/2-Gbps Fibre Channel—Shortwave, SFP, LC
DS-SFP-FC-2G-LW	Cisco MDS 9000 Family 1/2-Gbps Fibre Channel—Longwave, SFP, LC
DS-SFP-FCGE-SW	Cisco MDS 9000 Family 1 Gbps Ethernet, 1/2-Gbps Fibre Channel—Shortwave, SFP, LC
DS-SFP-FCGE-LW	Cisco MDS 9000 Family 1 Gbps Ethernet, 1/2-Gbps Fibre Channel—Longwave, SFP, LC
Advanced Software Packages	
M9200EXT12K9	Cisco MDS 9200 SAN Extension over IP Package for the Cisco MDS 9000 Family Multiprotocol Services Module
M9200ENT1K9	Cisco MDS 9200 Enterprise Package
M9200FMS1K9	Cisco MDS 9200 Fabric Manager Server Package
M9200FIC1K9	Cisco MDS 9200 Mainframe Package
M9500EXT12K9	Cisco MDS 9500 SAN Extension over IP Package for the Cisco MDS 9000 Family Multiprotocol Services Module
M9500ENT1K9	Cisco MDS 9500 Enterprise Package
M9500FMS1K9	Cisco MDS 9500 Fabric Manager Server Package
M9500FIC1K9	Cisco MDS 9500 Mainframe Package
Spare Components	
DS-X9302-14K9=	Cisco MDS 9000 Family 14/2-port Multiprotocol Services Module, Spare
DS-SFP-FC-2G-SW=	Cisco MDS 9000 Family 1/2-Gbps Fibre Channel—Shortwave, SFP, LC, Spare
DS-SFP-FC-2G-LW=	Cisco MDS 9000 Family 1/2-Gbps Fibre Channel—Longwave, SFP, LC, Spare
DS-SFP-FCGE-SW=	Cisco MDS 9000 Family 1 Gbps Ethernet, 1/2-Gbps Fibre Channel—Shortwave, SFP, LC, Spare
DS-SFP-FCGE-LW=	Cisco MDS 9000 Family 1 Gbps Ethernet, 1/2-Gbps Fibre Channel—Longwave, SFP, LC, Spare
DS-CWDM-1470=	Cisco 1470 NM CWDM Gigabit Ethernet and 1/2-Gbps Fibre Channel SFP, Spare

Part Number	Product Description
DS-CWDM-1490=	Cisco 1490 NM CWDM Gigabit Ethernet and 1/2-Gbps Fibre Channel SFP, Spare
DS-CWDM-1510=	Cisco 1510 NM CWDM Gigabit Ethernet and 1/2-Gbps Fibre Channel SFP, Spare
DS-CWDM-1530=	Cisco 1530 NM CWDM Gigabit Ethernet and 1/2-Gbps Fibre Channel SFP, Spare
DS-CWDM-1550=	Cisco 1550 NM CWDM Gigabit Ethernet and 1/2-Gbps Fibre Channel SFP, Spare
DS-CWDM-1570=	Cisco 1570 NM CWDM Gigabit Ethernet and 1/2-Gbps Fibre Channel SFP, Spare
DS-CWDM-1590=	Cisco 1590 NM CWDM Gigabit Ethernet and 1/2-Gbps Fibre Channel SFP, Spare
DS-CWDM-1610=	Cisco 1610 NM CWDM Gigabit Ethernet and 1/2-Gbps Fibre Channel SFP, Spare
M9200EXT12K9=	Cisco MDS 9200 SAN Extension over IP Package for the Cisco MDS 9000 Family Multiprotocol Services Module, Spare
M9200ENT1K9=	Cisco MDS 9200 Enterprise Package, Spare
M9200FMS1K9=	Cisco MDS 9200 Fabric Manager Server Package, Spare
M9200FIC1K9=	Cisco MDS 9200 Mainframe Package, Spare
M9500EXT12K9=	Cisco MDS 9500 SAN Extension over IP Package for the Cisco MDS 9000 Family Multiprotocol Services Module, Spare
M9500ENT1K9=	Cisco MDS 9500 Enterprise Package, Spare
M9500FMS1K9=	Cisco MDS 9500 Fabric Manager Server Package, Spare
M9500FIC1K9=	Cisco MDS 9500 Mainframe Package, Spare

SERVICE AND SUPPORT

Cisco offers a wide range of services programs to accelerate customer success. These innovative services programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you to protect your network investment, optimize network operations, and prepare the network for new applications to extend network intelligence and the power of your business. For more information about Cisco Services, see [Cisco Technical Support Services](#) or [Cisco Advanced Services](#).

FOR MORE INFORMATION

For more information about the Cisco MDS 9000 Family Multiprotocol Services Module, visit <http://www.cisco.com/en/US/products/hw/ps4159/ps4358/index.html> or contact your local account representative.

**Corporate Headquarters**

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

European Headquarters

Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: 31 0 20 357 1000
Fax: 31 0 20 357 1100

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-7660
Fax: 408 527-0883

Asia Pacific Headquarters

Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on **the Cisco Website at www.cisco.com/go/offices.**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel
Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal
Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan
Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright 2006 Cisco Systems, Inc. All rights reserved. CCSP, CCVP, the Cisco Square Bridge logo, Follow Me Browsing, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, the Networkers logo, Networking Academy, Network Registrar, Packet, PIX, Post-Routing, Pre-Routing, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0601R)

