

# Cisco 100GBASE QSFP-100G Modules

## Product Overview

The Cisco® 100GBASE Quad Small Form-Factor Pluggable (QSFP) portfolio offers customers a wide variety of high-density and low-power 100 Gigabit Ethernet connectivity options for data center, high-performance computing networks, enterprise core and distribution layers, and service provider applications. The QSFP-100G modules are our new generation of 100G transceiver modules solution based on a QSFP form factor. (See Figure 1.)

**Figure 1.** QSFP-100G Optical Modules



## Features and Benefits of Cisco QSFP Modules

- Hot-swappable input/output device that plugs into a 100G Gigabit Ethernet Cisco QSFP port
- Interoperable with other IEEE-compliant 100GBASE interfaces where applicable
- Certified and tested on Cisco QSFP-100G ports for superior performance, quality, and reliability
- High-speed electrical interface compliant to IEEE 802.3bm

Table 1 describes the Cisco QSFP-100G portfolio.

**Table 1.** Cisco QSFP-100G Portfolio

Product	Description	Connector Type
<b>QSFP-100G-SR4-S</b>	100GBASE SR4 QSFP Transceiver, MPO, 100m over OM4 MMF	MPO-12 (12 fibers)
<b>QSFP-100G-LR4-S</b>	100GBASE LR4 QSFP Transceiver, LC, 10km over SMF	LC
<b>QSFP-100G-ER4L-S</b>	100GBASE QSFP Transceiver, 25-40KM reach over SMF, Duplex LC	LC
<b>QSFP-100G-CWDM4-S</b>	100GBASE CWDM4 QSFP Transceiver, LC, 2km over SMF	LC
<b>QSFP-100G-PSM4-S</b>	100GBASE PSM4 QSFP Transceiver, MPO, 500m over SMF	MPO-12 (12 fibers)
<b>QSFP-100G-SM-SR</b>	100GBASE CWDM4 Lite QSFP Transceiver, 2km over SMF, 10-60C	LC
<b>QSFP-100G-CU(1M, 2M, 3M, 5M)</b>	100GBASE-CR4 Passive Copper Cable	
<b>QSFP-4SFP25G-CU(1M, 2M, 3M)</b>	100GBASE QSFP to 4xSFP25G Passive Copper Splitter Cables	
<b>QSFP-100G-AOC (1M, 2M, 3M, 5M, 7M, 10M, 15M, 20M, 25M, 30M)</b>	100GBASE QSFP Active Optical Cables	

## Cisco QSFP-100G-SR4-S

The Cisco 100GBASE-SR4-S QSFP Module supports link lengths of up to 70m (100m) over OM3 (OM4) Multimode Fiber with MPO connectors. It primarily enables high-bandwidth 100G optical links over 12-fiber parallel fiber terminated with MPO multifiber connectors. QSFP-100G-SR4-S supports 100GBase Ethernet rate.

## Cisco QSFP-100G-LR4-S

The Cisco 100GBASE-LR4-S QSFP Module supports link lengths of up to 10km over a standard pair of G.652 single-mode fiber with duplex LC connectors. The 100 Gigabit Ethernet signal is carried over four wavelengths. Multiplexing and demultiplexing of the four wavelengths are managed within the device. QSFP-100G-LR4-S supports 100GBase Ethernet rate.

## Cisco QSFP-100G-ER4L-S

The Cisco QSFP100 ER4-Lite supports link lengths of up to 40km over a standard pair of G.652 single-mode fiber with duplex LC connectors. The 100 Gigabit Ethernet signal is carried over four wavelengths. Multiplexing and demultiplexing of the four wavelengths are managed within the device. Full 40km reach requires the use of FEC on the host platform. Without FEC, the reach is 30km. The QSFP100 ER4-Lite provides backward compatibility with Cisco's CPAK ER4-Lite, whose reach is up to 25km, and with IEEE 100GBASE-ER4 standardized transceivers, such as Cisco's CFP 100G ER4, up to 30km. It also interoperates with Cisco's QSFP100 and CPAK IEEE 100GBASE-LR4 modules up to 10km.

**Table 2.** Interoperability matrix for QSFP-100G-ER4L-S.

Interoperability matrix	QSFP-100G-ER4L-S with host FEC	CFP-100G-ER4 (IEEE 100GBASE-ER4)	QSFP-100G-ER4L-S (no FEC)	CPAK-100G-ER4L	CPAK-100G-LR4 QSFP-100G-LR4-S
QSFP-100G-ER4L-S with host FEC	40km				
CFP-100G-ER4 (IEEE 100GBASE-ER4)	x	40km			
QSFP-100G-ER4L-S (no FEC)	x	30km	30km		
CPAK-100G-ER4L	x	25km	25km*	25km	
CPAK-100G-LR4 QSFP-100G-LR4-S	x	10km	10km	10km	10km

\* Maximum connector insertion loss 1.5dB.

## Cisco QSFP-100G-CWDM4-S

The Cisco QSFP-100G-CWDM4-S Module supports link lengths of up to 2 km over a standard pair of G.652 Single-Mode Fiber (SMF) with duplex LC connectors. The 100 Gigabit Ethernet signal is carried over four wavelengths. Multiplexing and demultiplexing of the four wavelengths are managed within the device.

## Cisco QSFP-100G-PSM4-S

The Cisco QSFP-100G-PSM4-S Module supports link lengths of up to 500 meters over SMF with MPO connectors. The 100 Gigabit Ethernet signal is carried over 12-fiber parallel fiber terminated with MPO multifiber connectors.

---

## Cisco QSFP-100G-SM-SR

The Cisco QSFP-100G-SM-SR QSFP module supports link lengths of up to 2 kilometers over a standard pair of G.652 Single-Mode Fiber (SMF) with duplex LC connectors. The 100 Gigabit Ethernet signal is carried over four wavelengths. Multiplexing and demultiplexing of the four wavelengths are managed within the device. The operating temperature range is from +10 to +60°C with an optical link budget of 4.2 decibels. This 4.2-decibel link budget offers the ability to support the loss from patch panels in the link in a data center environment. QSFP-100G-SM-SR is interoperable with QSFP-100G-CWDM4-S.

## Cisco QSFP-4SFP25G-CUxM

Cisco QSFP-100G to four SFP-25G copper direct-attach breakout cables (Figure 2) are suitable for very short links and offer a cost-effective way to connect within racks and across adjacent racks. These breakout cables connect to a 100G QSFP port of a Cisco switch on one end and to four 25G SFP ports of a Cisco switch/server on the other end. Cisco currently offers passive cables in lengths of x=1, 2 and 3 meters.

**Figure 2.** QSFP-4SFP25G-CUxM Cables



## Cisco QSFP-100G-CUxM

Cisco QSFP to QSFP copper direct-attach 100GBASE-CR4 cables (Figure 3) are suitable for very short links and offer a cost-effective way to establish a 100-Gigabit link between QSFP-100G ports of Cisco switches within racks and across adjacent racks. Cisco currently offers passive copper cables in lengths of x=1, 2, 3 and 5 meters.

**Figure 3.** QSFP-100G-CU1M Cables



## Cisco QSFP-100G-AOCxM

Cisco QSFP-100G to QSFP-100G AOC cables (Figure 4) are suitable for short distances and offer a flexible way to connect within racks and across racks. Active optical cables are much thinner and lighter than copper cables, which makes cable management easier. AOCs enable efficient system airflow, which is critical in high-density racks. Cisco currently offers active optical cables in lengths of x=1, 2, 3, 5, 7, 10, 15, 20, 25, and 30 meters.

**Figure 4.** QSFP-100G-AOC3M Cables



## Technical Specifications

### Platform Support

Cisco QSFP modules are supported on Cisco switches and routers. For more details, refer to the [Cisco 100 Gigabit Ethernet Transceiver Modules Compatibility Matrix](#).

### Connectors and Cabling

Refer to Table 3 for connector type information and cabling specifications for each QSFP product.

**Table 3.** QSFP Port Cabling Specifications

Cisco QSFP	Nominal Wavelength (nm)	Cable Type	Core Size (Microns)	Modal Bandwidth (MHz·km) <sup>1</sup>	Cable Distance	Power Consumption (W)	Pull Tab Color		
QSFP-100G-SR4-S	850	MMF	50.0 50.0	2000 (OM3) 4700 (OM4)	70m 100m	3.5	Beige		
QSFP-100G-LR4-S	1295, 1300, 1304, 1309	SMF	G.652	-	10km	3.5	Blue		
QSFP-100G-ER4L-S	1295, 1300, 1304, 1309	SMF	G.652	-	40km (with host FEC) 30km (without host FEC)	4.5	Red		
QSFP-100G-CWDM4-S	1271, 1291, 1311, 1331	SMF	G.652	-	2km	3.5	Green		
QSFP-100G-PSM4-S	1310	SMF	G.652	-	500m	3.5	Orange		
QSFP-100G-SM-SR	1271, 1291, 1311, 1331	SMF	G.652	-	2km	3.5	Green		
QSFP-100G-CU1M	-	Direct-attach copper cable assembly	-	-	1m	1.5	Beige		
QSFP-100G-CU2M	-		-	-	2m		Brown		
QSFP-100G-CU3M	-		-	-	3m		Orange		
QSFP-100G-CU5M	-		-	-	5m		Gray		
QSFP-4SFP25G-CU1M	-		-	-	1m		Beige		
QSFP-4SFP25G-CU2M	-		-	-	2m		Brown		
QSFP-4SFP25G-CU3M	-		-	-	3m		Orange		
QSFP-100G-AOC1M	-		Active optical cable assembly	-	-		1m	3.5	Beige
QSFP-100G-AOC2M	-			-	-		2m		Brown
QSFP-100G-AOC3M	-			-	-		3m		Orange
QSFP-100G-AOC5M	-	-		-	5m	Gray			
QSFP-100G-AOC7M	-	-		-	7m	Blue			
QSFP-100G-AOC10M	-	-		-	10m	Red			

Cisco QSFP	Nominal Wavelength (nm)	Cable Type	Core Size (Microns)	Modal Bandwidth (MHz km) <sup>1</sup>	Cable Distance	Power Consumption (W)	Pull Tab Color
QSFP-100G-AOC15M	-		-	-	15m		Black
QSFP-100G-AOC20M	-		-	-	20m		Green
QSFP-100G-AOC25M	-		-	-	25m		Green
QSFP-100G-AOC30M	-		-	-	30m		Green

<sup>1</sup> Specified at transmission wavelength.

Table 4 shows the key optical characteristics for the Cisco QSFP modules.

**Table 4.** Optical Characteristics

Product	Descriptions	Transmit Power (dBm) per lane <sup>2</sup>		Receive Power (dBm) per lane <sup>2,3</sup>		Transmit and Receive Wavelength (nm)
		Maximum	Minimum	Maximum	Minimum	
QSFP-100G-SR4-S	100GBASE SR4 QSFP Transceiver, MPO, 100m over OM4 MMF	+2.4	-8.4	+2.4	-10.3	840 to 860
QSFP-100G-LR4-S	100GBASE LR4 QSFP Transceiver, LC, 10km over SMF	+4.5	-4.3	4.5	-10.6	Four lanes: 1295, 1300, 1304, 1309
QSFP-100G-ER4L-S <sup>4</sup>	100GBASE QSFP Transceiver, 25-40KM reach over SMF, Duplex LC	+4.5	+0.6	-4.9	-16.4 (with FEC) -13.75 (without FEC)	Four lanes: 1295, 1300, 1304, 1309
QSFP-100G-CWDM4-S	100GBASE CWDM4 QSFP Transceiver, LC, 2km over SMF	+2.5	-6.5	+2.5	-11.5	Four lanes: 1271, 1291, 1311, 1331
QSFP-100G-PSM4-S	100GBASE PSM4 QSFP Transceiver, MPO, 500m over SMF	+2.0	-9.4	+2	-12.66	1295 to 1325
QSFP-100G-SM-SR	100GBASE CWDM4 Lite QSFP Transceiver, 2km over SMF, 10-60C	+2.5	-6.9	+2.5	-11.1	Four lanes: 1271, 1291, 1311, 1331

<sup>2</sup> Transmitter and receiver power is average optical power, unless specified.

<sup>3</sup> Optical power at RX is informative only. A received power within this range is required but does not ensure operation.

<sup>4</sup> Minimum channel insertion loss is 6.4dB for QSFP-100G-ER4L-S.

## Dimensions

Maximum outer dimensions for the QSFP connector module are (H x W x D) 13.5 x 18.4 x 72.4 mm.

Cisco QSFP connector modules typically weigh 100 grams or less.

## Environmental Conditions

Operating temperature range:

- Commercial temperature range: 0 to 70°C (32 to 158°F). Exceptions are
  - QSFP-100G-SM-SR: +10 to 60°C (50 to 140°F)
- Storage temperature range: -40 to 85°C (-40 to 185°F)

## Warranty

- Standard warranty: 90 days

## Ordering Information

Table 5 provides the ordering information for Cisco QSFP 100G modules and related cables.

**Table 5.** Ordering Information

Description	Product Number
<b>QSFP Optics Modules</b>	
Cisco 100GBASE-SR4 QSFP Transceiver, MPO-12, 100m over OM4 MMF	QSFP-100G-SR4-S
Cisco 100GBASE-LR4 QSFP Transceiver, LC, 10km over SMF	QSFP-100G-LR4-S
Cisco 100GBASE QSFP Transceiver, 40KM reach over SMF, Duplex LC	QSFP-100G-ER4L-S
Cisco 100GBASE CWDM4 QSFP Transceiver, LC, 2km over SMF	QSFP-100G-CWDM4-S
Cisco 100GBASE PSM4 QSFP Transceiver, MPO-12, 500m over SMF	QSFP-100G-PSM4-S
Cisco 100GBASE CWDM4 Lite QSFP Transceiver, 2km over SMF, 10-60C	QSFP-100G-SM-SR
<b>QSFP Direct-Attach Copper Modules</b>	
Cisco 100GBASE-CR4 QSFP Passive Copper Cable, 1-meter	QSFP-100G-CU1M
Cisco 100GBASE-CR4 QSFP Passive Copper Cable, 2-meter	QSFP-100G-CU2M
Cisco 100GBASE-CR4 QSFP Passive Copper Cable, 3-meter	QSFP-100G-CU3M
Cisco 100GBASE-CR4 QSFP Passive Copper Cable, 5-meter	QSFP-100G-CU5M
Cisco 100GBase QSFP to 4xSFP25G Passive Copper Splitter Cable, 1-meter	QSFP-4SFP25G-CU1M
Cisco 100GBase QSFP to 4xSFP25G Passive Copper Splitter Cable, 2-meter	QSFP-4SFP25G-CU2M
Cisco 100GBase QSFP to 4xSFP25G Passive Copper Splitter Cable, 3-meter	QSFP-4SFP25G-CU3M
Cisco 100GBase QSFP Active Optical Cable, 1-meter	QSFP-100G-AOC1M
Cisco 100GBase QSFP Active Optical Cable, 2-meter	QSFP-100G-AOC2M
Cisco 100GBase QSFP Active Optical Cable, 3-meter	QSFP-100G-AOC3M
Cisco 100GBase QSFP Active Optical Cable, 5-meter	QSFP-100G-AOC5M
Cisco 100GBase QSFP Active Optical Cable, 7-meter	QSFP-100G-AOC7M
Cisco 100GBase QSFP Active Optical Cable, 10-meter	QSFP-100G-AOC10M
Cisco 100GBase QSFP Active Optical Cable, 15-meter	QSFP-100G-AOC15M
Cisco 100GBase QSFP Active Optical Cable, 20-meter	QSFP-100G-AOC20M
Cisco 100GBase QSFP Active Optical Cable, 25-meter	QSFP-100G-AOC25M
Cisco 100GBase QSFP Active Optical Cable, 30-meter	QSFP-100G-AOC30M

## Regulatory and Standards Compliance

### Standards:

- SFF-8665: QSFP+ 28 Gb/s 4X Pluggable Transceiver Solution (QSFP28) - Rev 1.8 May 10, 2013
- SFF-8636: Common Management Interface - DRAFT Rev 1.9 May 12, 2014
- 802.3™ -2012 IEEE Standard for Ethernet
- IEEE 802.3ba Amendment of IEEE Std 802.3-2012
- IEEE 802.3bm Amendment of IEEE Std 802.3-2012 (D3.1, 1<sup>st</sup> August 2014)
- GR-20-CORE: Generic Requirements for Optical Fiber and Optical Fiber Cable
- GR-326-CORE: Generic Requirements for Single-Mode Optical Connectors and Jumper Assemblies
- GR-468-CORE: Generic Requirements for Optoelectronic Devices Used in Telecommunications Equipment
- GR-1435-CORE: Generic Requirements for Multifiber Optical Connectors
- RoHS 6

## Safety:

- Cable jacket of QSFP copper modules is UL E116441 Compliant
- QSFP copper cables are ELV compliant

**Table 6.** Laser Class for the QSFP-100G Optical Modules

Product	Laser Class
Cisco QSFP-100G-SR4-S	1
Cisco QSFP-100G-LR4-S	1
Cisco QSFP-100G-ER4L-S	1
Cisco QSFP-100G-CWDM4-S	1
Cisco QSFP-100G-PSM4-S	1
Cisco QSFP-100G-SM-SR	1

## Cisco Capital Financing to Help You Achieve Your Objectives

Cisco Capital<sup>®</sup> financing can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx. Accelerate your growth. Optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries.

[Learn more.](#)

## Additional Information

For more information about Cisco 100GBASE QSFP optics and copper modules, contact your sales representative or visit [https://www.cisco.com/en/US/products/hw/modules/ps5455/prod\\_module\\_series\\_home.html](https://www.cisco.com/en/US/products/hw/modules/ps5455/prod_module_series_home.html).



**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)