

# Cisco 100GBASE CFP2 Modules

## Product Overview

The Cisco® 100GBASE CFP2 modules offer customers 100 Gigabit Ethernet connectivity options for data center networking, enterprise core aggregation, and service provider transport applications.

## Features and Benefits

Main features of Cisco 100GBASE CFP2 modules include:

- Supports 100GBASE Ethernet and OTU3 rates.
- Hot-swappable input-output device that plugs into an Ethernet CFP2 port of a Cisco switch or router
- Provides flexibility of interface choice
- Supports “pay-as-you-populate” model
- Supports digital optical monitoring (DOM)
- Supports the Cisco quality identification (ID) feature, which enables a Cisco switch to identify whether the module is certified and tested by Cisco

## Cisco CFP2-100G-ER4

The Cisco 100GBASE-ER4 (Figure 1) CFP2 module can support link lengths up to 40 kilometers on standard duplex single-mode fiber (SMF, G.652) terminated with LC optical connectors. The 100 Gigabit Ethernet signal is carried over four wavelengths. Multiplexing and demultiplexing of the four wavelengths are managed within the device. The Cisco 100GBASE-ER4 CFP2 module meets the IEEE 802.3ba requirements for 100GBASE-ER4 performance and also supports DOM of the transmit-and-receive optical signal levels.

**Figure 1.** Cisco CFP2-100G-ER4



## Technical Specifications

### Platform Support

Cisco CFP2 modules are supported on Cisco switches and routers. For more details, refer to the document [Cisco 100-Gigabit Ethernet Transceiver Modules Compatibility Matrix](#).

### Connectors and Cabling

Connectors: dual LC connector.

**Note:** Only connections with patch cords with physical contact (PC) or ultraphysical contact (UPC) connectors are supported. Patch cords with APC connectors are not supported. All cables and cable assemblies used must be compliant with the standards specified in the standards section.

Table 1 provides cabling specifications for the Cisco CFP2 modules.

**Table 1.** CFP2 Port Fiber Specifications

Cisco CFP2	Wavelength (nm)	Fiber Type	Core Size (microns)	Modal Bandwidth (MHz-km) <sup>***</sup>	Max Distance <sup>*</sup>	Digital Optical Monitoring (DOM)
Cisco CFP2-100G-ER4	1310 band (LAN-WDM)	SMF	G.652	-	40 km <sup>****</sup>	Yes

<sup>\*\*\*</sup> Specified at transmission wavelength.

<sup>\*\*\*\*</sup> Links longer than 30 km for the same link power budget are considered engineered links. Attenuation for such links needs to be less than the worst case specified for single-mode fiber.

Table 2 shows the main optical characteristics.

**Table 2.** CFP2 Port Fiber Specifications

Product	Type	Average Transmit Power (dBm)		Average Receive Power (dBm)		Transmit and Receive Wavelength
		Max	Min	Max	Min	
Cisco CFP2-100G-ER4	100GBASE-ER4 1310 nm SMF	2.9 per lane	-2.9 per lane	4.5 per lane	-20.9 per lane	Four lanes: 1295.6 nm, 1300.1 nm, 1304.6 nm, and 1309.1 nm

### Dimensions

- Dimensions (D x W x H): 144.8 x 82 x 13.6 mm.
- Cisco CFP2 modules typically weigh less than 300 grams.

### Environmental Conditions and Power Requirements

- The operating temperature range is from 32 to 158°F (0 to 70°C).
- The storage temperature range is -40 to 185° F (-40 to 85° C).
- The maximum power consumption per Cisco CFP2-100G-ER4 module is 8W.

### Warranty

- Standard warranty: 90 days.
- Extended warranty (optional): Cisco CFP2 modules can be covered in a Cisco SMARTnet<sup>®</sup> Service support contract for the Cisco switch or router chassis.

Table 3 provides the ordering information for Cisco CFP2 modules and related cables.

**Table 3.** Ordering Cisco CFP2 Modules and Respective Cables

Description	Part Number
Cisco 100GBASE-ER4 CFP2 Module for SMF (<40 km)	CFP2-100G-ER4

## Regulatory and Standards Compliance

### Standards

- GR-20-CORE: Generic Requirements for Optical Fiber and Optical Fiber Cable
- GR-326-CORE: Generic Requirements for Single-Mode Optical Connectors and Jumper Assemblies
- IEEE 802.3ba
- RoHS-6 compliant

### Safety

Table 4 provides safety information.

**Table 4.** Safety Information

Product	Laser Class
Cisco CFP2-100G-ER4	1

## Cisco Capital

### Financing to Help You Achieve Your Objectives

Cisco Capital<sup>®</sup> financing can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx, accelerate your growth, and optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries. [Learn more.](#)

### Additional Information

For more information about Cisco 100GBASE CFP2 modules, contact your sales representative or visit <http://www.cisco.com/go/dcnm>.



Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)