

# Cisco IOS XR Software Release 5.1.0 for Cisco ASR 9000 Series Routers

PB729736

## Product Overview

Cisco® ASR 9000 Series Aggregation Services Routers deliver unprecedented scale, service flexibility, and high availability for service provider fixed and mobile networks, data centers, and transport networks. The routers are powered by Cisco IOS® XR Software, an innovative, self-healing, distributed operating system designed for always-on operation while scaling system capacity into multiple terabits per second (Tbps).

Cisco IOS XR Software Release 5.1.0 expands the existing Cisco ASR 9000 Series portfolio with the introduction of the Cisco ASR 9904 Router. Cisco IOS XR Software Release 5.1.0 also brings to market new features for Carrier Ethernet, Broadband Network Gateways, and enterprise market segments.

## New Hardware Features

Cisco IOS XR Software Release 5.1.0 introduces support for the Cisco ASR 9904 Router, the newest addition to the Cisco ASR 9000 Series portfolio. It delivers up to 8 Tbps of system throughput in a compact 6-RU form factor and supports two slots for route switch processors (RSPs) and two slots for line cards. The Cisco ASR 9904 Router also features the same hardware innovations as other Cisco 9000 Series routers like the Cisco ASR 9922 Router and 9912 Router, with each slot capable of switching up to 2 Tbps of bidirectional traffic.

Table 1 lists the new hardware support added in Cisco IOS XR Software Release 5.1.0.

**Table 1.** New Hardware Supported on Cisco ASR 9000 Series Routers in Cisco IOS XR Software Release 5.1.0

Part Number	Description
<b>ASR-9904-AC</b>	ASR 9904 AC Chassis with PEM V2
<b>ASR-9904-AC=</b>	ASR 9904 AC Chassis with PEM V2 Spare
<b>ASR-9904-DC</b>	ASR 9904 DC Chassis with PEM V2
<b>ASR-9904-DC=</b>	ASR 9904 DC Chassis with PEM V2 Spare
<b>ASR-9904-FAN</b>	ASR-9904 System Fan Tray
<b>ASR-9904-FAN=</b>	ASR-9904 System Fan Tray Spare
<b>ASR-9904-FILTER</b>	ASR-9904 System Fan Filter
<b>ASR-9904-FILTER=</b>	ASR-9904 System Fan Filter Spare
<b>ASR-9904-BAFFLE</b>	ASR-9904 System Baffle
<b>ASR-9904-BAFFLE=</b>	ASR-9904 System Baffle Spare

## New Software Features

Table 2 lists new software features in Cisco IOS XR Software Release 5.1.0 supported on Cisco ASR 9000 Series Aggregation Services Routers.

**Table 2.** New Software Features Supported on Cisco ASR 9000 Series Routers in Cisco IOS XR Software Release 5.1.0

Feature	Description
<b>Broadband network gateway (BNG)</b>	The BNG technology segment introduces a critical feature, an onboard Dynamic Host Configuration Protocol (DHCP) server, including advanced features such as RADIUS-based address allocation. Important manageability features, such as Session Switched Port Analyzer (SPAN), idle timeout, and MIBs, are also introduced in this release.
<b>Ethernet data-plane loopback (DPL)</b>	Service providers widely deploy Ethernet as an access and transport technology. DPL is an operational enhancement simplifying the service activation process. DPL activates loopback on specific traffic types, such as VLAN or class of service (CoS) combinations, and specific MAC addresses, without affecting other users on the same port. New customers' circuits can now be tested from local loop to the central office (CO) without interrupting traffic on other circuits, which traditional physical loopbacks would cause. Cisco IOS XR Software Release 5.1.0 supports external loopback capability in Cisco ASR 9000 Series Routers.
<b>Virtual Private LAN Service-Label Switched Multicast (VPLS-LSM)</b>	VPLS is a widely deployed service provider L2VPN technology that is also used for multicast transport. Although L2 technology allows snooping to be used to optimize replication of multicast traffic into L2 pseudowires, the core remains agnostic to multicast traffic. As a result, multiple copies of the same flow traverse core networks. Pairing LSM with VPLS mitigates this inefficiency by introducing LSM multicast trees over the core. In Cisco IOS-XR Software Release 5.1.0, Cisco ASR 9000 Series Routers implement VPLS LSM with point-to-multipoint traffic engineering (P2MP-TE) inclusive trees. VPLS end points are automatically discovered and P2MP-TE trees are set-up using Resource Reserve Protocol traffic engineering (RSVP-TE), without operational intervention.
<b>Carrier Ethernet</b>	Cisco IOS XR Software Release 5.1.0 allows multiple enhancements in Carrier Ethernet functional area. Multiprotocol Label Switching Transport Profile (MPLS-TP) MIB provides standard SNMP monitoring capabilities to MPLS-TP-based networks. Rapid Per-VLAN Spanning Tree (PVST) brings feature parity with Cisco IOS Software and allows easier integration with next-generation platforms. Layer 2 Sampled Span allows intelligent monitoring of networks where the number of flows can be excessively high by redirecting a sample of packets to an external monitoring device. Storm control bandwidth support enhances previous versions of the implementation, providing the flexibility to configure threshold in packets per second or explicit bandwidth.
<b>Integrated routing and bridging (IRB) features: BFD, MPLS, and mVPN</b>	IRB features continue to be enhanced in Cisco IOS XR Release 5.1.0 with bidirectional forwarding detection (BFD) and MPLS support added. With BFD, customers can monitor multiple Layer 3 end points residing on a single bridge domain by enabling BFD on the IRB interface. MPLS support allows integration of MPLS transport over Layer 2 access technology. Edge devices residing on a Resilient Ethernet Protocol (REP) or G.8032 ring can support MPLS pseudowires over Layer 2 rings. In Cisco IOS XR Release 5.1.0, the feature is supported for Ethernet and TDM pseudowires.
<b>Multi-instance Enhance Interior Gateway Routing Protocol (EIGRP)</b>	Multi-instance EIGRP allows Cisco ASR 9000 Series Routers to be inserted in a high-scale enterprise environment. EIGRP multi-instance provides the ability to create multiple EIGRP processes, each with its own topology and routing table. Each EIGRP process can be used to control routing on different network segments such as dynamic multipoint VPN (DMVPN).
<b>Border Gateway Protocol (BGP) knobs</b>	Resilient per-CE-label allocation: <ul style="list-style-type: none"> <li>Allows eiBGP multipath and BGP prefix-independent convergence (PIC) edge to work with per-CE-label.</li> <li>Before this enhancement, BGP PIC edge and eiBGP multipath was restricted to per-prefix-label.</li> </ul> User-specific Martian list check: <ul style="list-style-type: none"> <li>BGP Martian list includes all bogon prefixes (i.e., 10.0.0.0/8 or 0:0/1) and allows protection against a peering partner announcing a bogon prefix. This list is quite static and well documented by the Internet Society (RIPE, IETF, ARIN, etc.)</li> <li>An ISP may want to add or remove bogon to the standard BGP Martian list, this feature allows the BGP Martian list to be customized.</li> </ul>
<b>Open Shortest Path First (OSPF) enhancements</b>	<ul style="list-style-type: none"> <li>OSPFv3 Graceful Shutdown provides the ability to temporarily shut down an OSPF version 3 (OSPFv3) process or interface in the least disruptive manner and to notify its neighbors that it is going away. A graceful shutdown of a protocol can be initiated on all OSPFv3 interfaces or on a specific interface.</li> <li>OSPFv3 Sham-Link support overcomes the OSPFv3 default behavior for selecting an intra-area backdoor route between VPN sites instead of an interarea (PE-to-PE) route. A sham link helps ensure that OSPFv3 client sites sharing a backdoor link can communicate over the MPLS VPN backbone and participate in VPN services.</li> </ul>
<b>Virtual Router Redundancy Protocol (VRRP) or Hot Standby Router Protocol (HSRP) scale increase</b>	HSRP or VRRP scale is increased to 4K per port, 4K per line card and 4K per system.

## Ordering Information

Table 3 lists ordering information for Cisco IOS XR Software Release 5.1.0 for Cisco ASR 9000 Series Aggregation Services Routers. When future rebuilds of Cisco IOS XR Software Release 5.1.0 are available, the latest release is automatically shipped when this product is ordered.

**Table 3.** Ordering Information for Cisco IOS XR Software Release 5.1.0 for Cisco ASR 9000 Series Aggregation Services Routers

Product Name	Part Number
<b>XR-A9K-PX-05.01</b>	Cisco IOS-XR IP/MPLS Core Software
<b>XR-A9K-PXK9-05.01</b>	Cisco IOS-XR IP/MPLS Core Software 3DES

## Release 5.1.0 Lifecycle

The Cisco IOS XR Software release strategy is time-based, with a fixed release date and lifecycle, rather than being a feature-based release strategy with a variable release date. Table 4 lists the major milestones of Cisco IOS XR Software Release 5.1.0 and later.

**Table 4.** Major Milestones for Cisco IOS XR Software Release 5.1.0

Milestone	Definition	Date
<b>Availability date</b>	The date that Cisco IOS XR Software Release 5.1.0 information is published on Cisco.com and becomes available to the general public.	Sept. 11, 2013
<b>End-of-life announcement date</b>	The date when the official end-of-life documents announcing the end of sale and end of life of Cisco IOS XR Software 5.1 (and later versions of 5.1) are distributed to the general public.	Mar. 11, 2014
<b>End-of-sale date</b>	The last date to order Cisco IOS XR Software 5.1.0 through Cisco point-of-sale mechanisms (The product is no longer for sale after this date.)	Mar. 11, 2015
<b>End of software maintenance</b>	The last date that Cisco Engineering may release any final software maintenance releases or bug fixes (After this date, Cisco Engineering will no longer develop, repair, maintain, or test the product software.)	Sept. 11, 2015
<b>End of software maintenance for Product Security Incident Response Team (PSIRT)</b>	The last date that Cisco Engineering may release any final software maintenance releases or bug fixes for PSIRTs through Software Maintenance Unit to Release 5.1 (Beyond this date, PSIRT bugs become candidates for following feature releases.)	Sept. 11, 2017
<b>Last date of support</b>	The last date to receive applicable service and support for the product, as entitled by active service contracts or by warranty terms and conditions (After this date, all support services for the product are unavailable, and the product becomes obsolete.)	Mar. 11, 2020

## For More Information

For official end-of-life and end-of-sale announcements for Cisco IOS XR Software, please visit [http://www.cisco.com/en/US/products/ps5845/prod\\_eol\\_notices\\_list.html](http://www.cisco.com/en/US/products/ps5845/prod_eol_notices_list.html), or contact your local Cisco account representative.

For more information about the Cisco ASR 9000 Series or Cisco IOS XR Software, visit <http://www.cisco.com/>, or contact your local Cisco account representative.



---

Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

 Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)