

Cisco WVC2300 Wireless-G Business Internet Video Camera with Two-Way Audio

Cisco Small Business Video Surveillance Cameras

High-Quality Wireless Video Surveillance Platform Provides Flexible Installation

Highlights

- Wireless box camera with interchangeable lenses and I/O ports that allow flexible installation for multiple applications
- High-quality CCD sensor with low-light sensitivity and an IR filter switcher provides optimal video image under a range of conditions
- Simultaneous dual codecs provide optimal combination of viewing and storage of video
- Two-way audio, IP multicast, 3GPP (3rd Generation Partnership Project), and lots of other advanced features make this solution ideal for surveillance deployments

Figure 1. Cisco WVC2300 Wireless-G Business Internet Video Camera with Two-Way Audio



Product Overview

Cisco[®] Small Business Video Surveillance products provide customizable ways for small business owners to monitor and protect their companies. These high-quality solutions can be optimized for many different applications and sites. Each camera can be quickly mounted using the bracket included in the package. Their compact form factor also enables the cameras to be put inside a protective enclosure for interior or exterior installations. The cameras use removable CS-mount lenses and can be customized with optional zoom, wide-angle, vari-focal, auto-iris, and other types of lenses as required for a specific application or setting.

The Cisco WVC2300 Wireless-G Business Internet Video Camera (Figure 1) can be mounted on any pan-tilt (PT) base that supports the Pelco D protocol and can be remotely rotated and controlled through an RS-485 interface. It has two input and two output ports, which can be used to connect the camera to an alarm panel, siren, passive infrared (PIR) sensors, smoke detectors, lighting switch (on/off), door sensors, etc.

The Cisco WVC2300 uses a high-quality progressive-scan charge-coupled device (CCD) sensor, delivering good-quality video. The CCD sensor also has low-light sensitivity so video can be captured even in environments with very low light or during near-dark times of day. Additionally, the camera incorporates an infrared (IR) cut filter that, when used with a separate IR lamp, allows for video capture in total darkness.

The Cisco WVC2300 camera supports dual codecs (MPEG-4 and MJPEG). Both codecs can be used simultaneously. MPEG-4 gives efficient bandwidth consumption with good-quality compression and is optimal for real-time viewing of video. MJPEG gives optimal video quality with lossy compression, making it ideal for large-volume storage to a network attached storage (NAS) device.

The Cisco WVC2300's audio capabilities include two-way audio, embedded microphone, external speaker and microphone ports, and voice compression. With extensive feature support, such as IP multicast, Real Time Streaming Protocol (RTSP), Real Time Protocol (RTP), and 3rd Generation Partnership Project (3GPP), it enables video to be viewed from multiple endpoints and client applications such as 3G phones, and QuickTime clients on PCs or Wi-Fi phones. The wireless capabilities of the WVC2300 include support for 1x2 multiple-input, multiple-output (MIMO), providing better range than traditional 802.11g, and strong wireless security utilizing Wi-Fi Protected Access (WPA). Support for multiple network protocols like 802.1p priority, 802.1Q VLANs, and Dynamic DNS (DDNS), make the solution ideal for multiple IP surveillance applications. The cameras can also be managed securely using HTTPS.

Features

- Standard box-type camera allows for flexible installation
- Mounts in a standard outdoor or indoor enclosure
- Provides controls for mounting on a Pelco pan/tilt base to control movement remotely
- Removable CS-mount lens enables the camera to be customized for multiple applications - including zoom lens, wide-angle, vari-focal, and auto-iris lenses
- 1/4-in. progressive-scan CCD sensor delivers good-quality video
- Low-light sensitivity with high-quality lens, sensor, and programmable IR cut filter capability
- Audio input/output for external microphone and/or speaker
- I/O ports facilitate alarm triggers, turn lights on and off, etc.
- IEEE 802.11b/g wireless support with 1x2 MIMO offers better wireless range and coverage
- Dual codecs (MPEG-4 and MJPEG) supported simultaneously
- IP multicast support
- RTSP video/audio streaming to unicast and multicast clients
- 4x digital zoom; can also use optical zoom with appropriate interchangeable lens
- 3GPP allows viewing of video on a mobile device
- Real-Time video recording from the Web interface directly with one button recording

- PC-less event recording directly to Network Attached Storage via integrated Samba client
- Motion detection with event notifications to an email account or alarm log in the monitoring software
- JPEG snapshots at multiple resolutions that can be sent to an FTP server
- Overlay watermarks/graphics and text
- Up to 10 unicast users and unlimited multicast users
- Built-in web server for remote access over IP
- Secure control via HTTPS
- Includes software for monitoring and recording up to 16 cameras simultaneously

Specifications

Table 1 gives the specifications, package contents, and minimum requirements for the Cisco WVC2300 Wireless-G Business Internet Video Camera with Two-Way Audio.

Table 1. Specifications for the Cisco WVC2300 Wireless-G Business Internet Video Camera with Two-Way Audio

| Specifications | |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards | IEEE 802.11g, IEEE 802.11b, IEEE 802.3, IEEE 802.3u, IEEE 802.1p (quality of service [QoS] priority), IEEE 802.1Q (VLAN), IEEE 802.11e (wireless QoS), IEEE 802.11i (security) |
| Protocols supported | TCP/IP, HTTP, Dynamic Host Configuration Protocol (DHCP), Simple Mail Transfer Protocol (SMTP), FTP, Bonjour, Network Time Protocol (NTP), DNS, Universal Plug and Play (UPnP), RTP, RTSP, and DDNS |
| Ports | Ethernet, microphone IN, speaker OUT, power (12V, 1A), general-purpose I/O (GPIO), 4-pin IRIS port, RS-485 Serial Port |
| Buttons | Reset |
| Cabling type | Unshielded twisted pair (UTP) Category 5 |
| LEDs | Power, Network |
| Camera type | Box |
| I/O ports | <ul style="list-style-type: none"> • RS-485 x 1 (2 pins) - supports Pelco D protocol commands • Input control x 2 (2 pins) • Output control x 2 (2 pins) |
| Lens | |
| Sensor | 1/4-in. progressive CCD sensor |
| Illumination | 0.4 LUX at f1.7 |
| Lens type | CS-mount lens, fixed focus; adapter included for lenses that require more distance between sensor and lens |
| Focal length | 500mm–infinity (for included lens) |
| Field of view | 47° Diagonal (for included lens) |
| Video resolution | 640 x 480 (VGA), 320 x 240 (QVGA), 160 x 120 (QQVGA) |
| Frame rate | 1 to 30 frames per second (selectable) |
| Iris | Provides iris control for CS-mount auto-iris lens when attached |
| Setup/Configuration | |
| Web user interface | Built-in web user interface for easy browser-based configuration (HTTP) |
| Management | |
| Web browser | <ul style="list-style-type: none"> • Internet Explorer 5.x or later • Limited support for Netscape and Firefox. Browser controls for pan/tilt/zoom (PTZ), audio, and motion detection are limited or not supported with Netscape and Firefox. |
| Event logging | Event logging (syslog) |
| Web firmware upgrade | Firmware upgradable through web browser |

| Video Compression | |
|-----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dual codec | <ul style="list-style-type: none"> • MPEG-4 simple profile • MJPEG • Simultaneous dual stream |
| Snapshot | JPEG |
| Modulation | National Television System Committee (NTSC) and Phase Alternating Line (PAL) |
| Image settings | Brightness and contrast |
| Zoom | 4x digital zoom |
| Night vision | IR cut filter for low light |
| Video controls | Auto white balance (AWB), auto exposure (AES) |
| Image controls | Select video by quality, bandwidth, and frame rate |
| Format | 3GPP for use with 3G phones |
| Alerts | |
| Motion detection | 4 detection areas with individual sensitivity |
| Email alert | 3 email addresses |
| FTP uploading | FTP server address and login settings |
| Instant messaging | Jabber client support |
| Scheduled | Schedule by time |
| Triggers | Input 1, Input 2, motion detection |
| Actions | Output 1, output 2, messaging, email, FTP |
| Audio | |
| Summary | <ul style="list-style-type: none"> • 2-way audio • Built-in microphone: 6 mm, -40 db + 3 db • Microphone input: 3.5-mm phone jack • Speaker output: 3.5-mm phone jack |
| Compression | G.726: 16 kbps, G.711 A-law and μ -law |
| Sampling rate | 8 kHz |
| Default bit rate | 16 kbps |
| Included Video Monitoring System Software (SWVMS16) | |
| Monitoring/recording software | <ul style="list-style-type: none"> • Monitoring, recording, and playback for up to 16 cameras • Advanced search histogram or by time and date • Recording set up to record by motion trigger, manual, or schedule; recording and playback |
| Security | |
| Wired Equivalent Privacy (WEP)/WPA | WEP 64 bit/128 bit, WPA Temporal Key Integrity Protocol (WPA-TKIP), WPA Pre-Shared Key (WPA-PSK), WPA2-PSK, WPA2-Enterprise |
| User list | User rights list to view video and/or to control camera functions. Multi-level permissions (Administrator, Operator, and Viewer) |
| Username/password | Logon authentication: 20-character username and 8-character password |
| Kensington lock | Physical security option |
| Network | |
| RTP/RTSP | RTP and RTSP allow for viewing from any client supporting these protocols, like 3G phones or QuickTime client |
| NTP | Keeps time of camera in sync with your network |
| SMTP | Allows video clips to be emailed |
| FTP client | Facilitates scheduling transfer of images to an FTP server |
| DDNS | Facilitates reaching the camera by a name irrespective of the camera's IP address. Supports DDNS, TZO, and 3322 DDNS services |
| UPnP | Allows autodiscovery of the camera by other UPnP devices |
| IP filtering | Allow or disallow access by IP address |

| | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------|
| Power | |
| Power options | External power adapter: 12V 1A, 110~120V AC/60 Hz, switching |
| Power consumption | 10W |
| Environmental | |
| Dimensions | 4.72 x 2.99 x 1.81 in. (120 x 76 x 46 mm) |
| Unit weight | 1.15 lb (0.52 kg) |
| Power | External power adapter 12V DC 1A 110~120V AC/60 Hz switching |
| Certification | FCC Part 15C Class B, CE, UL, EMC/EMI Part 15B Class B for US |
| Operating temperature | 32° to 122°F (0° to 50°C) |
| Storage temperature | -4° to 158°F (-20° to 70°C) |
| Operating humidity | 10% to 80% |
| Storage humidity | 0% to 19% |
| Package Contents | |
| <ul style="list-style-type: none"> • Cisco WVC2300 Wireless-G Business Internet Video Camera • Stand kit • Antennas (2) • Power supply (12V 1A) • 6-foot Ethernet cable • Adapter ring to allow for C mount lens • Allen wrench • Quick installation guide • CD including setup wizard, user guide and video monitoring software | |
| Minimum Requirements (Camera) | |
| <ul style="list-style-type: none"> • Wired Ethernet or wireless 802.11b/802.11g network • Network adapter with Ethernet network cable and TCP/IP installed per PC • Switch/router to support multiple connection points • Internet Explorer 6.x or later with ActiveX support for viewing • Microsoft Windows Vista, XP, 2000, ME, or 98SE to support Installation Wizard • 2-GHz Pentium 4 or AMD Athlon-class CPU with 512 MB RAM • 128-MB AGP video adapter | |
| Minimum Video Monitoring System Requirements (4-Camera Viewing) | |
| <p>CPU - Intel Pentium 4, 2.4 GHz</p> <ul style="list-style-type: none"> • RAM - 512 MB • Motherboard - Intel 945 or 965 chip or above; Intel chipset recommended • Video card - ATI Radeon 9200, NVIDIA GeForce FX-5200, or Intel 945G/965G or later; ATI recommended • Ethernet - 100 BASE-T or above; Gigabit LAN recommended • Hard disk - 80 GB or more • Operating system - Microsoft Windows XP Pro Service Pack 2 or Microsoft Vista | |
| Product Warranty | |
| 3-year limited hardware warranty with return to factory replacement and 90-day limited software warranty. | |

Table 2. Camera Upgrade Accessories

| SKU | Description | Camera Compatible | Auto Iris | Lens Types | Manufacturer |
|-----------------------|---------------------------------------------------------|-------------------|-----------|------------|--------------|
| CAMLMI | Camera Lens Tamron 3-8mm Varifocal Manual Iris | PVC/WVC2300 | No | 3-8 mm | Tamron |
| CAMLWA | Camera Lens Computar Wide Angle 2.3mm Fixed Manual Iris | PVC/WVC2300 | No | 2.3 mm | Computar |
| CIVS-IPC-VF31= | IP Camera Fujinon 3-11 mm Varifocal Lens | PVC/WVC2300 | Yes - DC | 3-11mm | Fujinon |
| CIVS-IPC-VT31= | IP Camera Tamron 3-11 mm Varifocal Lens | PVC/WVC2300 | Yes - DC | 3-11mm | Tamron |
| CIVS-IPC-VF38= | IP Camera Fujinon 3-8 mm Varifocal Lens | PVC/WVC2300 | Yes - DC | 3-8 mm | Fujinon |

| | | | | | |
|-----------------------|------------------------------------------|-------------|----------|---------|---------|
| CIVS-IPC-VT38= | IP Camera Tamron 3-8 mm Varifocal Lens | PVC/WVC2300 | Yes - DC | 3-8 mm | Tamron |
| CIVS-IPC-VF55= | IP Camera Fujinon 5-50 mm Varifocal Lens | PVC/WVC2300 | Yes - DC | 5-50 mm | Fujinon |
| CIVS-IPC-VT55= | IP Camera Tamron 5-50 mm Varifocal Lens | PVC/WVC2300 | Yes - DC | 5-50 mm | Tamron |

Cisco Limited Warranty for Cisco Small Business Series Products

This Cisco Small Business product comes with a 3-year limited hardware warranty with return to factory replacement and a 90-day limited software warranty. In addition, Cisco offers software application updates for bug fixes and telephone technical support at no charge for the first 12 months following the date of purchase. To download software updates, go to:

<http://www.cisco.com/go/smallbiz>.

Product warranty terms and other information applicable to Cisco products are available at

<http://www.cisco.com/go/warranty>.

For More Information

For more information on Cisco Small Business Video Surveillance Camera Solutions, visit:

<http://www.cisco.com/go/surveillance>.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCENT, CCSI, Cisco Eos, Cisco HealthPresence, Cisco IronPort, the Cisco logo, Cisco Lumin, Cisco Nexus, Cisco Nurse Connect, Cisco StackPower, Cisco StadiumVision, Cisco TelePresence, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flip Video, Flip Video (Design), Flipshare (Design), Flip Ultra, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Store, and Flip Gift Card are service marks; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0907R)