

Cisco CRS 8-Slot Single-Shelf System

The Cisco[®] Carrier Routing System (CRS) offers industry-leading performance, advanced services intelligence, environmentally conscious design, and system longevity. The Cisco CRS is powered by a chipset architecture based on multidimensional engineering and Cisco IOS[®] XR Software, a unique self-healing, distributed operating system.

Packet-based data communications are being replaced by video and interactive multimedia transported on the Next-Generation Network (NGN) in multiple directions. This new traffic strains the architectural foundations of both public and private networks serving businesses and consumers. As part of a media-aware Cisco Next Generation Network, the Cisco CRS delivers highly reliable operations and scales easily from single-chassis form factors to a massive multi-chassis system. The Cisco CRS also referred to as the CRS-1, CRS-3, and CRS-X is a system that is both forward and backward compatible, built for investment protection and designed to provide industry-leading efficiencies in scaling, energy use, cooling, and rack-space resources.

The Cisco CRS 8-Slot Single-Shelf System (Figure 1) offers many advantages:

- The system is powered by a chipset architecture engineered for the Cisco CRS Router Family, which provides higher bandwidth than competing products, without compromising service performance. The Cisco CRS chipset is based on multidimensional engineering that includes several functional components working in tandem throughout the platform.
- The system uses Cisco IOS XR Software, the only fully modular, fully distributed internetwork operating system using a memory-protected, microkernel-based architecture and control-plane distribution that allows the system to scale and provide always-on operation.
- This single-shelf system is compatible with existing and future line cards of the Cisco CRS Family.
- The fully redundant carrier-class configuration supports in-service upgrades from 40 Gbps to 400 Gbps per slot.
- Integrated technology includes IP and Multiprotocol Label Switching (MPLS) routing, IP over dense wavelength-division multiplexing (IPoDWDM), network virtualization with secure domain routers (SDRs), fabric multicast replication, fabric quality of service (QoS), Cisco NetFlow accounting, and Carrier-Grade IPv6 (CGv6) to provide an outstanding quality of experience (QoE) at the lowest possible total cost of ownership (TCO).
- The system can also scale with back-to-back system capability, connecting two CRS 8-Slot Chassis directly, using switch fabric cards and optical cables to form a single logical system.

Figure 1. Cisco CRS 8-Slot Single Shelf System



Product Specifications

Table 1 provides detailed product specification for both the Cisco CRS-8/S and CRS-8/S-B chassis as well as specifications for the CRS 8-Slot Single-Shelf System back-to-back multichassis.

Table 1. Specifications of Cisco CRS 8-Slot Single Shelf System Chassis

	CRS-8/S-B CRS	CRS-8/SCRS
Feature	Description	
Product compatibility	Compatible with all current Cisco CRS Family modular services cards (MSCs), forwarding processors, physical layer interface modules (PLIMs), Label Switch Processors (CRS-LSPs), route processors, and fabric cards	Compatible with all current Cisco CRS Family modular services cards (MSCs), forwarding processors, physical layer interface modules (PLIMs), CRS Label Switch Processors (CRS-LSPs), route processors, and fabric cards
Back-to-Back Compatibility	Yes	Yes
Software compatibility	Cisco IOS XR Software Release 4.1.2 or later	Cisco IOS XR Software Release 4.0.0 or later * Cisco IOS XR Software Release 3.0.0 or later
Protocols	<ul style="list-style-type: none"> • Cisco Discovery Protocol • IPv4 and IPv6 addressing • Internet Control Message Protocol (ICMP) • Layer 3 routing protocols, including: <ul style="list-style-type: none"> ◦ Border Gateway Protocol Version 4 (BGPv4) ◦ Multiprotocol BGP Version 4 (MP-BGP v4) ◦ Open Shortest Path First Version 2 (OSPFv2) ◦ OSPFv3 ◦ Intermediate System-to-Intermediate System (IS-IS) Protocol ◦ Static Routes ◦ Routing Policy Language (RPL) • Multicast forwarding with support for source-based and shared distribution trees and the following protocols: <ul style="list-style-type: none"> ◦ Protocol Independent Multicast sparse mode (PIM-SM) 	<ul style="list-style-type: none"> • Cisco Discovery Protocol • IPv4 and IPv6 addressing • Internet Control Message Protocol (ICMP) • Layer 3 routing protocols, including: <ul style="list-style-type: none"> ◦ Border Gateway Protocol Version 4 (BGPv4) ◦ Multiprotocol BGP Version 4 (MP-BGP v4) ◦ Open Shortest Path First Version 2 (OSPFv2) ◦ OSPFv3 ◦ Intermediate System-to-Intermediate System (IS-IS) Protocol ◦ Static Routes ◦ Routing Policy Language (RPL) • Multicast forwarding with support for source-based and shared distribution trees and the following protocols: <ul style="list-style-type: none"> ◦ Protocol Independent Multicast sparse mode (PIM-SM)

	CRS-8/S-B CRS	CRS-8/SCRS
Feature	Description	
	<ul style="list-style-type: none"> ◦ Bidirectional PIM (Bidir-PIM) ◦ PIM source-specific mode (PIM SSM) ◦ Automatic route processing (AutoRP) ◦ Internet Group Management Protocol (IGMP) Versions 1, 2, and 3 ◦ Multiprotocol BGP (MBGP) ◦ Multicast Source Discovery Protocol (MSDP) • Multiprotocol Label Switching (MPLS): <ul style="list-style-type: none"> ◦ MPLS Label Distribution Protocol (LDP) ◦ Resource Reservation Protocol (RSVP) ◦ DiffServ-Aware Traffic Engineering (TE) • MPLS Traffic Engineering control plane (RFCs 2702 and 2430) • Route Policy Language (RPL) • Management: <ul style="list-style-type: none"> ◦ Simple Network Management Protocol (SNMP) ◦ Programmatic interfaces (XML) • Security: <ul style="list-style-type: none"> ◦ Message Digest Algorithm (MD5) ◦ IP Security (IPsec) Protocol ◦ Secure Shell Protocol Version 2 (SSHv2) ◦ Secure FTP (SFTP) ◦ Secure Sockets Layer (SSL) 	<ul style="list-style-type: none"> ◦ Bidirectional PIM (Bidir-PIM) ◦ PIM source-specific mode (PIM SSM) ◦ Automatic route processing (AutoRP) ◦ Internet Group Management Protocol (IGMP) Versions 1, 2, and 3 ◦ Multiprotocol BGP (MBGP) ◦ Multicast Source Discovery Protocol (MSDP) • Multiprotocol Label Switching (MPLS): <ul style="list-style-type: none"> ◦ MPLS Label Distribution Protocol (LDP) ◦ Resource Reservation Protocol (RSVP) ◦ DiffServ-Aware Traffic Engineering (TE) • MPLS Traffic Engineering control plane (RFCs 2702 and 2430) • Route Policy Language (RPL) • Management: <ul style="list-style-type: none"> ◦ Simple Network Management Protocol (SNMP) ◦ Programmatic interfaces (XML) • Security: <ul style="list-style-type: none"> ◦ Message Digest Algorithm (MD5) ◦ IP Security (IPsec) Protocol ◦ Secure Shell Protocol Version 2 (SSHv2) ◦ Secure FTP (SFTP) ◦ Secure Sockets Layer (SSL)
Components	<p>Each Cisco CRS enhanced 8-slot line card chassis includes:</p> <ul style="list-style-type: none"> • 2 Cisco CRS 8-slot line card chassis route processors (CRS-8-RP) • 4 Cisco CRS 8-slot fabric cards • 2 power supplies (either DC or AC) • 2 fan trays <p>Optional items:</p> <ul style="list-style-type: none"> • 8 Cisco CRS line cards • 8 Cisco CRS PLIMs 	<p>Each Cisco CRS 8-slot line card chassis includes:</p> <ul style="list-style-type: none"> • 1 Cisco CRS 8-slot line card chassis route processor (CRS-8-RP) • 4 Cisco CRS 8-slot fabric cards • 2 power supplies (either DC or AC) • 2 fan trays <p>Optional items include:</p> <ul style="list-style-type: none"> • 8 Cisco CRS line cards • 8 Cisco CRS PLIMs
Line Cards, ports, and slots	<ul style="list-style-type: none"> • 1-port OC-768c/STM-256c packet over SONET (PoS) • 4-port OC-192c/STM-64c PoS/Dynamic Packet Transport (DPT) • 16-port OC-48c/STM-16 PoS/DPT • 8-port 10 Gigabit Ethernet (GE) • 4-port 10 GE • 42-port 1 GE • 1-port OC-768c/STM-256c Tunable WDMPoS • 4-port 10 GE tunable WDMPHY • 14-port 10 GE LAN/WAN PHY • 20-port 10 GE LAN/WAN PHY • 1-Port 100 Gigabit Ethernet Interface Module • Cisco CRS-1-SIP-800 Carrier Card • 2- and 4-port OC-3c/STM-1c PoS shared port adapters (SPAs) • 1-port, 2-port, and 4-port OC-48c/STM-16c PoS/RPR SPA • 1-port OC-192c/STM-64c PoS/RPR SPA • 1-port 10 GE SPA • 2-port and 4-port Clear Channel T3/E3 SPAs • 2-port, 4-port, and 8-port OC-12c/STM-4 PoS SPAs • 2-port, 5-port, 8-port, and 10-port GE SPAs • 1-port 10 GE LAN/WAN-PHY SPA • 20-port GE flexible interface module 	<ul style="list-style-type: none"> • 1-port OC-768c/STM-256c packet over SONET (PoS) • 4-port OC-192c/STM-64c PoS/Dynamic Packet Transport (DPT) • 16-port OC-48c/STM-16 PoS/DPT • 8-port 10 Gigabit Ethernet (GE) • 4-port 10 GE • 42-port 1 GE • 1-port OC-768c/STM-256c Tunable WDMPoS • 4-port 10 GE tunable WDMPHY • 14-port 10 GE LAN/WAN PHY • 20-port 10 GE LAN/WAN PHY • 1-Port 100 Gigabit Ethernet Interface Module • Cisco CRS-1-SIP-800 Carrier Card • 2- and 4-port OC-3c/STM-1c PoS shared port adapters (SPAs) • 1-port, 2-port, and 4-port OC-48c/STM-16c PoS/RPR SPA • 1-port OC-192c/STM-64c PoS/RPR SPA • 1-port 10 GE SPA • 2-port and 4-port Clear Channel T3/E3 SPAs • 2-port, 4-port, and 8-port OC-12c/STM-4 PoS SPAs • 2-port, 5-port, 8-port, and 10-port GE SPAs • 1-port 10 GE LAN/WAN-PHY SPA • 20-port GE flexible interface module

	CRS-8/S-B CRS	CRS-8/SCRS
Feature	Description	
	<ul style="list-style-type: none"> • 2-port 10 GE WAN/LAN-PHY flexible interface module • Flexible SPA and 6-port 10GE PLIM • 2-Port 40GE LAN/OTN Interface Module • 4-Port 40GE LAN/OTN Interface Module • 1-Port 100 Gigabit Ethernet Coherent DWDM Interface Module • 40x10 Gigabit Ethernet Interface Module • 4-Port 100GE LAN/OTN Interface Module 	<ul style="list-style-type: none"> • 2-port 10 GE WAN/LAN-PHY flexible interface module • Flexible SPA and 6-port 10GE PLIM • 2-Port 40GE LAN/OTN Interface Module • 4-Port 40GE LAN/OTN Interface Module • 1-Port 100 Gigabit Ethernet Coherent DWDM Interface Module • 40x10 Gigabit Ethernet Interface Module • 4-Port 100GE LAN/OTN Interface Module
Fabric Cards	CRS-8-FC/S CRS-8-140FC/S CRS-8-FC140/M CRS-8-FC400/S CRS-8-FC400/M	CRS-8-FC/S CRS-8-140FC/S CRS-8-FC140/M CRS-8-FC400/S CRS-8-FC400/M *Note: Legacy chassis is limited to 200G on CRS-8-FC400/S on CRS-8-FC400/M
Connectivity	PoS, WDM, DPT, T3/E3, 100 GE, 10 GE, 1 GE	PoS, WDM, DPT, T3/E3, 100 GE, 10 GE, 1 GE
Features and functions	IP features: <ul style="list-style-type: none"> • Control-plane packet handling • IPv4 host services • IPv4 unicast forwarding • IPv4 equal-cost multipath (ECMP) • IPv6 host services • IPv6 forwarding services • IPv6 ECMP Forwarding features: <ul style="list-style-type: none"> • Access control lists (ACLs) • Quality of service (QoS) and class of service (CoS) using Modular QoS CLI (MQC) • IP packet classification and marking • Queuing (both ingress and egress) • Policing (both ingress and egress) • Diagnostic and network-management support IPv4 multicast features: <ul style="list-style-type: none"> • Dynamic registration using IGMP • Multicast Reverse Path Forwarding (RPF) • PIM sparse mode (SM) • PIM source-specific mode (PIM SSM) • Automatic route processing • MSDP • MBGP • Bidirectional PIM • Source Specific Multicast with IGMPv3 • Explicit tracking of hosts, group, and channels for IGMPv3 • Multicast nonstop forwarding (NSF) MPLS features: <ul style="list-style-type: none"> • MPLS forwarding and load balancing • LDP • RSVP • MPLS traffic-engineering features • User-Network Interface (UNI) • Link Management Protocol (LMP) Security features: <ul style="list-style-type: none"> • Message Digest Algorithm 5 (MD5) • Secure Sockets Layer (SSL) • Secure Shell (SSH) Protocol and Secure FTP (SFTP) • Secure HTTP (SHTTP) support • Control packet policing 	IP features: <ul style="list-style-type: none"> • Control-plane packet handling • IPv4 host services • IPv4 unicast forwarding • IPv4 equal-cost multipath (ECMP) • IPv6 host services • IPv6 forwarding services • IPv6 ECMP Forwarding features: <ul style="list-style-type: none"> • Access control lists (ACLs) • Quality of service (QoS) and class of service (CoS) using Modular QoS CLI (MQC) • IP packet classification and marking • Queuing (both ingress and egress) • Policing (both ingress and egress) • Diagnostic and network-management support IPv4 multicast features: <ul style="list-style-type: none"> • Dynamic registration using IGMP • Multicast Reverse Path Forwarding (RPF) • PIM sparse mode (SM) • PIM source-specific mode (PIM SSM) • Automatic route processing • MSDP • MBGP • Bidirectional PIM • Source Specific Multicast with IGMPv3 • Explicit tracking of hosts, group, and channels for IGMPv3 • Multicast nonstop forwarding (NSF) MPLS features: <ul style="list-style-type: none"> • MPLS forwarding and load balancing • LDP • RSVP • MPLS traffic-engineering features • User-Network Interface (UNI) • Link Management Protocol (LMP) Security features: <ul style="list-style-type: none"> • Message Digest Algorithm 5 (MD5) • Secure Sockets Layer (SSL) • Secure Shell (SSH) Protocol and Secure FTP (SFTP) • Secure HTTP (SHTTP) support

	CRS-8/S-B CRS	CRS-8/SCRS
Feature	Description	
	<ul style="list-style-type: none"> • IP Security (IPsec) Manageability features: <ul style="list-style-type: none"> • Alarms management • Configuration management • Accounting and statistics management • Performance management • Control point and network management - Generic requirements • Terminal services enhancements • Enhanced command-line interface (CLI) • Extensible Markup Language (XML) interface • XML schemas • Cisco Craft Works Interface (CWI) • Common Object Request Broker Architecture (CORBA) support • Simple Network Management Protocol (SNMP) and MIB support 	<ul style="list-style-type: none"> • Control packet policing • IP Security (IPsec) Manageability features: <ul style="list-style-type: none"> • Alarms management • Configuration management • Accounting and statistics management • Performance management • Control point and network management: Generic requirements • Terminal services enhancements • Enhanced command-line interface (CLI) • Extensible Markup Language (XML) interface • XML schemas • Cisco Craft Works Interface (CWI) • Common Object Request Broker Architecture (CORBA) support • Simple Network Management Protocol (SNMP) and MIB support
Options	Cisco CRS-1 8-Slot Line Card Chassis Route Processor (CRS-8-RP)	Cisco CRS-1 8-Slot Line Card Chassis Route Processor (CRS-8-RP)
Performance	6.4/2.24-Tbps switching capacity	2.24-Tbps switching capacity
Reliability and availability	System redundancy: <ul style="list-style-type: none"> • Power-shelf redundancy 1:1 • Fan-tray redundancy 1:1 • Route-processor redundancy 1:1 • Fabric-card redundancy 1:4 • Dual homing with line cards • Support for APS Software features: <ul style="list-style-type: none"> • NSF using graceful restart for: IS-IS, OSPF, BGP, LDP, and RSVP • SONET APS 1:1 • Line-card OIR support • Fabric-card OIR support • Out-of-resource management • Process restartability • MPLS Fast Reroute (FRR) • Hot Standby Router Protocol (HSRP) and Virtual Router Redundancy Protocol (VRRP) 	System redundancy: <ul style="list-style-type: none"> • Power-shelf redundancy 1:1 • Fan-tray redundancy 1:1 • Route-processor redundancy 1:1 • Fabric-card redundancy 1:4 • Dual homing with line cards • Support for APS Software features: <ul style="list-style-type: none"> • NSF using graceful restart for: IS-IS, OSPF, BGP, LDP, and RSVP • SONET APS 1:1 • Line-card OIR support • Fabric-card OIR support • Out-of-resource management • Process restartability • MPLS Fast Reroute (FRR) • Hot Standby Router Protocol (HSRP) and Virtual Router Redundancy Protocol (VRRP)
MIBs	SNMP framework support: <ul style="list-style-type: none"> • SNMPv1 • SNMPv2c • SNMPv3 • MIB II, including interface extensions (RFC 1213) • SNMP-FRAMEWORK-MIB • SNMP-TARGET-MIB • SNMP-NOTIFICATION-MIB • SNMP-USM-MIB • SNMP-VACM-MIB System management: <ul style="list-style-type: none"> • CISCO- BULK-FILE-MIB • CISCO-CONFIG-COPY-MIB • CISCO-CONFIG-MAN-MIB • CISCO-FLASH-MIB • CISCO-MEMORY-POOL-MIB 	SNMP framework support: <ul style="list-style-type: none"> • SNMPv1 • SNMPv2c • SNMPv3 • MIB II, including interface extensions (RFC 1213) • SNMP-FRAMEWORK-MIB • SNMP-TARGET-MIB • SNMP-NOTIFICATION-MIB • SNMP-USM-MIB • SNMP-VACM-MIB System management: <ul style="list-style-type: none"> • CISCO- BULK-FILE-MIB • CISCO-CONFIG-COPY-MIB • CISCO-CONFIG-MAN-MIB • CISCO-FLASH-MIB • CISCO-MEMORY-POOL-MIB

	CRS-8/S-B CRS	CRS-8/SCRS
Feature	Description	
	<ul style="list-style-type: none"> • Cisco FTP Client MIB • Cisco Process MIB • Cisco Syslog MIB • CISCO-SYSTEM-MIB • CISCO-CDP-MIB • IF-MIB (RFC 2233/RFC 2863) <p>Chassis:</p> <ul style="list-style-type: none"> • ENTITY-MIB (RFC 2737) • CISCO-entity-asset-MIB • CISCO-entity-sensor-MIB • CISCO-FRU-MIB (Cisco-Entity-FRU-Control-MIB) <p>Fabric:</p> <ul style="list-style-type: none"> • CISCO-Fabric-HFR-MIB • CISCO-Fabric-Mcast-MIB • CISCO-Fabric-Mcast-Appl-MIB <p>Routing protocols:</p> <ul style="list-style-type: none"> • BGP4-MIB Version 1 • OSPFv1MIB (RFC1253) • CISCO-IETF-IP-FORWARDING-MIB • IP-MIB (was RFC2011-MIB) • TCP-MIB (RFC 2012) • UDP-MIB • CISCO-HSRP-EXT-MIB • CISCO-HSRP-MIB • CISCO-BGP-POLICY-ACCOUNTING-MIB <p>QoS:</p> <ul style="list-style-type: none"> • MQC-MIB (Cisco Class-Based QoS MIB) • CISCO-PING-MIB <p>Traps:</p> <ul style="list-style-type: none"> • RFC 1157 • Authentication • Linkup • Linkdown • Coldstart • Warmstart 	<ul style="list-style-type: none"> • Cisco FTP Client MIB • Cisco Process MIB • Cisco Syslog MIB • CISCO-SYSTEM-MIB • CISCO-CDP-MIB • IF-MIB (RFC 2233/RFC 2863) <p>Chassis:</p> <ul style="list-style-type: none"> • ENTITY-MIB (RFC 2737) • CISCO-entity-asset-MIB • CISCO-entity-sensor-MIB • CISCO-FRU-MIB (Cisco-Entity-FRU-Control-MIB) <p>Fabric:</p> <ul style="list-style-type: none"> • CISCO-Fabric-HFR-MIB • CISCO-Fabric-Mcast-MIB • CISCO-Fabric-Mcast-Appl-MIB <p>Routing protocols:</p> <ul style="list-style-type: none"> • BGP4-MIB Version 1 • OSPFv1MIB (RFC1253) • CISCO-IETF-IP-FORWARDING-MIB • IP-MIB (was RFC2011-MIB) • TCP-MIB (RFC 2012) • UDP-MIB • CISCO-HSRP-EXT-MIB • CISCO-HSRP-MIB • CISCO-BGP-POLICY-ACCOUNTING-MIB <p>QoS:</p> <ul style="list-style-type: none"> • MQC-MIB (Cisco Class-Based QoS MIB) • CISCO-PING-MIB <p>Traps:</p> <ul style="list-style-type: none"> • RFC 1157 • Authentication • Linkup • Linkdown • Coldstart • Warmstart
Network management	<ul style="list-style-type: none"> • Enhanced CLI • XML interface • Cisco Craft Works Interface (CWI) • SNMP and MIB support 	<ul style="list-style-type: none"> • Enhanced CLI • XML interface • Cisco Craft Works Interface (CWI) • SNMP and MIB support
Programming interfaces	XML schema support	XML schema support
Physical dimensions	<p>Chassis height: 38.5 in. (97.79 cm, with base cosmetics)</p> <p>Chassis width: 17.5 in. (44.45 cm)</p> <p>Chassis depth: 36.6 in (92.964 cm); 40.5 in. (102.87 cm), including full cosmetics</p> <p>Weight:</p> <ul style="list-style-type: none"> • 330.8 lb (148.86 kg) chassis with fans, PDUs, and blanks (as shipped) • 650 lb (292.5 kg) chassis as shipped, including power shelves and all line cards and route processors 	<p>Chassis height: 38.5 in. (97.79 cm, with base cosmetics)</p> <p>Chassis width: 17.5 in. (44.45 cm)</p> <p>Chassis depth: 36.6 in (92.964 cm); 40.5 in. (102.87 cm), including full cosmetics</p> <p>Weight:</p> <ul style="list-style-type: none"> • 330.8 lb (148.86 kg) chassis with fans, PDUs, and blanks (as shipped) • 650 lb (292.5 kg) chassis as shipped, including power shelves and all line cards and route processors
Power	<ul style="list-style-type: none"> • Chassis power supply maximum output capacity: 8.4 kW for DC power supply and 9 kW for AC power supply 	<ul style="list-style-type: none"> • Chassis power supply maximum output capacity: 8.4 kW for DC power supply and 9 kW for AC power supply

	CRS-8/S-B CRS	CRS-8/SCRS
Feature	Description	
Environmental conditions	Storage temperature: -40 to 158°F (-40 to 70°C) Operating temperature: <ul style="list-style-type: none"> • Normal: 41 to 104°F (5 to 40°C) • Short-term: 23 to 122°F (-5 to 50°C) Relative humidity: <ul style="list-style-type: none"> • Normal: 5 to 85% • Short-term: 5 to 90% but not to exceed 0.024 kg water per kg of dry air • Note: Short-term refers to a period of not more than 96 consecutive hours and a total of not more than 15 days in 1 year (a total of 360 hours in any given year, but no more than 15 occurrences during that 1-year period) 	Storage temperature: -40 to 158°F (-40 to 70°C) Operating temperature: <ul style="list-style-type: none"> • Normal: 41 to 104°F (5 to 40°C) • Short-term: 23 to 122°F (-5 to 50°C) Relative humidity: <ul style="list-style-type: none"> • Normal: 5 to 85% • Short-term: 5 to 90% but not to exceed 0.024 kg water per kg of dry air • Note: Short-term refers to a period of not more than 96 consecutive hours and a total of not more than 15 days in 1 year (a total of 360 hours in any given year, but no more than 15 occurrences during that 1-year period)

Approvals and Compliance

Table 2 lists compliance and agency approvals for both models of the Cisco CRS 8-Slot Single-Shelf System.

Table 2. Approvals and Compliance for Cisco CRS-8/S and Cisco CRS-8/S-B

Feature	Description
Safety standards	<ul style="list-style-type: none"> • UL/CSA/IEC/EN 60950-1 • AS/NZS 60950.1 • IEC/EN 60825 Laser Safety • FDA - Code of Federal Regulations Laser Safety
Electromagnetic interference (EMI)	<ul style="list-style-type: none"> • FCC Class A • ICES 003 Class A • AS/NZS CISPR 22 Class A • CISPR 22 (EN55022) Class A • VCCI Class A • IEC/EN 61000-3-2: Power Line Harmonics • IEC/EN 61000-3-3: Voltage Fluctuations and Flicker
Immunity (basic standards)	<ul style="list-style-type: none"> • IEC/EN-61000-4-2: Electrostatic Discharge Immunity (8-kV contact, 15-kV air) • IEC/EN-61000-4-3: Radiated Immunity (10V/m) • IEC/EN-61000-4-4: Electrical Fast Transient Immunity (2-kV power, 1-kV signal) • IEC/EN-61000-4-5: Surge AC Port (4-kV CM, 2-kV DM) • IEC/EN-61000-4-5: Signal Ports (1 kV) • IEC/EN-61000-4-5: Surge DC Port (1 kV) • IEC/EN-61000-4-6: Immunity to Conducted Disturbances (10 Vrms) • IEC/EN-61000-4-8: Power Frequency Magnetic Field Immunity (30A/m) • IEC/EN-61000-4-11: Voltage Dips, Short Interruptions, and Voltage Variations
ETSI and EN	<ul style="list-style-type: none"> • EN300 386: Telecommunications Network Equipment (EMC) • EN55022: Information Technology Equipment (Emissions) • EN55024: Information Technology Equipment (Immunity) • EN50082-1/EN-61000-6-1: Generic Immunity Standard
Network Equipment Building Systems (NEBS)	This product is designed to meet the following requirements (qualification in progress): <ul style="list-style-type: none"> • SR-3580: NEBS Criteria Levels (Level 3) • GR-1089-CORE: NEBS EMC and Safety • GR-63-CORE: NEBS Physical Protection

System Capacity

Table 3 shows the system capacity of the Cisco CRS 8-Slot Single-Shelf System.

Table 3. System Capacity for Cisco CRS 8-Slot Single-Shelf System

Number of Interface Slots	Maximum Capacity per Slot	Total Capacity
8	400 Gbps per slot ingress and 400 Gbps per slot egress	6.4 Tbps per single-shelf system

Ordering Information

To place an order, visit the [Cisco ordering homepage](#) and refer to Table 4 for ordering information. To download Cisco IOS Software, visit the [Cisco Software Center](#).

Table 4. Ordering Information for Cisco CRS 8-Slot Single-Shelf System

Product Name	Product Part Number
Cisco CRS 8-Slot Single-Shelf System	CRS-8/S
Cisco CRS 8-Slot Single-Shelf System Enhanced	CRS-8/S-B

Cisco Services

Cisco Services make networks, applications, and the people who use them work better together.

Today, the network is a strategic platform in a world that demands better integration between people, information, and ideas. The network works better when services, together with products, create solutions aligned with business needs and opportunities.

The unique Cisco Lifecycle approach to services defines the requisite activities at each phase of the network lifecycle to help ensure service excellence. With a collaborative delivery methodology that joins the forces of Cisco, our skilled network of partners, and our customers, we achieve the best results.

For More Information

For more information about the Cisco 8-Slot Single-Shelf System, the Cisco CRS, other available interfaces, and related products, visit Cisco at <http://www.cisco.com/go/crs> or contact your local Cisco account representative.

For more information about the Cisco CRS Multichassis System see the [Cisco CRS Multichassis System data sheet](#).



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)