

# Cisco RV320 Dual Gigabit WAN VPN Router

## Product Overview

Network connectivity is at the heart of every small business, and secure access, firewall protection, and high performance are the cornerstones of every Cisco® Small Business RV Series Router. The Cisco RV320 Dual Gigabit WAN VPN Router is no exception. With an intuitive user interface, the Cisco RV320 enables you to be up and running in minutes. The Cisco RV320 provides reliable, highly secure access connectivity for you and your employees that is so transparent you will not know it is there.

**Figure 1.** Cisco RV320 Dual Gigabit WAN VPN Router



## Features and Benefits

- Dual Gigabit Ethernet WAN ports allow load balancing and business continuity.
- Affordable, high-performance Gigabit Ethernet ports enable rapid transfer of large files, supporting multiple users.
- Dual USB ports support a 3G/4G modem or flash drive. The WAN can also fail over to the 3G/4G modem connected to the USB port.
- SSL VPN and site-to-site VPN enable highly secure connectivity, making the Cisco RV320 perfect for remote employees and multiple offices.
- Stateful packet inspection (SPI) firewall and hardware encryption provide strong security.
- Easy-to-use wizard-based configuration tools can be used to establish network connectivity and manage security.

The Cisco RV320 Dual Gigabit WAN VPN Router is the choice for any network in which performance, security, reliability, and adaptability top the list of requirements. The Cisco RV320 supports two connections to one service provider, delivering high performance by using load balancing, or to two different providers to deliver business continuity. High-capacity virtual private networks (VPNs) connect multiple offices and enable dozens of employees to access the information they need from any geographic location just as securely as if they were working at your main office.

## Product Specifications

Table 1 lists the product specifications for the Cisco RV320.

**Table 1.** Product Specifications

Description	Specification
Dual WAN	<ul style="list-style-type: none"> <li>Dual Gigabit Ethernet Ports</li> <li>Failover</li> <li>Load balancing</li> </ul>
Standards	<ul style="list-style-type: none"> <li>802.3, 802.3u</li> <li>IPv4 (RFC 791)</li> <li>IPv6 (RFC 2460)</li> </ul>
WAN connectivity	<ul style="list-style-type: none"> <li>Dynamic Host Configuration Protocol (DHCP) server, DHCP client, DHCP relay agent</li> <li>Static IP</li> <li>Point-to-Point Protocol over Ethernet (PPPoE)</li> <li>Point-to-Point Tunneling Protocol (PPTP)</li> <li>Transparent bridge</li> <li>DNS relay, Dynamic DNS (DynDNS.org, 3322.org), DNS local database</li> <li>IPv6</li> </ul>
Routing protocols	<ul style="list-style-type: none"> <li>Routing Information Protocol (RIP) v1 and v2, and RIP for IPv6 (RIPng)</li> <li>Inter-VLAN routing</li> <li>Static routing</li> <li>VLANs supported: 7</li> </ul>
Network Address Translation (NAT)	<ul style="list-style-type: none"> <li>Port Address Translation (PAT)</li> <li>One-to-one NAT</li> <li>NAT traversal</li> </ul>
Protocol binding	Protocols can be bound to a specific WAN port for load-balancing purposes
Network edge (DMZ)	<ul style="list-style-type: none"> <li>DMZ port</li> <li>DMZ host</li> </ul>
Dual USB 2.0 ports	Storage and 3G/4G modem support
<b>Security</b>	
Firewall	<ul style="list-style-type: none"> <li>SPI firewall</li> <li>Denial-of-service (DoS) prevention: ping of death, SYN flood, IP spoofing, WinNuke</li> </ul>
Access rules	<ul style="list-style-type: none"> <li>Schedule-based access rules</li> <li>Up to 50 entries</li> </ul>
Port forwarding	Up to 30 entries
Port triggering	Up to 30 entries
Blocking	Java, cookies, ActiveX, HTTP proxy
Content filtering	Static URL blocking or keyword blocking
Secure management	<ul style="list-style-type: none"> <li>HTTPS web access to device manager</li> <li>Username/password complexity enforcement</li> </ul>
VLAN	802.1Q VLAN 7 VLANs supported
<b>VPN</b>	
IP Security (IPsec)	<ul style="list-style-type: none"> <li>25 IPsec site-to-site tunnels for branch office connectivity</li> <li>25 IPsec VPN tunnels via third-party clients such as "The GreenBow" for remote-access VPN connectivity</li> </ul>
SSL VPN	10 SSL VPN tunnels for remote client access
PPTP	10 PPTP tunnels for remote access
Encryption	<ul style="list-style-type: none"> <li>Data Encryption Standard (DES)</li> </ul>

Description	Specification
	<ul style="list-style-type: none"> <li>• Triple Data Encryption Standard (3DES)</li> <li>• Advanced Encryption Standard (AES) encryption: AES-128, AES-192, AES-256</li> </ul>
<b>Authentication</b>	MD5/SHA1
<b>IPsec NAT traversal</b>	Supported for gateway-to-gateway and client-to-gateway tunnels
<b>VPN pass-through</b>	PPTP, Layer 2 Tunneling Protocol (L2TP), IPsec
<b>Advanced VPN</b>	<ul style="list-style-type: none"> <li>• Dead peer detection (DPD)</li> <li>• Split DNS</li> <li>• VPN backup</li> <li>• Internet Key Exchange (IKE) with certificate</li> </ul>
<b>Quality of Service (QoS)</b>	
<b>Service-based QoS</b>	Rate control or priority
<b>Rate control</b>	Upstream/downstream bandwidth per service
<b>Prioritization types</b>	Application-based priority on WAN port
<b>Priority</b>	Services mapped to one of two priority levels
<b>Performance</b>	
<b>IPsec VPN throughput</b>	100 Mbps
<b>SSL VPN throughput</b>	20 Mbps
<b>Concurrent connections</b>	20,000
<b>Configuration</b>	
<b>Web user interface</b>	Browser-based device manager (HTTP/HTTPS)
<b>Management</b>	
<b>Management protocols</b>	<ul style="list-style-type: none"> <li>• Web browser (HTTP/HTTPS)</li> <li>• Simple Network Management Protocol (SNMP) v1, v2c, and v3</li> <li>• Bonjour</li> </ul>
<b>Event logging</b>	<ul style="list-style-type: none"> <li>• Local log</li> <li>• Syslog</li> <li>• Email alert</li> <li>• Short Message Service (SMS)</li> </ul>
<b>Upgradability</b>	<ul style="list-style-type: none"> <li>• Firmware upgradable through the web browser</li> <li>• Import or export configuration files from or to a USB flash drive</li> </ul>

## System Specifications

Table 2 lists the system specifications for the Cisco RV320.

**Table 2.** System Specifications

Description	Specification
<b>Product dimensions (W x H x D)</b>	206 x 132 x 44 mm (8.1 x 5.2 x 1.7 in)
<b>Ports</b>	Four 10/100/1000 Gigabit Ethernet RJ-45 ports One 10/100/1000 Gigabit Ethernet RJ-45 Internet (WAN) port One 10/100/1000 Gigabit Ethernet RJ-45 DMZ/Internet (WAN) port
<b>Power supply</b>	12V 1.5A
<b>Certification</b>	FCC Class B, CE Class B, UL, cUL, CB, CCC, BSMI, KC, Anatel
<b>Operating temperature</b>	0° to 40°C (32° to 104°F)
<b>Storage temperature</b>	0° to 70°C (32° to 158°F)
<b>Operating humidity</b>	10% to 85% noncondensing
<b>Storage humidity</b>	5% to 90% noncondensing

## Warranty Information

Find warranty information on Cisco.com at the [Product Warranties](#) page.

## Ordering Information

Help customers understand all the components or parts they need to purchase in order to install and use the product. Table 3 lists ordering information for the Cisco RV320. This section also provides a direct link to the Cisco Ordering Tool and lists part numbers for customer convenience.

To place an order, visit the [Cisco Ordering Home Page](#). To download software, visit the [Cisco Software Center](#).

**Table 3.** Ordering Information

Product Name	Part Number
RV320 Dual WAN VPN Router	RV320-K9-NA
RV320 Dual WAN VPN Router	RV320-K9-G5
RV320 Dual WAN VPN Router	RV320-K9-AU
RV320 Dual WAN VPN Router	RV320-K9-CN
RV320 Dual WAN VPN Router	RV320-K9-AR

## Cisco Limited Lifetime Warranty for Cisco Small Business Products

This Cisco Small Business product comes with a limited lifetime hardware warranty. Product warranty terms and other information applicable to Cisco products are available at <https://www.cisco.com/go/warranty>.

## Cisco Small Business Support Service

This optional service offers affordable, 3-year peace-of-mind coverage. This subscription-based, device-level service helps you protect your investment and derive maximum value from Cisco Small Business products. Delivered by Cisco and backed by your trusted partner, this comprehensive service includes software updates, extended access to the Cisco Small Business Support Center, and expedited hardware replacement, should it be required.

## Cisco Capital

### Financing to Help You Achieve Your Objectives

Cisco Capital can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx. Accelerate your growth. Optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries. [Learn more](#).

## For More Information

For more information on the Cisco RV320 Dual Gigabit WAN VPN Router, visit <https://www.cisco.com/go/rv320>.

For more information on Cisco Small Business products and solutions, visit <https://www.cisco.com/smallbusiness>.




---

Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

 Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)