

Cisco R42612 Rack

Product Overview

Cisco® R Series Racks are excellent solutions for mission-critical environments that require the highest levels of reliability, structural integrity, and security. The series' modern design delivers exceptional power, cooling, and cable management features as well as the strength and stability required in today's rack enclosures, offering peace of mind for the most important infrastructure elements. Cisco R42612 Rack is designed and certified for use with the Cisco Unified Computing System™ (Cisco UCS®) and selected Cisco Nexus® products, allowing Cisco to offer a complete infrastructure solution, including computing, networking, rack, power, and services (Figure 1).

Figure 1. Cisco R42612 Rack



Features and Benefits

Table 1 lists the main features and benefits of the Cisco R42612 Rack.

Table 1. Features and Benefits

Feature	Benefit
Tested with Cisco UCS platform	<ul style="list-style-type: none"> • Industry-standard EIA-310-D racks are optimized for the Cisco UCS platform (for example, optimal EIA rail placement). • Racks are compatible with Cisco UCS Integrated Infrastructure solutions such as FlexPod and VersaStack. • Cisco R42612 standard and expansion racks are well suited for single-rack and multiple-rack Cisco UCS installations at customer sites. • Cisco R42612 dynamic rack is certified for shipping pre-racked Cisco UCS solutions.

Feature	Benefit
Frame	<ul style="list-style-type: none"> • 16-fold fully welded frame creates a robust structure and low profile to increase internal volume. • Fully welded frame provides improved grounding continuity compared to bolt-together frames. • Repetitive internal mounting hole patterns provide adaptable mounting surfaces.
Front and rear doors	<ul style="list-style-type: none"> • 80% perforation on the front and rear doors increase airflow. • Locks are included for added security. • Toolless door removal allows convenient servicing. • Split rear doors reduce the clearance required at the rear of the rack. • Adjustable front door can swing from right to left or left to right.
Split side panels	<ul style="list-style-type: none"> • Lightweight, 2-piece side panels are easy to install and remove. • Locks provide additional security.
Top panel	<ul style="list-style-type: none"> • Solid top panel with brush baffled cutout can accommodate power cords for 3-phase PDUs.
Power distribution unit (PDU) tray	<ul style="list-style-type: none"> • Cisco R42612 racks support industry-standard PDUs including Cisco RP Series PDUs. • Integrated PDU trays allow quick toolless mounting of 0-rack-unit (0RU) PDUs. • Deeply inset PDU trays reduce PDU interference and improve the serviceability of Cisco UCS servers. • Robust cable management attachment points support both ¼-turn toolless solutions and zip ties.
Other	<ul style="list-style-type: none"> • Stabilizer brackets are included. • Hardware kit with a sample of mounting hardware and cable management accessories is included. • Joining kit option connects adjacent standard or expansion racks within a row. • Grounding kit is available as an option. • Casters permit greater mobility. • RU markings on rack rails simplify equipment installation. • Racks are UL 2416 and CSA C22.2 No. 60950-1-07 compliant and RoHS compliant.

Product Specifications

Table 2 lists the specifications for the Cisco R42612 Rack.

Table 2. Product Specifications

Cisco R42612 Rack	Standard	Expansion	Dynamic
Dimensions (H x W x D)	79.3 x 23.5 x 49.8 in (/2013 x 597 x 1266 mm)	79.3 x 23.5 x 49.8 in (/2013 x 597 x 1266 mm)	79.3 x 23.5 x 49.8 in (/2013 x 597 x 1266 mm)
Dimensions (H x W x D) with packaging	84.3 x 36.2 x 54.8 in (/2140 x 920 x 1393 mm)	84.3 x 36.2 x 54.8 in (/2140 x 920 x 1393 mm)	86.4 x 46.4 x 57.4 in (/2195 x 1180 x 1460 mm)
Weight without packaging	339 lb (/154 kg)	264 lb (/120 kg)	359 lb (/163 kg)
Weight with packaging	410 lb (/186 kg)	335 lb (/152 kg)	705 lb (/320 kg)
Side panels included	Yes	No	Yes
Equipment mounting capacity	42RU	42RU	42RU
Static load capacity	3000 lb (1360 kg) of IT equipment	3000 lb (1360 kg) of IT equipment	3000 lb (1360 kg) of IT equipment
Dynamic load capacity	2700 lb (1224 kg) of IT equipment	2700 lb (1224 kg) of IT equipment	2700 lb (1224 kg) of IT equipment
Ship load capacity	Not available	Not available	2700 lb (1224 kg) of IT equipment

Warranty Information

Find warranty information on Cisco.com on the [Product Warranties](#) page.

Ordering Information

To place an order, visit the [Cisco Ordering homepage](#).

Cisco Services

Cisco Services make networks, applications, and the people who use them work better together.

Today, the network is a strategic platform in a world that demands better integration of people, information, and ideas. The network works better when services, together with products, create solutions aligned with business needs and opportunities.

The unique Cisco Lifecycle approach to services defines the requisite activities at each phase of the network lifecycle to help ensure service excellence. With a collaborative delivery methodology that joins the forces of Cisco, our skilled network of partners, and our customers, we achieve the best results.

Cisco Capital

Financing to Help You Achieve Your Objectives

Cisco Capital[®] can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx. Accelerate your growth. Optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries. [Learn more.](#)

For More Information

For additional information about the Cisco R42612 Rack, contact your local Cisco representative or visit:

- <http://www.cisco.com/c/en/us/products/servers-unified-computing/r-series-racks/index.html>
- <http://www.cisco.com/c/en/us/products/servers-unified-computing/rp-series-power-distribution-units/index.html>



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)