

## Cisco Catalyst 3560 Series Switches

Product	Part Number	Port Speed	Number of Ports	Uplinks	Software Image	When to Buy
<b>Cisco Catalyst 3560-8PC</b>	WS-C3560-8PC-S	10/100 with IEEE 802.3af and Cisco prestandard Power over Ethernet (PoE)	8	1 dual-purpose 10/100/1000 and Small Form-Factor Pluggable (SFP) port	IP Base	For deployments outside the wiring closet requiring low-density access with PoE
<b>Cisco Catalyst 3560-24TS</b>	WS-C3560-24TS-S	10/100	24	2 SFP-based ports	IP Base	For networks requiring low-density access, Layer 2+ features, and one or more fiber uplinks
<b>Cisco Catalyst 3560-24TS</b>	WS-C3560-24TS-E	10/100	24	2 SFP-based ports	IP Services	For networks requiring low-density access, advanced IP routing, and one or more fiber uplinks
<b>Cisco Catalyst 3560-48TS</b>	WS-C3560-48TS-S	10/100	48	4 SFP-based ports	IP Base	For networks requiring medium-density access, Layer 2+ features, and one or more fiber uplinks
<b>Cisco Catalyst 3560-48TS</b>	WS-C3560-48TS-E	10/100	48	4 SFP-based ports	IP Services	For networks requiring medium-density access, advanced IP routing, and one or more fiber uplinks
<b>Cisco Catalyst 3560-24PS</b>	WS-C3560-24PS-S	10/100 with IEEE 802.3af and Cisco prestandard PoE	24	2 SFP-based ports	IP Base	For networks requiring low-density access, PoE, Layer 2+ features, and one or more fiber uplinks

Product	Part Number	Port Speed	Number of Ports	Uplinks	Software Image	When to Buy
<b>Cisco Catalyst 3560-24PS</b>	WS-C3560-24PS-E	10/100 with IEEE 802.3af and Cisco prestandard PoE	24	2 SFP-based ports	IP Services	For networks requiring low-density access, PoE, advanced IP routing, and one or more fiber uplinks
<b>Cisco Catalyst 3560-48PS</b>	WS-C3560-48PS-S	10/100 with IEEE 802.3af and Cisco prestandard PoE	48	4 SFP-based ports	IP Base	For networks requiring medium-density access, PoE, Layer 2+ features, and one or more fiber uplinks
<b>Cisco Catalyst 3560-48PS</b>	WS-C3560-48PS-E	10/100 with IEEE 802.3af and Cisco prestandard PoE	48	4 SFP-based ports	IP Services	For networks requiring medium-density access, PoE, advanced IP routing, and one or more fiber uplinks
<b>Cisco Catalyst 3560G-24TS</b>	WS-C3560G-24TS-S	10/100/1000	24	4 SFP-based ports	IP Base	For networks requiring low-density 10/100/1000 access, Layer 2+ features, and one or more fiber uplinks
<b>Cisco Catalyst 3560G-24TS</b>	WS-C3560G-24TS-E	10/100/1000	24	4 SFP-based ports	IP Services	For networks requiring low-density 10/100/1000 access, advanced IP routing, and one or more fiber uplinks
<b>Cisco Catalyst 3560G-24PS</b>	WS-C3560G-24PS-S	10/100/1000 with IEEE 802.3af and Cisco prestandard PoE	24	4 SFP-based ports	IP Base	For networks requiring low-density 10/100/1000 access, PoE, Layer 2+ features, and one or more fiber uplinks
<b>Cisco Catalyst 3560G-24PS</b>	WS-C3560G-24PS-E	10/100/1000 with IEEE 802.3af and Cisco prestandard PoE	24	4 SFP-based ports	IP Services	For networks requiring low-density 10/100/1000 access, PoE, advanced IP routing, and one or more fiber uplinks

Product	Part Number	Port Speed	Number of Ports	Uplinks	Software Image	When to Buy
<b>Cisco Catalyst 3560G-48TS</b>	WS-C3560G-48TS-S	10/100/1000	48	4 SFP-based ports	IP Base	For networks requiring medium-density 10/100/1000 access, Layer 2+ features, and one or more fiber uplinks
<b>Cisco Catalyst 3560G-48TS</b>	WS-C3560G-48TS-E	10/100/1000	48	4 SFP-based ports	IP Services	For networks requiring medium-density 10/100/1000 access, advanced IP routing, and one or more fiber uplinks
<b>Cisco Catalyst 3560G-48PS</b>	WS-C3560G-48PS-S	10/100/1000 with IEEE 802.3af and Cisco prestandard PoE	48	4 SFP-based ports	IP Base	For networks requiring medium-density 10/100/1000 access, PoE, Layer 2+ features, and one or more fiber uplinks
<b>Cisco Catalyst 3560G-48PS</b>	WS-C3560G-48PS-E	10/100/1000 with IEEE 802.3af and Cisco prestandard PoE	48	4 SFP-based ports	IP Services	For networks requiring medium-density 10/100/1000 access, PoE, advanced IP routing, and one or more fiber uplinks



**Americas Headquarters**  
Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
www.cisco.com  
Tel: 408 526-4000  
800 553-NETS (6387)  
Fax: 408 527-0883

**Asia Pacific Headquarters**  
Cisco Systems, Inc.  
168 Robinson Road  
#28-01 Capital Tower  
Singapore 068912  
www.cisco.com  
Tel: +65 6317 7777  
Fax: +65 6317 7799

**Europe Headquarters**  
Cisco Systems International BV  
Haarlerbergpark  
Haarlerbergweg 13-19  
1101 CH Amsterdam  
The Netherlands  
www-europe.cisco.com  
Tel: +31 0 800 020 0791  
Fax: +31 0 20 357 1100

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

©2006 Cisco Systems, Inc. All rights reserved. CCVP, the Cisco logo, and the Cisco Square Bridge logo are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networking Academy, Network Registrar, Packet, PIX, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0609R)