

## Cisco Catalyst 6509 Enhanced Vertical Chassis

Cisco® introduces the Cisco Catalyst® 6509 Enhanced Vertical Chassis as part of the Cisco Catalyst 6500 Series enhanced (E-Series) switches, delivering chassis with up to 1440 Gbps of system bandwidth capacity (80 Gbps/slot), enhanced cable management, and front-to-back airflow optimized for hot aisle/cold aisle designs in data center and service provider colocation (NEBS-L3 compliant) deployments.

Cisco Catalyst 6500 E-Series chassis provide superior investment protection by supporting multiple generations of products on the same chassis, lowering the total cost of ownership. The Cisco Catalyst 6509-V-E chassis (Figure 1) supports both the Cisco Catalyst 6500 Supervisor Engine 32 and the Cisco Catalyst 6500 Series Supervisor Engine 720 family of supervisor engines and associated LAN, WAN, and services modules.

**Figure 1.** Cisco Catalyst 6509-V-E Chassis



### Features

Cisco Catalyst 6509-V-E chassis benefits include:

- **1440 Gbps system bandwidth capacity:** The Cisco Catalyst 6509-V-E chassis is capable of providing up to 1440 Gbps of system bandwidth capacity at 80 Gbps/slot. This provides investment protection and the ability to grow to future high-bandwidth requirements in the network.
- **Front-to-back airflow:** The Cisco Catalyst 6509-V-E chassis is designed to allow for hot aisle/cold aisle design in modern data centers with its front-to-back airflow design.
- **Enhanced cable management kit:** The Cisco Catalyst 6509-V-E chassis comes default with an enhanced cable management kit that allows management of Category 5e, Category 6, Category 6a, and fiber cabling in a high-density configuration.

- **Redundant fan tray:** The Cisco Catalyst 6509-V-E offers redundant fan trays to increase the availability of the system. Each fan tray has redundant fans, and the addition of a redundant fan tray helps ensure that the system becomes extremely reliable to fan/fan tray failure.
- **Standby fabric hot sync:** The Cisco Catalyst 6509-V-E chassis supports the standby fabric hot sync feature, which enables as low as 50 ms failover from active to standby supervisor engine, increasing the availability of the system.
- **Redundant control channel:** The Cisco Catalyst 6509-V-E chassis supports redundant Ethernet out of Band Channel (EoBC) for increased resiliency of backplane control traffic.
- **High system power capacity:** The Cisco Catalyst 6509-V-E provides system power capacity up to 14500W, providing the ability to support fully loaded configurations of current and future high-density 10 Gigabit Ethernet cards.
- **AC and DC power options:** The Cisco Catalyst 6509-V-E chassis supports both AC and DC power supply options. For AC power, 3000W, 4000W, 6000W, and 8700W power supplies are available. For DC power, 2500W and 4000W power supplies are available.

## Upgrade Paths

Cisco Catalyst 6509-V-E chassis is part of the enhanced Cisco Catalyst 6500 series of switches, offering enhanced benefits over the Cisco Catalyst 6509-NEB-A chassis. Table 1 compares the Cisco Catalyst 6509-NEB-A to the Cisco Catalyst 6509-V-E chassis.

**Table 1.** Feature Comparison Between Cisco Catalyst 6509-NEB-A and Cisco Catalyst 6509-V-E Chassis

Feature	Cisco Catalyst 6509-NEB-A	Cisco Catalyst 6509-V-E
Bandwidth Capacity per Slot	40 Gbps	80 Gbps
System Bandwidth Capacity	720 Gbps	1440 Gbps
Cable Management	Category 5e and fiber	Category 5e, Category 6, Category 6a and fiber
Supported Maximum System Power	4500W	14500W
Standby Fabric Hot Sync (Supervisor Engine Switchover)	1.5 s	50 ms
Number of EoBC Channels	1	2
NEBS L3 Compliant	Yes	Yes

## Availability

The Cisco Catalyst 6509-V-E chassis will be orderable and available in October 2007.

## Ordering Information

Table 2 lists the ordering information for the Cisco Catalyst 6509-V-E chassis. To place an order, visit the Cisco ordering homepage.

**Table 2.** Ordering Information

Product Name	Part Number
Cisco Catalyst 6509 Enhanced Vertical Chassis	WS-C6509-V-E
Cisco Catalyst 6509 Enhanced Vertical Chassis Fan Tray	WS-C6509-V-E-FAN
Cisco Catalyst 6509 Enhanced Vertical Chassis Cable Management Kit	WS-C6509-V-E-CM
Cisco Catalyst 6500 3000W AC Power Supply	WS-CAC-3000W
Cisco Catalyst 6500 6000W AC Power Supply	WS-CAC-6000W

Product Name	Part Number
Cisco Catalyst 6500 8700W Enhanced AC Power Supply	WS-CAC-8700W-E
Cisco Catalyst 6500 4000W AC Power Supply for US	WS-CAC-4000W-US
Cisco Catalyst 6500 4000W AC Power Supply for International	WS-CAC-4000W-INT
Cisco Catalyst 6500 2500W DC Power Supply	WS-CDC-2500W
Cisco Catalyst 6500 4000W DC Power Supply	PWR-4000-DC

### For More Information

For more information about the Cisco Catalyst 6509-V-E chassis, visit

[http://www.cisco.com/en/US/partner/products/hw/switches/ps708/products\\_data\\_sheets\\_list.html](http://www.cisco.com/en/US/partner/products/hw/switches/ps708/products_data_sheets_list.html).



**Americas Headquarters**  
 Cisco Systems, Inc.  
 170 West Tasman Drive  
 San Jose, CA 95134-1706  
 USA [www.cisco.com](http://www.cisco.com)  
 Tel: 408 526-4000  
 800 553-NETS (6387)  
 Fax: 408 527-0883

**Asia Pacific Headquarters**  
 Cisco Systems, Inc.  
 168 Robinson Road  
 #28-01 Capital Tower  
 Singapore 068912  
[www.cisco.com](http://www.cisco.com)  
 Tel: +65 6317 7777  
 Fax: +65 6317 7799

**Europe Headquarters**  
 Cisco Systems International BV  
 Haarlerbergpark  
 Haarlerbergweg 13-19  
 1101 CH Amsterdam  
 The Netherlands  
[www-europe.cisco.com](http://www-europe.cisco.com)  
 Tel: +31 0 800 020 0791  
 Fax: +31 0 20 357 1100

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

©2007 Cisco Systems, Inc. All rights reserved. CCVP, the Cisco logo, and the Cisco Square Bridge logo are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networking Academy, Network Registrar, PIX, ProConnect, ScriptShare, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0708R)