

Cisco MCS 7825-H4

Cisco Unified Communications Solutions unify voice, video, data, and mobile applications on fixed and mobile networks enabling easy collaboration every time from any workspace.

Cisco[®] Unified Communications is a comprehensive IP communications system of voice, video, data, and mobility products and applications. It enables more effective, more secure, more personal communications that directly affect both sales and profitability. It brings people together by enabling a new way of communicating — where your business moves with you, security is everywhere, and information is always available...whenever and wherever it is needed. Cisco Unified Communications is part of an integrated solution that includes network infrastructure, security, mobility, network management products, lifecycle services, flexible deployment and outsourced management options, end-user and partner financing packages, and third-party communications applications.

Product Overview

The Cisco MCS 7825-H4 Media Convergence Server is an entry-level server platform used for Cisco Unified Communications Solutions. An integral part of a complete, scalable architecture for a new generation of high-quality IP voice solutions that run on enterprise data networks, the Cisco MCS 7825-H4 is an easily deployed, cost-effective solution that delivers the high performance and availability demanded by today's enterprise networks. At only 1 rack unit (1RU) high, the Cisco MCS 7825-H4 offers tremendous power in a low-profile chassis that minimizes rack space

Features and Benefits

Ease of Installation

The Cisco MCS 7825-H4 Unified Communications Manager Appliance is a high availability appliance platform used for Cisco Unified Communications Solutions. An integral part of a complete, scalable architecture for a new generation of high-quality IP voice solutions that run on enterprise data networks, the Cisco MCS 7825-H4 is an easily deployed, cost-effective solution. At only 1 rack unit (1RU) high, the Cisco MCS 7825-H4 offers tremendous power in a low-profile chassis that minimizes rack space while providing drive redundancy for higher availability.

DAT Tape Drive Support

The Cisco MCS 7825-H4 can support a 36/72-GB universal-serial-bus (USB) external Digital Audio Tape (DAT) drive (part number DAT-USB-EXT-72=) or an optional 36/72-GB USB rack-mount DAT drive (part number DAT-USB-RM-72=). This tape drive connects through one of the USB 2.0 ports provided by the Cisco MCS 7825-H4 Unified Communications Manager Appliance and allows the system to back up the configuration database.

Features and Benefits

Supported Cisco Applications

- Cisco Unified Application Environment

- Cisco Unified Communications Manager 4.3
- Cisco IP Interoperability and Collaboration System (IPICS)
- Cisco Emergency Responder 1.3
- Cisco Unified Contact Center Enterprise Versions 6 and 7
- Cisco Unified Contact Center Express Versions 5, 6, and 7
- Cisco Unified Contact Center Hosted Version 7
- Cisco Unified Intelligent Contact Management Enterprise Versions 6 and 7
- Cisco Unified Intelligent Contact Management Hosted Version 7
- Cisco Unified IP Interactive Voice Response Versions 5, 6, and 7
- Cisco Unified Customer Voice Portal Version 4.x, 7.x
- Cisco Unified MeetingPlace[®] Express
- Cisco Unified MeetingPlace Express
- Cisco Unified Mobile Communicator 3.0
- Cisco Unified Presence
- Cisco Unity[®]

Product Specifications

Table 1 lists the product configuration, and Table 2 gives specifications.

Table 1. Cisco MCS 7825-H4 Configuration

Component	Value
Product part number	<ul style="list-style-type: none"> • MCS-7825-H4-CCE1 • MCS-7825-H4-CCX1 • MCS-7825-H4-ECS1 • MCS-7825-H4-IPC1 • MCS-7825-H4-RC1
Preload	None
OS included	None
Processor	Single Intel Dual Core Xeon E8400 3.0GHz 6M L2
Memory	2-GB (two 1-GB) PC2-6400 Error Checking and Correction (ECC) double-data-rate 2 (DDR2)
Hard disks	Two 250-GB Serial Advanced Technology Attachment (SATA) 3.5-in. cold-swap drive
Remote management	HP Integrated Lights Out (iLO) Advanced supported; license not provided
Component	Value

Table 2. Product Specifications

Processor	
Maximum processors	1
Processors installed	1
Basic input/output system (BIOS) type	Flash memory
Memory	
Memory maximum	8 GB
Memory interface mega transfers per second	800 MHz
Memory technology	PC2-6400 DDR2 synchronous dynamic RAM (SDRAM)

Bit-error mitigation	ECC
Total RAM slots	4
Hard Disk	
Hard disk bays	2
Hard disk revolutions per minute (rpm)	7200
Hard disk I/O transfer rate	3 GBps
Hard disk interface type	SATA
Redundant Array of Independent Disks (RAID)	RAID 1
Network Connectivity	
Ethernet network interface card (NIC)	2 onboard 10/100/1000
Connector	2 RJ-45 connectors on back of server
10BASE-T cable support	EIA Category 3, 4, or 5 unshielded twisted pair (UTP) (2 or 4 pair) up to 328 ft (100m)
100BASE-TX cable support	EIA Category 5 UTP (2 pair) up to 328 ft (100m)
1000BASE-T cable support	EIA Category 6 UTP (recommended), Category 5E UTP, 5 UTP (2 pair) up to 328 ft (100m)
Expansion Options	
PCI-* non-hot plug slots 133-MHz and 64-bit slots	1 PCI Express x8 low profile half-length slot 1 PCI Express x8 full-length slot
Interfaces	
Ethernet	2
Serial ports	1
Universal-serial-bus (USB) 2.0 ports	4 (2 at front and 2 at back of chassis)
Keyboard port	1 PS/2
Mouse port	1 PS/2
Security	
<ul style="list-style-type: none"> • Power-on password • Keyboard password • USB port control • Removable optical drive assembly • Dedicated iLO2 port • Administrator's password 	
Power	
Rated input voltage specifications	100 to 240 VAC
Rated input line	90 to 264 VAC
Rated input frequency	47 to 63 Hz
Rated input power	@ 115V input, Rated input power = 486W (assume Output wattage = 450W) @ 230V input, Rated input power = 479W (assume Output wattage = 450W)
Rated input current	6 A (at 100 VAC) 3 A (at 200 VAC)
Steady-state power	420W (rated)
BTU rating	1836 BTU/hr (at 100 VAC) 1706 BTU/hr (at 200 VAC)
Operating ambient temperature range	50 to 118°F (10 to 48°C)
Nonoperating ambient temperature range	-40 to 158°F (-40 to 70°C)
Operating relative humidity (noncondensing)	55 to 85%
Nonoperating relative humidity (noncondensing)	5 to 95%

Maximum wet-bulb temperature	106.3F (41.3°C)
Dimensions	
Form factor	Rack-mount 1RU
Rack-mounting	Standard 4-post rail kit (non-proprietary) (included)
Weight	33.5 lb (15.2 kg), base chassis
Height	1.7 in. (4.3 cm)
Width	17.64 in. (44.8 cm)
Depth	26.85 in. (68.19 cm)
Equipment Approvals and Safety	
<ul style="list-style-type: none"> • FCC - Verified to comply with Part 15 of the FCC Rules, Class A • ICES-003 Class A • AS/NZS CISPR22 Class A • CISPR22:2005 Class A • EN55022: 2006 Class A • EN55024: 1998 +A1:2001 + A2:2003 • IEC 61000-3-2:2000/EN 61000-3-2: 2000 • IEC 61000-3-3: 1995 + A1:2001/EN 61000-3-3: 1995 + A1:2001 • KN22 Class A (MIC Certification) • CNS13438 Class A (BSMI Certification) • GB9254 Class A (CCC Certification) • VCCI-03 Class A (VCCI Certification) • CSA C22.2 No. 60950-1-03 Information Technology Equipment-Safety-Part 1:General Requirements • UL 60950-1 Information Technology Equipment-Safety-Part 1:General Requirements • IEC 60950-1 Information Technology Equipment-Safety-Part 1:General Requirements + CB report covering national deviations for intended markets. • EN 60950-1:2001, A11:2004 First Edition • CCC – China Certification for China Compulsory Product Certification • CE Mark (Low Voltage Directive 73/23/EEC, EMC Directive 89/336 EEC) • NOM (Mexico Safety) • EN50082-1 (European Union Immunity) • SASO (Saudi Arabia Safety) • KN24 Immunity Series (MIC Certification) • WEEE 	

Ordering Information

Tables 3 through 5 give ordering information for the Cisco MCS 7825-H4.

Table 3. Ordering Information

Product Name	Part Number
Cisco Unified Application Environment	See Cisco Unified Application Environment data sheet
Cisco Unified Communications Manager 4.3	CALLMANAGER-4.3
Cisco Emergency Responder	See Emergency Responder datasheet
Cisco Unified Presence	See Unified Presence datasheet
Cisco Unified Intelligent Contact Management Enterprise	ICME-BUNDLE
Cisco Unified Intelligent Contact Management Hosted	HOSTED-BUNDLE
Cisco Unified Contact Center Enterprise	IPCE-BUNDLE
Cisco Unified Contact Center Hosted	HOSTED-BUNDLE

Cisco Unified Contact Center Express	<ul style="list-style-type: none"> • CCX-50-STANDARD • CCX-50-ENHANCED • CCX-50-PREMIUM • CCX-60-STANDARD • CCX-60-ENHANCED • CCX-60-PREMIUM • CCX-70-NEW
Cisco Unified IP IVR	<ul style="list-style-type: none"> • IVR-5.0-NEW • IVR-6.0-NEW • IVR-70-NEW-BUNDLE
Cisco Unified Customer Voice Portal	It is applicable for CVP Operation Server. Please see CCBU Ordering Guide for detail
Cisco Unified MeetingPlace conferencing	See Unified MeetingPlace datasheet
Cisco Unified MeetingPlace Express	See Unified MeetingPlace Express datasheet
Cisco Unity Unified Messaging	See Server Spares below

Table 4. Spare Server Ordering Information

Product Name	Part Number
Cisco MCS 7825-H4 for Cisco Unified Application Environment	MCS-7825-H4-IPC1
Cisco MCS 7825-H4 for Cisco Emergency Responder 1.3	MCS-7825-H4-IPC1
Cisco MCS 7825-H4 for Cisco Unified Communications Manager 4.3	MCS-7825-H4-IPC1
Cisco MCS 7825-H4 for Cisco IPCS	MCS-7825-H4-S31
Cisco MCS 7825-H4 for Cisco Unified Contact Center Enterprise 6.x	MCS-7825-H4-CCE1
Cisco MCS 7825-H4 for Cisco Unified Contact Center Enterprise 7.x	MCS-7825-H4-CCE1
Cisco MCS 7825-H4 for Cisco Contact Center Express 5.x	MCS-7825-H4-CCX1
Cisco MCS 7825-H4 for Cisco Contact Center Express 6.x	MCS-7825-H4-CCX1
Cisco MCS 7825-H4 for Cisco Contact Center Express 7.x	MCS-7825-H4-CCX1
Cisco MCS 7825-H4 for Cisco Unified Contact Center Hosted 7.x	MCS-7825-H4-CCE1
Cisco MCS 7825-H4 for Cisco Unified Intelligent Contact Manager Enterprise 6.x	MCS-7825-H4-CCE1
Cisco MCS 7825-H4 for Cisco Unified Intelligent Contact Manager Enterprise 7.x	MCS-7825-H4-CCE1
Cisco MCS 7825-H4 for Cisco Unified Intelligent Contact Manager Hosted 7.x	MCS-7825-H4-CCE1
Cisco MCS 7825-H4 for Cisco Unified IP IVR 5.x	MCS-7825-H4-CCX1
Cisco MCS 7825-H4 for Cisco Unified IP IVR 6.x	MCS-7825-H4-CCX1
Cisco MCS 7825-H4 for Cisco Unified IP IVR 7.x	MCS-7825-H4-CCX1
Cisco MCS 7825-H4 for Cisco Unified CVP 4.x, 7.x Operation Server	MCS-7825-H4-CCE1
Cisco MCS 7825-H4 for Cisco Unified Meeting Express	MCS-7825-H4-RC1
Cisco MCS 7825-H4 for Cisco Unified Presence	MCS-7825-H4-IPC1
Cisco MCS 7825-H4 for Cisco Unified Mobile Communicator 3.0, Proxy Server	MCS-7825-H4-IPC1
Cisco MCS 7825-H4 for Cisco Unity	MCS-7825-H4-ECS1

Table 5. Spare Parts Ordering Information

Description	Spare Part Number
Spare 1024-MB SDRAM DIMM for Cisco MCS 7825-H4	MEM-7825-H4-1GB=
Spare 250-GB SATA drive for Cisco MCS 7825-H4	HDD-7825-H4-250=

Warranty Information

Cisco offers a 1-year limited hardware warranty on Cisco Media Convergence Servers. For terms and conditions of this warranty, refer to

http://www.cisco.com/en/US/docs/general/warranty/English/1Y1DEN_.html.

Cisco Unified Communications Services

Cisco Unified Communications Services allows you to accelerate cost savings and productivity gains associated with deploying a secure, resilient Cisco Unified Communications Solution. Delivered by Cisco and our certified partners, our portfolio of services is based on proven methodologies for unifying voice, video, data, and mobile applications on fixed and mobile networks. Our unique lifecycle approach to services can enhance your technology experience to accelerate true business advantage.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCENT, Cisco Eos, Cisco HealthPresence, the Cisco logo, Cisco Lumin, Cisco Nexus, Cisco StadiumVision, Cisco TelePresence, Cisco WebEx, DCE, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn and Cisco Store are service marks; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0812R)